

## Multi-purpose oil

# AUTOL AGROTECH SAE 10W-30

Modern Supertractor oil (STOU) with improved cold flow behaviour for all agricultural equipment.

### Characteristics (typical figures):

Viscosity	at 40°C	mm <sup>2</sup> /s	65,0
	at 100°C	mm <sup>2</sup> /s	10,3
Viscosity index			min. 135
Density at 15°C		kg/m <sup>3</sup>	866
Flashpoint o. C.		°C	min. 220
Pourpoint		°C	max. -33

The use of a special base oil gives AUTOL AGROTECH a high natural viscosity index to meet the requirement for an optimum lubrication at all working temperatures.

Since modern agricultural machines have special demands in reference to wear protection and friction behaviour due to their combined oil supply, these properties can only be guaranteed with the necessary special additive package.

### Applications:

**AUTOL AGROTECH 10W-30** is a universally applicable lubricant especially for aggregates in agricultural equipment. It can be used for diesel engines with and without turbocharger, hydrostatical and mechanical gears, gear reducer units, axles and transmission with wet brakes as well as hydraulic systems. To maintain the efficiency of the product, all additionally used equipment should be reoiled with this high performance lubricant.

**AUTOL AGROTECH 10W-30** meets the requirements of the following specifications:

STOU, ACEA E2/E3, API CG-4, API GL 4, SAE 80W, HVLP-D 68, Allison C-4, Caterpillar TO-2, Ford M2C-86A/134D/159B/C, I-280-S, John Deere JDM J20C/J27, Massey Ferguson CMS M1135/1139/1144/1145, New Holland NH030C/82009201/NH410B, Sauer Sunstrand/ Danfoss&Hydro, Sperry Vickers/Eaton M29505, ZF TE-ML 03A/05K/06B/06C/07B/07D.