

Engine oils

AUTOL GRAND PRIX LL PLUS SAE 10W-40

Variable applicable fuel efficiency engine oil with fuel saving properties for highly loaded gasoline, naturally aspirated diesel and turbo diesel engines of passenger cars and transporters.

Characteristics (typical figures):

Viscosity	at 40°C	mm ² /s	94
	at 100°C	mm ² /s	14,1
Viscosity Index			155
Density at 15°C		kg/m ³	866
Flashpoint o.C.		°C	210
Pour point		°C	-33

Due to the use of efficient semi-synthetic base oils and carefully selected adjusted additives **AUTOL GRAND PRIX LL PLUS** ensures excellent thermo oxidative stability, low evaporation loss, however primarily an excellent wear and corrosion protection behaviour. The black sludge protection had been confirmed in different manufacturer tests and ACEA specifications.

Due to its efficient and economical semi-synthesis technology **AUTOL GRAND PRIX LL PLUS** provides:

- very good easy running with proven fuel saving
- optimum conditions for Stop-and-Go traffic
- conserving cold start behaviour, fast engine lubrication
- high safety reserves

AUTOL GRAND PRIX LL PLUS can be applied where the following specifications are required:

ACEA A3/B3; A3/B4, API SN, MB 229.3