



## APPLICATIONS

**Eni i-Ride racing 2T** is a top synthetic lubricant, specifically developed for 2 stroke motorcycle engines. Its excellent performances make it suitable to the most stressed 2 stroke engines, either air or liquid cooled.

## CUSTOMER ADVANTAGES

- The peculiar formulation of **Eni i-Ride racing 2T** guarantees the best engine protection, reducing wear and deposits formation even in the most extreme driving conditions.
- The product is formulated with innovative additives to ensure high efficiency for a long service time of catalyst exhaust systems.
- **Eni i-Ride racing 2T** reduces exhaust smoke and the formation of deposits inside exhaust system, ensuring the original performances to the engine.

## SPECIFICATIONS & APPROVALS

- JASO FC/FD
- ISO-L-EGD
- HUSQVARNA

## CHARACTERISTICS

Properties	Method	Unit	Typical
Density at 15°C	ASTM D 4052	kg/m <sup>3</sup>	869
Viscosity at 100°C	ASTM D 445	mm <sup>2</sup> /s	11.1
Viscosity at 40°C	ASTM D 445	mm <sup>2</sup> /s	72
Viscosity index	ASTM D 2270	-	146
Flash point P.M.	ASTM D 93	°C	96
Pour point	ASTM D 97	°C	-45

