



APPLICATIONS

Eni Rotra LSX 75W-90 is a special top sythetic lubricant for manual gearboxes requiring an API GL-4 or GL-5 level of performance. It has especially formulated for the lubrication of both gearboxes and differentials in modern vehicles. It is also suitable for the lubrication of gearboxes in outboard engines and sterndrive systems.

CUSTOMER ADVANTAGES

- This product guarantees an extraordinary thermo-oxidative stability, an exceptional protection against corrosion, and full seal compatibility. It can satisfy the most demanding specifications of OEMs for Long-drain operations.

SPECIFICATIONS

- API GL-4 + GL-5
- API MT-1
- MAN 341 type GA1 (Approved)
- MAN 341 type Z2 (Approved)
- MAN 342 type S1 (Approved)
- MACK GO-J
- SAE J 2360 (ex MIL-PRF-2105E)
- Scania STO 1:1 G (Feedback)
- Scania STO 2:0 A FS (Feedback)
- Volvo 97312
- ZF TE-ML 02B, 05A, 12L, 12N, 16F, 17B, 19C, 21A (Approved)
- DTFR 12B140





CHARACTERISTICS

Properties	Method	Unit	Typical
Density at 15°C	ASTM D 4052	kg/m ³	865
Viscosity at 100°C	ASTM D 445	mm ² /s	16.0
Viscosity Index	ASTM D 2270	-	160
Viscosity at -40°C	ASTM D 2983	mPa·s	127000
Flash point COC	ASTM D 92	°C	200
Pour point	ASTM D 5950	°C	-48

