



APPLICATIONS

Eni Rotra ATF is a special multifunctional lubricant suitable for automatic transmissions and power steering; is also indicated for all those industrial applications where very high performance hydraulic fluids are required.

CUSTOMER ADVANTAGES

- **Eni Rotra ATF** provides reliable transmission operation and smooth gear shifting, with maximum driving comfort also in case of sudden variations of road speed.
- Its antiwear properties ensure the protection of the transmission components, so that they maintain a perfect efficiency in time.
- The formulation of **Eni Rotra ATF** has an exceptional thermo-oxidative stability, which limits the formation of sludges and deposits. This allows prolonged oil drain intervals, according to the indication of the transmission manufacturers.
- Its antifoam properties prevent the formation of air bubbles which could adversely affect the continuity of the lubricant film, and ensure a quick air release.
- **Eni Rotra ATF** is suitable for use in those applications for which manufacturer Daimler Truck requires the DTFR 13C120 performance claim.

SPECIFICATIONS

- GM DEXRON IID
- Ford ESP-M2C166-H
- Ford ESP-M2C138-CJ





CHARACTERISTICS

Properties	Method	Unit	Typical
Colour	-	-	red
Density at 15°C	ASTM D 4052	kg/m ³	870
Viscosity at 100°C	ASTM D 445	mm ² /s	6.7
Viscosity at 40°C	ASTM D 445	mm ² /s	34.0
Viscosity Index	ASTM D 2270	-	159
Viscosity at -40°C	ASTM D 2983	mPa·s	44000
Flash point COC	ASTM D 92	°C	220
Pour point	ASTM D 5950	°C	-45

