

Grease

Autol Top 2000 TYP 000

GP 000 G-30

extremely adhesive

Synthetic gear fluid grease for non-oiltight gears.

Characteristics (typical figures):

AUTOL TOP 2000 TYP 000	Typ 000
Soap basis	special Ca-soap
Behaviour against water	1-90
Corr. protection properties (EMCOR-Test)	Corr.-grade 0 and 1
NLGI grade	000
Working temperature range [°C]	-30 to +100
Drop point [°C]	140

AUTOL TOP 2000 TYP 000 is a fluid oil with extremely adhesive and distinct extreme pressure properties for long-term lubrication.

The selected synthetic base oils and balanced additives reduce wear on the tooth flanks also under difficult conditions, e.g. starting up or sudden loads.

Its special properties include the good water resistance, even to salt water, high pressure absorbing lubricating film, resistance against washing out and good corrosion protection. Due to its composition and if applied as directed, according to the manufacturer's specification, it is physiological harmless and therefore also suitable as a lubricant for the application in the foodstuff industry.

Applications:

AUTOL TOP 2000 TYP 000 can be used as a fluid grease for non-oiltight gears, e.g. in the agricultural and forestry industry. Due to its good qualities it is various applicable.

Please observe the manufacturer's specifications when selecting products.

Attention! The maximum short-time top temperature permitted is +125°C.

