



Eni Coro DWV 45 L

Eni Coro DWV 45 L is a barium free dewatering fluid. It has high corrosion protection and good dewatering properties.

Characteristics (typical figures):

Coro DWV 45 L		Unit	Test method
Colour	3,5		DIN ISO 2049
Density at 15°C	820	kg/m ³	DIN 51 757
Viscosity at 20°C	4,5	mm ² /s	DIN 51 562
Flash point	>61	°C	DIN EN ISO 22719
Salt spray test	>50	h	DIN EN ISO 9227
Condensation climate	>50	cycles	DIN EN ISO 6270-2
Film weight			FLV-F-03

Properties and Performance:

- barium free
- forms a vaseline-like protection film with very good corrosion protection
- good dewatering properties
- removable with common industrial cleansing agents or solvents
- stable against sour and alkaline drag-in
- very productive

Applications:

Eni Coro DWV 45 L is a corrosion protection fluid for the fast draining and simultaneously preservation of metal parts and tools especially after electro-plating. Suitable for intermediate and end preservation. Preferable application by dipping but it can also be sprayed.

Information:

The product has to be stored at room temperature. Storage period at least 6 months.

The product is a water hazardous liquid.

For specific technical questions please contact our technical department. Get information in reference to our training seminar about the subject cooling lubricants.