

# Eni i-Ride moto 10W-40



## APPLICATIONS

**Eni i-Ride moto 10W-40** is a lubricant with synthetic technology formula that brings together the experience and knowledge acquired over many decades by Enilive in the lubricants field.

It is specially designed to meet the lubrication requirements of the 4-stroke engines that equip the latest generation motorcycles.

It is a superior quality product expressly formulated to meet the high standards and performance levels required by the motorcycle industry. The product is registered with JASO code M039ENL037.

## CUSTOMER ADVANTAGES

- In a constantly evolving scenario, driven by increasingly stringent emission regulations, a progressive updating of performance specifications and continuous technological evolution, the choice of lubricant becomes a strategic element to ensure optimal engine performance, protection and efficiency. In this context, **Eni i-Ride moto 10W-40** plays a key role in meeting the performance and environmental requirements set by regulatory bodies and manufacturers.
- **Eni i-Ride moto 10W-40** ensures deposit control and oxidation stability, which are particularly challenging aspects that require careful selection of the raw materials present in the lubricant additive. In this regard, the formulation of the product uses an innovative additive technology developed specifically to meet the needs of the motorcycle sector.
- The formulation of the **Eni i-Ride moto 10W-40** is suitable not only to protect the engine, but also to limit transmission wear and to provide friction suitable for engaging the clutch, avoiding unwanted slippage.
- **Eni i-Ride moto 10W-40** is the result of a careful and accurate selection of base oils and specific additives that optimize engine performance in all operating conditions, protect the mechanical parts of the gearbox and improve clutch response during gear shifting.

## SPECIFICATIONS

- API SN
- JASO MA2



# Eni i-Ride moto 10W-40



## CHARACTERISTICS

Properties	Method	Unit	Typical
Density at 15°C	ASTM D 4052	kg/m <sup>3</sup>	861
Viscosity at 100°C	ASTM D 445	mm <sup>2</sup> /s	13.5
Viscosity at 40°C	ASTM D 445	mm <sup>2</sup> /s	88
Viscosity Index	ASTM D 2270	-	155
Viscosity at -25°C	ASTM D 5293	mPa·s	5000
Pour point	ASTM D 5950	°C	-30
Flash point COC	ASTM D 92	°C	224

