

Eni i-Ride racing 10W-60



APPLICATIONS

Eni i-Ride racing 10W-60 is a high performance top synthetic lubricant containing high performance additives to meet the needs of 4-stroke engines with high specific power.

CUSTOMER ADVANTAGES

- The special synthetic bases used guarantee excellent resistance to high operating temperatures and excellent product stability thanks to the fundamental action of additives totally developed and manufactured by Eni.
- The characteristics of **Eni i-Ride racing 10W-60** make it particularly suitable for use in racing engines.

SPECIFICATIONS - APPROVALS

- API SL
- JASO MA, MA2



Eni i-Ride racing 10W-60



CHARACTERISTICS

| Properties | Method | Unit | Typical |
|--------------------|-------------|--------------------|---------|
| Density at 15°C | ASTM D 4052 | kg/m ³ | 856 |
| Viscosity at 100°C | ASTM D 445 | mm ² /s | 23.4 |
| Viscosity at 40°C | ASTM D 445 | mm ² /s | 165 |
| Viscosity Index | ASTM D 2270 | - | 172 |
| Viscosity at -25°C | ASTM D 5293 | mPa·s | 6800 |
| Flash point (COC) | ASTM D 92 | °C | 230 |
| Pour point | ASTM D 97 | °C | -27 |

