



Eni PRECIS HVLP-D

Multigrade hydraulic fluid with detergent effect with high viscosity index, excellent cold flow behaviour and low flow and friction loss, especially suitable for precision hydraulic systems.

Characteristics (typical figures):

Eni PRECIS HVLP-D	Unit	32	46	Test method
Kin. Viscosity at 40°C	mm ² /s	31,5	43,6	ASTM D7279
Kin. Viscosity at 100°C	mm ² /s	6,2	8,0	ASTM D7279
Viscosity index	-	150	150	ASTM D2270
Density at 15°C	kg/m ³	850	861	DIN EN ISO 12185
Flashpoint o. C.	°C	>225	>235	DIN ISO 2592
Pourpoint	°C	<-38	<-38	ASTM D7346

Properties and Performance:

The high viscosity index provides excellent viscosity-temperature behavior, covering the entire viscosity range of the adjacent ISO-VG standard HLP oils. Special additives guarantee optimal shear strength. The improved low-temperature flow properties protect components, especially during hydraulic system start-up in low-temperature environments.

Eni PRECIS HVLP-D is equipped with polar wear inhibiting components and therefore especially suitable for high pressure hydraulic systems that are exposed to high wear due to extreme load.

Eni PRECIS HVLP-D protects all metal parts in the hydraulic system from rust and corrosion. Detergent, dispersing synthetic agents dissolve pollution, keep them in suspension and therefore enable the cleaning of soiled hydraulic systems. Penetrated water is emulsified up to some percent and harmlessly distributed for the operation of the hydraulic system.

Eni PRECIS HVLP-D has good air release properties and a very good foam behaviour, which effectively prevents the formation of surface foam.

Applications:

Eni PRECIS HVLP-D exceeds the performance of conventional HLP and HVLP hydraulic oils. The application of **Eni PRECIS HVLP-D**, instead of hydraulic oils of standard quality, is especially recommended for excavators, wheel loaders, bulldozers and truck hydraulic systems, but they are also used in stationary systems in the production and machine tool field to reduce the various products. **PRECIS HVLP-D 32** is approved for **KraussMaffei injection molding machines**.

Spezifikationen:

DIN 51 524 T.3 HVLP-D
ISO 11158 HV (ISO 6743-4 HV)