

Eni i-Ride racing 5W-40



APPLICATIONS

Eni i-Ride racing 5W-40 is an innovative lubricant with a top synthetic formula, developed by Eni's research to meet the requirements of 4-stroke high performance engines. The product formulation has been developed to ensure the best performance even under higher mechanical and thermal stress conditions to which motorcycle engines are subjected.

CUSTOMER ADVANTAGES

- **Eni i-Ride racing 5W-40** with its particular additivation is able to guarantee a good engine detergent, in particular it has characteristics that allow efficient control of the formation of deposits areas submitted to high temperature.
- The adoption of an innovative formulation technology makes it possible to enhance the engine performance in all operating conditions.
- The product effectively counteracts wear phenomena that may occur in engines submitted to higher stresses.

SPECIFICATIONS - APPROVALS

- API SL
- JASO MA, MA2



Eni i-Ride racing 5W-40



CHARACTERISTICS

Properties	Method	Unit	Typical
Density at 15°C	ASTM D 4052	kg/m ³	854
Viscosity at 100°C	ASTM D 445	mm ² /s	13.6
Viscosity at 40°C	ASTM D 445	mm ² /s	85
Viscosity Index	ASTM D 2270	-	164
Viscosity at -30°C	ASTM D 5293	mPa·s	6300
Flash point	ASTM D 92	°C	232
Pour point	ASTM D 97	°C	-36

