

Active agent

AUTOL HEL PREMIUMWIRKSTOFF

Combustion improver



AUTOL HEL PREMIUMWIRKSTOFF is a highly effective combustion stabilizer with a fragrance for the production of premium heating oil.

Characteristics (typical figures):

Viscosity at 40°C	mm ² /s	1,3
Density at 20°C	g/cm ³	0,901
Flashpoint	°C	>60
Water hazardous class		WGK II
Mixing ratio		1 : 2000
		1 litre agent on 2.000 litres heating oil

Properties and Performance of AUTOL HEL Premiumwirkstoff:

- Reduces fuel oil consumption and thus lowers operating costs
- Causes efficient combustion of heating oil through special high-performance active ingredients and thus improves the efficiency of the heating system
- Improved aging stability
- Prevents formation of sediments and fouling
- Efficient with the typical heating oil qualities
- No deposits due to ash-free active agents
- Counteracts burner problems and filter blockings
- Contains own scent against the awkward heating oil odour

Possible Uses:

AUTOL HEL PREMIUMWIKSTOFF contains an ash-free burning active ingredient and is suitable for:

- Shell, Yellow, Blue and Rocket Burners
- For all DIN heating oil qualities: standard heating oil, low-sulphur or sulfur-free heating oil, heating oil with biocomponents
- Steel, plastic and battery tanks

When using the product, the manufacturer's instructions must be observed.