

Eni i-Ride moto 15W-50



APPLICATIONS

Eni i-Ride moto 15W-50 is an engine lubricant with synthetic technology formula that integrates the innovation of the new formulation technologies with the knowledge acquired from Enilive in the lubricants field, through a long and consolidated experience.

The product is formulated with latest additive technology, ensures superior performance, engine protection and, at the same time, hardware durability. It is a high-performance lubricant specifically formulated for motorcycle sector, registered with JASO code M039ENL038.

CUSTOMER ADVANTAGES

- In a constantly evolving scenario, driven by increasingly stringent emission regulations, a progressive updating of performance specifications and continuous technological evolution, the choice of lubricant becomes a strategic element to ensure optimal engine performance, protection and efficiency. In this context, **Eni i-Ride moto 15W-50** plays a key role in meeting the performance and environmental requirements set by regulatory bodies and manufacturers.
- The perfect balance of additives used in the formulation ensures maximum protection and engine durability, while optimizing clutch and transmission performance. In this regard, the formulation of the product uses an innovative additive technology developed specifically to meet the needs of the motorcycle engines.
- The detergent and dispersing qualities of **Eni i-Ride moto 15W-50** are the result of a careful selection of the components included in the formulation, which results in effective control on the formation of deposits such as sludge, lacquers and of carbonaceous type.
- **Eni i-Ride moto 15W-50** is the result of a careful and accurate selection of base oils and specific additives that optimize engine performance in all operating conditions, protect the mechanical parts of the gearbox and improve clutch response during gear shifting.
- The components in the additive package of **Eni i-Ride moto 15W-50** have been selected for prevent the build-up of carbon deposits in the piston ring grooves, which can lead to ring sticking.
- The formulation of the **Eni i-Ride moto 15W-50** is suitable not only to protect the engine, but also to limit transmission wear and to provide friction suitable for engaging the clutch, avoiding unwanted slippage.



Eni i-Ride moto 15W-50



SPECIFICATIONS

- API SN
- JASO MA2

CHARACTERISTICS

Properties	Method	Unit	Typical
Density at 15°C	ASTM D 4052	kg/m ³	871
Viscosity at 100°C	ASTM D 445	mm ² /s	18.9
Viscosity at 40°C	ASTM D 445	mm ² /s	145
Viscosity Index	ASTM D 2270	-	148
Viscosity at -20°C	ASTM D 5293	mPa·s	6300
Pour point	ASTM D 5950	°C	-27
Flash point COC	ASTM D 92	°C	205

