



APPLICATIONS

Eni Geum LFG 40 is a lubricant for modern stationary engines, spark-ignition type, burning landfill gas, biogas or other fermentation gases (digestors). **Eni Geum LFG 40** is formulated with high Viscosity Index basestocks and selected additives that deliver detergent-dispersant, antiwear and antifoam properties. The product retains a particularly high resistance to oxidation processes and low content of phosphorus.

CUSTOMER ADVANTAGES

- Prevention of deposits and lacquers formation on pistons and valves for an outstanding engine cleanliness
- Protection of lubricated components from mechanical wear
- Particularly extended oil drain intervals

SPECIFICATIONS - APPROVALS

- GE Jenbacher engines type 2/3/4/6 on gas class B and C
- MAN M 3271-4
- MAN M 3271-5





CHARACTERISTICS

Properties	Method	Unit	Typical
Appearance	APM 27	-	clear
Density at 15°C	ASTM D 4052	kg/m ³	873
Viscosity at 100°C	ASTM D 445	mm ² /s	13.4
Viscosity Index	ASTM D 2270	-	110
Flash point COC	ASTM D 92	°C	231
Pour point	ASTM D 5950	°C	-30
B. N.	ASTM D 2896	mgKOH/g	4.5
Sulphated ash	ASTM D 874	% (m/m)	0.5



eni