

Gear oils

AUTOL GETRIEBEÖL 75W-90

Universal, energy-saving, fully synthetic, all-year gear oil of the latest generation according to the latest world standards. For heavily loaded mechanisms of transmissions for commercial vehicles (trucks, buses) as well as construction/mining agricultural machinery and special vehicles.

Characteristics (typical figures):

AUTOL Getriebeöl LS	Unit	Value	Test
Kin. Viscosity at 40°C	mm ² /s	>90	ISO 3104
Density at 15°C	kg/l	0,881	DIN 51 757
Flash point o. C.	°C	210	ISO 2592
Pourpoint	°C	-45	ISO 3016

Properties and Performance:

- Excellent synthetic quality with the latest additive package for excellent sliding, anti-wear and anti-seizure properties, resulting in significant fuel savings
- Excellent low-temperature properties for reliable lubrication as well as easy and precise gear changes at any ambient temperature (down to -45 °C) and under any operating conditions.
- Unique thermal-oxidative stability
- Effective protection against mud and abrasive deposits
- Excellent corrosion inhibitors successfully protect metal parts from all types of corrosion
- Excellent compatibility with sealing materials, prevents swelling, hardening and shrinkage
- Noise reduction

Please observe the manufacturer's specifications when selecting products.

Specifications/Applications:

API GL-4, GL-5, MT-1
 MIL-L-2105D, PRF 2105E
 SAE J2360
 MB 235.8
 EATON Europe
 MAN 341 Z2, MAN 342 S1
 VOLVO 97312
 MERITOR O-76-N
 SCANIA STO 1:0,
 ZF TE-ML 02B/05A/12L/12N/16F/17B/19C/21A