



Eni Rotra ATF MBX

Eni Rotra ATF MBX is a very high graded automatic transmission fluid formulated with a number of special selected base oils and additives to obtain the following properties:

- High shifting comfort
- Very low pour point
- Excellent thermal and oxidative stability
- Positive activity against wear, corrosion and foam
- Constant friction stability over lifetime ensuring perfect clutch operation
- Perfect compatibility with seals and non-ferro metals
- Extremely resistant against shudder vibration
- Best low temperature properties
- Suitable for longest change intervals
- The very high viscosity index offers perfect fuel efficiency potential (Fuel saving properties)

Characteristics (typical values):

Eni Rotra ATF MBX	Unit	Value	Method
Kin. Viscosity	at 100°C	6,37	ASTM D 445
	at 40°C	27,4	ASTM D 445
Viscosity index		197	ASTM D 2270
Density at 15°C	kg/m ³	857	ASTM D 4052
Flash point COC	°C	297	ASTM D 92
Pourpoint	°C	-57	ASTM D 97
Colour		yellow-brown	

Quality characteristics:

- This universal ATF with lower viscosity than conventional ATFs, can be used for automatic gearboxes of various car manufacturers, both in the low and high viscosity ATF segment that allow this.
- Also for hybrid applications. In addition to the specified specifications, this ATF is also applicable in certain types of automatic transmissions including: Bentley, Chrysler / Dodge / Jeep, Jaquar, Land Rover, Maserati and Porsche, for which a correspondingly low viscosity ATF is prescribed.
- In general, this multi-purpose ATF also meets the hardware protection of specified ATF specifications for ultra low viscosity.

Eni Rotra ATF MBX

Specifications and suitable for use:

- AISIN WARNER JWS 3324/JWS 3309/AAW-1/AAW-2
- Allison C-4
- BMW 7045E/8072B/LA2634/LT71141/ATF3/3+/6/M-1375.4
- Chrysler ATF+ / +2 / +3 / +4
- DTFR 13C110(MB 236.11)/13C140(MB 236.7)/13C150(MB 236.8)/13C170(MB 236.9)
- Ford Mercon ULV/LV/V/SP/WSS-M2C922-A1/WSS-M2C949-A
- GM Dexron ULV/VI/II/IID/IIE/IIIG/IIIH/Suffix A
- Honda DW-1/3.0/3.1/ATF-Z1 (except in CVT)
- Hyundai/Kia SP-II/-III/-IV/-IV RR/RED-1K/NWS 9638
- JASO M315 Type 1A LV
- Mazda FZ/M-III/Type T-IV
- MB 236.41/236.5/236.6/236.10/236.12/236.14/236.15/236.17
- Mitsubishi SP-II/III/J2/J3/PA
- Nissan D/J/K/S/W
- PSA B71 2340
- Toyota DII/T/T-III/T-IV/WS
- VW G 052 025/052 055/052 162/052 533/052 990
- VW G 055 005/055 025/055 540/060 162
- Isuzu ATF II/III
- Jaguar JLM 20238/20292/21044
- Subaru ATF HP
- Suzuki ATF 3314/3317
- Volvo 1161540
- ZF TE-ML 11A/11B
- ZF Lifeguard 6 / 6+ / 8 / 9