

Engine oils

AUTOL TRUCKTEC 5W-30

Synthetic high-performance engine oil with fuel-saving properties and reduced HTHS viscosity based on modern HC synthetic oils.

Physical properties:

Kin. Viscosity	at 40°C	mm ² /s	57,5
	at 100°C	mm ² /s	10,0
Viscosity index			160
Density at 15°C		kg/m ³	855
Flash point PM		°C	> 210
Pourpoint		°C	-33
Base number		mg KOH/g	9,8

AUTOL TRUCKTEC 5W-30 is based on the latest HC synthetic oils and a specially coordinated additive package. Due to the reduced HTHS viscosity (high-temperature-high-shear), it offers high fuel saving potential. As a modern low-ash engine oil, it is ideally suited for the latest generations of diesel engines with exhaust aftertreatment systems, such as diesel particulate filters, catalysts with selective catalytic reduction (SCR) and exhaust gas recirculation (EGR).

AUTOL TRUCKTEC 5W-30 is mixable with mineral and synthetic engine oils, but in order to achieve the full performance spectrum, a complete oil change is recommended before use.

AUTOL TRUCKTEC 5W-30 can be used wherever the following specifications are required:

- API FA-4/SN
- DTFR 15C130 (previous MB 228.61)
- Volvo VDS-5
- JASO DH-2
- CAT ECF-3
- Cummins 20087
- Detroit Diesel 93K223

Note: When selecting a product, the manufacturer's instructions must be observed.