

Fuel Additives

AUTOL DESOLITE DW

Multifunctional fuel system cleaner for all diesel engines.

The additive package ensures maximum performance and optimal filterability in winter use in cold conditions.

Characteristics (typical figures):

Density at 15°C	kg/m ³	895
Flash point o. C.	°C	63
Danger class		9 III

AUTOL DESOLITE DW contains a special cold flow improver with an integrated paraffin sedimentation inhibitor, which helps reduce wear (e.g. of the injection pump), reduces the filterability (CFPP) of the diesel fuel by up to 8°C and at the same time prevents the sedimentation of the crystallized paraffin.

AUTOL DESOLITE DW also offers further advantages:

- Improved lubricity
- Increased cetane number
- Fuel savings
- Better starting behavior
- Quieter engine running
- Improved exhaust emissions
- Effective corrosion protection for the fuel system

Possible uses:

The use of **AUTOL DESOLITE DW** is particularly recommended for vehicles on short journeys or in difficult operation and under cold winter conditions.

We recommend using the product in a mixing ratio of **1:200**.

Water hazard class: 3

Please observe the manufacturer's specifications when selecting products.

Attention! **AUTOL DESOLITE DW** must have a temperature above 0°C when pouring into the tank, because paraffin clumps (agglomerates) that have already formed cannot be dissolved. If possible, the product should be filled before refueling