

Fuel Additives

AUTOL DESOLITE DX-W

Multifunctional fuel system cleaner for all diesel engines.

The additive package ensures maximum performance in winter use and optimal filterability in particularly cold conditions.

Characteristics (typical figures):

Density at 15°C	kg/m ³	895
Flash point o. C.	°C	63
Danger class		9 / III

AUTOL DESOLITE DX-W contains a special cold flow improver with an integrated paraffin sedimentation inhibitor, which helps to reduce wear (e.g. of the injection pump), lowers the filterability limit (CFPP: cold filter plugging point) of the diesel fuel by up to 12°C and at the same time prevents the sedimentation of the crystallized paraffin.

AUTOL DESOLITE DX-W also offers further advantages:

- Improved lubricity
- Increased cetane number
- Fuel savings
- Better starting behavior
- Quieter engine running
- Improved exhaust emissions
- Effective corrosion protection for the fuel system

Possible uses:

The use of **AUTOL DESOLITE DX-W** is particularly recommended for vehicles on short journeys or in difficult operation and under particularly cold conditions.

Mixing ratio 1:100 → Reduction of the CFPP by ~ 12°C.

Mixing ratio 1:200 → Reduction of the CFPP by ~ 7°C.

Mixing ratio 1:300 → Reduction of the CFPP by ~ 5°C.

Mixing ratio 1:400 → Reduction of the CFPP by ~ 3°C.

We recommend using the product in a mixing ratio of **1:100**.

Water hazard class: 3

Please observe the manufacturer's specifications when selecting products.

Attention! **AUTOL DESOLITE DX-W** must have a temperature above 0°C when pouring into the tank, because paraffin clumps (agglomerates) that have already formed cannot be dissolved. If possible, the product should be filled before refueling.