

Grease

AUTOL MEHRZWECKFETT CA EP 2

KP 2 K-30

Mineral high pressure multi-purpose grease based on calcium soap for the lubrication of rolling and plain bearings, even under high loads.

Physical Properties:

Soap base		Calcium
Color		Light brown
Usage temperature range	°C	-30 till +120 (short-term 130)
Dropping point	°C	>150
Base oil viscosity 40°C	mm ² /s	110
Behavior towards water		0-90
Anti-corrosion properties (EMCOR-test)		Corr.-grad. 0-0
Four-cylinder welding force	N	2600

AUTOL MULTI-PURPOSE GREASE CA EP 2 is made from selected age-resistant mineral oils and contains special additives.

AUTOL MULTI-PURPOSE GREASE CA EP 2 is particularly easy to pump, age-resistant, water-resistant, mechanically very stable, corrosion-protective and adheres well.

Possible uses:

AUTOL MULTI-PURPOSE GREASE CA EP 2 is suitable for the lubrication of wheel bearings of trucks, construction machinery, industrial trucks, agricultural machinery, slewing ring bearings of construction machinery and cranes, machine tool bearings, presses, pumps, electric motors, central lubrication stops and much more.

When selecting products, the manufacturer’s instructions must be observed.