

## Engine oil

# AUTOL CARRERA S 5W-30

### Meets the requirements of:

ACEA C3	MB 229.31 / 229.51 / 229.52
API SN Plus	PSA B71 2290 / 2297
GM Dexos 2	Stellantis FPW9.55535/03

**AUTOL CARRERA S 5W-30** is a **synthetic Mid-SAPS multigrade engine oil** developed for modern, high-efficiency gasoline, diesel, and hybrid vehicles (passenger cars, SUVs, light commercial vehicles) from Stellantis (PSA, Opel, Vauxhall), Mercedes-Benz, General Motors, and Asian manufacturers requiring SAE 5W-30 engine oil.

### AUTOL CARRERA S 5W-30

- meets the highest standards for engine cleanliness, wear protection, and environmental compatibility
- ensures long-term efficiency of aftertreatment systems such as DPF, SCR, and NOx storage catalysts, supporting compliance with the latest emission regulations
- contains friction-optimized additives and advanced base oils that help reduce fuel consumption
- offers excellent cold start protection thanks to fast oil circulation even at low temperatures
- enables extended oil drain intervals due to outstanding oxidation and thermal stability
- provides reliable protection against wear, deposits, and corrosion, even under extreme operating conditions

### Characteristics (typical figures):

Properties	Unit	Value	Test method
Colour	-	light brown	visually
Kin. Viscosity at 40°C	mm²/s	66	ASTM D 445
Kin. Viscosity at 100°C	mm²/s	11,5	ASTM D 445
Viscosity index	-	170	ASTM D 2270
Density at 15°C	kg/l	0,848	ASTM D 4052
Flashpoint	°C	> 250	ASTM D 92
Pourpoint	°C	-36	ASTM D 6892

When selecting a product, the manufacturer's instructions must be observed.