



APPLICATIONS

Fuel economy

Engine protection

Eni i-Sint tech S/03 5W-30 is a lubricant formulated with high-performance synthetic technology, specifically designed to meet the needs of a wide range of Stellantis Diesel and gasoline vehicles equipped with EB2 Turbo GEN 1 and GEN 2, DV5R, DW12RU and DW10F engines, as well as naturally aspirated EB GEN 1 and GEN 2 engines.

Its innovative formulation provides comprehensive protection for critical engine components, including pistons, piston rings and the cylinder liner, helping to maintain high performance, efficiency and reliability in the long term.

The product fully complies with the new Stellantis FPW9.55535/03 specification, reflecting the manufacturer's latest technical developments.

It is also backwards compatible with Opel Vauxhall OV 0401547 G30 and D30, and PSA B71 2290 and 2297 specifications.

CUSTOMER ADVANTAGES

- **Eni i-Sint tech S/03 5W-30** represents an optimal balance between advanced technology, efficiency and reliability, meeting the increasingly demanding requirements of modern engine designs.
- Its advanced additive technology, with reduced sulfate ash and Sulfur content, helps minimize mechanical wear, prevents deposit and soot formation, and enhances overall engine durability and reliability.
- The latest generation synthetic formulation contributes to reduced fuel consumption, resulting in lower CO₂ emissions.
In addition, it ensures the correct operation and efficiency of exhaust aftertreatment systems, such as particulate filters, supporting compliance with current emissions regulations.
- **Eni i-Sint tech S/03 5W-30** provides targeted protection against wear and premature elongation of the timing chain, helping to preserve engine performance and prevent the need for costly maintenance.



Eni i-Sint tech S/03 5W-30



SPECIFICATIONS

- Stellantis FPW9.55535/03
- ACEA C3
- PSA B71 2290
- PSA B71 2297
- OV 0401547 - G30
- OV 0401547 - D30

CHARACTERISTICS

Properties	Method	Unit	Typical
Density at 15°C	ASTM D 4052	kg/m ³	853
Viscosity at 100°C	ASTM D 445	mm ² /s	12.1
Viscosity at 40°C	ASTM D 445	mm ² /s	67.5
Viscosity Index	ASTM D 2270	-	180
Viscosity at -30°C	ASTM D 5293	mPa·s	6270
Flash point COC	ASTM D 92	°C	230
Pour point	ASTM D 5950	°C	-39
B. N.	ASTM D 2896	mg KOH/g	9.3

WARNINGS

- Check the vehicle's maintenance guide before using the product.
- Oil changes should be carried out in accordance with the manufacturer's recommendations.

