

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878 Revision date: 5/9/2024 Supersedes: 2/10/2023 Version: 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Trade name	: Eni i-Sint tech F 5W-30
Product code	: 1009
Type of product	: Lubricant
Formula	: 0065-2017
Product group	: Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses	
Main use category	: Industrial use, Professional use, Consumer use
Industrial/Professional use spec	: Non-dispersive use
Use of the substance/mixture	: Lubricant for internal combustion engines
	Do not use the product for any purposes that have not been advised by the manufacturer.
Function or use category	: Lubricants and additives
1.2.2. Uses advised against	

No additional information available

1.3. Details of the supplier of the safety data sheet	
Enilive S.p.A, Viale Giorgio Ribotta 51, 00144 Rome, ITALY, Tel. +39 06 59821, www.eni.com	

Competent person responsible for the safety data sheet (Reg. EC nr. 1907/2006): SDS.Enilive@eni.com

Distributed by: Enilive Schmiertechnik GmbH, Paradiesstraße 14, 97080 Würzburg, GERMANY, www.oilproducts.eni.com Department responsible for information: Application Engineering & Product Management (AEPM), Tel. +49 (0)931-900 98-0 e-mail: technik.wuerzburg@enilive.com

1.4. Emergency telephone number

Emergency number

: CNIT +39 0382 24444 (24h) (IT + EN) Poison Center

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]

Not classified

Adverse physicochemical, human health and environmental effects

Prolonged and repeated skin contact may cause reddening, irritation and dermatitis. May cause an allergic skin reaction. For specific information about the toxicological/ecotoxicological properties and classification of this product, see Sect. 11 and/or Sect. 12.

2.2. Label elements

Labelling according to Regulation	on (EC) No. 1272/2008 [CLP]
EUH-statements	: EUH208 - Contains C14-16-18 Alkyl phenol. May produce an allergic reaction. EUH210 - Safety data sheet available on request.
Nordic countries regulation	
Denmark	
MAL code	: 00-1 (Executive Order No. 301 from 1993)

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

2.3. Other hazards (not relevant for classification)				
Other hazards not contributing to the classification	: This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels. In case of contact with eyes, this product may cause irritation. Any substance, in case of accidents involving pressurized circuits and the like, may be accidentally injected under the skin, even without external damage. In such a case, the victim should be brought to an hospital as soon as possible, to get specialized medical treatment. Do not wait for symptoms to develop. A potential risk may arise from the release of hydrogen sulfide, when the product is stored or handled at high temperature. Hydrogen sulfide may accumulate in the tanks or other confined spaces, with danger to the workers that enter the spaces. In these cases overexposure to hydrogen sulfide may cause irritation to airways, nausea, dizziness. loss of consciousness and death.			

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII Contains no PBT and/or vPvB substances \geq 0.1% assessed in accordance with REACH Annex XIII

Component	
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate) (93819-94-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
C14-16-18 Alkyl phenol	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Paraffin oils (petroleum), catalytic dewaxed heavy, Baseoil - unspecified (64742-70-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Distillates (petroleum) hydrotreated light paraffinic (64742-55-8)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Distillates (petroleum), solvent-refined light paraffinic (64741-89-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Component	
Distillates (petroleum), hydrotreated heavy paraffinic(64742-54-7)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605
Distillates (petroleum), solvent-dewaxed light paraffinic(64742-56-9)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605
Distillates (petroleum), solvent-dewaxed heavy paraffinic(64742-65-0)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Component		
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)(93819-94-4)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	
C14-16-18 Alkyl phenol	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	
Paraffin oils (petroleum), catalytic dewaxed heavy, Baseoil - unspecified(64742-70-7)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	
Distillates (petroleum) hydrotreated light paraffinic (64742-55-8)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	
Distillates (petroleum), solvent-refined light paraffinic(64741-89-5)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Notes

: Composition/information on ingredients Mixture of hydrocarbons Polymers Additives

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]
Distillates (petroleum), hydrotreated heavy paraffinic (see note [*], see note [**])	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627- 25	80 – 90	Asp. Tox. 1, H304
Distillates (petroleum), solvent-dewaxed light paraffinic (see note [*], see note [**])	CAS-No.: 64742-56-9 EC-No.: 265-159-2 EC Index-No.: 649-469-00-9 REACH-no: 01-2119480132- 48	0,5 - 1,5	Asp. Tox. 1, H304
Distillates (petroleum), solvent-dewaxed heavy paraffinic (see note [*], see note [**])	CAS-No.: 64742-65-0 EC-No.: 265-169-7 EC Index-No.: 649-474-00-6 REACH-no: 01-2119471299- 27	0,5 - 1,5	Asp. Tox. 1, H304

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate) (Additive)	CAS-No.: 93819-94-4 EC-No.: 298-577-9 EC Index-No.: N/A REACH-no: 01-2119543726- 33	0,5 - 1,5	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411 (M=1)
C14-16-18 Alkyl phenol (Additive)	EC-No.: 931-468-2 EC Index-No.: N/A REACH-no: 01-2119498288- 19	0,5 - 1,5	Skin Sens. 1B, H317 STOT RE 2, H373
Paraffin oils (petroleum), catalytic dewaxed heavy, Baseoil - unspecified (see note [*], see note [**])	CAS-No.: 64742-70-7 EC-No.: 265-174-4 EC Index-No.: 649-477-00-2 REACH-no: 01-2119487080- 42	0,5 - 1,5	Asp. Tox. 1, H304
Distillates (petroleum) hydrotreated light paraffinic (see note [*], see note [**])	CAS-No.: 64742-55-8 EC-No.: 265-158-7 EC Index-No.: 649-468-00-3 REACH-no: 01-2119487077- 29	0.53 – 1.06	Asp. Tox. 1, H304
Distillates (petroleum), solvent-refined light paraffinic (see note [*], see note [**])	CAS-No.: 64741-89-5 EC-No.: 265-091-3 EC Index-No.: 649-455-00-2 REACH-no: 01-2119487067- 30	0.53 – 1.06	Asp. Tox. 1, H304

Specific concentration limits:		
Name	Product identifier	Specific concentration limits (%)
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate) (Additive)	CAS-No.: 93819-94-4 EC-No.: 298-577-9 EC Index-No.: N/A REACH-no: 01-2119543726- 33	(6.25 ≤ C < 100) Skin Irrit. 2, H315 (10 ≤ C < 12.5) Eye Irrit. 2, H319 (12.5 ≤ C < 100) Eye Dam. 1, H318
Notes :	•	O extract < 3 % wt, according to IP 346. According to the L, Annex VI of Regulation (CE) 1272/2008), this product

must be regarded as non carcinogenic.

substance with occupational exposure limits for some EU countries affecting the category of

mineral oils (finely refined mineral base oil mists; see section 8.1)

Note [**]:

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures after inhalation	: In case of disturbances owing to inhalation of vapours or mists, remove the victim from exposure; keep at rest; if necessary, seek medical attention. See also section 4.3.
First-aid measures after skin contact	: Take off contaminated clothing and shoes. Wash thoroughly with soap and water. If skin irritation or rash occurs, get medical advice/attention. In case of burns, cool affected part with cold running water for at least 10 min. Cover with gauze or clean cloth. Ask for medical assistance or bring to a hospital. Do not apply salves or other substances, unless by doctor's advice. Do not put ice on the burn.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

First-aid measures after eye contact First-aid measures after ingestion	 Rinse eyes thoroughly for at least 15 minutes. Keep eyelids well apart. If irritation, blurred vision or swelling occurs and persists, obtain medical advice from a specialist. In case of burns, cool affected part with cold running water for at least 10 min. Cover with gauze or clean cloth. Ask for medical assistance or bring to a hospital. Do not apply salves or other substances, unless by doctor's advice. Do NOT induce vomiting. If the person is conscious, rinse mouth with water without swallowing. Keep at rest. Call for medical assistance or bring to an hospital. If the casualty is unconscious, place in the recovery position. In case of spontaneous vomiting, keep head low, to avoid the risk of aspiration into the lungs. Do not give anything by mouth to an unconscious person.
4.2. Most important symptoms and effects,	both acute and delayed
Symptoms/effects after inhalation	: This product has a low vapour pressure, and in normal conditions at ambient temperature the concentration in the air is negligible. A significant concentration may build up only in case of sprays and mists. In these cases overexposure to mists (e.g. through prolonged use in confined insufficiently ventilated spaces) may cause irritation to airways, nausea and dizziness.
Symptoms/effects after skin contact	: Prolonged and repeated skin contact may cause reddening, irritation and dermatitis. May produce an allergic reaction. Contact with hot product may cause thermal burns.
Symptoms/effects after eye contact	: Contact with eyes may cause a light transient irritation. Contact with hot product or vapours may cause burns.
Symptoms/effects after ingestion	: Accidental ingestion of small quantities of the product may cause nausea, discomfort and gastric disturbances.
Symptoms/effects upon intravenous administration	: No information available.
Chronic symptoms	: None to be reported, according to the present classification criteria.

4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical attention if casualty has an altered state of consciousness or if symptoms do not resolve. Seek medical attention in all cases of serious burns. If there is any suspicion of inhalation of H2S (hydrogen sulphide), Rescuers must wear breathing apparatus, belt and safety rope, and follow rescue procedures. Send patient to hospital. Immediately begin artificial respiration if breathing has ceased. Administer oxygen if necessary.

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media Unsuitable extinguishing media	 Small-size fires: carbon dioxide, dry chemicals, foam, sand or earth. Large fires: foam or water fog (mist). These means should be used by trained personnel only. Other extinguishing gases (according to regulations). Do not use water jets. They could cause splattering, and spread the fire. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.
5.2. Special hazards arising from the subst	ance or mixture
Fire hazard Explosion hazard Hazardous decomposition products in case of fire	 This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels. In case of losses from pressurized circuits, the sprays may form mists. Take into account that in this case the lower explosion limit for mists is about 45 g/m³ air. Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, NOx, H2S and SOx (harmful/toxic gases). Oxygenated compounds (aldehydes, etc.). POx. ZnOx.
5.3. Advice for firefighters	
Firefighting instructions Special protective equipment for firefighters	 Shut off source of product, if possible. If possible, move containers and drums away from the danger area, if safe to do so. Spilled product which is not burning should be covered with sand or foam. Use water sprays to cool containers and surfaces exposed to the flames. If the fire cannot be controlled, evacuate area. Wear personal protection equipment. (see chapter 8). In case of a large fire or in confined or poorly ventilated spaces, wear full fire resistant protective clothing and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. EN 443. EN 469. EN 659.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Other information

: In case of fire, do not discharge residual product, waste materials and runoff water: collect separately and use a proper treatment.

6.1. Personal precautions, protecti	ve equipment and emergency procedures
General measures	: Stop or contain leak at the source, if safe to do so. Eliminate all ignition sources if safe to d so (e.g. electricity, sparks, fires, flares). Avoid direct contact with released material. Avoid accidental sprays on hot surfaces or electrical contacts. Keep upwind.
6.1.1. For non-emergency personnel	
Protective equipment Emergency procedures	 See Section 8. Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency.
6.1.2. For emergency responders	
Protective equipment	: Small spillages: normal antistatic working clothes are usually adequate. Large spillages: ful body suit of chemically resistant and antistatic material. if necessary heat resistant and insulated. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Gloves made of PVA are not water-resistant, and are not suitable for emergency use. If contact with hot product is possible or anticipated, gloves should be heat resistant and thermally insulated. Antistatic non-skid safety shoes or boots, chemical resistant, if necessary heat resistant and insulated. Work helmet. Goggles and /or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory protection: A half or full-face respirator with filter(s) for organic vapours (A) (or A+B when applicable for H2S), or a Self-contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. A Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
Emergency procedures	: If required, notify relevant authorities according to all applicable regulations.

Do not let the product accumulate in confined or underground spaces. Do not let the product flow into sewers or water courses, or in any way contaminate the environment. In case of contamination of environment compartments (soil, subsoil, surface or underground waters), remove contaminated soil when possible, and in any case treat all involved compartments in accordance with local regulations. The site should have a spill plan to ensure that adequate safeguards are in place to minimize the impact of episodic releases.

For containment	: Contain spilled liquid with sand, earth or other suitable absorbents (non-flammable).
	Recover free liquid and waste materials in suitable waterproof and oil-resistant containers.
	Clean contaminated area. Dispose of according to local regulations. If in water: Confine the
	spillage. Remove from surface by skimming or suitable floating absorbents. Collect
	recovered product and other waste materials in suitable waterproof, oil resistant containers
	Recover or dispose of according to local regulations. Do not use solvents or dispersants,
	unless specifically advised by an expert, and, if required, approved by local authorities.
Other information	: Recommended measures are based on the most likely spillage scenarios for this material;
	however, local conditions (wind, air/water temperature, wave/current direction and speed)
	may significantly influence the choice of appropriate actions. Local regulations may also
	prescribe or limit actions to be taken. For this reason, local experts should be consulted
	when necessary.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SECTION 7: Handling and storage

7.1. Precautions for safe handling	
Precautions for safe handling	: This material is combustible, but will not ignite readily. Provide adequate ventilation. Use adequate personal protective equipment as needed. Due to the extremely slippery nature of this material, more care than usual must be exercised in material handling practices to keep off all walking surfaces. Floors, walls and other surfaces in the hazard area must be cleane regularly. Avoid release to the environment. Emptied containers can contain combustible product residues. Do not cut, weld, drill, burn or incinerate empty containers or drums, unless they have been drained and cleaned. The product may release Hydrogen Sulphide: a specific assessment of inhalation risks from the presence of hydrogen sulphide in tank headspaces, confined spaces, product residue, tank waste and waste water, and unintentional releases should be made to help determine controls appropriate to local circumstances. Before entering storage tanks and commencing any operation in a confined area (e.g. tunnels), carry out an adequate clean-up, and check the atmosphere for oxygen content, flammability, and the presence of sulphur compounds. See also Section 16, "Other information".
Hygiene measures	: Ensure that proper housekeeping measures are in place. Avoid contact with skin. Do not breathe fume/ mist/ vapours. Do not ingest. Do not smoke. Do not eat and do not drink during use. Do not clean hands with dirty or oil-soaked rags. Do not re-use clothes, if they are still contaminated. Keep away from food and beverages. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Contaminated work clothing should not be allowed out of the workplace. Separate working clothes from town clothes. Launder separately.
7.2. Conditions for safe storage, in	cluding any incompatibilities
Storage conditions	: Store in dry, well-ventilated area. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Incompatible products	: Keep away from strong oxidizers.
Storage area	: Storage area layout, tank design, equipment and operating procedures must comply with the relevant European, national or local legislation. Storage installations/areas should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations.
Packages and containers:	: If the product is supplied in containers: Keep containers tightly closed and properly labelled. Keep only in the original container or in a suitable container for this kind of product.
Packaging materials	: For containers, or container linings use materials specifically approved for use with this product. Compatibility should be checked with the manufacturer, according to the specific

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)		
Austria - Occupational Exposure Limits		
MAK (OEL TWA) 5 mg/m ³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Belgium - Occupational Exposure Limits		
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	

use conditions.

Safety Data Sheet

Distillates (petroleum), solvent-dewaxed light	paraffinic (64742-56-9)	
OEL STEL	2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Hungary - Occupational Exposure Limits	·	
AK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits	·	
VLA-ED (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KGV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
United Kingdom - Occupational Exposure Limits	·	
WEL TWA (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
WEL STEL (OEL STEL)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH OEL STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Distillates (petroleum), solvent-dewaxed heav	/y paraffinic (64742-65-0)	
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Belgium - Occupational Exposure Limits	1	
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
OEL STEL	2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KGV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
WEL STEL (OEL STEL)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	

Safety Data Sheet

Distillates (petroleum), solvent-dewaxed heav	vy paraffinic (64742-65-0)
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
ACGIH OEL STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Distillates (petroleum) hydrotreated light para	affinic (64742-55-8)
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Belgium - Occupational Exposure Limits	
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Denmark - Occupational Exposure Limits	
OEL TWA [1]	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
OEL STEL	2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Netherlands - Occupational Exposure Limits	·
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
KGV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
WEL STEL (OEL STEL)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
ACGIH OEL STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Distillates (petroleum), solvent-refined light p	paraffinic (64741-89-5)
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Belgium - Occupational Exposure Limits	·
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Denmark - Occupational Exposure Limits	·
OEL TWA [1]	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
OEL STEL	2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Hungary - Occupational Exposure Limits	·
AK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)

Safety Data Sheet

Distillates (petroleum), solvent-refined light p	paraffinic (64741-89-5)	
Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KGV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
WEL STEL (OEL STEL)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH OEL STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Belgium - Occupational Exposure Limits		
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
OEL STEL	2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Hungary - Occupational Exposure Limits	·	
AK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KGV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
WEL STEL (OEL STEL)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH OEL STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	

Safety Data Sheet

Monitoring methods	
Monitoring methods	Monitoring procedures should be chosen according to the indications set by national authorities or labour contracts. Refer to relevant legislation and in any case to the good practice of industrial hygiene.
3.1.3. Air contaminants formed	
No additional information available	
3.1.4. DNEL and PNEC	
Eni i-Sint tech F 5W-30	
DNEL/DMEL (additional information)	
Additional information	Not applicable
PNEC (additional information)	
Additional information	Not applicable
Zinc bis[O-(6-methylheptyl)] bis[O-(s	sec-butyl)] bis(dithiophosphate) (93819-94-4)
DNEL/DMEL (Workers)	

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)]	bis(dithiophosphate) (93819-94-4)	
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	0.58 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	8.31 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	0.24 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	2.11 mg/m ³	
Long-term - systemic effects, dermal	0.29 mg/kg bodyweight/day	
PNEC (Water)		
PNEC aqua (freshwater)	0.004 mg/l	
PNEC aqua (marine water)	0.0046 mg/l	
PNEC aqua (intermittent, freshwater)	0.021 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	0.0116 mg/kg dwt	
PNEC sediment (marine water)	0.00116 mg/kg dwt	
PNEC (Soil)		
PNEC soil	0.00528 mg/kg dwt	
PNEC (Oral)		
PNEC oral (secondary poisoning)	10.67 mg/kg	
PNEC (STP)		
PNEC sewage treatment plant	100 mg/l	
C14-16-18 Alkyl phenol		
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	0.3 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	1.17 mg/m³	
PNEC (Water)		
PNEC aqua (freshwater)	100 μg/l	

Safety Data Sheet

C14-16-18 Alkyl phenol		
PNEC aqua (marine water)	10 µg/l	
PNEC aqua (intermittent, freshwater)	1 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	4266.16 mg/kg dwt	
PNEC sediment (marine water)	426.62 mg/kg dwt	
PNEC (Soil)		
PNEC soil	852.58 mg/kg dwt	
PNEC (Oral)		
PNEC oral (secondary poisoning)	3.3 mg/kg food	
PNEC (STP)		
PNEC sewage treatment plant	100 mg/l	
Distillates (petroleum), solvent-dewaxed light	paraffinic (64742-56-9)	
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	0.97 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	2.73 mg/m³	
Long-term - local effects, inhalation	5.58 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	0.74 mg/kg bodyweight/day	
Long-term - local effects, inhalation	1.19 mg/m³	
PNEC (Oral)		
PNEC oral (secondary poisoning)	9.33 mg/kg food	
Distillates (petroleum), solvent-dewaxed heav	y paraffinic (64742-65-0)	
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	0.97 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	2.73 mg/m ³	
Long-term - local effects, inhalation	5.4 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	0.74 mg/kg bodyweight/day	
Long-term - local effects, inhalation	1.2 mg/m³	
PNEC (Oral)		
PNEC oral (secondary poisoning)	9.33 mg/kg food	
Paraffin oils (petroleum), catalytic dewaxed heavy, Baseoil - unspecified (64742-70-7)		
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	0.97 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	2.73 mg/m ³	
Long-term - local effects, inhalation	5.58 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	0.74 mg/kg bodyweight/day	

Safety Data Sheet

Long-term - local effects, inhalation 1.19 mg/m³ PNEC (Oral) 9.33 mg/kg food PNEC oral (secondary poisoning) 9.33 mg/kg food Distillates (petroleum) hydrotreated light par=tinic (64742-55-8) DNEL/DMEL (Workers) Long-term - systemic effects, dermal 220 mg/kg bodyweight/day Long-term - systemic effects, inhalation 160 mg/m³/day DNEL/DMEL (General population) 40 mg/kg bodyweight/day Long-term - systemic effects, inhalation 35 mg/m³ Long-term - systemic effects, dermal 92 mg/kg bodyweight/day Distillates (petroleum), solvent-refined light par=tifinic (64741-89-5) DNEL/DMEL (Workers)		
PNEC oral (secondary poisoning)9.33 mg/kg foodDistillates (petroleum) hydrotreated light paraffinic (64742-55-8)DNEL/DMEL (Workers)Long-term - systemic effects, dermal220 mg/kg bodyweight/dayLong-term - systemic effects, inhalation160 mg/m³/dayDNEL/DMEL (General population)Long-term - systemic effects, oral40 mg/kg bodyweight/dayLong-term - systemic effects, inhalation35 mg/m³Long-term - systemic effects, dermal92 mg/kg bodyweight/dayDistillates (petroleum), solvent-refined light paraffinic (64741-89-5)DNEL/DMEL (Workers)		
Distillates (petroleum) hydrotreated light paraffinic (64742-55-8) DNEL/DMEL (Workers) Long-term - systemic effects, dermal 220 mg/kg bodyweight/day Long-term - systemic effects, inhalation 160 mg/m³/day DNEL/DMEL (General population) 100 mg/kg bodyweight/day Long-term - systemic effects, oral 40 mg/kg bodyweight/day Long-term - systemic effects, inhalation 35 mg/m³ Long-term - systemic effects, dermal 92 mg/kg bodyweight/day Long-term - systemic effects, dermal 92 mg/kg bodyweight/day Distillates (petroleum), solvent-refined light paraffinic (64741-89-5) DNEL/DMEL (Workers)		
DNEL/DMEL (Workers) 220 mg/kg bodyweight/day Long-term - systemic effects, dermal 220 mg/kg bodyweight/day Long-term - systemic effects, inhalation 160 mg/m³/day DNEL/DMEL (General population) 40 mg/kg bodyweight/day Long-term - systemic effects, oral 40 mg/kg bodyweight/day Long-term - systemic effects, inhalation 35 mg/m³ Long-term - systemic effects, dermal 92 mg/kg bodyweight/day Distillates (petroleum), solvent-refined light partifinic (64741-89-5) DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal220 mg/kg bodyweight/dayLong-term - systemic effects, inhalation160 mg/m³/dayDNEL/DMEL (General population)Long-term - systemic effects, oral40 mg/kg bodyweight/dayLong-term - systemic effects, inhalation35 mg/m³Long-term - systemic effects, dermal92 mg/kg bodyweight/dayDistillates (petroleum), solvent-refined light = affinic (64741-89-5)DNEL/DMEL (Workers)		
Long-term - systemic effects, inhalation 160 mg/m³/day DNEL/DMEL (General population) 40 mg/kg bodyweight/day Long-term - systemic effects, oral 40 mg/kg bodyweight/day Long-term - systemic effects, inhalation 35 mg/m³ Long-term - systemic effects, dermal 92 mg/kg bodyweight/day Distillates (petroleum), solvent-refined light paraffinic (64741-89-5) DNEL/DMEL (Workers)		
DNEL/DMEL (General population) Long-term - systemic effects, oral 40 mg/kg bodyweight/day Long-term - systemic effects, inhalation 35 mg/m³ Long-term - systemic effects, dermal 92 mg/kg bodyweight/day Distillates (petroleum), solvent-refined light paraffinic (64741-89-5) DNEL/DMEL (Workers)		
Long-term - systemic effects, oral40 mg/kg bodyweight/dayLong-term - systemic effects, inhalation35 mg/m³Long-term - systemic effects, dermal92 mg/kg bodyweight/dayDistillates (petroleum), solvent-refined light paraffinic (64741-89-5)DNEL/DMEL (Workers)		
Long-term - systemic effects, inhalation 35 mg/m ³ Long-term - systemic effects, dermal 92 mg/kg bodyweight/day Distillates (petroleum), solvent-refined light paraffinic (64741-89-5) DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal 92 mg/kg bodyweight/day Distillates (petroleum), solvent-refined light paraffinic (64741-89-5) DNEL/DMEL (Workers)		
Distillates (petroleum), solvent-refined light paraffinic (64741-89-5) DNEL/DMEL (Workers)		
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal 0.97 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation 2.73 mg/m ³		
Long-term - local effects, inhalation 5.58 mg/m³		
DNEL/DMEL (General population)		
Long-term - systemic effects,oral 0.74 mg/kg bodyweight/day		
Long-term - local effects, inhalation 1.19 mg/m ³		
PNEC (Oral)		
PNEC oral (secondary poisoning) 9.33 mg/kg food		
PNEC (additional information)		
Additional information Not derived - Not classified as hazardous for environment		
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal 50 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation 140 mg/m ³		
Long-term - local effects, inhalation 5.4 mg/m³		
DNEL/DMEL (General population)		
Long-term - systemic effects,oral 0.74 mg/kg bodyweight/day		
Long-term - local effects, inhalation 1.2 mg/m³/day		
PNEC (Oral)		
PNEC oral (secondary poisoning) 9.33 mg/kg food		

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

: The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a governmental regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH.

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station. Before entering storage tanks and commencing any operation in a confined area (e.g. tunnels), check the atmosphere for oxygen content, presence of hydrogen sulphide (H2S) and SOx, and flammability. See also Section 16, "Other information".

8.2.2. Personal protection equipment

Personal protective equipment (for industrial or professional use):

Gloves. Protective clothing. Safety glasses. Safety shoes or boots. Dust. aerosol mask.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

When there is a risk of contact with the eyes, use safety goggles or other means of protection (face shield). If necessary, refer to national standards or to the EN 166 standard.

8.2.2.2. Skin protection

Skin and body protection:

Long-sleeved overalls. If necessary, refer to the EN 340 and related standards, for definition of characteristics and performance according to the risk rating of the area. Antistatic non-skid safety shoes or boots, chemical resistant, if necessary heat resistant and insulated.

Hand protection:

When there is a risk of contact with the skin, use waterproof gloves, resistant to chemical products. Gloves must be felt-lined. Adequate materials: nitrile (NBR) or PVC with a protection index > 5 (permeation time > 240 mins). Use gloves respecting all the conditions and within the limits set by the manufacturer. Replace gloves immediately in case of cuts, holes or other signs of damages or degradation. If necessary, refer to the EN 374 standard.

8.2.2.3. Respiratory protection

Respiratory protection:

Independently from other possible actions (technical modifications, operating procedures, and other means to limit the exposure of workers), personal protection equipment can be used according to necessity. Open or well ventilated spaces: in presence of oil mists and if the product is handled without adequate containment means: use full or half-face masks with filter for mists/aerosols (P). In case there is a significant presence of vapours (e.g. through handling at high temperature), use full or half-face masks with a filter for organic vapours (A), and H2S (B) where applicable. (EN 136/140/145). Combined gas/dust mask with filter type: EN 14387. Closed or confined areas (e.g. tank interiors): the use of protection measures for airways (masks or self-contained breathing apparatus), must be assessed according to the specific activity, as well as level and duration of predicted exposure. Approved respiratory protection equipment shall be used in spaces where hydrogen sulphide may accumulate: full face mask with cartridge/filter type "B" (grey for inorganic vapours including H2S) or self-contained breathing apparatus (SCBA). (EN 136/140/145)

8.2.2.4. Thermal hazards

Thermal hazard protection:

If contact with hot product is possible or anticipated, gloves should be heat-resistant and thermally insulated.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

8.2.3. Environmental exposure controls

Environmental exposure controls:

Do not discharge the product into the environment. Prevent discharge of undissolved substance to or recover from onsite wastewater. Storage areas/installations should be designed with adequate bunds so as to prevent ground and water pollution in case of leaks or spills. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Consumer exposure controls:

Ensure adequate air ventilation. Wear protective gloves.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Yellow-brown.
Appearance	: Liquid, bright & clear.
Odour	: Slight odour of petroleum.
Odour threshold	: Not determined
Melting point	: -39 °C (pour point) (ASTM D 97)
Freezing point	: -60 – 0 °C (CAS 64742-54-7)
Boiling point	: ≥ 315 °C (CAS 64742-54-7)
Flammability	: Not flammable
Lower explosion limit	: Not determined
Upper explosion limit	: Not determined
Flash point	: 217 °C (ASTM D 92)
Auto-ignition temperature	: Not determined
Decomposition temperature	: Not determined
pH	: Not determined
Viscosity, kinematic	: 56 mm²/s (40 °C) (ASTM D 445)
Solubility	: Water: Immiscible and insoluble
Log Kow	: Not applicable for mixtures
Log Pow	: Not applicable for mixtures
Vapour pressure	: < 0.1 hPa (20°C)
Vapour pressure at 50°C	: Not determined
Critical pressure	: Not applicable for mixtures
Density	: 853 kg/m³ (15 °C) (ASTM D 4052)
Relative density	: Not determined
Relative vapour density at 20°C	: Not determined
Particle characteristics	: Not applicable
0.0 Other information	

9.2. Other information

9.2.1. Information with regard to physical hazard classes		
Explosion limits Critical temperature	: ≥ 45 g/m³ (Aerosol) : Not applicable for mixtures	
9.2.2. Other safety characteristics		
Relative evaporation rate (butylacetate=1) : Negligible.		

SECTION 10: Stability and reactivity

10.1. Reactivity

Additional information

This mixture does not offer any further hazard for reactivity, except what is reported in the following paragraphs.

: No data available

10.2. Chemical stability

Stable product, according to its intrinsic properties.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

10.3. Possibility of hazardous reactions

None (in normal conditions of storage and handling). Contact with strong oxidizers (peroxides, chromates, etc.) or alkali metals may cause a fire hazard.

10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Thermal decomposition may produce : Toxic fumes. In exceptional cases (i.e prolonged storage in tanks contaminated with water, and presence of anaerobic sulfate-reducing microbial colonies), the product may undergo a degradation and generate small amounts of sulfur compounds, including H2S.

SECTION 11: Toxicological information		
11.1. Information on hazard classes as defined	d in Regulation (EC) No 1272/2008	
Acute toxicity (dermal):Acute toxicity (inhalation):Additional information:	Not classified (Based on available data, the classification criteria are not met) Not classified (Based on available data, the classification criteria are not met) Not classified (Based on available data, the classification criteria are not met) (according to composition)	
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate) (93819-94-4)		
LD50 oral rat	2600 mg/kg bodyweight	
LD50 dermal rabbit	> 3160 mg/kg bodyweight (OECD 402)	
LC50 Inhalation - Rat	> 2 mg/l/4h	
C14-16-18 Alkyl phenol		
LD50 oral rat	2000 mg/kg bodyweight	
LD50 dermal rat	2000 mg/kg bodyweight	
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)		
LD50 oral rat	> 5000 mg/kg (OECD 401)	
LD50 dermal rat	> 5000 mg/kg (OECD 402)	
LC50 Inhalation - Rat	> 5 mg/l/4h (OECD 403)	
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)		
LD50 oral rat	> 5000 mg/kg (OECD 401)	
LD50 dermal rat	> 5000 mg/kg (OECD 402)	
LC50 Inhalation - Rat	> 5 mg/l/4h (OECD 403)	
Paraffin oils (petroleum), catalytic dewaxed heavy, Baseoil - unspecified (64742-70-7)		
LD50 oral rat	5000 mg/kg bodyweight	
LD50 dermal rat	2000 – 5000 mg/kg bodyweight	
LC50 Inhalation - Rat	2.18 – 5.53 mg/l/4h	
Distillates (petroleum) hydrotreated light paraffinic (64742-55-8)		
LD50 oral rat	> 5000 mg/kg (OECD 401)	
LD50 dermal rat	> 5000 mg/kg (OECD 402)	

Safety Data Sheet

Distillates (petroleum), solvent-refined light p	araffinic (64741-89-5)		
LD50 oral rat	> 5000 mg/kg (OECD 401)		
LD50 dermal rat	> 5000 mg/kg (OECD 402)		
LC50 Inhalation - Rat	> 5 mg/l/4h (OECD 403)		
Distillates (petroleum), hydrotreated heavy pa	raffinic (64742-54-7)		
LD50 oral rat	> 5000 mg/kg (OECD 401)		
LD50 dermal rabbit	> 2000 mg/kg bodyweight (OECD 402)		
LC50 Inhalation - Rat	> 5.53 mg/l/4h (OECD 403) (EBSI, 1988)		
Skin corrosion/irritation :	Not classified (Based on available data, the classification criteria are not met)		
Additional information :	pH: Not determined (according to composition)		
	This product contains components with a Specific Concentration Limit (SCL).		
Distillates (petroleum), solvent-dewaxed light	paraffinic (64742-56-9)		
рН	Not applicable		
Distillates (petroleum), solvent-dewaxed heav	y paraffinic (64742-65-0)		
рН	Not applicable		
Distillates (petroleum) hydrotreated light para	ffinic (64742-55-8)		
рН	Not applicable		
Distillates (petroleum), solvent-refined light p	araffinic (64741-89-5)		
рН	Not applicable		
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)			
рН	Not applicable		
	Not classified (Based on available data, the classification criteria are not met) pH: Not determined		
	(according to composition)		
	This product contains components with a Specific Concentration Limit (SCL).		
Distillates (petroleum), solvent-dewaxed light	paraffinic (64742-56-9)		
рН	Not applicable		
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)			
рН	Not applicable		
Distillates (petroleum) hydrotreated light para	Distillates (petroleum) hydrotreated light paraffinic (64742-55-8)		
рН	Not applicable		
Distillates (petroleum), solvent-refined light paraffinic (64741-89-5)			
рН	Not applicable		
Distillates (petroleum), hydrotreated heavy pa	raffinic (64742-54-7)		
рН	Not applicable		
Respiratory or skin sensitisation :	Not classified (Based on available data, the classification criteria are not met)		

Safety Data Sheet

Additional information :	(according to composition) Contains {0 message= <name of="" sensitizing<br="" the="">substance> fieldvalue=_SENSITIZER_COMPONENTS}. On basis of test data: not sensitising. This evaluation is based on the information provided by the suppliers. This result has been used for classification of the final mixture (Bridging principle "Dilution"). Exposure may produce an allergic reaction</name>
	Not classified (Based on available data, the classification criteria are not met) (according to composition)
	Not classified (Based on available data, the classification criteria are not met)
	(according to composition) This product contains : Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.], Distillates (petroleum), solvent dewaxed heavy paraffinic, clay- treated; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating dewaxed heavy paraffinic distillate with neutral or modified clay in either a contacting or percolation process. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50.], Distillates (petroleum), solvent dewaxed light paraffinic, hydrotreated; Baseoil— unspecified; [A complex combination of hydrocarbons produced by Treating a dewaxed light paraffinic distillate with hydrogen in the presence of a catalyst. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C15 through C30.], Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil— unspecified; [A complex combination of hydrocarbons obtained from a catalytic dewaxing process. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least 100 SUS at 100 °F (19cSt at 40 °C).], Lubricating oils (petroleum), C24- 50, solvent-extd, dewaxed, hydrogenated; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by solvent extraction and hydrogenation of atmospheric distillation residues. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C24 through C50 and produces a finished oil with a viscosity in the order of 16cSt to 75cSt at 40 °C (104 °F).]
	Not classified (Based on available data, the classification criteria are not met) (according to composition)
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate) (93819-94-4)
NOAEL (animal/male, F0/P)	160 mg/kg (OECD TG 422)
Distillates (petroleum), hydrotreated heavy pa	araffinic (64742-54-7)
NOAEL (animal/male, F0/P)	1000 mg/kg bodyweight
STOT-single exposure : Additional information :	Not classified (Based on available data, the classification criteria are not met) (according to composition)
STOT-repeated exposure :	Not classified (Based on available data, the classification criteria are not met)
Additional information :	(according to composition)
C14-16-18 Alkyl phenol	
NOAEL (oral, rat, 90 days)	30 – 100 mg/kg bodyweight/day
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Distillates (petroleum), solvent-dewaxed light	paraffinic (64742-56-9)
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)
Distillates (petroleum), solvent-dewaxed heav	y paraffinic (64742-65-0)
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)

Safety Data Sheet

Paraffin oils (petroleum), catalytic dewaxed h	eavy, Baseoil - unspecified (64742-70-7)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day	
NOAEL (dermal, rat/rabbit, 90 days)	30 – 2000 mg/kg bodyweight/day	
NOAEC (inhalation,rat, vapour, 90 days)	980 mg/m ³	
Distillates (petroleum) hydrotreated light para		
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)	
Distillates (petroleum), solvent-refined light p		
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)	
Distillates (petroleum), hydrotreated heavy pa	araffinic (64742-54-7)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)	
Additional information :	Not classified (Based on available data, the classification criteria are not met) (according to composition) Viscosity, kinematic: > 20,5 mm2/s (40 °C) (ASTM D 445)	
Eni i-Sint tech F 5W-30		
Viscosity, kinematic	56 mm²/s (40 °C) (ASTM D 445)	
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)		
Viscosity, kinematic	15 – 16.5 mm²/s (40 °C) (ASTM D 445)	
Distillates (petroleum), solvent-dewaxed heav	y paraffinic (64742-65-0)	
Viscosity, kinematic	< 20.5 mm²/s (40 °C) (ASTM D 445)	
Distillates (petroleum) hydrotreated light paraffinic (64742-55-8)		
Viscosity, kinematic	> 20.5 mm²/s (40 °C) (ASTM D 445)	
Distillates (petroleum), solvent-refined light paraffinic (64741-89-5)		
Viscosity, kinematic	12.5 – 14.5 mm²/s (40°C, ASTM D 445)	
Distillates (petroleum), hydrotreated heavy pa	araffinic (64742-54-7)	
Viscosity, kinematic	17.9 mm²/s (40 °C) (ASTM D 445)	
11.2. Information on other hazards		
11.2.1. Endocrine disrupting properties		
disrupting properties	The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %	
11.2.2. Other information		
symptoms	Contact with eyes may cause temporary reddening and irritation,Prolonged and repeated skin contact may cause reddening, irritation and dermatitis,May produce an allergic reaction,Avoid all eye and skin contact and do not breathe vapour and mist	
Other information :	None	

Safety Data Sheet

SECTION 12: Ecological information			
12.1. Toxicity			
Ecology - air :	The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment. An uncontrolled release to the environment may nevertheless produce a contamination of different environmental compartments (air, soil, underground, surface water bodies, aquifers). Handle according to general working hygiene practices to avoid pollution and release into the environment. This product has a low vapour pressure, and in normal conditions at ambient temperature the concentration in the air is negligible. A significant concentration may build up only in case of sprays and mists. In these cases overexposure to mists (e.g. through prolonged use in confined insufficiently ventilated spaces) may cause irritation to airways, nausea and dizziness.		
	This product is not soluble in water. It floats on water and forms a film on the surface. The damage to aquatic organisms is of mechanical kind (immobilization and entrapment) Not classified (Based on available data, the classification criteria are not met)		
(acute)			
	Not classified (Based on available data, the classification criteria are not met)		
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)	bis(dithiophosphate) (93819-94-4)		
LC50 fish 1	4.5 mg/l (96h - Oncorhynchus mykiss) (OECD 203)		
EC50 Daphnia 1	5.4 mg/l (48h)		
EC50 96h - Algae [1]	2.1 mg/l (Selenastrum capricornutum)		
ErC50 (algae)	2.1 mg/l (96h - Selenastrum capricornutum) (OECD 201)		
C14-16-18 Alkyl phenol			
EC50 Daphnia 1	100 mg/l		
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)			
LC50 fish 1	> 100 mg/l (LL 50)		
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)		
Distillates (petroleum), solvent-dewaxed heav	y paraffinic (64742-65-0)		
LC50 fish 1	> 100 mg/l (LL 50)		
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)		
Paraffin oils (petroleum), catalytic dewaxed he	eavy, Baseoil - unspecified (64742-70-7)		
LC50 fish 1	100 mg/l (LL50)		
EC50 Daphnia 1	10 g/l (EL50)		
NOEC chronic fish	1 g/l (NOELR, 14d)		
Distillates (petroleum) hydrotreated light para	ffinic (64742-55-8)		
LC50 fish 1	100 – 10000 mg/l (LL 50)		
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)		
EC50 72h - Algae [1]	100 mg/l (EL0, Pseudokirchneriella subcapitata)		
NOEC (chronic)	10 – 1000 mg/l (NOELR, Daphnia Magna)		
NOEC chronic algae	100 mg/l (72h, Pseudokirchneriella subcapitata)		
Distillates (petroleum), solvent-refined light p	araffinic (64741-89-5)		
LC50 fish 1	> 100 mg/l (LL 50)		
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)		

Safety Data Sheet

Distillates (petroleum), hydrotreated heavy pa	raffinic (64742-54-7)	
LC50 fish 1	> 100 mg/l (LL 50)	
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)	
12.2. Persistence and degradability		
Eni i-Sint tech F 5W-30		
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.	
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)]	bis(dithiophosphate) (93819-94-4)	
Biodegradation	1.5 % (28d) (OECD 301 B)	
C14-16-18 Alkyl phenol		
Biodegradation	24 % (Zahn-Wellens, 10-20 %)	
Distillates (petroleum), solvent-dewaxed light	paraffinic (64742-56-9)	
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.	
Distillates (petroleum), solvent-dewaxed heav	y paraffinic (64742-65-0)	
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.	
Distillates (petroleum) hydrotreated light paraffinic (64742-55-8)		
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.	
Biodegradation	< 60 % (28d)	
Distillates (petroleum), solvent-refined light pa	araffinic (64741-89-5)	
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.	
Biodegradation	31 % (28d, Exxon 1995)	
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.	
12.3. Bioaccumulative potential		
Eni i-Sint tech F 5W-30		
Log Pow	Not applicable for mixtures	

Log Kow	Not applicable for mixtures	
Bioaccumulative potential	Not established.	
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate) (93819-94-4)		
Log Pow	0.9 (23 °C)	

Safety Data Sheet

C14-16-18 Alkyl phenol	C14-16-18 Alkyl phenol	
Log Kow	4.5 (0.1 d, 10-20 %)	
Distillates (petroleum) hydrotreated light para	affinic (64742-55-8)	
Log Kow	< 1	
Distillates (petroleum), solvent-refined light p	araffinic (64741-89-5)	
Bioaccumulative potential	The test methods for this endpoint are not applicable to UVCB substances.	
12.4. Mobility in soil		
Eni i-Sint tech F 5W-30		
Mobility in soil	Not determined	
Ecology - soil	No data available.	
Distillates (petroleum), solvent-refined light p	araffinic (64741-89-5)	
Ecology - soil	This product is not soluble in water. It floats on water and forms a film on the surface.	
12.5. Results of PBT and vPvB assessment		
Eni i-Sint tech F 5W-30		
This substance/mixture does not meet the PBT criteria	of REACH regulation, annex XIII	
This substance/mixture does not meet the vPvB criteria	a of REACH regulation, annex XIII	
Results of PBT-vPvB assessment	The components in this formulation do not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)	
Component		
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate) (93819-94-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)	
C14-16-18 Alkyl phenol	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)	
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)	
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)	
Paraffin oils (petroleum), catalytic dewaxed heavy, Baseoil - unspecified (64742-70-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Component	
Distillates (petroleum) hydrotreated light paraffinic (64742-55-8)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Distillates (petroleum), solvent-refined light paraffinic (64741-89-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)
12.6. Endocrine disrupting properties	
Adverse effects on the environment caused by : endocrine disrupting properties	The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.
12.7. Other adverse effects	
Other adverse effects : Additional information :	None. This product has no specific properties for inhibition of bacterial activity. In any case, wastewater containing this product should be treated in plants that are suited for the specifi purpose.

SECTION 13: Disposal considerations			
13.1. Waste treatment methods			
Waste treatment methods	: Do not dispose of the product, either new or used, by dumping on the ground, or discharging into sewers, tunnels, lakes or water courses. Deliver to a qualified official collector.		
Sewage disposal recommendations	: Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed. Dispose of in a safe manner in accordance with local/national regulations.		
Product/Packaging disposal recommendations	: European Waste Catalogue code(s) (Decision 2001/118/CE): 13 02 05* (mineral-based non-chlorinated engine, gear and lubricating oils). This EWC code is only a general indication, and takes into account the original composition of the product and its intended use. The user has the responsibility of choosing the right EWC code, considering the actual use of the product, alterations and contaminations.		
Additional information	: Empty containers may contain combustible product residues. Do not cut, weld, bore, burn or incinerate emptied containers, unless they have been cleaned and declared safe.		
Ecology - waste materials EURAL code (EWC)	 The product as it is does not contain halogenated substances. 13 02 05* - Mineral-based non-chlorinated engine, gear and lubricating oils 		

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID				
ADR IMDG IATA A		ADN	RID	
14.1. UN number or ID number				
Not regulated for transport				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Not regulated Not regulated	Not regulated	Not regulated	Not regulated
)			
-	Not regulated	Not regulated	Not regulated
lot regulated	Not regulated	Not regulated	Not regulated
		J	. tet regulated
lot regulated	Not regulated	Not regulated	Not regulated
1			
Not regulated	Not regulated	Not regulated	Not regulated

14.6. Special precautions for user

Overland transport Not regulated

Transport by sea Not regulated

Air transport Not regulated

Inland waterway transport

Not regulated

Rail transport

Not regulated

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Other information, restriction and prohibition Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 regulations December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). (et sequens). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (et sequens). Directives 89/391/CEE, 89/654/CEE, 89/655/CEE, 89/656/CEE, 90/269/CEE, 90/270/CEE, 90/394/CEE, 90/679/CEE, 93/88/CEE, 95/63/CE, 97/42/CE, 98/24/CE, 99/38/CE, 99/92/CE, 2001/45/CE, 2003/10/CE, 2003/18/CE (Health and safety on the workplace). Directive 2012/18/CE (Control of major-accident hazards involving dangerous substances). Directive 2004/42/CE (Limitation of emissions of Volatile Organic Compounds). Directive 98/24/EC (protection of the health and safety of workers from the risks related to chemical agents at work). Directive 92/85/CE (measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding). Substances Depleting the Ozone layer (1005/2009) - Annex I Substances (ODP). Regulation EU (649/2012) - Export and Import of hazardous chemicals (PIC). Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants).

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

No ingredients are included in the REACH Candidate list (> 0,1 % m/m).

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

National adoption of EU Directives concerning health and safety on the workplace.

National adoption of EU Directives concerning control of major-accident hazards involving dangerous substances (2012/18/CE).

Relevant national laws on prevention of water pollution.

Relevant national laws on protection of the health of pregnant workers (National adoption of Dir. 92/85/EEC).

National adoption of Directive 2008/98/CE concerning disposal of used oils.

France

Maladies professionelles (F)		
Code	Description	
RG 36	Diseases caused by oils and fats of mineral or synthetic origin	
Germany		
Employment restrictions		: Employment prohibitions or restrictions on the protection of young people at work according to § 22 JArbSchG in the case of formation of hazardous substances have to be observed.
National Rules and Recomn	nendations	 TRGS 400: Hazard assessment for activities involving Hazardous Substances. TRGS 401: Risks resulting from skin contact - identification, assessment, measures. TRGS 402: Identification and Assessment of the Risks from Activities involving Hazardous Substances: Inhalation Exposure. TRGS 555: Working instruction and information for workers. TRGS 800: Fire protection measures. TRGS 900: Occupational Exposure Limits.
VbF class (D)		: Not applicable.
Water hazard class (WGK) (WGK remark	(D)	 WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1). Classification is carried out on the basis of the Ordinance on facilities for handling substances that are hazardous to water (Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV)) of 18 April 2017 (BGBI 2017, Teil I, Nr. 22, Seite
		905).
Storage class (LGK, TRGS	510)	: LGK 10 - Combustible liquids.
Hazardous Incident Ordinance (12. BImSchV)		: Is not subject to the Hazardous Incident Ordinance (12. BImSchV)
Netherlands		
Saneringsinspanningen SZW-lijst van kankerverwek SZW-lijst van mutagene stof SZW-lijst van reprotoxische	ffen	 C - Minimize discharge None of the components are listed None of the components are listed None of the components are listed

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SZW-lijst van reprotoxische stoffen –	: None of the components are listed
Vruchtbaarheid SZW-lijst van reprotoxische stoffen – Ontwikkeling	: None of the components are listed
Denmark	
MAL code	: 00-1 (Executive Order No. 301 from 1993)
Danish National Regulations	Young people under 18 years are not allowed to use the product
	Pregnant/breastfeeding women working with the product must not be in direct contact with it
Switzerland	
Storage class (LK)	: LK 10/12 - Liquids

15.2. Chemical safety assessment

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP] No chemical safety assessment has been carried out

A chemical safety assessment has been carried out for the following components of this mixture::

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)

C14-16-18 Alkyl phenol

Distillates (petroleum), solvent-dewaxed light paraffinic

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Paraffin oils (petroleum), catalytic dewaxed heavy, Baseoil - unspecified

Distillates (petroleum) hydrotreated light paraffinic

Distillates (petroleum), solvent-refined light paraffinic

Distillates (petroleum), hydrotreated heavy paraffinic

SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Notes
1.3	Supplier information	Modified	

Abbreviations and acronyms:		
	Complete text of the H phrases quoted in this Safety Data Sheet. These phrases are reported here for information only, and MAY NOT correspond to the classification of the product.	
	N/A = not applicable	
	N/D = not available	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC50	Effective concentration for 50 percent of test population (median effective concentration)	
IARC	International Agency for Research on Cancer	
ΙΑΤΑ	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Lethal concentration for 50 percent of test population (median lethal concentration)	
LD50	Lethal dose for 50 percent of test population (median lethal dose)	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Abbreviations and acronyms:		
LOAEL	Lowest Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
OECD	Organisation for Economic Co-operation and Development	
РВТ	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals, Regulation (EC) No 1907/2006	
RID	Regulation concerning the International Carriage of Dangerous Goods by Railways	
SDS	Safety Data Sheet	
STP	Sewage treatment plant	
vPvB	Very Persistent and Very Bioaccumulative	

Data sources

Training advice

Other information

: This Safety Data Sheet is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.

: Provide adequate training to professional operators for the use of PPEs, according to the information contained in this Safety Data Sheet.

: Do not use the product for any purposes that have not been advised by the manufacturer. In exceptional cases (i.e prolonged storage in tanks contaminated with water, and presence of anaerobic sulfate-reducing microbial colonies), the product may undergo a degradation and generate small amounts of sulfur compounds, including H2S. This situation is especially relevant in all those circumstances which require to enter a confined space, with direct exposure to the vapours. If this possibility is suspected, a specific assessment of inhalation risks from the presence of H2S in confined spaces must be made, to help determine prevention measures and controls (i.e. PPE) appropriate to local circumstances, and adequate emergency procedures. If there is any suspicion of inhalation of H2S (hydrogen sulphide), Rescuers must wear breathing apparatus, belt and safety rope, and follow rescue procedures. Send patient to hospital. Immediately begin artificial respiration if breathing has ceased. Administer oxygen if necessary. This situation is especially relevant for those operations which involve direct exposure to the vapours in the interior of tanks or other confined spaces. Therefore, it is very important to follow the above mentioned precautionary measures also with used oils.

Full text of H- and EUH-statements:		
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2	
Asp. Tox. 1	Aspiration hazard, Category 1	
EUH208	Contains C14-16-18 Alkyl phenol. May produce an allergic reaction.	
EUH210	Safety data sheet available on request.	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
H304	May be fatal if swallowed and enters airways.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H319	Causes serious eye irritation.	
H373	May cause damage to organs through prolonged or repeated exposure.	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Full text of H- and EUH-statements:	
H411	Toxic to aquatic life with long lasting effects.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.