

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878 Revision date: 7/24/2024 Supersedes: 12/27/2023 Version: 1.1

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **1.1. Product identifier** Product form : Mixture : Eni i-Sint tech R 5W-30 Trade name Product code : 1015 Type of product : Lubricant Formula : 0019-2019 Product group : Trade product 1.2. Relevant identified uses of the substance or mixture and uses advised against 1.2.1. Relevant identified uses Main use category : Industrial use, Professional use, Consumer use Industrial/Professional use spec : Used in closed systems Wide dispersive use Use of the substance/mixture : Lubricant for internal combustion engines Do not use the product for any purposes that have not been advised by the manufacturer. Function or use category : Lubricants and additives 1.2.2. Uses advised against No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Enilive S.p.A, Viale Giorgio Ribotta 51, 00144 Rome, ITALY, Tel. +39 06 59821, www.eni.com Competent person responsible for the safety data sheet (Reg. EC nr. 1907/2006): SDS.Enilive@eni.com

Distributed by: Enilive Schmiertechnik GmbH, Paradiesstraße 14, 97080 Würzburg, GERMANY, www.oilproducts.eni.com Department responsible for information: Application Engineering & Product Management (AEPM), Tel. +49 (0)931-900 98-0

e-mail: technik.wuerzburg@enilive.com

1.4. Emergency telephone number

Emergency number

: CNIT +39 0382 24444 (24h) (IT + EN) Poison Center

## **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]

Hazardous to the aquatic environment – Chronic Hazard, H412

Category 3 Full text of H- and EUH-statements: see section 16

## Adverse physicochemical, human health and environmental effects

Contact with eyes may cause temporary reddening and irritation. For specific information about the toxicological/ecotoxicological properties and classification of this product, see Sect. 11 and/or Sect. 12.

### 2.2. Label elements

### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

CLP Signal word	: •
Hazard statements (CLP)	: H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P273 - Avoid release to the environment.
	P501 - Dispose of contents/container to hazardous or special waste collection point, in
	accordance with local, regional, national and/or international regulation.

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

2.3. Other hazards (not relevant for classification)		
Other hazards not contributing to the classification	: This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels. If the product is handled or used at high temperature, contact with hot product or vapours may cause burns. Do not wait for symptoms to develop. Any substance, in case of accidents involving pressurized circuits and the like, may be accidentally injected under the skin, even without external damage. In such a case, the victim should be brought to an hospital as soon as possible, to get specialized medical treatment.	

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII Contains no PBT and/or vPvB substances  $\geq$  0.1% assessed in accordance with REACH Annex XIII

Component	
Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7), Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7), reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0), Dodecylphenol, mixed isomers, branched (121158-58-5)( <sup>1</sup> ), Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)
Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7), Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7), reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0), Dodecylphenol, mixed isomers, branched (121158-58-5)( <sup>1</sup> ), Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)

(1) Substance(s) in concentration below 0.1 % and displayed on a voluntary basis

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Component	
Substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	Dodecylphenol, mixed isomers, branched (121158-58-5)(1)
Substance(s) not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7), Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7), reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)

 $(\ensuremath{^1})$  Substance(s) in concentration below 0.1 % and displayed on a voluntary basis

### SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

## 3.2. Mixtures

### Comments

: Composition/information on ingredients Additives Mixture of hydrocarbons Mineral base oil, severely refined

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]
Distillates (petroleum), hydrotreated heavy paraffinic (Main component, see note [**]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627- 25	80 - 90	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated heavy paraffinic (see note [**]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627- 25	20 – 25	Not classified
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (see note [**]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	CAS-No.: 72623-87-1 EC-No.: 276-738-4 EC Index-No.: 649-483-00-5 REACH-no: 01-2119474889- 13	10 – 15	Not classified
Mineral base oil, severely refined (For identification of the substance, see note [*] ) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	EC-No.: N/A	1 - 10	Not classified
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert- butyl-4-hydroxyphenyl)propionate (Additive)	CAS-No.: 125643-61-0 EC-No.: 406-040-9 EC Index-No.: 607-530-00-7 REACH-no: 01-0000015551- 76	1 - 2	Aquatic Chronic 4, H413
Diphenylamine substance with national workplace exposure limit(s) (AT, BE, DE, DK, ES, FR, GB, IE, SE)	CAS-No.: 122-39-4 EC-No.: 204-539-4 EC Index-No.: 612-026-00-5 REACH-no: N/D	0.13 – 0.65	Acute Tox. 3 (Inhalation), H331 (ATE=0.5 mg/l/4h) Acute Tox. 3 (Dermal), H311 (ATE=300 mg/kg bodyweight) Acute Tox. 3 (Oral), H301 (ATE=100 mg/kg bodyweight) STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
phenol, dodecyl-, branched; phenol, 2-dodecyl-, branched; phenol, 3-dodecyl-, branched (Additive) Substance included in REACH Candidate List (Phenol, alkylation products (mainly in para position) with C12-rich branched alkyl chains from oligomerisation, covering any individual isomers and/ or combinations thereof (PDDP))	CAS-No.: 121158-58-5 EC-No.: 310-154-3 EC Index-No.: 604-092-00-9 REACH-no: 01-2119513207- 49	0.001 – 0.033	Skin Corr. 1C, H314 Eye Dam. 1, H318 Repr. 1B, H360F Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Comments	<ul> <li>[*] Note: this product may be formulated with one or more of the following severely refined mineral base oils (not classified as hazardous):</li> <li>CAS 64742-54-7/EC 265-157-1/REACH Reg. # 01-2119484627-25-xxxx; CAS 64742-65-</li> </ul>
	0/EC 265-169-7/REACH Reg. # 01-2119471299-27-xxxx; CAS 64742-70-7/EC 265-174-
	4/REACH Reg. # 01-2119487080-42-xxxx; CAS 64742-56-9/EC 2265-159-2/ REACH Reg. # 01-2119480132-48-xxxx.
	All these substances have a value < 3 % wt of DMSO extract, according to IP 346 (Nota L - Annex VI Reg (CE) 1272/2008, # 1.1.3)
	Note [**]:
	this product has a value of DMSO extract < 3 % wt, according to IP 346. According to the
	criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product must be regarded as non carcinogenic.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures after inhalation	: In case of disturbances owing to inhalation of vapours or mists, remove the victim from exposure; keep at rest; if necessary, seek medical attention. See also section 4.3.
First-aid measures after skin contact	: Take off contaminated clothing and shoes. Wash thoroughly with soap and water. If inflammation or irritation persists, seek medical advice. In case of burns, cool affected part with cold running water for at least 10 min. Cover with gauze or clean cloth. Ask for medical assistance or bring to a hospital. Do not apply salves or other substances, unless by doctor's advice. Do not put ice on the burn.
First-aid measures after eye contact	<ul> <li>Rinse eyes thoroughly for at least 15 minutes. Keep eyelids well apart. If irritation persists, seek medical advice. In case of burns, cool affected part with cold running water for at least 10 min. Cover with gauze or clean cloth. Ask for medical assistance or bring to a hospital. Do not apply salves or other substances, unless by doctor's advice.</li> </ul>
First-aid measures after ingestion	: Do not induce vomiting to avoid aspiration into the lungs. Keep at rest. If the person is conscious, rinse mouth with water without swallowing. Keep at rest. Call for medical assistance or bring to an hospital. If the casualty is unconscious, place in the recovery position. In case of spontaneous vomiting, keep head low, to avoid the risk of aspiration into the lungs. Do not give anything by mouth to an unconscious person.
4.2. Most important symptoms and effects,	, both acute and delayed
Symptoms/effects after inhalation	: This product has a low vapour pressure, and in normal conditions at ambient temperature the concentration in the air is negligible. A significant concentration may build up only in case of sprays and mists. In these cases overexposure to mists (e.g. through prolonged use in confined insufficiently ventilated spaces) may cause irritation to airways, nausea and dizziness.
Symptoms/effects after skin contact	: Contact with hot product may cause thermal burns.
Symptoms/effects after eye contact	: Contact with eyes may cause a light transient irritation. Contact with hot product or vapours may cause burns.
Symptoms/effects after ingestion	<ul> <li>Accidental ingestion of small quantities of the product may cause irritation, nausea and gastric disturbances. Taking into account the taste of the product, however, ingestion of dangerous quantites is very unlikely.</li> </ul>
Symptoms/effects upon intravenous administration	: No information available.
Chronic symptoms	: None to be reported, according to the present classification criteria.
4.3 Indication of any immediate modical at	tention and enabled treatment needed

4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical attention if casualty has an altered state of consciousness or if symptoms do not resolve. Seek medical attention in all cases of serious burns.

## Safety Data Sheet

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media Unsuitable extinguishing media	<ul> <li>Small-size fires: carbon dioxide, dry chemicals, foam, sand or earth. Large fires: foam or water fog (mist). These means should be used by trained personnel only. Other extinguishing gases (according to regulations).</li> <li>Do not use water jets. They could cause splattering, and spread the fire. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.</li> </ul>
5.2. Special hazards arising from the subs	tance or mixture
Fire hazard Explosion hazard Hazardous decomposition products in case of fire	<ul> <li>This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels.</li> <li>In case of losses from pressurized circuits, the sprays may form mists. Take into account that in this case the lower explosion limit for mists is about 45 g/m<sup>3</sup> air.</li> <li>Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases. Oxygenated compounds (aldehydes, etc.). POx. ZnOx. CaOx.</li> </ul>
5.3. Advice for firefighters	
Firefighting instructions Special protective equipment for firefighters	<ul> <li>Shut off source of product, if possible. If possible, move containers and drums away from the danger area, if safe to do so. Spilled product which is not burning should be covered with sand or foam. Use water sprays to cool containers and surfaces exposed to the flames. If the fire cannot be controlled, evacuate area.</li> <li>Wear personal protection equipment. (see chapter 8). In case of a large fire or in confined or poorly ventilated spaces, wear full fire resistant protective clothing and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. EN</li> </ul>
Other information	<ul> <li>443. EN 469. EN 659.</li> <li>In case of fire, do not discharge residual product, waste materials and runoff water: collect separately and use a proper treatment.</li> </ul>

SECTION 6: Accidental releas	e measures
6.1. Personal precautions, protec	tive equipment and emergency procedures
General measures	: Stop or contain leak at the source, if safe to do so. Eliminate all ignition sources if safe to do so (e.g. electricity, sparks, fires, flares). Avoid direct contact with released material. Avoid accidental sprays on hot surfaces or electrical contacts. Keep upwind.
6.1.1. For non-emergency personnel	
Protective equipment	: See Section 8.
Emergency procedures	: Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency.
6.1.2. For emergency responders	
Protective equipment	: Small spillages: normal antistatic working clothes are usually adequate. Large spillages: full body suit of chemically resistant and antistatic material. if necessary heat resistant and insulated. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Gloves made of PVA are not water-resistant, and are not suitable for emergency use. If contact with hot product is possible or anticipated, gloves should be heat resistant and thermally insulated. Antistatic non-skid safety shoes or boots, chemical resistant, if necessary heat resistant and insulated. Work helmet. Goggles and /or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory protection: a half or full-face respirator with filter(s) for organic vapours (AX), or a Self-contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. A Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
Emergency procedures	: If required, notify relevant authorities according to all applicable regulations.

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

C.2. Methode and meterial for containment and ale

### 6.2. Environmental precautions

Do not let the product accumulate in confined or underground spaces. Do not let the product flow into sewers or water courses, or in any way contaminate the environment. In case of contamination of environment compartments (soil, subsoil, surface or underground waters), remove contaminated soil when possible, and in any case treat all involved compartments in accordance with local regulations. The site should have a spill plan to ensure that adequate safeguards are in place to minimize the impact of episodic releases.

6.3. Methods and material for containment and cleaning up	
For containment	: Contain spilled liquid with sand, earth or other suitable absorbents (non-flammable). Recover free liquid and waste materials in suitable waterproof and oil-resistant containers. Clean contaminated area. Dispose of according to local regulations. If in water: Confine the spillage. Remove from surface by skimming or suitable floating absorbents. Collect recovered product and other waste materials in suitable waterproof, oil resistant containers. Recover or dispose of according to local regulations. Do not use solvents or dispersants, unless specifically advised by an expert, and, if required, approved by local authorities.
Other information	Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air/water temperature, wave/current direction and speed) may significantly influence the choice of appropriate actions. Local regulations may also prescribe or limit actions to be taken. For this reason, local experts should be consulted when necessary.

### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage			
7.1. Precautions for safe handling			
Precautions for safe handling Hygiene measures	<ul> <li>Ensure that all relevant regulations regarding handling and storage facilities of flammable products are followed. Do not use compressed air for filling, discharging, or handling operations. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use and store only outdoors or in a well-ventilated area. During transfer operations, ensure that all equipment and containers are correctly grounded. Avoid the build-up of electric charges. Emptied containers can contain combustible product residues. Do not cut, weld, drill, burn or incinerate empty containers or drums, unless they have been drained and cleaned. Before entering storage tanks and commencing any operation in a confined area (e.g. tunnels), carry out an adequate clean-up, and check the atmosphere for oxygen content and flammability. See also Section 16, "Other information".</li> <li>Avoid contact with skin. Do not breathe fume/ mist/ vapours. Do not ingest. Do not smoke. Do not eat and do not drink during use. Do not clean hands with dirty or oil-soaked rags. Do not re-use clothes, if they are still contaminated. Keep away from food and beverages. Take off immediately all contaminated clothing and wash it before reuse. Contaminated materials should not be allowed to accumulate in the workplaces and should never be kept inside the pockets. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.</li> </ul>		
7.2. Conditions for safe storage, including	ng any incompatibilities		
Storage area	: Storage area layout, tank design, equipment and operating procedures must comply with the relevant European, national or local legislation. Storage installations/areas should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations.		
Packages and containers:	: If the product is supplied in containers: Keep containers tightly closed and properly labelled. Keep only in the original container or in a suitable container for this kind of product.		
Packaging materials	: For containers, or container linings use materials specifically approved for use with this product. Compatibility should be checked with the manufacturer, according to the specific use conditions.		
Germany			
Storage class (LGK, TRGS 510)	: LGK 10 - Combustible liquids		

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

#### Switzerland

Storage class (LK)

: LK 10/12 - Liquids

## 7.3. Specific end use(s)

No additional information available

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

### 8.1.1 National occupational exposure and biological limit values

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Belgium - Occupational Exposure Limits		
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Denmark - Occupational Exposure Limits		
OEL TWA	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
OEL STEL	2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KGV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
WEL STEL (OEL STEL)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH OEL STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Belgium - Occupational Exposure Limits		
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Denmark - Occupational Exposure Limits		
OEL TWA	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	

## Safety Data Sheet

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
OEL STEL	2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Hungary - Occupational Exposure Limits	·	
AK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Netherlands - Occupational Exposure Limits	·	
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits	·	
VLA-ED (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Sweden - Occupational Exposure Limits	·	
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KGV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
United Kingdom - Occupational Exposure Limits	·	
WEL TWA (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
WEL STEL (OEL STEL)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
USA - ACGIH - Occupational Exposure Limits	·	
ACGIH OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH OEL STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Mineral base oil, severely refined		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Belgium - Occupational Exposure Limits	·	
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Denmark - Occupational Exposure Limits	·	
OEL TWA	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
OEL STEL	2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Hungary - Occupational Exposure Limits	·	
AK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Netherlands - Occupational Exposure Limits	·	
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KGV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
United Kingdom - Occupational Exposure Limits	·	
WEL TWA (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
WEL STEL (OEL STEL)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	

## Safety Data Sheet

Mineral base oil, severely refined		
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH OEL STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Lubricating oils (petroleum), C20-50, hydrotre Baseoil - unspecified (72623-87-1)	ated neutral oil-based	
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Belgium - Occupational Exposure Limits		
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Denmark - Occupational Exposure Limits		
OEL TWA	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
OEL STEL	2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KGV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
WEL STEL (OEL STEL)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH OEL STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Diphenylamine (122-39-4)		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	< 5 mg/m³	
MAK [ppm]	0.7 ppm	
MAK (OEL STEL)	10 mg/m <sup>3</sup>	
MAK Short time value [ppm]	1.4 ppm	
Belgium - Occupational Exposure Limits	•	
OEL TWA	10 mg/m <sup>3</sup>	
Denmark - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
UEL I WA	o mg/m-	

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Diphenylamine (122-39-4)		
France - Occupational Exposure Limits		
VLE [mg/m³]	10 mg/m³	
Germany - Occupational Exposure Limits (TRGS 900)		
AGW (OEL TWA)	5 mg/m³ (Inhalable aerosol)	
Limitation of exposure peaks (mg/m³)	10 mg/m³ (Inhalable aerosol)	
Ireland - Occupational Exposure Limits		
OEL TWA	20 mg/m <sup>3</sup>	
OEL (15 min ref) (mg/m3)	10 mg/m <sup>3</sup>	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA)	10 mg/m³	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	4 mg/m <sup>3</sup>	
KGV (OEL STEL)	12 mg/m³	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA)	10 mg/m <sup>3</sup>	
WEL STEL (OEL STEL)	20 mg/m <sup>3</sup>	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	10 mg/m <sup>3</sup>	
8.1.2. Recommended monitoring procedures		

Monitoring methods	
Monitoring methods	Monitoring procedures should be chosen according to the indications set by national authorities or labour contracts. Refer to relevant legislation and in any case to the good practice of industrial hygiene.

## 8.1.3. Air contaminants formed

## No additional information available

8.1.4. DNEL and PNEC Eni i-Sint tech R 5W-30

DNEL/DMEL (additional information)	
Additional information	Not applicable
PNEC (additional information)	
Additional information	Not applicable
	The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a governmental regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH.

### 8.1.5. Control banding

No additional information available

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

#### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Before entering storage tanks and commencing any operation in a confined area (e.g. tunnels), carry out an adequate clean-up, and check the atmosphere for oxygen content and flammability. See also Section 16, "Other information".

### 8.2.2. Personal protection equipment

#### Personal protective equipment (for industrial or professional use):

Face shield. Gloves. Protective clothing. Safety glasses. Safety shoes or boots. Dust/aerosol mask with filter type P1.

#### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

No additional information available

#### 8.2.2.2. Skin protection

#### Skin and body protection:

Long-sleeved overalls. If necessary, refer to the EN 340 and related standards, for definition of characteristics and performance according to the risk rating of the area. Antistatic non-skid safety shoes or boots, chemical resistant, if necessary heat resistant and insulated.

#### Hand protection:

When there is a risk of contact with the skin, use waterproof gloves, resistant to chemical products. Gloves must be felt-lined. Adequate materials: nitrile (NBR) or PVC with a protection index > 5 (permeation time > 240 mins). Use gloves respecting all the conditions and within the limits set by the manufacturer. Replace gloves immediately in case of cuts, holes or other signs of damages or degradation. If necessary, refer to the EN 374 standard.

#### 8.2.2.3. Respiratory protection

#### **Respiratory protection:**

Independently from other possible actions (technical modifications, operating procedures, and other means to limit the exposure of workers), personal protection equipment can be used according to necessity. Open or well ventilated spaces: in presence of mists and if the product is handled without adequate containment means: use full or half-face masks with filter for mists/aerosols. (EN 136/140/145). Combination filter device (DIN EN 141). Closed or confined areas (e.g. tank interiors): the use of protection measures for airways (masks or self-contained breathing apparatus), must be assessed according to the specific activity, as well as level and duration of predicted exposure.

#### 8.2.2.4. Thermal hazards

#### Thermal hazard protection:

If contact with hot product is possible or anticipated, gloves should be heat-resistant and thermally insulated.

#### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Do not discharge the product into the environment. Prevent discharge of undissolved substance to or recover from onsite wastewater. Storage areas/installations should be designed with adequate bunds so as to prevent ground and water pollution in case of leaks or spills. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

#### Consumer exposure controls:

No special requirements.

SECTION 9: Physical and chemical properties		
9.1. Information on basic physical and chemical properties		
Physical state	: Liquid	
Colour	Yellow-brown.	
Appearance	: Liquid, bright & clear.	
Odour	: Slight odour of petroleum.	
Odour threshold	: There are no data available on the preparation/mixture itself.	
Melting point	: Not determined	

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Freezing point	: Not determined
Softening point	: -36 °C (ASTM D 97)
Boiling point	: Not determined
Flammability	: Not flammable
Lower explosion limit	: Not determined
Upper explosion limit	: Not determined
Flash point	: > 200 °C (ASTM D 92)
Auto-ignition temperature	: Not determined
Decomposition temperature	: Not determined
pH	: Not applicable
Viscosity, kinematic	: 70 mm²/s (40 °C) (ASTM D 445)
Solubility	: Water: Immiscible and insoluble
Log Kow	: Not available
Log Pow	: Not applicable for mixtures
Vapour pressure	: Not determined
Vapour pressure at 50°C	: Not determined
Density	: 850 kg/m <sup>3</sup>
Relative density	: Not determined
Relative vapour density at 20°C	: Not determined
Particle characteristics	: Not applicable

#### 9.2. Other information

9.2.1. Information with regard to physical hazar	d classes
Explosion limits	: ≥ 45 g/m³ (Aerosol)
9.2.2. Other safety characteristics	
Relative evaporation rate (butylacetate=1) Additional information	: Negligible. : No data available

### **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

This mixture does not offer any further hazard for reactivity, except what is reported in the following paragraphs.

#### 10.2. Chemical stability

No additional information available

### 10.3. Possibility of hazardous reactions

None (in normal conditions of storage and handling). Contact with strong oxidizers (peroxides, chromates, etc.) or alkali metals may cause a fire hazard. Sensitivity to heat, friction or shock cannot be assessed in advance.

#### **10.4. Conditions to avoid**

Keep away from open flames, hot surfaces and sources of ignition. Avoid the build-up of electrostatic charge.

### 10.5. Incompatible materials

Strong oxidizing agents.

### **10.6. Hazardous decomposition products**

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition may produce : Toxic fumes.

SECTION 11: Toxicological information		
11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008		
Acute toxicity (oral) Acute toxicity (dermal)	<ul> <li>Not classified (Based on available data, the classification criteria are not met)</li> <li>Not classified (Based on available data, the classification criteria are not met)</li> </ul>	

: Not classified (Based on available data, the classification criteria are not met)

## Safety Data Sheet

	·	
	(according to composition)	
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
LD50 oral rat	> 5000 mg/kg (OECD 401)	
LD50 dermal rat	> 5000 mg/kg (OECD 402)	
LC50 Inhalation - Rat	> 5 mg/l/4h (OECD 403)	
Distillates (petroleum), hydrotreated heavy p	araffinic (64742-54-7)	
LD50 oral rat	> 5000 mg/kg (OECD 401)	
LD50 dermal rat	> 5000 mg/kg (OECD 402)	
LD50 dermal rabbit	> 2000 mg/kg bodyweight	
LC50 Inhalation - Rat	> 5.53 mg/l/4h (EBSI, 1988)	
Mineral base oil, severely refined		
LD50 oral rat	> 5000 mg/kg bodyweight (OECD 401)	
LD50 dermal rat	> 5000 mg/kg bodyweight (OECD 402)	
LC50 Inhalation - Rat	> 5 mg/l/4h (OECD 403)	
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)		
LD50 oral rat	500 – 2000 mg/kg bodyweight	
LD50 dermal rat	2000 mg/kg bodyweight	
phenol, dodecyl-, branched; phenol, 2-dodec	yl-, branched; phenol, 3-dodecyl-, branched (121158-58-5)	
LD50 oral rat	2200 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)	
LD50 dermal rabbit	15000 mg/kg bodyweight	
Lubricating oils (petroleum), C20-50, hydrotr Baseoil - unspecified (72623-87-1)	eated neutral oil-based	
LD50 oral rat	> 5000 mg/kg (OECD 401)	
LD50 dermal rat	> 5000 mg/kg (OECD 402)	
LC50 Inhalation - Rat	> 5 mg/l/4h (OECD 403)	
Skin corrosion/irritation :	Not classified	
Additional information :	pH: Not applicable (according to composition)	
Distillates (petroleum), hydrotreated heavy p	araffinic (64742-54-7)	
pH	Not applicable	
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
рН	Not applicable	
Mineral base oil, severely refined		
рН	Not applicable	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)		
pH	Not applicable	
Serious eye damage/irritation :	Not classified pH: Not applicable	

## Safety Data Sheet

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
рН	Not applicable	
Distillates (petroleum), hydrotreated heavy pa	raffinic (64742-54-7)	
рН	Not applicable	
Mineral base oil, severely refined		
рН	Not applicable	
Lubricating oils (petroleum), C20-50, hydrotre Baseoil - unspecified (72623-87-1)	ated neutral oil-based	
рН	Not applicable	
Respiratory or skin sensitisation:Additional information:Germ cell mutagenicity:Additional information:Carcinogenicity:Additional information:	Not classified (according to composition) Not classified (Based on available data, the classification criteria are not met) (according to composition) Not classified (Based on available data, the classification criteria are not met) (according to composition) This product contains : Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] this product has a value of DMSO extract < 3 % wt, according to IP 346. According to the criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product must be regarded as non carcinogenic. All the mineral base oils contained in this product have a value < 3 % wt of DMSO extract, according to IP 346 (Nota L - Annex VI Reg (CE) 1272/2008, # 1.1.3)	
	Not classified (Based on available data, the classification criteria are not met) (according to composition)	
Distillates (petroleum), hydrotreated heavy pa	uraffinic (64742-54-7)	
NOAEL (animal/male, F0/P)	1000 mg/kg bodyweight	
phenol, dodecyl-, branched; phenol, 2-dodecy	/l-, branched; phenol, 3-dodecyl-, branched (121158-58-5)	
NOAEL (animal/male, F1)	1.5 mg/kg	
NOAEL (animal/female, F1)	15 mg/kg (OECD 416)	
STOT-single exposure : Additional information :	Not classified (Based on available data, the classification criteria are not met) (according to composition)	
reaction mass of isomers of: C7-9-alkyl 3-(3,5	-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)	
LOAEL (oral, rat)	5 mg/kg bw/day (28 d)	
	Not classified (Based on available data, the classification criteria are not met) (according to composition)	
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)	
Distillates (petroleum), hydrotreated heavy pa	raffinic (64742-54-7)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)	
Mineral base oil, severely refined		
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)	

## Safety Data Sheet

reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)		
NOAEL (oral, rat, 90 days)	5 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)		
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)	
Diphenylamine (122-39-4)		
NOAEL (oral, rat, 90 days)	3 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 452 (Chronic Toxicity Studies)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.	
Aspiration hazard : Additional information :	Not classified (Based on available data, the classification criteria are not met) Viscosity, kinematic: > 20,5 mm2/s (40 °C) (ASTM D 445)	
Eni i-Sint tech R 5W-30		
Viscosity, kinematic	70 mm²/s (40 °C) (ASTM D 445)	
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
Viscosity, kinematic	17.9 mm²/s (40 °C) (ASTM D 445)	
Distillates (petroleum), hydrotreated heavy pa	araffinic (64742-54-7)	
Viscosity, kinematic	36.82 mm²/s (40 °C) (ASTM D 445)	
Mineral base oil, severely refined		
Viscosity, kinematic	> 21 mm²/s	
Hydrocarbon	Yes	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)		
Viscosity, kinematic	48 mm²/s (40°C) (ASTM D 445)	
11.2. Information on other hazards		
11.2.1. Endocrine disrupting properties		
Adverse health effects caused by endocrine : disrupting properties	The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %	
Component		
phenol, dodecyl-, branched; phenol, 2-dodecyl-, branched; phenol, 3-dodecyl-, branched (121158-58- 5)	The substance is identified for having endocrine disrupting properties but there is no additional data available (see section 2.3)	
11.2.2. Other information		
symptoms	Contact with eyes may cause temporary reddening and irritation.	

## Safety Data Sheet

SECTION 12: Ecological information		
12.1. Toxicity		
Ecology - general Ecology - water Hazardous to the aquatic environment, short–term (acute) Hazardous to the aquatic environment, long–term (chronic)	<ul> <li>An uncontrolled release to the environment may nevertheless produce a contamination of different environmental compartments (air, soil, underground, surface water bodies, aquifers). Handle according to general working hygiene practices to avoid pollution and release into the environment.</li> <li>This product is not soluble in water. It floats on water and forms a film on the surface. The damage to aquatic organisms is of mechanical kind (immobilization and entrapment)</li> <li>Not classified (Based on available data, the classification criteria are not met)</li> <li>Harmful to aquatic life with long lasting effects.</li> </ul>	
Distillates (petroleum), hydrotreated heav	y paraffinic (64742-54-7)	
LC50 fish 1	> 100 mg/l (LL 50)	
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)	
Distillates (petroleum), hydrotreated heav	y paraffinic (64742-54-7)	
LC50 fish 1	> 100 mg/l (LL 50)	
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)	
Mineral base oil, severely refined		
LC50 fish 1	> 100 mg/l (LL 50)	
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)	
reaction mass of isomers of: C7-9-alkyl 3-	-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)	
LC50 fish 1	> 74 mg/l (Brachydanio rerio, OECD 203)	
LC50 fish 2	> 2 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)	
EC50 Daphnia 1	> 100 mg/l (24h, OECD 202)	
EC50 Daphnia 2	> 1000 mg/l Test organisms (species): Daphnia magna	
EC50 72h - Algae [1]	> 3 mg/l (Scenedesmus sp, OECD 201)	
ErC50 (algae)	> 33.7 mg/l (OECD 201, 72 h, Pseudokirchnerella subspicata)	
NOEC (acute)	33.7 mg/l (72 h, Pseudokirchnerella subspicata)	
NOEC (chronic)	≤ 0.01 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
NOEC chronic crustacea	≥ 1 mg/l (21d, Daphnia magna)	
Dodecylphenol, mixed isomers, branched	l (121158-58-5)	
LC50 fish 1	40 mg/l (Pimephales promelas)	
EC50 Daphnia 1	92.7 μg/l Test organisms (species): Daphnia magna	
EC50 other aquatic organisms 1	> 0.58 mg/l (96h, Mysidopsis Bahia)	
EC50 72h - Algae [1]	> 0.765 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)	
EC50 72h - Algae [2]	0.36 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)	
ErC50 (algae)	0.36 mg/l (21d)	
LOEC (chronic)	0.012 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
NOEC (chronic)	0.0037 mg/l (21d)	

## Safety Data Sheet

Diphenylamine (122-39-4)         LC50 fish 1       3.79 mg/l (96h; F         LC50 fish 2       5.1 mg/l (48h; Or         EC50 Daphnia 1       2 mg/l Test organ         EC50 72h - Algae [1]       2.17 mg/l Test or         Pseudokirchnerid       0.18 mg/l (72h)         12.2. Persistence and degradability       The most signific biodegradability	0) AF, 48 h (OECD 202) Pimephales promelas)		
EC50 Daphnia 1       > 10000 mg/l W/         Diphenylamine (122-39-4)	AF, 48 h (OECD 202) Pimephales promelas) ryzias latipes) nisms (species): Daphnia magna rganisms (species): Raphidocelis subcapitata (previous names: ella subcapitata, Selenastrum capricornutum) cant constituents of the product should be considered as "inherently but not "readily biodegradable", and they may be moderately persistent,		
Diphenylamine (122-39-4)         LC50 fish 1       3.79 mg/l (96h; F         LC50 fish 2       5.1 mg/l (48h; Or         EC50 Daphnia 1       2 mg/l Test organ         EC50 72h - Algae [1]       2.17 mg/l Test or         Pseudokirchnerid       0.18 mg/l (72h)         12.2. Persistence and degradability       The most signific biodegradability	Pimephales promelas) ryzias latipes) nisms (species): Daphnia magna rganisms (species): Raphidocelis subcapitata (previous names: ella subcapitata, Selenastrum capricornutum) cant constituents of the product should be considered as "inherently but not "readily biodegradable", and they may be moderately persistent,		
LC50 fish 1       3.79 mg/l (96h; F         LC50 fish 2       5.1 mg/l (48h; Or         EC50 Daphnia 1       2 mg/l Test organ         EC50 72h - Algae [1]       2.17 mg/l Test or         Pseudokirchnerid       0.18 mg/l (72h)         12.2. Persistence and degradability       The most signific biodegradability         Persistence and degradability       The most signific biodegradability	ryzias latipes) nisms (species): Daphnia magna rganisms (species): Raphidocelis subcapitata (previous names: ella subcapitata, Selenastrum capricornutum) cant constituents of the product should be considered as "inherently but not "readily biodegradable", and they may be moderately persistent,		
LC50 fish 2       5.1 mg/l (48h; Or         EC50 Daphnia 1       2 mg/l Test organ         EC50 72h - Algae [1]       2.17 mg/l Test or         Precision       0.18 mg/l (72h)         12.2. Persistence and degradability       12.2. Persistence and degradability         Persistence and degradability       The most signific biodegradability	ryzias latipes) nisms (species): Daphnia magna rganisms (species): Raphidocelis subcapitata (previous names: ella subcapitata, Selenastrum capricornutum) cant constituents of the product should be considered as "inherently but not "readily biodegradable", and they may be moderately persistent,		
EC50 Daphnia 1       2 mg/l Test organ         EC50 72h - Algae [1]       2.17 mg/l Test or         Pseudokirchnerie       Pseudokirchnerie         ErC50 (algae)       0.18 mg/l (72h)         12.2. Persistence and degradability       Eni i-Sint tech R 5W-30         Persistence and degradability       The most signific biodegradable", I	nisms (species): Daphnia magna rganisms (species): Raphidocelis subcapitata (previous names: ella subcapitata, Selenastrum capricornutum) cant constituents of the product should be considered as "inherently but not "readily biodegradable", and they may be moderately persistent,		
EC50 72h - Algae [1]       2.17 mg/l Test or Pseudokirchnerie         ErC50 (algae)       0.18 mg/l (72h)         12.2. Persistence and degradability       12.2. Persistence and degradability         Eni i-Sint tech R 5W-30       The most signific biodegradability	rganisms (species): Raphidocelis subcapitata (previous names: ella subcapitata, Selenastrum capricornutum) cant constituents of the product should be considered as "inherently but not "readily biodegradable", and they may be moderately persistent,		
Pseudokirchnerie         ErC50 (algae)       0.18 mg/l (72h)         12.2. Persistence and degradability         Eni i-Sint tech R 5W-30         Persistence and degradability         The most signific biodegradability	ella subcapitata, Selenastrum capricornutum) cant constituents of the product should be considered as "inherently but not "readily biodegradable", and they may be moderately persistent,		
12.2. Persistence and degradability         Eni i-Sint tech R 5W-30         Persistence and degradability         The most signific biodegradable", I	but not "readily biodegradable", and they may be moderately persistent,		
Eni i-Sint tech R 5W-30 Persistence and degradability The most signific biodegradable", I	but not "readily biodegradable", and they may be moderately persistent,		
Persistence and degradability The most signific biodegradable", I	but not "readily biodegradable", and they may be moderately persistent,		
biodegradable",	but not "readily biodegradable", and they may be moderately persistent,		
particularly in an			
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)			
biodegradable",	cant constituents of the product should be considered as "inherently but not "readily biodegradable", and they may be moderately persistent, aerobic conditions		
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)			
biodegradable",	cant constituents of the product should be considered as "inherently but not "readily biodegradable", and they may be moderately persistent, aerobic conditions		
Mineral base oil, severely refined			
biodegradable", l	cant constituents of the product should be considered as "inherently but not "readily biodegradable", and they may be moderately persistent, aerobic conditions		
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-	-hydroxyphenyl)propionate (125643-61-0)		
Persistence and degradability Not biodegradab	le		
Dodecylphenol, mixed isomers, branched (121158-58-5)			
Persistence and degradability Rapidly degradal	ble		
Biodegradation 25 % (28 d, OEC	CD TG 301 B)		
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)			
biodegradable",	cant constituents of the product should be considered as "inherently but not "readily biodegradable", and they may be moderately persistent, aerobic conditions		
Diphenylamine (122-39-4)			
Persistence and degradability Rapidly degrada	ble		
Biodegradation 26 % (28d)			

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

12.3. Bioaccumulative potential			
Eni i-Sint tech R 5W-30			
Log Pow	Not applicable for mixtures		
Bioaccumulative potential	Not established.		
reaction mass of isomers of: C7-9-alkyl 3-(3,5	-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)		
Bioconcentration factor (BCF REACH)	260 (35 d, Oncorhynchus mykiss, OECD 305)		
Dodecylphenol, mixed isomers, branched (121158-58-5)			
Bioconcentration factor (BCF REACH)	794.33		
Log Kow	7.14		
Lubricating oils (petroleum), C20-50, hydrotre Baseoil - unspecified (72623-87-1)	ated neutral oil-based		
Log Kow	> 6		
12.4. Mobility in soil			
Eni i-Sint tech R 5W-30			
Ecology - soil	No data available.		
12.5. Results of PBT and vPvB assessment			
Eni i-Sint tech R 5W-30			
This substance/mixture does not meet the PBT criteria	of REACH regulation, annex XIII		
This substance/mixture does not meet the vPvB criteria	a of REACH regulation, annex XIII		
Results of PBT-vPvB assessment	The components in this formulation do not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)		
Component			
Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7), Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7), reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0), Dodecylphenol, mixed isomers, branched (121158-58-5)( <sup>1</sup> ), Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)		
Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII (1) Substance(s) in concentration below 0.1 % and displa	Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7), Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7), reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0), Dodecylphenol, mixed isomers, branched (121158-58-5)( <sup>1</sup> ), Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)		

**12.6. Endocrine disrupting properties** 

 Adverse effects on the environment caused by endocrine disrupting properties

 : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Component		
Dodecylphenol, mixed isomers, branched (121158-58- 5)	Has an endocrine mode of action, i.e. it alters the function(s) of the endocrine system	
12.7. Other adverse effects		

Other adverse effects

: None.

SECTION 13: Disposal considerations			
13.1. Waste treatment methods			
Sewage disposal recommendations	: Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed. Dispose of in a safe manner in accordance with local/national regulations.		
Product/Packaging disposal recommendations	: European Waste Catalogue code(s) (Decision 2001/118/CE): 13 02 05* (mineral-based non-chlorinated engine, gear and lubricating oils). This EWC code is only a general indication, and takes into account the original composition of the product and its intended use. The user has the responsibility of choosing the right EWC code, considering the actua use of the product, alterations and contaminations.		
EURAL code (EWC)	: 13 02 05* - Mineral-based non-chlorinated engine, gear and lubricating oils		

## SECTION 14: Transport information

ADR	IMDG	ΙΑΤΑ	ADN	RID
14.1. UN number or ID number				
Not regulated for transport				
14.2. UN proper shipping name				
Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.3. Transport hazard class(es)				
Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.4. Packing group				
Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.5. Environmental hazards				
Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.

## 14.6. Special precautions for user

Overland transport Not regulated.

Transport by sea Not regulated.

Air transport Not regulated.

Inland waterway transport Not regulated.

Rail transport Not regulated.

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

## 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.1.1. EU-Regulations

Other information, restriction and prohibition regulations	<ul> <li>Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). (et sequens). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (et sequens). Directives 89/391/CEE, 89/654/CEE, 89/655/CEE, 89/656/CEE, 90/269/CEE, 90/270/CEE, 90/394/CEE, 90/679/CEE, 93/88/CEE, 95/63/CE, 97/42/CE, 98/24/CE, 99/38/CE, 99/92/CE, 2001/45/CE, 2003/10/CE, 2003/18/CE (Health and safety on the workplace). Directive 2012/18/CE (Control of major-accident hazards involving dangerous substances). Directive 2004/42/CE (Limitation of emissions of Volatile Organic Compounds). Directive 98/24/EC (protection of the health and safety of workers from the risks related to chemical agents at work). Directive 92/85/CE (measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding). Substances Depleting the Ozone layer (1005/2009) - Annex I Substances (ODP). Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC. Regulation</li> </ul>
	(ODP). Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC. Regulation EU (649/2012) - Export and Import of hazardous chemicals (PIC).

### **REACH Annex XVII (Restriction List)**

EU restriction list (REACH Annex XVII)		
Reference code         Applicable on         Entry title or description		Entry title or description
3(c)	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di- tert-butyl-4- hydroxyphenyl)propionate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
3(b)	Distillates (petroleum), hydrotreated heavy paraffinic	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
30.	phenol, dodecyl-, branched; phenol, 2- dodecyl-, branched; phenol, 3-dodecyl-, branched	Substances which are classified as reproductive toxicant category 1A or 1B in Part 3 of Annex VI to Regulation (EC) No 1272/2008 and are listed in Appendix 5 or Appendix 6, respectively.

#### **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

#### REACH Candidate List (SVHC)

Contains substance(s) listed on the REACH Candidate List in concentrations ≥ 0.1 % or SCL: phenol, dodecyl-, branched; phenol, 2-dodecyl-, branched; phenol, 3-dodecyl-, branched (EC 310-154-3, CAS 121158-58-5)

### PIC Regulation (Prior Informed Consent)

Contains substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals): Diphenylamine (122-39-4)

### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

#### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

#### Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

### **Explosives Precursors Regulation (2019/1148)**

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

#### **Drug Precursors Regulation (273/2004)**

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

#### 15.1.2. National regulations

National adoption of EU Directives concerning health and safety on the workplace. National adoption of EU Directives concerning control of major-accident hazards involving dangerous substances (2012/18/CE).

Relevant national laws on prevention of water pollution.

Relevant national laws on protection of the health of pregnant workers (National adoption of Dir. 92/85/EEC).

National adoption of Directive 2008/98/CE concerning disposal of used oils.

#### Finland

Finnish National Regulations

: Occupational Safety and Health Act No. 738/2002.

#### France

Maladies professionelles (F)		
Code	Description	
RG 15	Diseases caused by aromatic amines, their salts and derivatives, especially hydroxylated, halogenated, nitrated, nitrosated and sulphonated	
RG 15 BIS	Allergic mechanism disorders caused by aromatic amines, their salts, their derivatives, especially hydroxylated, halogenated, nitrated, nitrosated, sulphonated and products containing them in the free state	
RG 36	Diseases caused by oils and fats of mineral or synthetic origin	

#### Germany

Employment restrictions	: Employment prohibitions or restrictions on the protection of young people at work according to § 22 JArbSchG in the case of formation of hazardous substances have to be observed.
National Rules and Recommendations	<ul> <li>TRGS 900: Occupational Exposure Limits.</li> <li>TRGS 800: Fire protection measures.</li> <li>TRGS 555: Working instruction and information for workers.</li> </ul>
	TRGS 402: Identification and Assessment of the Risks from Activities involving Hazardous Substances: Inhalation Exposure.
	TRGS 401: Risks resulting from skin contact - identification, assessment, measures. TRGS 400: Hazard assessment for activities involving Hazardous Substances.
VbF class (D)	: Not applicable.
Water hazard class (WGK) (D)	: WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1).
WGK remark	: Classification based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS).
Hazardous Incident Ordinance (12. BImSchV)	: Is not subject to the Hazardous Incident Ordinance (12. BImSchV)
Netherlands	
Saneringsinspanningen	: C - Minimize discharge
SZW-lijst van kankerverwekkende stoffen	: None of the components are listed
SZW-lijst van mutagene stoffen	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid	: Dodecylphenol, mixed isomers, branched is listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling	: None of the components are listed
Denmark	
Danish National Regulations	: Young people under 18 years are not allowed to use the product Pregnant/breastfeeding women working with the product must not be in direct contact with it

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### Norway

Norwegian National Regulations	: Working Environment Act (LOV-2005-06-17 NO. 62). People under the age of 18 may not work with this product at all.
Sweden	
Swedish National Regulations	: This product is in compliance with Ordinance 1998:944. Work Environment Act (1977: 1160). Chemical Hazards in the Working Environment (AFS 2011:19).

## 15.2. Chemical safety assessment

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP] No chemical safety assessment has been carried out

A chemical safety assessment has been carried out for the following components of this mixture:: Distillates (petroleum), hydrotreated heavy paraffinic Distillates (petroleum), hydrotreated heavy paraffinic

reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based

Baseoil - unspecified

## **SECTION 16: Other information**

Indication of changes			
Section	Changed item	Change	Comments
1.3	Supplier information	Modified	
2.3	Other hazards not contributing to the classification	Modified	
4.3	Other medical advice or treatment	Modified	
5.2	Hazardous decomposition products in case of fire	Modified	
6.1	Protective equipment	Modified	
7.1	Precautions for safe handling	Modified	
8.2	Respiratory protection	Modified	
10.6	Hazardous decomposition products	Modified	
16	Other information	Modified	

Abbreviations and acronyms:		
	N/A = not applicable	
	N/D = not available	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC50	Effective concentration for 50 percent of test population (median effective concentration)	
IARC	International Agency for Research on Cancer	

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

ATA	International Air Transport Association		
IMDG	International Maritime Dangerous Goods		
LC50	Lethal concentration for 50 percent of test population (median lethal concentration)		
LD50	Lethal dose for 50 percent of test population (median lethal dose)		
LOAEL	Lowest Observed Adverse Effect Level		
NOAEC	No-Observed Adverse Effect Concentration		
NOAEL	No-Observed Adverse Effect Level		
NOEC	No-Observed Effect Concentration		
OECD	Organisation for Economic Co-operation and Development		
РВТ	Persistent Bioaccumulative Toxic		
PNEC	Predicted No-Effect Concentration		
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals, Regulation (EC) No 1907/2006		
RID	Regulation concerning the International Carriage of Dangerous Goods by Railways		
SDS	Safety Data Sheet		
STP	Sewage treatment plant		
vPvB	Very Persistent and Very Bioaccumulative		

## Data sources Training advice

This Safety Data Sheet is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.
Provide adequate training to professional operators for the use of PPEs, according to the information contained in this Safety Data Sheet.

: Do not use the product for any purposes that have not been advised by the manufacturer.

Other information

Full text of H- and EUH-statements:				
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3			
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3			
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3			
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1			
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1			
Aquatic Chronic 4	Hazardous to the aquatic environment – Chronic Hazard, Category 4			
Asp. Tox. 1	Aspiration hazard, Category 1			
Eye Dam. 1	Serious eye damage/eye irritation, Category 1			
H301	Toxic if swallowed.			
H304	May be fatal if swallowed and enters airways.			
H311	Toxic in contact with skin.			
H314	Causes severe skin burns and eye damage.			
H318	Causes serious eye damage.			
H331	Toxic if inhaled.			
H360F	May damage fertility.			
H373	May cause damage to organs through prolonged or repeated exposure.			
H400	Very toxic to aquatic life.			

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Full text of H- and EUH-statements:			
H410	Very toxic to aquatic life with long lasting effects.		
H412	Harmful to aquatic life with long lasting effects.		
H413	May cause long lasting harmful effects to aquatic life.		
Repr. 1B	Reproductive toxicity, Category 1B		
Skin Corr. 1C	Skin corrosion/irritation, Category 1, Sub-Category 1C		
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2		

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]					
Aquatic Chronic 3	H412	Calculation method			

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.