

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878 Revision date: 7/12/2024 Supersedes: 11/27/2023 Version: 1.1

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture

Trade name : Eni i-Sint MS 5W-40

Product code : 1022
Formula : 0025-2020
Product group : Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Intended ONLY for general public

Main use category : Industrial use, Professional use, Consumer use

Industrial/Professional use spec : Used in closed systems

Wide dispersive use

Use of the substance/mixture : Lubricant for internal combustion engines

---

Do not use the product for any purposes that have not been advised by the manufacturer.

Function or use category : Lubricants and additives

#### 1.2.2. Uses advised against

No additional information available

## 1.3. Details of the supplier of the safety data sheet

Enilive S.p.A, Viale Giorgio Ribotta 51, 00144 Rome, ITALY, Tel. +39 06 59821, www.eni.com

Competent person responsible for the safety data sheet (Reg. EC nr. 1907/2006): SDS.Enilive@eni.com

Distributed by: Enilive Schmiertechnik GmbH, Paradiesstraße 14, 97080 Würzburg, GERMANY, www.oilproducts.eni.com Department responsible for information: Application Engineering & Product Management (AEPM), Tel. +49 (0)931-900 98-0 e-mail: technik.wuerzburg@enilive.com

#### 1.4. Emergency telephone number

Emergency number : CNIT +39 0382 24444 (24h) (IT + EN)

Poison Center

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]

Not classified

## Adverse physicochemical, human health and environmental effects

Prolonged and repeated skin contact may cause reddening, irritation and dermatitis, due to a defatting effect. For specific information about the toxicological/ecotoxicological properties and classification of this product, see Sect. 11 and/or Sect. 12.

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH208 - Contains C14-16-18 Alkyl phenol. May produce an allergic reaction.

EUH210 - Safety data sheet available on request.

Child-resistant fastening : No Tactile warning : No

Nordic countries regulation

Denmark

MAL code : 00-1 (Executive Order No. 301 from 1993)

7/12/2024 (Revision date) EN (English) 1/19

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

## 2.3. Other hazards (not relevant for classification)

Other hazards not contributing to the classification

: This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels. If the product is handled or used at high temperature, contact with hot product or vapours may cause burns. Do not wait for symptoms to develop. Any material in case of accidents involving pressurized circuits and the like, may be accidentally injected under the skin, even without external damage. In such a case, the victim should be brought to an hospital as soon as possible, to get specialized medical treatment.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

Component		
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
Mineral base oil, severely refined (N/A)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
C14-16-18 Alkyl phenol	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Component		
Distillates (petroleum), hydrotreated heavy paraffinic(64742-54-7)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	
Mineral base oil, severely refined(N/A)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	
C14-16-18 Alkyl phenol	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	

## **SECTION 3: Composition/information on ingredients**

## 3.1. Substances

Not applicable

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]
Distillates (petroleum), hydrotreated heavy paraffinic (see note [**]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627- 25	70 - 85	Asp. Tox. 1, H304
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	CAS-No.: 72623-87-1 EC-No.: 276-738-4 EC Index-No.: 649-483-00-5 REACH-no: 01-2119474889- 13	15 – 20	Not classified
Mineral base oil, severely refined (see note [*]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	CAS-No.: N/A EC-No.: N/A	1 - 10	Asp. Tox. 1, H304
C14-16-18 Alkyl phenol	EC-No.: 931-468-2 EC Index-No.: N/A REACH-no: 01-2119498288- 19	0.01 - 0.2	Skin Sens. 1B, H317 STOT RE 2, H373

Notes

: [\*] Note: this product may be formulated with one or more of the following severely refined mineral base oils (not classified as hazardous):

CAS 64742-54-7/EC 265-157-1/REACH Reg. # 01-2119484627-25-xxxx; CAS 64742-65-0/EC 265-169-7/REACH Reg. # 01-2119471299-27-xxxx; CAS 64742-70-7/EC 265-174-4/REACH Reg. # 01-2119487080-42-xxxx; CAS 64742-56-9/EC 2265-159-2/ REACH Reg. # 01-2119480132-48-xxxx.

All these substances have a value < 3 % wt of DMSO extract, according to IP 346 (Nota L - Annex VI Reg (CE) 1272/2008, # 1.1.3)

Note [\*\*]:

this product has a value of DMSO extract < 3 % wt, according to IP 346. According to the criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product must be regarded as non carcinogenic.

Full text of H- and EUH-statements: see section 16

## **SECTION 4: First aid measures**

First-aid measures after skin contact

## 4.1. Description of first aid measures

First-aid measures general : In case of spontaneous vomiting, transport the victim to a hospital, to verify the possibility

that the product has been aspired into the lungs.

First-aid measures after inhalation : In case of disturbances owing to inhalation of vapours or mists, remove the victim from exposure; keep at rest; if necessary, seek medical attention. See also section 4.3.

: Take off immediately all contaminated clothing and wash it before reuse. If inflammation or irritation persists, seek medical advice. In case of burns, cool affected part with cold running water for at least 10 min. Cover with gauze or clean cloth. Ask for medical assistance or bring to a hospital. Do not apply salves or other substances, unless by doctor's advice.

Body hypothermia must be avoided. Do not put ice on the burn.

First-aid measures after eye contact

Rinse eyes thoroughly for at least 15 minutes. Keep eyelids well apart. If irritation, blurred vision or swelling occurs and persists, obtain medical advice from a specialist. In case of burns, cool affected part with cold running water for at least 10 min. Cover with gauze or

clean cloth. Ask for medical assistance or bring to a hospital. Do not apply salves or other substances, unless by doctor's advice.

First-aid measures after ingestion : In case of spontaneous vomiting, keep head low, to avoid the risk of aspiration into the lungs. Do not induce vomiting to avoid aspiration into the lungs. Keep at rest.

7/12/2024 (Revision date) EN (English) 3/19

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms / injuries (general indications) : Prolonged and repeated skin contact may cause reddening, irritation and dermatitis. Contact with eyes may cause temporary reddening and irritation.

Symptoms/effects after inhalation : This product has a low vapour pressure, and in normal conditions at ambient temperature

the concentration in the air is negligible. A significant concentration may build up only in case of sprays and mists. In these cases overexposure to mists (e.g. through prolonged use in confined insufficiently ventilated spaces) may cause irritation to airways, nausea and

dizziness

Symptoms/effects after skin contact : Prolonged and repeated skin contact may cause reddening, irritation and dermatitis, due to a defatting effect. Contact with hot product may cause thermal burns.

Symptoms/effects after eye contact

: Contact with eyes may cause a light transient irritation. Contact with hot product or vapours

may cause burns.

Symptoms/effects after ingestion : Accidental ingestion of small quantities of the product may cause nausea, discomfort and

gastric disturbances.

Symptoms/effects upon intravenous administration : No information available.

Chronic symptoms : None to be reported, according to the present classification criteria.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical attention if casualty has an altered state of consciousness or if symptoms do not resolve. Seek medical attention in all cases of serious burns.

## **SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

Suitable extinguishing media : Small-size fires: carbon dioxide, dry chemicals, foam, sand or earth. Large fires: foam or

water fog (mist). These means should be used by trained personnel only. Other

extinguishing gases (according to regulations).

Unsuitable extinguishing media : Do not use water jets. They could cause splattering, and spread the fire. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

## 5.2. Special hazards arising from the substance or mixture

Fire hazard : This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels.

Explosion hazard : Vapours are heavier than air and may spread along floors. Heat may build pressure in tank

and containers, rupturing closed vessels, spreading fire and increasing risk of burns and injuries.

Hazardous decomposition products in case of fire : Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases. Oxygenated compounds (aldehydes, etc.).

## 5.3. Advice for firefighters

Firefighting instructions : Shut off source of product, if possible. If possible, move containers and drums away from the danger area, if safe to do so. Spilled product which is not burning should be covered

with sand or foam. Use water sprays to cool containers and surfaces exposed to the flames.

If the fire cannot be controlled, evacuate area.

Special protective equipment for firefighters

: Advice for firefighters and protective measures

Special protective equipment for firefighters : Advice for firefighters and protective measures. Self-contained breathing apparatus. Other information : In case of fire, do not discharge residual product, waste materials and runoff water: of the contained breathing apparatus.

: In case of fire, do not discharge residual product, waste materials and runoff water: collect separately and use a proper treatment.

## **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop or contain leak at the source, if safe to do so. Eliminate all ignition sources if safe to do so (e.g. electricity, sparks, fires, flares). Avoid direct contact with released material. Keep

upwind.

#### 6.1.1. For non-emergency personnel

Protective equipment : See Section 8.

7/12/2024 (Revision date) EN (English) 4/19

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

**Emergency procedures** 

: Avoid direct contact with released material. Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency.

#### 6.1.2. For emergency responders

Protective equipment

: Small spillages: normal antistatic working clothes are usually adequate. Large spillages: full body suit of chemically resistant and antistatic material. if necessary heat resistant and insulated. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Gloves made of PVA are not water-resistant, and are not suitable for emergency use. If contact with hot product is possible or anticipated, gloves should be heat-resistant and thermally insulated. Antistatic non-skid safety shoes or boots, chemical resistant, if necessary heat resistant and insulated. Work helmet. Goggles and /or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory protection: a half or full-face respirator with filter(s) for organic vapours (AX), or a Self-contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. A Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.

**Emergency procedures** 

: If required, notify relevant authorities according to all applicable regulations.

## 6.2. Environmental precautions

Do not let the product accumulate in confined or underground spaces. Do not let the product flow into sewers or water courses, or in any way contaminate the environment. In case of contamination of environment compartments (soil, subsoil, surface or underground waters), remove contaminated soil when possible, and in any case treat all involved compartments in accordance with local regulations. The site should have a spill plan to ensure that adequate safeguards are in place to minimize the impact of episodic releases.

#### 6.3. Methods and material for containment and cleaning up

For containment

: Soil. Contain spilled liquid with sand, earth or other suitable absorbents (non-flammable). Recover free liquid and waste materials in suitable waterproof and oil-resistant containers. Clean contaminated area. Dispose of according to local regulations. Confine the spillage. Remove from surface by skimming or suitable floating absorbents. Collect recovered product and other waste materials in suitable waterproof, oil resistant containers. Recover or dispose of according to local regulations.

Other information

: Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air/water temperature, wave/current direction and speed) may significantly influence the choice of appropriate actions. Local regulations may also prescribe or limit actions to be taken. For this reason, local experts should be consulted when necessary.

#### 6.4. Reference to other sections

Refer to chapter 16.

## **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Precautions for safe handling

: This material is combustible, but will not ignite readily. Provide adequate ventilation. Use adequate personal protective equipment as needed. Due to the extremely slippery nature of this material, more care than usual must be exercised in material handling practices to keep off all walking surfaces. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Avoid release to the environment. Emptied containers can contain combustible product residues. Do not cut, weld, drill, burn or incinerate empty containers or drums, unless they have been drained and cleaned. Before entering storage tanks and commencing any operation in a confined area (e.g. tunnels), carry out an adequate cleanup, and check the atmosphere for oxygen content and flammability. See also Section 16, "Other information".

Handling temperature

: This product can be handled at ambient temperatures.

7/12/2024 (Revision date) EN (English) 5/19

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Hygiene measures

: Ensure that proper housekeeping measures are in place. Avoid contact with skin. Do not breathe fume/ mist/ vapours. Do not ingest. Do not smoke. Do not eat and do not drink during use. Do not clean hands with dirty or oil-soaked rags. Do not re-use clothes, if they are still contaminated. Keep away from food and beverages. Take off immediately all contaminated clothing and wash it before reuse. Contaminated materials should not be allowed to accumulate in the workplaces and should never be kept inside the pockets. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

## 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep away from open flames, hot surfaces and sources of ignition. Do not smoke. Store in

dry, well-ventilated area.

Incompatible products : Keep away from strong oxidizers.

Storage temperature : ≥ 0 °C This product can be handled at ambient temperatures.

Storage area : Storage area layout, tank design, equipment and operating procedures must comply with

the relevant European, national or local legislation. Storage installations/areas should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped

and qualified personnel as defined by national, local or company regulations.

Packages and containers: : If the product is supplied in containers: Keep containers tightly closed and properly labelled.

Keep only in the original container or in a suitable container for this kind of product.

Packaging materials : For containers, or container linings use materials specifically approved for use with this

product. Compatibility should be checked with the manufacturer, according to the specific

use conditions.

## 7.3. Specific end use(s)

No information available.

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based  Baseoil - unspecified (72623-87-1)		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Belgium - Occupational Exposure Limits		
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
OEL STEL	2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based  Baseoil - unspecified (72623-87-1)		
KGV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
WEL STEL (OEL STEL)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH OEL STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Mineral base oil, severely refined (N/A)		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Belgium - Occupational Exposure Limits		
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
OEL STEL	2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KGV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
WEL STEL (OEL STEL)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH OEL STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Belgium - Occupational Exposure Limits		
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
OEL STEL	2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KGV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
WEL STEL (OEL STEL)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH OEL STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	

#### 8.1.2. Recommended monitoring procedures

Monitoring methods	
Monitoring methods	Monitoring procedures should be chosen according to the indications set by national authorities or labour contracts. Refer to relevant legislation and in any case to the good practice of industrial hygiene.

#### 8.1.3. Air contaminants formed

No additional information available

## 8.1.4. DNEL and PNEC

Note

The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a governmental regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH.

## 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

## 8.2.1. Appropriate engineering controls

## Appropriate engineering controls:

Before entering storage tanks and commencing any operation in a confined area (e.g. tunnels), carry out an adequate clean-up, and check the atmosphere for oxygen content and flammability. See also Section 16, "Other information".

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

#### 8.2.2. Personal protection equipment

#### Personal protective equipment (for industrial or professional use):

Face shield. Gloves. Protective clothing. Safety glasses. Safety shoes or boots.

#### Personal protective equipment symbol(s):











#### 8.2.2.1. Eye and face protection

#### Eye protection:

When there is a risk of contact with the eyes, use safety goggles or other means of protection (face shield). If necessary, refer to national standards or to the EN 166 standard.

#### 8.2.2.2. Skin protection

#### Skin and body protection:

Long-sleeved overalls. If necessary, refer to the EN 340 and related standards, for definition of characteristics and performance according to the risk rating of the area. Antistatic non-skid safety shoes or boots, chemical resistant and insulated.

#### Hand protection:

When there is a risk of contact with the skin, use waterproof gloves, resistant to chemical products. Gloves must be felt-lined. Adequate materials: nitrile (NBR) or PVC with a protection index > 5 (permeation time > 240 mins). Use gloves respecting all the conditions and within the limits set by the manufacturer. Replace gloves immediately in case of cuts, holes or other signs of damages or degradation. If necessary, refer to the EN 374 standard.

#### 8.2.2.3. Respiratory protection

#### Respiratory protection:

Independently from other possible actions (technical modifications, operating procedures, and other means to limit the exposure of workers), personal protection equipment can be used according to necessity. Open or well ventilated spaces: in presence of mists and if the product is handled without adequate containment means: use full or half-face masks with filter for mists/aerosols. (EN 136/140/145). Closed or confined areas (e.g. tank interiors): the use of protection measures for airways (masks or self-contained breathing apparatus), must be assessed according to the specific activity, as well as level and duration of predicted exposure.

#### 8.2.2.4. Thermal hazards

#### Thermal hazard protection:

If contact with hot product is possible or anticipated, gloves should be heat-resistant and thermally insulated.

#### 8.2.3. Environmental exposure controls

## **Environmental exposure controls:**

Do not discharge the product into the environment. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed. Storage areas/installations should be designed with adequate bunds so as to prevent ground and water pollution in case of leaks or spills.

#### Consumer exposure controls:

No special requirements.

## **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Colour : Yellow to amber.

Appearance : Liquid, bright & clear.

Odour : Slight odour of petroleum.

Odour threshold : There are no data available on the preparation/mixture itself.

Melting point : Not determined
Freezing point : Not determined
Boiling point : Not determined
Flammability : Not flammable
Lower explosion limit : Not determined
Upper explosion limit : Not determined

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Flash point : ≥ 195 °C (ASTM D 93)

Auto-ignition temperature : Not determined

Decomposition temperature : Not determined

pH : Not applicable

Viscosity, kinematic : ≤ 13.5 mm²/s (100 °C) (ASTM D 445) Solubility : Water: Immiscible and insoluble

Log Kow : Not available

Log Pow : Not applicable for mixtures

Vapour pressure : ≤ 0.1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)

Vapour pressure at 50°C : Not determined

Density : 854 kg/m³ (15 °C) (ASTM D 4052)

Relative density : Not determined Relative vapour density at 20°C : Not determined Particle characteristics : Not applicable

#### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

Sensitivity to impact : ≥ J

Explosion limits : ≥ 45 g/m³ (mineral oil mists)

#### 9.2.2. Other safety characteristics

No additional information available

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

This mixture does not offer any further hazard for reactivity, except what is reported in the following paragraphs.

### 10.2. Chemical stability

Stable product, according to its intrinsic properties.

## 10.3. Possibility of hazardous reactions

None (in normal conditions of storage and handling). Contact with strong oxidizers (peroxides, chromates, etc.) or alkali metals may cause a fire hazard. A mixture with nitrates or other strong oxidisers (e.g. chlorates, perchlorates, liquid oxygen) may create an explosive mass. Sensitivity to heat, friction or shock cannot be assessed in advance.

## 10.4. Conditions to avoid

Keep away from strong oxidizers. Keep away from open flames, hot surfaces and sources of ignition. Avoid the build-up of electrostatic charge.

#### 10.5. Incompatible materials

Strong oxidizing agents.

## 10.6. Hazardous decomposition products

In exceptional cases (i.e prolonged storage in tanks contaminated with water, and presence of anaerobic sulfate-reducing microbial colonies), the product may undergo a degradation and generate small amounts of sulfur compounds, including H2S.

# **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

Additional information : (according to composition)

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

<u></u>	*	
Eni i-Sint MS 5W-40		
LD50 oral rat	≥ 2000 mg/kg bodyweight (Calculated data). This evaluation is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.	
LD50 dermal rabbit	≥ 2000 mg/kg bodyweight (Calculated data). This evaluation is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.	
LC50 Inhalation - Rat	≥ 5 mg/l/4h (Calculated data). This evaluation is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.	
ATE CLP (vapours)	5 mg/l/4h	
ATE (dust,mist)	5 mg/l/4h	
Lubricating oils (petroleum), C20-50, hydrotre Baseoil - unspecified (72623-87-1)	eated neutral oil-based	
LD50 oral rat	> 5000 mg/kg (OECD 401)	
LD50 dermal rat	> 5000 mg/kg (OECD 402)	
LC50 Inhalation - Rat	> 5 mg/l/4h (OECD 403)	
Mineral base oil, severely refined (N/A)		
LD50 oral rat	≥ 5000 mg/kg bodyweight (OECD 401)	
LD50 dermal rat	≥ 5000 mg/kg bodyweight (OECD 402)	
C14-16-18 Alkyl phenol		
LD50 oral rat	2000 mg/kg bodyweight	
LD50 dermal rat	2000 mg/kg bodyweight	
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
LD50 oral rat	> 5000 mg/kg (OECD 401)	
LD50 dermal rat	> 5000 mg/kg (OECD 402)	
LC50 Inhalation - Rat	> 5 mg/l/4h (OECD 403)	
Skin corrosion/irritation :	Not classified (Based on available data, the classification criteria are not met)	
Additional information :	pH: Not applicable (according to composition)	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)		
рН	Not applicable	
Mineral base oil, severely refined (N/A)		
рН	Not applicable	
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
рН	Not applicable	
Serious eye damage/irritation :	Not classified (Based on available data, the classification criteria are not met) pH: Not applicable	
Additional information :	(according to composition)	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)		
рН	Not applicable	
	•	

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Mineral base oil, severely refined (N/A)		
рН	Not applicable	
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
рН	Not applicable	
Additional information :  Germ cell mutagenicity :	Not classified (Based on available data, the classification criteria are not met) (according to composition) This product does not contain any significant amounts of substances classified as sensitizers (in any case < 0.1 % wt) Not classified (Based on available data, the classification criteria are not met) (according to composition)	
Carcinogenicity : Reproductive toxicity : Additional information :	This product does not contain any significant amounts of substances classified as mutagenic by the EU (in any case < 0.1 % wt)  Not classified (Based on available data, the classification criteria are not met)  Not classified (Based on available data, the classification criteria are not met)  (according to composition)	
Additional information : STOT-repeated exposure :	Not classified (Based on available data, the classification criteria are not met) (according to composition)  Not classified (Based on available data, the classification criteria are not met) (according to composition)	
Lubricating oils (petroleum), C20-50, hydrotre Baseoil - unspecified (72623-87-1)	ated neutral oil-based	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)	
Mineral base oil, severely refined (N/A)		
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)	
C14-16-18 Alkyl phenol		
NOAEL (oral, rat, 90 days)	30 – 100 mg/kg bodyweight/day	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.	
Distillates (petroleum), hydrotreated heavy pa	raffinic (64742-54-7)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)	
•	Not classified (Based on available data, the classification criteria are not met) Viscosity, kinematic: > 20,5 mm2/s (40 °C) (ASTM D 445)	
Eni i-Sint MS 5W-40		
Viscosity, kinematic	≤ 13.5 mm²/s (100 °C) (ASTM D 445)	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)		
Viscosity, kinematic	48 mm²/s (40°C) (ASTM D 445)	
Mineral base oil, severely refined (N/A)		
Viscosity, kinematic	> 21 mm²/s	
Hydrocarbon	Yes	
Distillates (petroleum), hydrotreated heavy pa	raffinic (64742-54-7)	
Viscosity, kinematic	17.9 mm²/s (40 °C) (ASTM D 445)	

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

#### 11.2. Information on other hazards

#### 11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

#### 11.2.2. Other information

Potential adverse human health effects and symptoms

Other information

: Prolonged and repeated skin contact may cause reddening, irritation and dermatitis, due to a defatting effect, Contact with eyes may cause temporary reddening and irritation.

: None

## **SECTION 12: Ecological information**

### 12.1. Toxicity

Ecology - general : An uncontrolled release to the environment may nevertheless produce a contamination of different environmental compartments (air, soil, underground, surface water bodies, aquifers). Handle according to general working hygiene practices to avoid pollution and release into the environment. According to the components, and by comparison with other products of the same type and composition, it is expected that this product has a toxicity for aquatic organisms < 1 mg/l, and must be regarded as dangerous to the environment. This product has a low vapour pressure, and in normal conditions at ambient temperature Ecology - air the concentration in the air is negligible. A significant concentration may build up only if the product is used at high temperature, or in case of sprays and mists. In these cases overexposure to vapours may cause irritation to airways, nausea and dizziness. Ecology - water This product is not soluble in water. It floats on water and forms a film on the surface. The damage to aquatic organisms is of mechanical kind (immobilization and entrapment)

Hazardous to the aquatic environment, short-term

Hazardous to the aquatic environment, long-term

(chronic)

Not classified

Not classified

sinone)		
Eni i-Sint MS 5W-40		
LC50 fish 1	≥ 100 mg/l (Calculated data). This evaluation is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.	
EC50 Daphnia 1	≥ 100 mg/l (Calculated data). This evaluation is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.	
ErC50 (algae)	≥ 100 mg/l (Calculated data). This evaluation is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)		
LC50 fish 1	> 100 mg/l (LL 50)	
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)	
Mineral base oil, severely refined (N/A)		
LC50 fish 1	> 100 mg/l (LL 50)	
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)	
C14-16-18 Alkyl phenol		
EC50 Daphnia 1	100 mg/l	

7/12/2024 (Revision date) EN (English) 13/19

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
LC50 fish 1	> 100 mg/l (LL 50)
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)

# 12.2. Persistence and degradability

Eni i-Sint MS 5W-40		
Em rome mo ore 40		
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based  Baseoil - unspecified (72623-87-1)		
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.	
Mineral base oil, severely refined (N/A)		
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.	
C14-16-18 Alkyl phenol		
Biodegradation	24 % (Zahn-Wellens, 10-20 %)	
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.	

# 12.3. Bioaccumulative potential

Eni i-Sint MS 5W-40		
Log Pow	Not applicable for mixtures	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)		
Log Kow	> 6	
C14-16-18 Alkyl phenol		
Log Kow	4.5 (0.1 d, 10-20 %)	

# 12.4. Mobility in soil

No additional information available

# 12.5. Results of PBT and vPvB assessment

Eni i-Sint MS 5W-40		
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII		
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII		
Results of PBT-vPvB assessment	The components in this formulation do not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)	

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Component	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Mineral base oil, severely refined (N/A)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)
C14-16-18 Alkyl phenol	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)

#### 12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

## 12.7. Other adverse effects

Other adverse effects

: None.

Additional information

: This product has no specific properties for inhibition of bacterial activity. In any case, wastewater containing this product should be treated in plants that are suited for the specific purpose.

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Waste treatment methods

: Do not dispose of the product, either new or used, by dumping on the ground, or discharging into sewers, tunnels, lakes or water courses. Deliver to a qualified official collector

Sewage disposal recommendations

 Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Product/Packaging disposal recommendations

: European Waste Catalogue code(s) (Decision 2001/118/CE): 13 02 05\* (mineral-based non-chlorinated engine, gear and lubricating oils). This EWC code is only a general indication, and takes into account the original composition of the product and its intended use. The user has the responsibility of choosing the right EWC code, considering the actual use of the product, alterations and contaminations.

Additional information

: Empty containers may contain combustible product residues. Do not cut, weld, bore, burn or incinerate emptied containers, unless they have been cleaned and declared safe.

Ecology - waste materials

: The product as it is does not contain halogenated substances.

EURAL code (EWC)

: 13 02 05\* - Mineral-based non-chlorinated engine, gear and lubricating oils

## **SECTION 14: Transport information**

In accordance with ADR / IMDG / IATA / ADN / RID

7/12/2024 (Revision date) EN (English) 15/19

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

## 14.1. UN number or ID number

UN-No. : Not applicable UN-No. (IMDG) : Not applicable UN-No. (ICAO) : Not applicable UN-No. (ADN) : Not applicable UN-No. (RID) : Not applicable

## 14.2. UN proper shipping name

Proper Shipping Name : Not applicable
Proper Shipping Name (IMDG) : Not applicable
Proper Shipping Name (IATA) : Not applicable
Proper Shipping Name (ADN) : Not applicable
Proper Shipping Name (RID) : Not applicable

#### 14.3. Transport hazard class(es)

#### **ADR**

Transport hazard class(es) (ADR) : Not applicable

**IMDG** 

Transport hazard class(es) (IMDG) : Not applicable

**IATA** 

Transport hazard class(es) (IATA) : Not applicable

**ADN** 

Transport hazard class(es) (ADN) : Not applicable

**RID** 

Transport hazard class(es) (RID) : Not applicable

## 14.4. Packing group

Packing group (UN) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable
Packing group (ADN) : Not applicable
Packing group (RID) : Not applicable

## 14.5. Environmental hazards

Dangerous for the environment : No
Marine pollutant : No
Other information : None

### 14.6. Special precautions for user

## **Overland transport**

Not applicable

#### Transport by sea

Not applicable

#### Air transport

Not applicable

#### **Inland waterway transport**

Not applicable

#### Rail transport

Not applicable

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

## 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

#### **REACH Annex XVII (Restriction List)**

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(b)	Mineral base oil, severely refined; C14-16-18 Alkyl phenol	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10

#### **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

#### **REACH Candidate List (SVHC)**

No ingredients are included in the REACH Candidate list (> 0,1 % m/m).

#### **PIC Regulation (Prior Informed Consent)**

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

#### **POP Regulation (Persistent Organic Pollutants)**

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

## Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

#### **Explosives Precursors Regulation (2019/1148)**

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

### **Drug Precursors Regulation (273/2004)**

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

#### 15.1.2. National regulations

National adoption of EU Directives concerning health and safety on the workplace.

National adoption of EU Directives concerning control of major-accident hazards involving dangerous substances (2012/18/CE).

Relevant national laws on prevention of water pollution.

Relevant national laws on protection of the health of pregnant workers (National adoption of Dir. 92/85/EEC).

National adoption of Directive 2008/98/CE concerning disposal of used oils.

#### **France**

Maladies professionelles (F)	
Code	Description
RG 36	Diseases caused by oils and fats of mineral or synthetic origin

## Germany

VbF class (D) : Not applicable.

Water hazard class (WGK) (D) : WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1).

WGK remark : Classification based on the components in compliance with Verwaltungsvorschrift

wassergefährdender Stoffe (VwVwS).

Storage class (LGK, TRGS 510) : LGK 12 - Non-combustible liquids.

Hazardous Incident Ordinance (12. BImSchV) : Is not subject to the Hazardous Incident Ordinance (12. BImSchV)

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

#### **Netherlands**

SZW-lijst van kankerverwekkende stoffen

: Distillates (petroleum), hydrotreated heavy paraffinic is listed
SZW-lijst van mutagene stoffen

: Distillates (petroleum), hydrotreated heavy paraffinic is listed

SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed SZW-lijst van reprotoxische stoffen – : None of the components are listed

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen – Ontwikkeling

: None of the components are listed

**Denmark** 

MAL code : 00-1 (Executive Order No. 301 from 1993)

Danish National Regulations : Pregnant/breastfeeding women working with the product must not be in direct contact with it

**Switzerland** 

Storage class (LK) : LK 10/12 - Liquids

## 15.2. Chemical safety assessment

For this mixture a chemical safety assessment has not been carried out

### A chemical safety assessment has been carried out for the following components of this mixture::

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based

Baseoil - unspecified

C14-16-18 Alkyl phenol

Distillates (petroleum), hydrotreated heavy paraffinic

## **SECTION 16: Other information**

Indication of changes			
Section	Changed item	Change	Notes
2.3	Other hazards not contributing to the classification	Modified	
3	Composition/information on ingredients	Modified	
4.1	First-aid measures after skin contact	Modified	
4.1	First-aid measures after ingestion	Modified	
4.1	First-aid measures after eye contact	Modified	
4.1	First-aid measures after inhalation	Modified	
4.3	Other medical advice or treatment	Modified	
5.2	Hazardous decomposition products in case of fire	Modified	
6.1	Protective equipment	Modified	
6.3	For containment	Modified	
7.1	Precautions for safe handling	Modified	
7.2	Incompatible products	Modified	
7.2	Storage conditions	Modified	
8.2	Respiratory protection	Modified	
8.2	Appropriate engineering controls	Modified	
8.2	Personal protective equipment (for industrial or professional use)	Modified	
12.1	Ecology - general	Modified	
14.5	Other information	Modified	
16	Abbreviations and acronyms	Modified	

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Indication of changes			
Section	Changed item	Change	Notes
16	Other information	Modified	

Abbreviations and acronyms:		
		Complete text of the H phrases quoted in this Safety Data Sheet. These phrases are reported here for information only, and MAY NOT correspond to the classification of the product.

Data sources : This Safety Data Sheet is based on the real characteristics of the components and their

combination, taking into account the information provided by the suppliers.

Training advice : Provide adequate training to professional operators for the use of PPEs, according to the

information contained in this Safety Data Sheet.

Other information : Do not use the product for any purposes that have not been advised by the manufacturer.

Full text of H- and EUH-statements:	
Asp. Tox. 1	Aspiration hazard, Category 1
EUH208	Contains C14-16-18 Alkyl phenol. May produce an allergic reaction.
EUH210	Safety data sheet available on request.
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H373	May cause damage to organs through prolonged or repeated exposure.
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.