

Product Safety Information Sheet

A safety data sheet is not required for this product under Article 31 of REACH. This Product Safety Information Sheet has been created on a voluntary basis Revision date: 9/10/2024 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : Eni i-Ride Moto 20W-50

Product code : 1538

Type of product : Lubricant

Formula : 0169-2021

Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use, Consumer use

Industrial/Professional use spec : Used in closed systems

Wide dispersive use

Use of the substance/mixture : Lubricant for internal combustion engines

Function or use category : Lubricants and additives

1.2.2. Uses advised against

Recommended use are listed above; other uses are not recommended unless an assessment has provided that risks are controlled.

1.3. Details of the supplier of product safety information sheet

Manufacturer:

Enilive Iberia S.L.U.

Avenida de Europa, 24, Edificio Torona B - Planta 1ª, 28108 Alcobendas (Madrid) Tel: (+34) 917 277 878 Competent person responsible for the Safety Data Sheet (Reg. EC nr. 1907/2006): SDS.Enilive@enilive.com

Distributed by: Enilive Schmiertechnik GmbH, Paradiesstraße 14, 97080 Würzburg, GERMANY

Department responsible for information: Application Engineering & Product Management (AEPM), Tel. +49 (0)931-900 98-0

e-mail: technik.wuerzburg@enilive.com

1.4. Emergency telephone number

Emergency number : CNIT +39 0382 24444 (24h) (IT + EN)

Poison Center

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]

Not classified

Adverse physicochemical, human health and environmental effects

None to be reported, according to the present EU regulations. For specific information about the toxicological/ecotoxicological properties and classification of this product, see Sect. 11 and/or Sect. 12.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

No labelling applicable

Product Safety Information Sheet

A safety data sheet is not required for this product under Article 31 of REACH. This Product Safety Information Sheet has been created on a voluntary basis

2.3. Other hazards (not relevant for classification)

Other hazards not contributing to the classification

: This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels. In case of contact with eyes, this product may cause irritation. Any substance, in case of accidents involving pressurized circuits and the like, may be accidentally injected under the skin, even without external damage. In such a case, the victim should be brought to an hospital as soon as possible, to get specialized medical treatment. If the product is handled or used at high temperature, contact with hot product or vapours may cause burns. Do not wait for symptoms to develop. A potential risk may arise from the release of hydrogen sulfide, when the product is stored or handled at high temperature. Hydrogen sulfide may accumulate in the tanks or other confined spaces, with danger to the workers that enter the spaces. In these cases overexposure to hydrogen sulfide may cause irritation to airways, nausea, dizziness, loss of consciousness and death.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

Component	
Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)
Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Component

Substance(s) not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)

Other information

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Comments

: Composition/information on ingredients

Polyolefins

Mixture of hydrocarbons

Additives

Product Safety Information Sheet

A safety data sheet is not required for this product under Article 31 of REACH. This Product Safety Information Sheet has been created on a voluntary basis

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (see note [**], see note [****]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	CAS-No.: 72623-87-1 EC-No.: 276-738-4 EC Index-No.: 649-483-00-5 REACH-no: 01-2119474889- 13	35 – 40	Not classified
Mineral base oil, severely refined (For identification of the substance, see note [*], see note [***]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	EC-No.: N/A	30 - 40	Not classified

Comments

: [*] Note: this product contains small amounts of severely refined mineral base oil (not classified as hazardous). The identity has not been specified by the original supplier. This substance has a value < 3 % wt of DMSO extract, according to IP 346 (Note L - Annex VI Reg (EC) 1272/2008, # 1.1.3)

Note [**]:

this product has a value of DMSO extract < 3 % wt, according to IP 346. According to the criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product must be regarded as non carcinogenic.

Note [***]:

substance with occupational exposure limits for some EU countries affecting the category of mineral oils (finely refined mineral base oil mists; see section 8.1)

Note [****]:

this product may be formulated with one or more of the following base oils (not classified as hazardous): CAS 64742-54-7/ EC: 265-157-1 REACH Reg. # 01-2119484627-25-XXXX

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation

First-aid measures after skin contact

First-aid measures after eye contact

First-aid measures after ingestion

- : In case of disturbances owing to inhalation of vapours or mists, remove the victim from exposure; keep at rest; if necessary, seek medical attention. See also section 4.3.
- : Take off contaminated clothing and shoes. Wash thoroughly with soap and water. If skin irritation occurs: Get medical advice/attention. In case of burns, cool affected part with cold running water for at least 10 min. Cover with gauze or clean cloth. Ask for medical assistance or bring to a hospital. Do not apply salves or other substances, unless by doctor's advice. Body hypothermia must be avoided. Do not put ice on the burn.
- : Rinse eyes thoroughly for at least 15 minutes. Keep eyelids well apart. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation, blurred vision or swelling occurs and persists, obtain medical advice from a specialist. In case of burns, cool affected part with cold running water for at least 10 min. Cover with gauze or clean cloth. Ask for medical assistance or bring to a hospital. Do not apply salves or other substances, unless by doctor's advice.
- : Do NOT induce vomiting. If the person is conscious, rinse mouth with water without swallowing. Keep at rest. Call for medical assistance or bring to an hospital. If the casualty is unconscious, place in the recovery position. In case of spontaneous vomiting, keep head low, to avoid the risk of aspiration into the lungs. Do not give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation

: This product has a low vapour pressure, and in normal conditions at ambient temperature the concentration in the air is negligible. A significant concentration may build up only in case of sprays and mists. In these cases overexposure to mists (e.g. through prolonged use in confined insufficiently ventilated spaces) may cause irritation to airways, nausea and dizziness.

Product Safety Information Sheet

A safety data sheet is not required for this product under Article 31 of REACH. This Product Safety Information Sheet has been created on a voluntary basis

Symptoms/effects after skin contact

: Contact with hot product may cause thermal burns.

Symptoms/effects after eye contact

: Contact with eyes may cause a light transient irritation. Contact with hot product or vapours

may cause burns.

Symptoms/effects after ingestion

 $: \ \ \ \text{Accidental ingestion of small quantities of the product may cause nausea, discomfort and}$

gastric disturbances.

Symptoms/effects upon intravenous administration

: No information available.

Chronic symptoms

: None to be reported, according to the present classification criteria.

4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical attention if casualty has an altered state of consciousness or if symptoms do not resolve. Seek medical attention in all cases of serious burns. If there is any suspicion of inhalation of H2S (hydrogen sulphide), Rescuers must wear breathing apparatus, belt and safety rope, and follow rescue procedures. Send patient to hospital. Immediately begin artificial respiration if breathing has ceased. Administer oxygen if necessary.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

: Small-size fires: carbon dioxide, dry chemicals, foam, sand or earth. Large fires: foam or water fog (mist). These means should be used by trained personnel only. Other extinguishing gases (according to regulations).

Unsuitable extinguishing media

: Do not use water jets. They could cause splattering, and spread the fire. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

5.2. Special hazards arising from the substance or mixture

Fire hazard

: This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels.

Explosion hazard

: Heat may build pressure in tank and containers, rupturing closed vessels, spreading fire and increasing risk of burns and injuries. Vapours may form explosive mixture with air.

Hazardous decomposition products in case of fire

: Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid particulates, gases, including carbon monoxide, NOx, H2S and SOx (harmful/toxic gases). Oxygenated compounds (aldehydes, etc.). POx. ZnOx. CaOx.

5.3. Advice for firefighters

Firefighting instructions

: Shut off source of product, if possible. If possible, move containers and drums away from the danger area, if safe to do so. Spilled product which is not burning should be covered with sand or foam. Use water sprays to cool containers and surfaces exposed to the flames. If the fire cannot be controlled, evacuate area.

Special protective equipment for firefighters

: Wear personal protection equipment. (see chapter 8). In case of a large fire or in confined or poorly ventilated spaces, wear full fire resistant protective clothing and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. EN 443. EN 469. EN 659.

Other information

: In case of fire, do not discharge residual product, waste materials and runoff water: collect separately and use a proper treatment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Stop or contain leak at the source, if safe to do so. Eliminate all ignition sources if safe to do so (e.g. electricity, sparks, fires, flares). Avoid direct contact with released material. Avoid accidental sprays on hot surfaces or electrical contacts. Keep upwind.

6.1.1. For non-emergency personnel

Protective equipment

Emergency procedures

: See Section 8.

: Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency.

Product Safety Information Sheet

A safety data sheet is not required for this product under Article 31 of REACH. This Product Safety Information Sheet has been created on a voluntary basis

6.1.2. For emergency responders

Protective equipment

: Small spillages: normal antistatic working clothes are usually adequate. Large spillages: full body suit of chemically resistant and antistatic material. if necessary heat resistant and insulated. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Gloves made of PVA are not water-resistant, and are not suitable for emergency use. If contact with hot product is possible or anticipated, gloves should be heat-resistant and thermally insulated. Antistatic non-skid safety shoes or boots, chemical resistant, if necessary heat resistant and insulated. Work helmet. Goggles and /or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory protection: A half or full-face respirator with filter(s) for organic vapours (A) (or A+B when applicable for H2S), or a Self-contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. A Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.

Emergency procedures

: If required, notify relevant authorities according to all applicable regulations.

6.2. Environmental precautions

Do not let the product accumulate in confined or underground spaces. Do not let the product flow into sewers or water courses, or in any way contaminate the environment. In case of contamination of environment compartments (soil, subsoil, surface or underground waters), remove contaminated soil when possible, and in any case treat all involved compartments in accordance with local regulations. The site should have a spill plan to ensure that adequate safeguards are in place to minimize the impact of episodic releases.

6.3. Methods and material for containment and cleaning up

For containment

: Contain spilled liquid with sand, earth or other suitable absorbents (non-flammable). Recover free liquid and waste materials in suitable waterproof and oil-resistant containers. Clean contaminated area. Dispose of according to local regulations. If in water: Confine the spillage. Remove from surface by skimming or suitable floating absorbents. Collect recovered product and other waste materials in suitable waterproof, oil resistant containers. Recover or dispose of according to local regulations. Do not use solvents or dispersants, unless specifically advised by an expert, and, if required, approved by local authorities.

Methods for cleaning up

Other information

- : Transfer recovered product and other materials to suitable tanks or containers and store/dispose according to relevant regulations.
- : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air/water temperature, wave/current direction and speed) may significantly influence the choice of appropriate actions. Local regulations may also prescribe or limit actions to be taken. For this reason, local experts should be consulted when necessary.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: This material is combustible, but will not ignite readily. Provide adequate ventilation. Use adequate personal protective equipment as needed. Due to the extremely slippery nature of this material, more care than usual must be exercised in material handling practices to keep off all walking surfaces. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Avoid release to the environment. Emptied containers can contain combustible product residues. Do not cut, weld, drill, burn or incinerate empty containers or drums, unless they have been drained and cleaned. Before entering storage tanks and commencing any operation in a confined area (e.g. tunnels), carry out an adequate cleanup, and check the atmosphere for oxygen content, flammability, and the presence of sulphur compounds. The product may release Hydrogen Sulphide: a specific assessment of inhalation risks from the presence of hydrogen sulphide in tank headspaces, confined spaces, product residue, tank waste and waste water, and unintentional releases should be made to help determine controls appropriate to local circumstances. See also Section 16, "Other information".

Product Safety Information Sheet

A safety data sheet is not required for this product under Article 31 of REACH. This Product Safety Information Sheet has been created on a voluntary basis

Hygiene measures

: Ensure that proper housekeeping measures are in place. Avoid contact with skin. Do not breathe fume/ mist/ vapours. Do not ingest. Do not smoke. Do not eat and do not drink during use. Do not clean hands with dirty or oil-soaked rags. Do not re-use clothes, if they are still contaminated. Keep away from food and beverages. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Contaminated work clothing should not be allowed out of the workplace. Separate working clothes from town clothes. Launder separately.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in dry, well-ventilated area. Keep away from open flames, hot surfaces and sources of

ignition. Do not smoke.

Incompatible products : Keep away from strong oxidizers.

Storage area : Storage area layout, tank design, equipment and operating procedures must comply with the relevant European, national or local legislation. Storage installations/areas should be

designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped

and qualified personnel as defined by national, local or company regulations.

Packages and containers: : If the product is supplied in containers: Keep containers tightly closed and properly labelled.

Keep only in the original container or in a suitable container for this kind of product.

Packaging materials : For containers, or container linings use materials specifically approved for use with this

product. Compatibility should be checked with the manufacturer, according to the specific

use conditions.

Germany

Storage class (LGK, TRGS 510) : LGK 10 - Combustible liquids

Switzerland

Storage class (LK) : LK 10/12 - Liquids

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Mineral base oil, severely refined		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Belgium - Occupational Exposure Limits		
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Denmark - Occupational Exposure Limits		
OEL TWA	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
OEL STEL	2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	

Product Safety Information Sheet

A safety data sheet is not required for this product under Article 31 of REACH. This Product Safety Information Sheet has been created on a voluntary basis

Mineral base oil, severely refined	
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
KGV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
WEL STEL (OEL STEL)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
ACGIH OEL STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Lubricating oils (petroleum), C20-50, hydrotre Baseoil - unspecified (72623-87-1)	ated neutral oil-based
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Belgium - Occupational Exposure Limits	o mg/m (winder base on mist, severely reinted, bivide extract 45 % m/m)
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Denmark - Occupational Exposure Limits	Trighti (Milleral base oil filist, severely relified, Diviso extract <5.6 fil/fil)
OEL TWA	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
OEL STEL	2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Hungary - Occupational Exposure Limits	2 mg/m (Milleral base oil mist, severely relined, biviso extract <5.6 m/m)
AK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Netherlands - Occupational Exposure Limits	Tright (Milleral base oil filist, severely relified, Diviso extract <5.6 fil/fil)
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Spain - Occupational Exposure Limits	Trighti (Milleral base oil filist, severely relified, Diviso extract <5.6 fil/fil)
VLA-ED (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Sweden - Occupational Exposure Limits	10 Highii (Militeral base oii Hilst, severely relified, Divisor extract <5 // Highli)
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
KGV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
United Kingdom - Occupational Exposure Limits	o mg/m (winter at base on mist, severely reinted, Divisor extract <5 // mi/m)
WEL TWA (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
,	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
WEL STEL (OEL STEL)	To might (witheral base oil filist, severely relified, Diviso extract <5% fil/fil)
USA - ACCIH - Occupational Exposure Limits	Emalm3 /Minoral base oil mist soverally rafined DMSO sytrast 220/ m/m)
ACCILLOSI STEL	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
ACGIH OEL STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)

8.1.2. Recommended monitoring procedures

Monitoring methods	
Monitoring methods	Monitoring procedures should be chosen according to the indications set by national authorities or labour contracts. Refer to relevant legislation and in any case to the good practice of industrial hygiene.

Product Safety Information Sheet

A safety data sheet is not required for this product under Article 31 of REACH. This Product Safety Information Sheet has been created on a voluntary basis

8.1.3. Air contaminants formed

Applicable OEL and BLV for air contaminants : None known

8.1.4. DNEL and PNEC

Enti-Ride Moto 20W-50 DNELDMEL (additional Information) Addisonal Information Not applicable PNEC (additional Information) Addisonal Information Not applicable Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) DNELDMEL (Workers) Long-term - systemic effects, dermal 1 mg/kg bodyweight/day Long-term - systemic effects, inhalation 2 7 mg/m² DNELDMEL (General population) Long-term - local effects, inhalation 1 2 mg/m²/day PNEC (oral) PNEC (oral) PNEC (oral) PNEC (oral) PNEC (oral) Says mg/kg food Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Basooil - unspecified (72623-87-1) DNELDMEL (Workers) Long-term - systemic effects, inhalation 2 73 mg/m² Long-term - systemic effects, inhalation 2 73 mg/m² DNELDMEL (General population) Long-term - systemic effects, inhalation 2 73 mg/m² DNELDMEL (General population) Long-term - systemic effects, inhalation 5 58 mg/m² DNELDMEL (General population) Long-term - systemic effects, inhalation 5 74 mg/kg bodyweight/day Long-term - systemic effects, inhalation 1 19 mg/m² PNEC (additional information) Additional information Not applicable (UVCB) Distillates (petroleum), solvent-refined heavy paraffilic; Baseoil— unspecified; (A complex combination of hydrocarbons bating acarbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least 100 SUS at 100 °F (1954 at 40 °C).] (64741-88-4) DNELDMEL (General population) Long-term - systemic effects, inhalation 5 6 mg/m² DNELDMEL (General population) Long-term - systemic effects, inhalation 5 6 mg/m² DNELDMEL (General population) Long-term - systemic effects, inhalation 5 6 mg/m² DNELDMEL (General population) Long-term - systemic effects, inhalation 5 7 mg/m² Long-term - systemic effects, inhalation 5 8 mg/m² Long-term - systemic effects, inhalation 5 9 mg/m² Long-term - local effects, inhalation 5 9 mg/m² Long-term - local effects, inhalation 5 9 mg/m² Long-term - local effects, inhalat	5.1.4. DNEL and PNEC		
Additional information Not applicable PNEC (additional information) Additional information Not applicable Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) DNEL/DMEL (Workers) Long-term - systemic effects, dermal 1 mg/kg bodyweight/day Long-term - local effects, inhalation 2.7 mg/m² DNEL/DMEL (General population) Long-term - local effects, inhalation 1.2 mg/m²/day PNEC (oral) PNEC (oral) PNEC oral (secondary poisoning) 9.33 mg/kg food Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1) DNEL/DMEL (Workers) Long-term - systemic effects, inhalation 2.73 mg/m² Long-term - systemic effects, inhalation 5.58 mg/m² DNEL/DMEL (General population) Long-term - systemic effects, inhalation 5.58 mg/m² DNEL/DMEL (General population) Long-term - local effects, inhalation 5.58 mg/m² DNEL/DMEL (General population) Long-term - local effects, inhalation 1.19 mg/m² PNEC (additional information) Additional information Not applicable (UVCB) Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydroca	Eni i-Ride Moto 20W-50		
PNEC (additional information) Additional information Not applicable Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) DNELDMEL (Workers) Long-term - systemic effects, demal 1 mg/kg bodyweight/day Long-term - systemic effects, inhalation 5.6 mg/m² DNELDMEL (General population) Long-term - systemic effects, oral 0.74 mg/kg bodyweight/day Long-term - systemic effects, inhalation 1.2 mg/m²/day PNEC (Oral) PNEC (Oral) PNEC (Oral) PNEC oral (secondary poisoning) 9.33 mg/kg food Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1) DNELDMEL (Workers) Long-term - systemic effects, demal 0.97 mg/kg bodyweight/day Long-term - systemic effects, inhalation 2.73 mg/m² Long-term - local effects, inhalation 5.58 mg/m² DNELDMEL (General population) Long-term - local effects, inhalation 1.19 mg/m² PNEC (additional information) Additional information Not applicable (UVCB) Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons baking carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least 100 SUS at 100 °F (19cSt at 40 °C).] (64741-88-4) DNELDMEL (Workers) Long-term - systemic effects, inhalation 2.7 mg/m² Long-term - systemic effects, inhalation 5	DNEL/DMEL (additional information)		
Additional information Not applicable Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) DNEL/DMEL (Workers) Long-term - systemic effects, dermal 1 mg/kg bodyweight/day Long-term - systemic effects, inhalation 2.7 mg/m² Long-term - systemic effects, inhalation 5.6 mg/m² DNEL/DMEL (General population) Long-term - systemic effects, inhalation 1.2 mg/m²/day PNEC (Oral) PNEC Oral (secondary poisoning) 9.33 mg/kg food Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1) DNEL/DMEL (Workers) Long-term - systemic effects, inhalation 2.73 mg/m² Long-term - systemic effects, inhalation 2.73 mg/m² Long-term - systemic effects, inhalation 5.58 mg/m² DNEL/DMEL (General population) Long-term - systemic effects oral 0.74 mg/kg bodyweight/day Long-term - systemic effects oral 1.19 mg/m² PNEC (additional information) Additional information Not applicable (UVCB) Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil - unspecified; [A complex combination of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least 100 SUS at 100 °F (19-St at 40 °C).] (64741-88-4) DNEL/DMEL (Workers) Long-term - systemic effects, inhalation 2.7 mg/m² Long-term - systemic effects, inhalation 5.6 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, inhalation 5.6 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, inhalation 5.6 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, oral 0.74 mg/kg bodyweight/day	Additional information	Not applicable	
Distillatos (petroleum), hydrotreated heavy paraffinic (64742-54-7) DNEL/DMEL (Workers) Long-term - systemic effects, inhalation 2.7 mg/m³ Long-term - local effects, inhalation 5.6 mg/m² DNEL/DMEL (General population) Long-term - systemic effects, inhalation 1.2 mg/m³/day PNEC (oral) PNEC (oral) PNEC (oral) Lubricating oils (petroleum), 220-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1) DNEL/DMEL (Workers) Long-term - systemic effects, inhalation 2.73 mg/m³ Long-term - systemic effects, inhalation 2.73 mg/m³ DNEL/DMEL (Workers) Long-term - systemic effects, inhalation 5.58 mg/m³ DNEL/DMEL (General population) Long-term - local effects, inhalation 1.19 mg/m³ PNEC (additional information) Additional information Not applicable (UVCB) Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons baking carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least 100 SUS at 100 °F (1495t at 40 °C).] (64741-88-4) DNEL/DMEL (Workers) Long-term - systemic effects, inhalation 2.7 mg/m³ Long-term - systemic effects, inhalation Not applicable (UVCB) Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least 100 SUS at 100 °F (1495t at 40 °C).] (64741-88-4) DNEL/DMEL (Workers) Long-term - systemic effects, inhalation 2.7 mg/m³ Long-term - systemic effects, inhalation 5.6 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, oral 0.74 mg/kg bodyweight/day	PNEC (additional information)		
DNEL/DMEL (Workers) Long-term - systemic effects, dermal 1 mg/kg bodyweight/day Long-term - systemic effects, inhalation 2.7 mg/m² Long-term - local effects, inhalation 5.6 mg/m² DNEL/DMEL (General population) Long-term - local effects, inhalation 1.2 mg/m²/day PNEC (Oral) PNEC oral (secondary poisoning) 9.33 mg/kg food Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1) DNEL/DMEL (Workers) Long-term - systemic effects, dermal 0.97 mg/kg bodyweight/day Long-term - systemic effects, inhalation 2.73 mg/m² Long-term - systemic effects, inhalation 5.58 mg/m² DNEL/DMEL (General population) Long-term - systemic effects, inhalation 1.19 mg/m² PNEC (additional information) Additional information Not applicable (UVCB) Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons baving carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least 100 SUs at 100 °F (19cSt at 40 °C).] (64741-88-4) DNEL/DMEL (Workers) Long-term - systemic effects, dermal 1 mg/kg bodyweight/day Long-term - systemic effects, inhalation 2.7 mg/m² Long-term - systemic effects, inhalation 5.6 mg/m² DNEL/DMEL (General population) Long-term - systemic effects, inhalation 5.6 mg/m² DNEL/DMEL (General population) Long-term - systemic effects, inhalation 5.6 mg/m² DNEL/DMEL (General population) Long-term - systemic effects, inhalation 5.6 mg/m² DNEL/DMEL (General population) Long-term - systemic effects, oral 0.74 mg/kg bodyweight/day	Additional information	Not applicable	
Long-term - systemic effects, inhalation 2.7 mg/m² Long-term - local effects, inhalation 5.6 mg/m² DNEL/DMEL (General population) Long-term - systemic effects, oral 0.74 mg/kg bodyweight/day Long-term - systemic effects, oral 1.2 mg/m³/day PNEC (Oral) PNEC (Oral) PNEC oral (secondary poisoning) 9.33 mg/kg food Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1) DNEL/DMEL (Workers) Long-term - systemic effects, inhalation 2.73 mg/m² Long-term - systemic effects, inhalation 5.5 8 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, inhalation 1.19 mg/m² PNEC (datitional information) Additional information Not applicable (UVCB) Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil – unspecified; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least 100 SUS at 100 °F (19cSt at 40 °C).] (64741-88-4) DNEL/DMEL (Workers) Long-term - systemic effects, inhalation 2.7 mg/m² Long-term - systemic effects, inhalation 2.7 mg/m² DNEL/DMEL (Workers) Long-term - systemic effects, inhalation 2.7 mg/m² Long-term - systemic effects, inhalation 5.6 mg/m² DNEL/DMEL (General population) Long-term - systemic effects, inhalation 5.6 mg/m² DNEL/DMEL (General population)	Distillates (petroleum), hydrotreated heavy pa	raffinic (64742-54-7)	
Long-term - systemic effects, inhalation 5.6 mg/m² DNEL/DMEL (General population) Long-term - local effects, oral 0.74 mg/kg bodyweight/day Long-term - systemic effects, oral 1.2 mg/m²/day PNEC (Oral) PNEC Oral) PNEC oral (secondary poisoning) 9.33 mg/kg food Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1) DNEL/DMEL (Workers) Long-term - systemic effects, dermal 0.97 mg/kg bodyweight/day Long-term - systemic effects, inhalation 2.73 mg/m² DNEL/DMEL (General population) Long-term - systemic effects, inhalation 5.58 mg/m² DNEL/DMEL (General population) Long-term - systemic effects, inhalation 1.19 mg/m² PNEC (additional information) Additional information Not applicable (UVCB) Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists prodominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least 100 SUS at 100 °F (19cSt at 40 °C).] (64741-88-4) DNEL/DMEL (Workers) Long-term - systemic effects, inhalation 2.7 mg/m² Long-term - systemic effects, inhalation 2.7 mg/m² DNEL/DMEL (General population) Long-term - systemic effects, inhalation 5.6 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, inhalation 5.6 mg/m³	DNEL/DMEL (Workers)		
Long-term - local effects, inhalation DNEL/DMEL (General population) Long-term - systemic effects, cral 1.2 mg/m³/day PNEC (Oral) PNEC oral (secondary poisoning) 9.33 mg/kg food Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1) DNEL/DMEL (Workers) Long-term - systemic effects, dermal Long-term - systemic effects, inhalation 2.73 mg/m³ DNEL/DMEL (General population) Long-term - local effects, inhalation 5.58 mg/m³ DNEL/DMEL (General population) Long-term - local effects, inhalation Not applicable (UVCB) Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least 100 SUS at 100 °F (1965t at 40 °C).] (64741-88-4) DNEL/DMEL (Workers) Long-term - systemic effects, dermal 1 mg/kg bodyweight/day Long-term - systemic effects, inhalation 2.7 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, inhalation 9.74 mg/kg bodyweight/day Long-term - systemic effects, inhalation 2.7 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, inhalation 5.6 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, inhalation 0.74 mg/kg bodyweight/day	Long-term - systemic effects, dermal	1 mg/kg bodyweight/day	
DNEL/DMEL (General population) Long-term - systemic effects, oral	Long-term - systemic effects, inhalation	2.7 mg/m³	
Long-term - systemic effects, inhalation PNEC (Oral) PNEC oral (secondary poisoning) 9.33 mg/kg food Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1) DNEL/DMEL (Workers) Long-term - systemic effects, inhalation 2.73 mg/m² Long-term - systemic effects, inhalation DNEL/DMEL (General population) Long-term - systemic effects, inhalation DNEL/DMEL (General population) Long-term - systemic effects, inhalation 1.19 mg/m² PNEC (additional information Additional information Not applicable (UVCB) Distillates (petroleum), solvent-refined heavy parafffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least 100 SUS at 100 °F (19cSt at 40 °C).] (64741-88-4) DNEL/DMEL (Workers) Long-term - systemic effects, inhalation 2.7 mg/m² 1 mg/kg bodyweight/day Long-term - systemic effects, inhalation 2.7 mg/m² DNEL/DMEL (Workers) Long-term - systemic effects, inhalation 2.7 mg/m² DNEL/DMEL (General population) Long-term - systemic effects, inhalation 2.7 mg/m² DNEL/DMEL (General population) Long-term - systemic effects, inhalation DNEL/DMEL (General population) Long-term - systemic effects, inhalation DNEL/DMEL (General population) DNEL/DMEL (General population) Long-term - systemic effects, oral	Long-term - local effects, inhalation	5.6 mg/m³	
Long-term - local effects, inhalation 1.2 mg/m²/day PNEC (Oral) PNEC oral (secondary poisoning) 9.33 mg/kg food Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1) DNEL/DMEL (Workers) Long-term - systemic effects, dermal 0.97 mg/kg bodyweight/day Long-term - systemic effects, inhalation 2.73 mg/m² DNEL/DMEL (General population) Long-term - systemic effects, inhalation 1.19 mg/m² PNEC (additional information) Additional information Not applicable (UVCB) Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least 100 SUS at 100 °F (19cSt at 40 °C).] (64741-88-4) DNEL/DMEL (Workers) 1 mg/kg bodyweight/day Long-term - systemic effects, inhalation 2.7 mg/m³ Long-term - systemic effects, inhalation 5.6 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, oral 0.74 mg/kg bodyweight/day DNEL/DMEL (General population) Long-term - systemic effects, oral 0.74 mg/kg bodyweight/day	DNEL/DMEL (General population)		
PNEC (Oral) PNEC oral (secondary poisoning) 9.33 mg/kg food Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1) DNEL/DMEL (Workers) Long-term - systemic effects, dermal Long-term - systemic effects, inhalation 2.73 mg/m² DNEL/DMEL (General population) Long-term - local effects, inhalation 1.19 mg/m² PNEC (additional information) Additional information Not applicable (UVCB) Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least 100 SUS at 100 °F (19cSt at 40 °C).] (64741-88-4) DNEL/DMEL (Workers) Long-term - systemic effects, inhalation 1 mg/kg bodyweight/day Long-term - systemic effects, inhalation 5.6 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, oral 0.74 mg/kg bodyweight/day	Long-term - systemic effects,oral	0.74 mg/kg bodyweight/day	
PNEC oral (secondary poisoning) James and produces a finished oil with a viscosity of at least 100 SUS at 100 °F (19cSt at 40 °C).] (64741-88-4) DNEL/DMEL (Workers) Long-term - systemic effects, dermal Long-term - systemic effects, inhalation Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least 100 SUS at 100 °F (19cSt at 40 °C).] (64741-88-4) DNEL/DMEL (Workers) Long-term - systemic effects, inhalation DNEL/DMEL (General population) Long-term - systemic effects, oral DNEL/DMEL (General population) Long-term - systemic effects, oral DNEL/DMEL (General population) Long-term - systemic effects, oral	Long-term - local effects, inhalation	1.2 mg/m³/day	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1) DNEL/DMEL (Workers) Long-term - systemic effects, dermal 0.97 mg/kg bodyweight/day Long-term - systemic effects, inhalation 5.58 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, oral 0.74 mg/kg bodyweight/day Long-term - systemic effects, oral 1.19 mg/m³ PNEC (additional information) Additional information Not applicable (UVCB) Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least 100 SUS at 100 °F (19cSt at 40 °C).] (64741-88-4) DNEL/DMEL (Workers) Long-term - systemic effects, inhalation 2.7 mg/m³ Long-term - systemic effects, inhalation 5.6 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, oral 0.74 mg/kg bodyweight/day	PNEC (Oral)		
Baseoil - unspecified (72623-87-1) DNEL/DMEL (Workers) Long-term - systemic effects, dermal 0.97 mg/kg bodyweight/day Long-term - systemic effects, inhalation 2.73 mg/m³ Long-term - local effects, inhalation 5.58 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, oral 0.74 mg/kg bodyweight/day Long-term - local effects, inhalation 1.19 mg/m³ PNEC (additional information) Additional information Not applicable (UVCB) Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least 100 SUS at 100 °F (19cSt at 40 °C).] (64741-88-4) DNEL/DMEL (Workers) Long-term - systemic effects, inhalation 2.7 mg/m³ Long-term - systemic effects, inhalation 5.6 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, oral 0.74 mg/kg bodyweight/day	PNEC oral (secondary poisoning)	9.33 mg/kg food	
Long-term - systemic effects, dermal Long-term - systemic effects, inhalation 2.73 mg/m³ Long-term - local effects, inhalation 5.58 mg/m² DNEL/DMEL (General population) Long-term - systemic effects, oral 0.74 mg/kg bodyweight/day Long-term - local effects, inhalation 1.19 mg/m³ PNEC (additional information) Additional information Not applicable (UVCB) Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least 100 SUS at 100 °F (19cSt at 40 °C).] (64741-88-4) DNEL/DMEL (Workers) Long-term - systemic effects, dermal Long-term - systemic effects, inhalation 2.7 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, oral 0.74 mg/kg bodyweight/day 0.74 mg/kg bodyweight/day			
Long-term - systemic effects, inhalation 2.73 mg/m³ Long-term - local effects, inhalation 5.58 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, oral 0.74 mg/kg bodyweight/day Long-term - local effects, inhalation 1.19 mg/m³ PNEC (additional information) Additional information Not applicable (UVCB) Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least 100 SUS at 100 °F (19cSt at 40 °C).] (64741-88-4) DNEL/DMEL (Workers) Long-term - systemic effects, dermal 1 mg/kg bodyweight/day Long-term - local effects, inhalation 5.6 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, oral 0.74 mg/kg bodyweight/day	DNEL/DMEL (Workers)		
Long-term - local effects, inhalation DNEL/DMEL (General population) Long-term - systemic effects, oral 0.74 mg/kg bodyweight/day Long-term - local effects, inhalation 1.19 mg/m³ PNEC (additional information) Additional information Not applicable (UVCB) Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least 100 SUS at 100 °F (19cSt at 40 °C).] (64741-88-4) DNEL/DMEL (Workers) Long-term - systemic effects, dermal 1 mg/kg bodyweight/day Long-term - local effects, inhalation 2.7 mg/m³ Long-term - local effects, inhalation 5.6 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, oral 0.74 mg/kg bodyweight/day	Long-term - systemic effects, dermal	0.97 mg/kg bodyweight/day	
DNEL/DMEL (General population) Long-term - systemic effects, oral 0.74 mg/kg bodyweight/day Long-term - local effects, inhalation 1.19 mg/m³ PNEC (additional information) Additional information Not applicable (UVCB) Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least 100 SUS at 100 °F (19cSt at 40 °C).] (64741-88-4) DNEL/DMEL (Workers) Long-term - systemic effects, dermal 1 mg/kg bodyweight/day Long-term - local effects, inhalation 5.6 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, oral 0.74 mg/kg bodyweight/day	Long-term - systemic effects, inhalation	2.73 mg/m³	
Long-term - systemic effects, oral Long-term - local effects, inhalation 1.19 mg/m³ PNEC (additional information) Additional information Not applicable (UVCB) Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least 100 SUS at 100 °F (19cSt at 40 °C).] (64741-88-4) DNEL/DMEL (Workers) Long-term - systemic effects, dermal Long-term - systemic effects, inhalation 2.7 mg/m³ Long-term - local effects, inhalation 5.6 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects,oral 0.74 mg/kg bodyweight/day	Long-term - local effects, inhalation	5.58 mg/m³	
Long-term - local effects, inhalation PNEC (additional information) Additional information Not applicable (UVCB) Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least 100 SUS at 100 °F (19cSt at 40 °C).] (64741-88-4) DNEL/DMEL (Workers) Long-term - systemic effects, dermal Long-term - local effects, inhalation 5.6 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects,oral 0.74 mg/kg bodyweight/day	DNEL/DMEL (General population)		
PNEC (additional information) Additional information Not applicable (UVCB) Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least 100 SUS at 100 °F (19cSt at 40 °C).] (64741-88-4) DNEL/DMEL (Workers) Long-term - systemic effects, dermal	Long-term - systemic effects,oral	0.74 mg/kg bodyweight/day	
Additional information Not applicable (UVCB) Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least 100 SUS at 100 °F (19cSt at 40 °C).] (64741-88-4) DNEL/DMEL (Workers) Long-term - systemic effects, dermal 1 mg/kg bodyweight/day Long-term - local effects, inhalation 2.7 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, oral 0.74 mg/kg bodyweight/day	Long-term - local effects, inhalation	1.19 mg/m³	
Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least 100 SUS at 100 °F (19cSt at 40 °C).] (64741-88-4) DNEL/DMEL (Workers) Long-term - systemic effects, dermal	PNEC (additional information)		
obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least 100 SUS at 100 °F (19cSt at 40 °C).] (64741-88-4) DNEL/DMEL (Workers) Long-term - systemic effects, dermal	Additional information	Not applicable (UVCB)	
Long-term - systemic effects, dermal Long-term - systemic effects, inhalation 2.7 mg/m³ Long-term - local effects, inhalation 5.6 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, oral 0.74 mg/kg bodyweight/day	carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least		
Long-term - systemic effects, inhalation 2.7 mg/m³ Long-term - local effects, inhalation 5.6 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, oral 0.74 mg/kg bodyweight/day	DNEL/DMEL (Workers)		
Long-term - local effects, inhalation 5.6 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, oral 0.74 mg/kg bodyweight/day	Long-term - systemic effects, dermal	1 mg/kg bodyweight/day	
DNEL/DMEL (General population) Long-term - systemic effects,oral 0.74 mg/kg bodyweight/day	Long-term - systemic effects, inhalation	2.7 mg/m³	
Long-term - systemic effects,oral 0.74 mg/kg bodyweight/day	Long-term - local effects, inhalation	5.6 mg/m³	
	DNEL/DMEL (General population)		
Long-term - local effects, inhalation 1.2 mg/m³/day	Long-term - systemic effects,oral	0.74 mg/kg bodyweight/day	
	Long-term - local effects, inhalation	1.2 mg/m³/day	

Product Safety Information Sheet

A safety data sheet is not required for this product under Article 31 of REACH. This Product Safety Information Sheet has been created on a voluntary basis

Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least 100 SUS at 100 °F (19cSt at 40 °C).] (64741-88-4)

PNEC (Oral)

PNEC oral (secondary poisoning)

9.33 mg/kg food

Note

: The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a governmental regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH.

8.1.5. Control banding

Control banding : None known

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure that there is a suitable ventilation system. Before entering storage tanks and commencing any operation in a confined area (e.g. tunnels), check the atmosphere for oxygen content, presence of hydrogen sulphide (H2S) and SOx, and flammability. See also Section 16, "Other information".

8.2.2. Personal protection equipment

Personal protective equipment (for industrial or professional use):

Face shield. Gloves. Protective clothing. Safety glasses. Safety shoes or boots. High gas/vapour concentration: gas mask with filter for organic vapours (A) or organic vapours/H2S (A+B).

Personal protective equipment symbol(s):













8.2.2.1. Eye and face protection

Eye protection:

When there is a risk of contact with the eyes, use safety goggles or other means of protection (face shield). If necessary, refer to national standards or to the EN 166 standard.

8.2.2.2. Skin protection

Skin and body protection:

Long-sleeved overalls. If necessary, refer to the EN 340 and related standards, for definition of characteristics and performance according to the risk rating of the area. Antistatic non-skid safety shoes or boots, chemical resistant, if necessary heat resistant and insulated.

Hand protection:

When there is a risk of contact with the skin, use waterproof gloves, resistant to chemical products. Gloves must be felt-lined. Adequate materials: nitrile (NBR) or PVC with a protection index > 5 (permeation time > 240 mins). Use gloves respecting all the conditions and within the limits set by the manufacturer. Replace gloves immediately in case of cuts, holes or other signs of damages or degradation. If necessary, refer to the EN 374 standard. Personal hygiene is a key element for an effective hand care. Gloves must be worn only with clean hands. After wearing gloves, hands must be carefully washed and dried.

Product Safety Information Sheet

A safety data sheet is not required for this product under Article 31 of REACH. This Product Safety Information Sheet has been created on a voluntary basis

8.2.2.3. Respiratory protection

Respiratory protection:

Independently from other possible actions (technical modifications, operating procedures, and other means to limit the exposure of workers), personal protection equipment can be used according to necessity. Open or well ventilated spaces: in presence of oil mists and if the product is handled without adequate containment means: use full or half-face masks with filter for mists/aerosols (P). In case there is a significant presence of vapours (e.g. through handling at high temperature), use full or half-face masks with a filter for organic vapours (A), and H2S (B) where applicable. (EN 136/140/145). Combined gas/dust mask with filter type: EN 14387. Closed or confined areas (e.g. tank interiors): the use of protection measures for airways (masks or self-contained breathing apparatus), must be assessed according to the specific activity, as well as level and duration of predicted exposure. Approved respiratory protection equipment shall be used in spaces where hydrogen sulphide may accumulate: full face mask with cartridge/filter type "B" (grey for inorganic vapours including H2S) or self-contained breathing apparatus (SCBA). (EN 136/140/145)

8.2.2.4. Thermal hazards

Thermal hazard protection:

If contact with hot product is possible or anticipated, gloves should be heat-resistant and thermally insulated.

8.2.3. Environmental exposure controls

Environmental exposure controls:

Do not discharge the product into the environment. Prevent discharge of undissolved substance to or recover from onsite wastewater. Storage areas/installations should be designed with adequate bunds so as to prevent ground and water pollution in case of leaks or spills. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Consumer exposure controls:

No special requirements.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Colour : Yellow-brown.
Appearance : Liquid, bright & clear.
Odour : Slight odour of petroleum.

Odour threshold : There are no data available on the preparation/mixture itself.

Melting point : Not applicable

Freezing point : Lack of data (on mixture / components of the mixture) - Data not available

Softening point : -48 °C (ASTM D97)

Boiling point : Lack of data (on mixture / components of the mixture) - Data not available

Flammability : Not flammable

Lower explosion limit : Lack of data (on mixture / components of the mixture) - Data not available Upper explosion limit : Lack of data (on mixture / components of the mixture) - Data not available

Flash point : 230 °C (ASTM D 92)

Auto-ignition temperature : Lack of data (on mixture / components of the mixture) - Data not available

Decomposition temperature : Lack of data (on mixture / components of the mixture) - Data not available

pH : Lack of data (on mixture / components of the mixture) - Data not available

Viscosity, kinematic : 141 mm²/s (40 °C) (ASTM D 445)
Solubility : Water: Immiscible and insoluble
Log Kow : Not applicable for mixtures
Log Pow : Not applicable for mixtures

Vapour pressure : < 0.1 hPa (20°C)

Vapour pressure at 50°C : Lack of data (on mixture / components of the mixture) - Data not available

Density : 852 kg/m³ (15 °C) (ASTM D 4052)

Relative density : Lack of data (on mixture / components of the mixture) - Data not available Relative vapour density at 20°C : Lack of data (on mixture / components of the mixture) - Data not available

Particle characteristics : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

Relative evaporation rate (butylacetate=1) : Negligible.

Product Safety Information Sheet

A safety data sheet is not required for this product under Article 31 of REACH. This Product Safety Information Sheet has been created on a voluntary basis

SECTION 10: Stability and reactivity

10.1. Reactivity

This mixture does not offer any further hazard for reactivity, except what is reported in the following paragraphs.

10.2. Chemical stability

Stable product, according to its intrinsic properties.

10.3. Possibility of hazardous reactions

None (in normal conditions of storage and handling). Contact with strong oxidizers (peroxides, chromates, etc.) or alkali metals may cause a fire hazard. Sensitivity to heat, friction or shock cannot be assessed in advance.

10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates: Toxic fumes. In exceptional cases (i.e prolonged storage in tanks contaminated with water, and presence of anaerobic sulfate-reducing microbial colonies), the product may undergo a degradation and generate small amounts of sulfur compounds, including H2S.

SECTION 11: Toxicological information

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)
Additional information	(according to composition)

Mineral base oil, severely refined	
LD50 oral rat	> 5000 mg/kg bodyweight (OECD 401)
LD50 dermal rat	> 5000 mg/kg bodyweight (OECD 402)
LC50 Inhalation - Rat	> 5 mg/l/4h (OECD 403)

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)

Baseon - unspecimen (72020-07-1)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg bodyweight
LC50 Inhalation - Rat	≥ 5.53 mg/l/4h
01-1	Not described (Described an excellent data the described for mitaging and material

Skin corrosion/irritation : Not classified (Based on available data, the classification criteria are not met) pH: Lack of data (on mixture / components of the mixture) - Data not available

Additional information : (according to composition)

Mineral base oil, severel	v refined	ed
---------------------------	-----------	----

pH Not applicable

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based

Baseoil - unspecified (72623-87-1)

pН

Serious eye damage/irritation : Not classified (Based on available data, the classification criteria are not met)

Not applicable

pH: Lack of data (on mixture / components of the mixture) - Data not available

Product Safety Information Sheet

A safety data sheet is not required for this product under Article 31 of REACH. This Product Safety Information Sheet has been created on a voluntary basis

Additional information :	(according to composition)		
Mineral base oil, severely refined			
рН	Not applicable		
Lubricating oils (petroleum), C20-50, hydrotre Baseoil - unspecified (72623-87-1)	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)		
pH	Not applicable		
Additional information : Germ cell mutagenicity : Additional information : Carcinogenicity : Additional information :	Not classified (Based on available data, the classification criteria are not met) (according to composition) Not classified (Based on available data, the classification criteria are not met) (according to composition) Not classified (Based on available data, the classification criteria are not met) (according to composition) This product contains: Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating light vacuum gas oil, heavy vacuum gas oil, and; solvent deasphalted residual oil with hydrogen in the presence of a catalyst in a two stage process with dewaxing being carried out between the two stages. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil having a viscosity of approximately 112cSt at 40 °C. It contains a relatively large proportion of saturated hydrocarbons.] this product has a value of DMSO extract < 3 % wt, according to IP 346. According to the criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product must be regarded as non carcinogenic. All the mineral base oils contained in this product have a value < 3 % wt of DMSO extract, according to IP 346 (Nota L - Annex VI Reg (CE) 1272/2008, # 1.1.3) No carcinogenic effect		
Additional information : STOT-single exposure : Additional information :	Not classified (Based on available data, the classification criteria are not met) (according to composition) Not classified (Based on available data, the classification criteria are not met) (according to composition) Not classified (Based on available data, the classification criteria are not met) (according to composition)		
Mineral base oil, severely refined			
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)		
Lubricating oils (petroleum), C20-50, hydrotre Baseoil - unspecified (72623-87-1)	ated neutral oil-based		
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)		
•	Not classified (Based on available data, the classification criteria are not met) (according to composition)		
Eni i-Ride Moto 20W-50			
Viscosity, kinematic	141 mm²/s (40 °C) (ASTM D 445)		
Mineral base oil, severely refined			
Viscosity, kinematic	> 21 mm²/s		
Hydrocarbon	Yes		
Lubricating oils (petroleum), C20-50, hydrotre Baseoil - unspecified (72623-87-1)	eated neutral oil-based		
Viscosity, kinematic	29 – 34 mm²/s (40°C) (ASTM D 445)		

Product Safety Information Sheet

A safety data sheet is not required for this product under Article 31 of REACH. This Product Safety Information Sheet has been created on a voluntary basis

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

11.2.2. Other information

Potential adverse human health effects and symptoms

Other information

: Contact with eyes may cause temporary reddening and irritation, Avoid all eye and skin contact and do not breathe vapour and mist

: None

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general

: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment. An uncontrolled release to the environment may nevertheless produce a contamination of different environmental compartments (air, soil, underground, surface water bodies, aquifers). Handle according to general working hygiene practices to avoid pollution and release into the environment.

Ecology - air

This product has a low vapour pressure, and in normal conditions at ambient temperature the concentration in the air is negligible. A significant concentration may build up only in case of sprays and mists. In these cases overexposure to mists (e.g. through prolonged use in confined insufficiently ventilated spaces) may cause irritation to airways, nausea and dizziness.

Ecology - water

This product is not soluble in water. It floats on water and forms a film on the surface. The damage to aquatic organisms is of mechanical kind (immobilization and entrapment)

Hazardous to the aquatic environment, short–term (acute)

Not classified (Based on available data, the classification criteria are not met)

Hazardous to the aquatic environment, long-term (chronic)

: Not classified (Based on available data, the classification criteria are not met)

Mineral base oil, severely refined	
LC50 fish 1	> 100 mg/l (LL 50)
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)	
LC50 fish 1	> 100 mg/l
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)

12.2. Persistence and degradability

Eni i-Ride Moto 20W-50	
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.
Mineral base oil, severely refined	
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions

Product Safety Information Sheet

A safety data sheet is not required for this product under Article 31 of REACH. This Product Safety Information Sheet has been created on a voluntary basis

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)	
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions

12.3. Bioaccumulative potential

Eni i-Ride Moto 20W-50	
Log Pow	Not applicable for mixtures
Log Kow	Not applicable for mixtures
Bioaccumulative potential	Not established.

12.4. Mobility in soil

Eni i-Ride Moto 20W-50	
Ecology - soil	No data available.

12.5. Results of PBT and vPvB assessment

Eni i-Ride Moto 20W-50		
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII		
This substance/mixture does not meet the vPvB criteria	of REACH regulation, annex XIII	
Results of PBT-vPvB assessment	The components in this formulation do not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)	
Component		
Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)	
Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)	

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

12.7. Other adverse effects

Other adverse effects

: None.

Additional information

: This product has no specific properties for inhibition of bacterial activity. In any case, wastewater containing this product should be treated in plants that are suited for the specific purpose.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods

: Do not dispose of the product, either new or used, by dumping on the ground, or discharging into sewers, tunnels, lakes or water courses. Deliver to a qualified official collector.

Product Safety Information Sheet

A safety data sheet is not required for this product under Article 31 of REACH. This Product Safety Information Sheet has been created on a voluntary basis

Sewage disposal recommendations

: Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed. Dispose of in a safe manner in accordance with local/national regulations.

Product/Packaging disposal recommendations

European Waste Catalogue code(s) (Decision 2001/118/CE): 13 02 05* (mineral-based non-chlorinated engine, gear and lubricating oils). This EWC code is only a general indication, and takes into account the original composition of the product and its intended use. The user has the responsibility of choosing the right EWC code, considering the actual use of the product, alterations and contaminations.

Additional information

: Empty containers may contain combustible product residues. Do not cut, weld, bore, burn or incinerate emptied containers, unless they have been cleaned and declared safe.

Ecology - waste materials

: The product as it is does not contain halogenated substances.

EURAL code (EWC)

: 13 02 05* - Mineral-based non-chlorinated engine, gear and lubricating oils

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID n	14.1. UN number or ID number			
Not regulated for transport				
14.2. UN proper shippin	g name			
Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.3. Transport hazard class(es)				
Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.4. Packing group				
Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.5. Environmental hazards				
Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
None.				

14.6. Special precautions for user

Overland transport

Not regulated.

Transport by sea

Not regulated.

Air transport

Not regulated.

Inland waterway transport

Not regulated.

Rail transport

Not regulated.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

Product Safety Information Sheet

A safety data sheet is not required for this product under Article 31 of REACH. This Product Safety Information Sheet has been created on a voluntary basis

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Other information, restriction and prohibition regulations

: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). (et sequens). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (et sequens). Directives 89/391/CEE, 89/654/CEE, 89/655/CEE, 89/656/CEE, 90/269/CEE, 90/270/CEE, 90/394/CEE, 90/679/CEE, 93/88/CEE, 95/63/CE, 97/42/CE, 98/24/CE, 99/38/CE, 99/92/CE, 2001/45/CE, 2003/10/CE, 2003/18/CE (Health and safety on the workplace). Directive 2012/18/CE (Control of major-accident hazards involving dangerous substances). Directive 2004/42/CE (Limitation of emissions of Volatile Organic Compounds). Directive 98/24/EC (protection of the health and safety of workers from the risks related to chemical agents at work). Directive 92/85/CE (measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding). Substances Depleting the Ozone layer (1005/2009) - Annex I Substances (ODP). POP (2019/1021) - Persistent Organic Pollutants. Regulation EU (649/2012) -Export and Import of hazardous chemicals (PIC). Commission Delegated Regulation (EU) 2017/2100. Commission Regulation (EU) 2018/605.

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

No ingredients are included in the REACH Candidate list (> 0,1 % m/m).

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

National adoption of EU Directives concerning health and safety on the workplace.

National adoption of EU Directives concerning control of major-accident hazards involving dangerous substances (2012/18/CE).

Relevant national laws on prevention of water pollution.

Relevant national laws on protection of the health of pregnant workers (National adoption of Dir. 92/85/EEC).

National adoption of Directive 2008/98/CE concerning disposal of used oils.

France

Maladies professionelles (F)

Product Safety Information Sheet

National Rules and Recommendations

A safety data sheet is not required for this product under Article 31 of REACH. This Product Safety Information Sheet has been created on a voluntary basis

Code	Description
RG 36	Diseases caused by oils and fats of mineral or synthetic origin

Germany

Employment restrictions : Employment prohibitions or restrictions on the protection of young people at work according

to § 22 JArbSchG in the case of formation of hazardous substances have to be observed. TRGS 400: Hazard assessment for activities involving Hazardous Substances.

TRGS 401: Risks resulting from skin contact - identification, assessment, measures.

TRGS 402: Identification and Assessment of the Risks from Activities involving Hazardous

Substances: Inhalation Exposure.

TRGS 555: Working instruction and information for workers.

TRGS 800: Fire protection measures. TRGS 900: Occupational Exposure Limits.

VbF class (D) : Not applicable.

Water hazard class (WGK) (D) WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1).

WGK remark Classification is carried out on the basis of the Ordinance on facilities for handling substances that are hazardous to water (Verordnung über Anlagen zum Umgang mit

wassergefährdenden Stoffen (AwSV)) of 18 April 2017 (BGBI 2017, Teil I, Nr. 22, Seite

Hazardous Incident Ordinance (12. BlmSchV) Is not subject to the Hazardous Incident Ordinance (12. BlmSchV)

Netherlands

Saneringsinspanningen : C - Minimize discharge

SZW-lijst van kankerverwekkende stoffen None of the components are listed SZW-lijst van mutagene stoffen None of the components are listed SZW-lijst van reprotoxische stoffen - Borstvoeding None of the components are listed : None of the components are listed

SZW-lijst van reprotoxische stoffen -

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen - Ontwikkeling

: None of the components are listed

Denmark

Danish National Regulations : Young people under 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct contact with it

15.2. Chemical safety assessment

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

No chemical safety assessment has been carried out

A chemical safety assessment has been carried out for the following components of this mixture::

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based

Baseoil - unspecified

SECTION 16: Other information

A safety data sheet is not required for this product under Article 31 of REACH. This Product Safety Information Sheet has been created on a voluntary basis

ı	Indication of changes			
•	Section	Changed item	Change	Comments
		First issue.		

Abbreviations and acronyms:		
Complete text of the H phrases quoted in this Safety Data Sheet. These phrases are reported here for information only, and MAY NOT correspond to the classification of the product.		
N/D = not available		
	N/A = not applicable	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	

Product Safety Information Sheet

A safety data sheet is not required for this product under Article 31 of REACH. This Product Safety Information Sheet has been created on a voluntary basis

Abbreviations and acronyms:		
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
CAS-No.	Chemical Abstract Service number	
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC50	Effective concentration for 50 percent of test population (median effective concentration)	
EC-No.	European Community number	
ED	Endocrine disrupting properties	
IARC	International Agency for Research on Cancer	
IATA	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Lethal concentration for 50 percent of test population (median lethal concentration)	
LD50	Lethal dose for 50 percent of test population (median lethal dose)	
LOAEL	Lowest Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
OECD	Organisation for Economic Co-operation and Development	
OEL	Occupational Exposure Limit	
PBT	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals, Regulation (EC) No 1907/2006	
RID	Regulation concerning the International Carriage of Dangerous Goods by Railways	
SDS	Safety Data Sheet	
STP	Sewage treatment plant	
VOC	Volatile Organic Compounds	
vPvB	Very Persistent and Very Bioaccumulative	
WGK	Water Hazard Class	

Data sources

Training advice

- : This Safety Data Sheet is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.
- : Provide adequate training to professional operators for the use of PPEs, according to the information contained in this Safety Data Sheet.

Product Safety Information Sheet

A safety data sheet is not required for this product under Article 31 of REACH. This Product Safety Information Sheet has been created on a voluntary basis

Other information

: Do not use the product for any purposes that have not been advised by the manufacturer. In exceptional cases (i.e prolonged storage in tanks contaminated with water, and presence of anaerobic sulfate-reducing microbial colonies), the product may undergo a degradation and generate small amounts of sulfur compounds, including H2S. This situation is especially relevant in all those circumstances which require to enter a confined space, with direct exposure to the vapours. If this possibility is suspected, a specific assessment of inhalation risks from the presence of H2S in confined spaces must be made, to help determine prevention measures and controls (i.e. PPE) appropriate to local circumstances, and adequate emergency procedures. This situation is especially relevant for those operations which involve direct exposure to the vapours in the interior of tanks or other confined spaces. If there is any suspicion of inhalation of H2S (hydrogen sulphide), Rescuers must wear breathing apparatus, belt and safety rope, and follow rescue procedures. Send patient to hospital. Immediately begin artificial respiration if breathing has ceased. Administer oxygen if necessary. Therefore, it is very important to follow the above mentioned precautionary measures also with used oils.

Safety Data Sheet (SDS), EU