

Product Safety Information Sheet

A safety data sheet is not required for this product under Article 31 of REACH. This Product Safety Information Sheet has been created on a voluntary basis Revision date: 12/19/2024 Supersedes: 7/17/2024 Version: 1.2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier Product form • Mixture Trade name Eni Acer 150 Product code 2165 Type of product Lubricant Formula 0065-2002 · Product group Trade product 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category	: Industrial use, Professional use
Industrial/Professional use spec	: Wide dispersive use
Use of the substance/mixture	: Functional fluids
	Hydraulic oil
Function or use category	: Hydraulic fluids and additives

Uses advised against

Recommended use are listed above; other uses are not recommended unless an assessment has provided that risks are controlled.

1.3. Details of the supplier of product safety information sheet

Enilive S.p.A, Viale Giorgio Ribotta 51, 00144 Rome, ITALY, Tel. +39 06 59821

Competent person responsible for the safety data sheet (Reg. EC nr. 1907/2006): SDS.Enilive@enilive.com

Distributed by: Enilive Schmiertechnik GmbH, Paradiesstraße 14, 97080 Würzburg, GERMANY Department responsible for information: Application Engineering & Product Management (AEPM), Tel. +49 (0)931-900 98-0 e-mail: technik.wuerzburg@enilive.com **1.4. Emergency telephone number**

Emergency number

: CNIT +39 0382 24444 (24h) (IT + EN) Poison Center

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]

Not classified

Adverse physicochemical, human health and environmental effects

None to be reported, according to the present EU regulations. For specific information about the toxicological/ecotoxicological properties and classification of this product, see Sect. 11 and/or Sect. 12.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

No labelling applicable

Product Safety Information Sheet

A safety data sheet is not required for this product under Article 31 of REACH. This Product Safety Information Sheet has been created on a voluntary basis

2.3. Other hazards (not relevant for classification)			
Other hazards not contributing to the classification	: This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels. In case of contact with eyes, this product may cause irritation. If the product is handled or used at high temperature, contact with hot product or vapours may cause burns. Any substance, in case of accidents involving pressurized circuits and the like, may be accidentally injected under the skin, even without external damage. In such a case, the victim should be brought to an hospital as soon as possible, to get specialized medical treatment. Do not wait for symptoms to develop.		

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Component	
Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	Residual oils (petroleum,) solvent-refined (64742-01-4), Distillates (petroleum), solvent- dewaxed heavy paraffinic (64742-65-0)
Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	Residual oils (petroleum,) solvent-refined (64742-01-4), Distillates (petroleum), solvent- dewaxed heavy paraffinic (64742-65-0)

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Component	
Substance(s) not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0), Residual oils (petroleum,) solvent-refined (64742-01-4)

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Comments

: Composition/ Information on ingredients: Mixture of hydrocarbons Additives

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (see note [*], see note [***])	CAS-No.: 64742-65-0 EC-No.: 265-169-7 EC Index-No.: 649-474-00-6 REACH-no: 01-2119471299- 27	60 – 70	Not classified

Product Safety Information Sheet

A safety data sheet is not required for this product under Article 31 of REACH. This Product Safety Information Sheet has been created on a voluntary basis

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]
Residual oils (petroleum,) solvent-refined (see note [*], see note [**])	CAS-No.: 64742-01-4 EC-No.: 265-101-6 EC Index-No.: 649-459-00-4 REACH-no: 01-2119488707- 21	25 – 30	Not classified

Comments

: Note [*]:

this product has a value of DMSO extract < 3 % wt, according to IP 346. According to the criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product must be regarded as non carcinogenic.

Note [**]:

substance with occupational exposure limits for some EU countries affecting the category of mineral oils (finely refined mineral base oil mists; see section 8.1)

Note [***]:

this product may be formulated with one or more of the following base oils: CAS 74869-22-0/ EC: 278-012-2/ REACH Reg. # 01-2119495601-36-XXXX; CAS 64742-54-7/ EC 265-157-1/ REACH Reg. # 01-2119484627-25-XXXX

SECTION 4: First aid measures 4.1. Description of first aid measures First-aid measures after inhalation : In case of disturbances owing to inhalation of vapours or mists, remove the victim from exposure; keep at rest; if necessary, seek medical attention. See also section 4.3. First-aid measures after skin contact Take off contaminated clothing and shoes. Wash thoroughly with soap and water. If skin irritation or rash occurs, get medical advice/attention. In case of burns, cool affected part with cold running water for at least 10 min. Cover with gauze or clean cloth. Ask for medical assistance or bring to a hospital. Do not apply salves or other substances, unless by doctor's advice. Body hypothermia must be avoided. Do not put ice on the burn. First-aid measures after eye contact Rinse eyes thoroughly for at least 15 minutes. Keep eyelids well apart. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation, blurred vision or swelling occurs and persists, obtain medical advice from a specialist. In case of burns, cool affected part with cold running water for at least 10 min. Cover with gauze or clean cloth. Ask for medical assistance or bring to a hospital. Do not apply salves or other substances, unless by doctor's advice. First-aid measures after ingestion Rinse mouth thoroughly with water. Give water to drink if victim completely conscious/alert. Do not induce vomiting. 4.2. Most important symptoms and effects, both acute and delayed Symptoms/effects after inhalation : This product has a low vapour pressure, and in normal conditions at ambient temperature the concentration in the air is negligible. A significant concentration may build up only if the product is used at high temperature, or in case of sprays and mists. In these cases overexposure to vapours may cause irritation to airways, nausea and dizziness. Symptoms/effects after skin contact Contact with hot product may cause thermal burns. Symptoms/effects after eye contact Contact with eyes may cause temporary reddening and irritation. Contact with hot product or vapours may cause burns. Symptoms/effects after ingestion : Accidental ingestion of small quantities of the product may cause nausea, discomfort and gastric disturbances. Symptoms/effects upon intravenous administration No information available. : None to be reported, according to the present classification criteria. Chronic symptoms

4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical attention if casualty has an altered state of consciousness or if symptoms do not resolve. Seek medical attention in all cases of serious burns.

Product Safety Information Sheet

SECTION 5: Firefighting measures		
5.1. Extinguishing media		
Suitable extinguishing media	: Small-size fires: carbon dioxide, dry chemicals, foam, sand or earth. Large fires: foam or water fog (mist). These means should be used by trained personnel only. Other extinguishing gases (according to regulations).	
Unsuitable extinguishing media	: Do not use water jets. They could cause splattering, and spread the fire. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.	
5.2. Special hazards arising from the substance or mixture		
Fire hazard	: This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels.	
Explosion hazard	: The vapours are flammable and may form explosive mixtures with air. Heat may build pressure in tank and containers, rupturing closed vessels, spreading fire and increasing risk of burns and injuries.	
Hazardous decomposition products in case of fire	: Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases. Oxygenated compounds (aldehydes, etc.).	
5.3. Advice for firefighters		
Firefighting instructions	: Shut off source of product, if possible. Move undamaged containers from immediate hazard area if it can be done safely. Spilled product which is not burning should be covered with sand or foam. Use water sprays to cool containers and surfaces exposed to the flames. If the fire cannot be controlled, evacuate area.	
Special protective equipment for firefighters	: Wear personal protection equipment. (see chapter 8). In case of a large fire or in confined or poorly ventilated spaces, wear full fire resistant protective clothing and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. EN 443. EN 469. EN 659.	
Other information	: In case of fire, do not discharge residual product, waste materials and runoff water: collect separately and use a proper treatment.	

SECTION 6: Accidental release	measures
6.1. Personal precautions, protect	ive equipment and emergency procedures
General measures	Stop or contain leak at the source, if safe to do so. Eliminate all ignition sources if safe to do so (e.g. electricity, sparks, fires, flares). Avoid accidental sprays on hot surfaces or electrica contacts. Avoid direct contact with released material. Keep upwind.
For non-emergency personnel	
Protective equipment	: See Section 8.
Emergency procedures	: Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency.
For emergency responders	
Protective equipment	: Small spillages: normal antistatic working clothes are usually adequate. Large spillages: full body suit of chemically resistant and antistatic material. if necessary heat resistant and insulated. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Gloves made of PVA are not water-resistant, and are not suitable for emergency use. If contact with hot product is possible or anticipated, gloves should be heat resistant and thermally insulated. Antistatic non-skid safety shoes or boots, chemical resistant, if necessary heat resistant and insulated. Work helmet. Goggles and /or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory protection: a half or full-face respirator with filter(s) for organic vapours (AX), or a Self-contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
Emergency procedures	: If required, notify relevant authorities according to all applicable regulations.

Product Safety Information Sheet

A safety data sheet is not required for this product under Article 31 of REACH. This Product Safety Information Sheet has been created on a voluntary basis

6.2. Environmental precautions

Do not let the product accumulate in confined or underground spaces. Do not let the product flow into sewers or water courses, or in any way contaminate the environment. In case of contamination of environment compartments (soil, subsoil, surface or underground waters), remove contaminated soil when possible, and in any case treat all involved compartments in accordance with local regulations. The site should have a spill plan to ensure that adequate safeguards are in place to minimize the impact of episodic releases.

6.3. Methods and material for containment and cleaning up

For containment	: Contain spilled liquid with sand, earth or other suitable absorbents (non-flammable). Recover free liquid and waste materials in suitable waterproof and oil-resistant containers. Clean contaminated area. Dispose of according to local regulations. If in water: Confine the spillage. Remove from surface by skimming or suitable floating absorbents. Collect recovered product and other waste materials in suitable waterproof, oil resistant containers. Recover or dispose of according to local regulations. Do not use solvents or dispersants, unless specifically advised by an expert, and, if required, approved by local authorities.
Methods for cleaning up	: Transfer recovered product and other materials to suitable tanks or containers and store/dispose according to relevant regulations.
Other information	: Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air/water temperature, wave/current direction and speed) may significantly influence the choice of appropriate actions. Local regulations may also prescribe or limit actions to be taken. For this reason, local experts should be consulted when necessary.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	: This material is combustible, but will not ignite readily. Provide adequate ventilation. Use adequate personal protective equipment as needed. Due to the extremely slippery nature of this material, more care than usual must be exercised in material handling practices to keep off all walking surfaces. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Avoid release to the environment. Emptied containers can contain combustible product residues. Do not cut, weld, drill, burn or incinerate empty containers or drums, unless they have been drained and cleaned. Before entering storage tanks and commencing any operation in a confined area (e.g. tunnels), carry out an adequate clean-up, and check the atmosphere for oxygen content and flammability. See also Section 16, "Other information".
Hygiene measures	: Ensure that proper housekeeping measures are in place. Avoid contact with skin. Do not breathe fume/ mist/ vapours. Do not ingest. Do not smoke. Do not eat and do not drink during use. Do not clean hands with dirty or oil-soaked rags. Do not re-use clothes, if they are still contaminated. Keep away from food and beverages. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Contaminated work clothing should not be allowed out of the workplace. Separate working clothes from town clothes. Launder separately.
7.2. Conditions for safe storage, including a	any incompatibilities
Storage conditions	: Store in dry, well-ventilated area. Keep away from open flames, hot surfaces and sources of ignition. Do not smoke.
Incompatible products	: Keep away from strong oxidizers.
Storage area	: Storage area layout, tank design, equipment and operating procedures must comply with the relevant European, national or local legislation. Storage installations/areas should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations.
Packages and containers:	: If the product is supplied in containers: Keep containers tightly closed and properly labelled. Keep only in the original container or in a suitable container for this kind of product.
Packaging materials	: For containers, or container linings use materials specifically approved for use with this product. Compatibility should be checked with the manufacturer.

Product Safety Information Sheet

A safety data sheet is not required for this product under Article 31 of REACH. This Product Safety Information Sheet has been created on a voluntary basis

Germany Storage class (LGK, TRGS 510)	: LGK 10 - Combustible liquids
Switzerland	
Storage class (LK)	: LK 10/12 - Liquids
7.3. Specific end use(s)	

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

Residual oils (petroleum,) solvent-refined (64742-01-4)		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Belgium - Occupational Exposure Limits	·	
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Denmark - Occupational Exposure Limits	·	
OEL TWA	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
OEL STEL	2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Hungary - Occupational Exposure Limits	·	
AK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KGV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
WEL STEL (OEL STEL)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH OEL STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	

Product Safety Information Sheet

A safety data sheet is not required for this product under Article 31 of REACH. This Product Safety Information Sheet has been created on a voluntary basis

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil- unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0) **Belgium - Occupational Exposure Limits** OEL TWA 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) **Denmark - Occupational Exposure Limits** OFI TWA 1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) OEL STEL 2 mg/m3 (Mineral base oil mist, severely refined, DMSO extract <3% m/m) **Hungary - Occupational Exposure Limits** AK (OEL TWA) 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) **Netherlands - Occupational Exposure Limits** MAC TGG 8h (mg/m³) 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) **Spain - Occupational Exposure Limits** VLA-ED (OEL TWA) 5 mg/m3 (Mineral base oil mist, severely refined, DMSO extract <3% m/m) VLA-EC (mg/m³) 10 mg/m3 (Mineral base oil mist, severely refined, DMSO extract <3% m/m) **Sweden - Occupational Exposure Limits** NGV (OEL TWA) 1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) KGV (OEL STEL) 3 mg/m3 (Mineral base oil mist, severely refined, DMSO extract <3% m/m) **United Kingdom - Occupational Exposure Limits** WEL TWA (OEL TWA) 5 mg/m3 (Mineral base oil mist, severely refined, DMSO extract <3% m/m) WEL STEL (OEL STEL) 10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) **USA - ACGIH - Occupational Exposure Limits** ACGIH OEL TWA 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) ACGIH OEL STEL 10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) **Recommended monitoring procedures Monitoring methods** Monitoring methods Monitoring procedures should be chosen according to the indications set by national authorities or labour contracts. Refer to relevant legislation and in any case to the good practice of industrial hygiene. Air contaminants formed Applicable OEL and BLV for air contaminants : None known **DNEL and PNEC** Eni Acer 150 **DNEL/DMEL** (additional information) Additional information Not applicable **PNEC** (additional information) Additional information Not applicable Residual oils (petroleum,) solvent-refined (64742-01-4) **DNEL/DMEL (Workers)**

0.97 mg/kg bodyweight/day

Product Safety Information Sheet

A safety data sheet is not required for this product under Article 31 of REACH. This Product Safety Information Sheet has been created on a voluntary basis

an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational					
Long-term - local effects, inhalation 5.58 mg/m ⁹ DNELIDMEL (General population) 0.74 mg/kg bodyweight/day Long-term - systemic effects, oral 0.74 mg/kg bodyweight/day Long-term - local effects, inhalation 1.19 mg/m ³ PNEC (oral) PNEC oral (secondary poisoning) PNEC oral (secondary poisoning) 9.33 mg/kg food Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists prodominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0) DNELDMEL (Workers) Long-term - systemic effects, dermal Long-term - systemic effects, inhalation 5.58 mg/m ³ DNELDMEL (General population) 2.73 mg/m ³ Long-term - systemic effects, cral 0.74 mg/kg bodyweight/day PNEC (ral) PNEC (ral) PNEC (ral) PNEC (ral	Residual oils (petroleum,) solvent-refined (64	742-01-4)			
DNEL/DMEL (General population) Long-term - systemic effects, oral 0.74 mg/kg bodyweight/day Long-term - local effects, inhalation 1.19 mg/m³ PNEC (Oral) PNEC oral (secondary poisoning) 9.33 mg/kg food Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0) DNELDMEL (Workers) Long-term - systemic effects, inhalation 2.73 mg/m³ Long-term - systemic effects, inhalation 5.58 mg/m³ DNEL/DMEL (General population) Long-term - systemic effects, oral 0.74 mg/kg bodyweight/day PNEC Oral) PNEC Oral (secondary poisoning) 9.33 mg/kg food PNEC Oral (secondary poisoning) PNEC oral (secondary poisoning) 9.33 mg/kg food PNEC foral (secondary poisoning) PNEC coral (secondary poisoning) 9.33 mg/kg food PNEC foral (secondary poisoning) PNEC and (secondary poisoning) P.33 mg/kg food PNEC box on the second with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OT the same chemical. OELs are	Long-term - systemic effects, inhalation	2.73 mg/m ³			
Long-term - systemic effects, oral 0.74 mg/kg bodyweight/day Long-term - local effects, inhalation 1.19 mg/m³ PNEC (Oral) 9.33 mg/kg food Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0) DNEL/DMEL (Workers) Long-term - systemic effects, inhalation 2.73 mg/m³ Long-term - systemic effects, inhalation 5.58 mg/m³ Description DNEL/DMEL (General population) 0.74 mg/kg bodyweight/day Description Long-term - systemic effects, orral 0.74 mg/kg bodyweight/day Description DNEL/DMEL (General population) 5.58 mg/m³ Description Long-term - systemic effects, orral 0.74 mg/kg bodyweight/day PNEC oral (secondary poisoning) PNEC oral (secondary poisoning) 9.33 mg/kg food PNEC The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is drived from toxicity data in accord with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (SEL), for the same chemical. OCELs may be recommended by an individual company, a goverimental regulatory body or an expert organizat	Long-term - local effects, inhalation	5.58 mg/m ³			
Long-term - local effects, inhalation 1.19 mg/m³ PNEC (Oral) PNEC oral (secondary poisoning) 9.33 mg/kg food Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0) DNEL/DMEL (Workers) Long-term - systemic effects, dermal 0.97 mg/kg bodyweight/day Long-term - systemic effects, inhalation 2.73 mg/m³ 1 Long-term - systemic effects, oral 0.74 mg/kg bodyweight/day 1 Long-term - systemic effects, oral 0.74 mg/kg bodyweight/day 1 Long-term - systemic effects, oral 0.74 mg/kg bodyweight/day 1 Long-term - systemic effects, oral 0.74 mg/kg bodyweight/day 1 Note #3.33 mg/kg food 1 1 Note The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGH), OCLs are considered to be safe exposure leveles for a typical worker in an occupational setting for an 8-hour	DNEL/DMEL (General population)	·			
PNEC (oral) PNEC oral (secondary poisoning) 9.33 mg/kg food Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0) DNELDMEL (Workers)	Long-term - systemic effects,oral	0.74 mg/kg bodyweight/day			
PNEC oral (secondary poisoning) 9.33 mg/kg food Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0) DNEL/DMEL (Workers)	Long-term - local effects, inhalation	1.19 mg/m ³			
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffinis from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0) DNEL/DMEL (Workers)	PNEC (Oral)	·			
hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0) DNEL/DMEL (Workers)	PNEC oral (secondary poisoning)	9.33 mg/kg food			
Long-term - systemic effects, dermal 0.97 mg/kg bodyweight/day Long-term - systemic effects, inhalation 2.73 mg/m³ Long-term - local effects, inhalation 5.58 mg/m³ DNEL/DMEL (General population)	hydrocarbons obtained by removal of normal predominantly of hydrocarbons having carbo	paraffins from a petroleum fraction by solvent crystallization. It consists in numbers predominantly in the range of C20 through C50 and produces a			
Long-term - systemic effects, inhalation 2.73 mg/m³ Long-term - local effects, inhalation 5.58 mg/m³ DNEL/DMEL (General population) 0.74 mg/kg bodyweight/day PNEC (Oral) 0.74 mg/kg bodyweight/day PNEC (Oral) 9.33 mg/kg food PNEC (additional information) 4.44 dditional information Additional information Not derived - Not classified as hazardous for environment Note : The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a governmental regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH. Control banding	DNEL/DMEL (Workers)				
Long-term - local effects, inhalation 5.58 mg/m³ DNEL/DMEL (General population) 0.74 mg/kg bodyweight/day Long-term - systemic effects, oral 0.74 mg/kg bodyweight/day PNEC (Oral) 9NEC oral (secondary poisoning) 9.33 mg/kg food PNEC (additional information) Additional information Not derived - Not classified as hazardous for environment Note : The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a governmental regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH.	Long-term - systemic effects, dermal	0.97 mg/kg bodyweight/day			
DNEL/DMEL (General population) Long-term - systemic effects,oral 0.74 mg/kg bodyweight/day PNEC (Oral) PNEC oral (secondary poisoning) 9.33 mg/kg food PNEC (additional information) Additional information Not derived - Not classified as hazardous for environment Note : The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a governmental regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limit (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH. Control banding	Long-term - systemic effects, inhalation	2.73 mg/m ³			
Long-term - systemic effects,oral 0.74 mg/kg bodyweight/day PNEC (Oral) PNEC oral (secondary poisoning) 9.33 mg/kg food PNEC (additional information) Additional information Not derived - Not classified as hazardous for environment Note : The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a governmental regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH. Control banding	Long-term - local effects, inhalation	5.58 mg/m³			
PNEC (Oral) PNEC oral (secondary poisoning) 9.33 mg/kg food PNEC (additional information) Additional information Not derived - Not classified as hazardous for environment Note : The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a governmental regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH. Control banding	DNEL/DMEL (General population)				
PNEC oral (secondary poisoning) 9.33 mg/kg food PNEC (additional information) Additional information Additional information Not derived - Not classified as hazardous for environment Note : The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a governmental regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH. Control banding	Long-term - systemic effects,oral	0.74 mg/kg bodyweight/day			
PNEC (additional information) Additional information Note * The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a governmental regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH. Control banding	PNEC (Oral)	·			
Additional information Not derived - Not classified as hazardous for environment Note : The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a governmental regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH. Control banding	PNEC oral (secondary poisoning)	9.33 mg/kg food			
Note : The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a governmental regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH. Control banding	PNEC (additional information)	·			
from toxicity data in accord with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a governmental regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH. Control banding	Additional information	Not derived - Not classified as hazardous for environment			
		from toxicity data in accord with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a governmental regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of			
		None known			

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station. Before entering storage tanks and commencing any operation in a confined area (e.g. tunnels), carry out an adequate clean-up, and check the atmosphere for oxygen content and flammability. See also Section 16, "Other information".

Personal protection equipment

Personal protective equipment (for industrial or professional use):

Gloves. Safety glasses. Safety shoes or boots.

Personal protective equipment symbol(s):



Product Safety Information Sheet

A safety data sheet is not required for this product under Article 31 of REACH. This Product Safety Information Sheet has been created on a voluntary basis

Eye and face protection

Eye protection:

When there is a risk of contact with the eyes, use safety goggles or other means of protection (face shield). If necessary, refer to national standards or to the EN 166 standard.

Skin protection

Skin and body protection:

Long-sleeved overalls. If necessary, refer to the EN 340 and related standards, for definition of characteristics and performance according to the risk rating of the area. Antistatic non-skid safety shoes or boots, chemical resistant, if necessary heat resistant and insulated.

Hand protection:

When there is a risk of contact with the skin, use waterproof gloves, resistant to chemical products. Gloves must be felt-lined. Adequate materials: nitrile (NBR) or PVC with a protection index > 5 (permeation time > 240 mins). Use gloves respecting all the conditions and within the limits set by the manufacturer. Replace gloves immediately in case of cuts, holes or other signs of damages or degradation. If necessary, refer to the EN 374 standard. Personal hygiene is a key element for an effective hand care. Gloves must be worn only with clean hands. After wearing gloves, hands must be carefully washed and dried.

Respiratory protection

Respiratory protection:

Independently from other possible actions (technical modifications, operating procedures, and other means to limit the exposure of workers), personal protection equipment can be used according to necessity. Open or well ventilated spaces: if the product is handled without adequate containment: use full or half-face masks with adequate filter for mists and organic vapours. (EN 136/140/145). Combined gas/dust mask with filter type: EN 14387. Closed or confined areas (e.g. tank interiors): the use of protection measures for airways (masks or self-contained breathing apparatus), must be assessed according to the specific activity, as well as level and duration of predicted exposure. (EN 136/140/145)

Thermal hazards

Thermal hazard protection:

If contact with hot product is possible or anticipated, gloves should be heat-resistant and thermally insulated.

Environmental exposure controls

Environmental exposure controls:

Do not discharge the product into the environment. Storage areas/installations should be designed with adequate bunds so as to prevent ground and water pollution in case of leaks or spills. Prevent discharge of undissolved substance to or recover from onsite wastewater. Onsite wastewater treatment required. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed. **Consumer exposure controls:**

Not applicable.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Yellow-brown.
Appearance	: Liquid, bright & clear.
Odour	: Slight odour of petroleum.
Odour threshold	There are no data available on the preparation/mixture itself.
Melting point	: Not applicable
Freezing point	: Not applicable
Boiling point	: Not determined
Flammability	: Not flammable
Lower explosion limit	: Not determined
Upper explosion limit	: Not determined
Flash point	: 243 °C (ASTM D 92)
Auto-ignition temperature	: Not determined
Decomposition temperature	: Not determined
pH	: Lack of data (on mixture / components of the mixture) - Data not available
Viscosity, kinematic	: 150 mm²/s (40 °C) (ASTM D 445)
Viscosity, dynamic	: Lack of data (on mixture / components of the mixture) - Data not available
Solubility	: Water: Immiscible and insoluble
Log Kow	: Not applicable for mixtures
Log Pow	: Not applicable for mixtures
Vapour pressure	Not determined

Product Safety Information Sheet

A safety data sheet is not required for this product under Article 31 of REACH. This Product Safety Information Sheet has been created on a voluntary basis

Vapour pressure at 50°C Critical pressure Density Relative density Relative vapour density at 20°C Particle characteristics	 Not determined Not applicable for mixtures 895 kg/m³ (15 °C) (ASTM D 4052) Not determined Not determined Not determined Not applicable
9.2. Other information	
Information with regard to physical haza	rd classes

Critical temperature

: Not applicable for mixtures

: Negligible.

Other safety characteristics

Relative evaporation rate (butylacetate=1)

SECTION 10: Stability and reactivity

10.1. Reactivity

This mixture does not offer any further hazard for reactivity, except what is reported in the following paragraphs.

10.2. Chemical stability

Stable product, according to its intrinsic properties.

10.3. Possibility of hazardous reactions

None (in normal conditions of storage and handling). Contact with strong oxidizers (peroxides, chromates, etc.) may cause a fire hazard. Sensitivity to heat, friction or shock cannot be assessed in advance.

10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Strong oxidants.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates : Carbon dioxide, Carbon monoxide, Toxic fumes.

SECTION 11: Toxicological information		
11.1. Information on hazard classes as defined	in Regulation (EC) No 1272/2008	
Acute toxicity (dermal):Acute toxicity (inhalation):	Not classified (Based on available data, the classification criteria are not met) Not classified (Based on available data, the classification criteria are not met) Not classified (Based on available data, the classification criteria are not met) (according to composition)	
Residual oils (petroleum,) solvent-refined (64742-01-4)		
LD50 oral rat	> 5000 mg/kg bodyweight	
LD50 dermal rat	> 2000 mg/kg bodyweight	
LC50 Inhalation - Rat	> 5 mg/l/4h	
hydrocarbons obtained by removal of normal	y paraffinic; Baseoil— unspecified; [A complex combination of paraffins from a petroleum fraction by solvent crystallization. It consists n numbers predominantly in the range of C20 through C50 and produces a SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)	
LD50 oral rat	> 5000 mg/kg bodyweight Not determined	

Product Safety Information Sheet

A safety data sheet is not required for this product under Article	31 of REACH. This Product Safety Information Sheet has been created on a voluntary basis
	Not classified (Based on available data, the classification criteria are not met) pH: Lack of data (on mixture / components of the mixture) - Data not available
Additional information :	(according to composition)
Distillates (petroleum), solvent-dewaxed hear	vy paraffinic; Baseoil— unspecified; [A complex combination of
	I paraffins from a petroleum fraction by solvent crystallization. It consists
	on numbers predominantly in the range of C20 through C50 and produces a
finished oil with a viscosity not less than 100	SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)
рН	Not applicable
Serious eye damage/irritation :	Not classified (Based on available data, the classification criteria are not met)
Additional information :	pH: Lack of data (on mixture / components of the mixture) - Data not available (according to composition)
Distillates (petroleum), solvent-dewaxed hea	vy paraffinic; Baseoil— unspecified; [A complex combination of
	I paraffins from a petroleum fraction by solvent crystallization. It consists
	on numbers predominantly in the range of C20 through C50 and produces a
finished oil with a viscosity not less than 100	SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)
pH	Not applicable
Respiratory or skin sensitisation :	Not classified (Based on available data, the classification criteria are not met)
Additional information :	(according to composition)
Germ cell mutagenicity :	Not classified (Based on available data, the classification criteria are not met)
Additional information :	(according to composition)
Carcinogenicity :	Not classified (Based on available data, the classification criteria are not met)
Additional information :	(according to composition)
	This product contains : Residual oils (petroleum) solvent-refined; Baseoil— unspecified; [A complex combination by hydrocarbons obtained as the solvent insoluble fraction from
	solvent refining of a residuum using a polar organic solvent such as phenol or furfural. It
	consists of hydrocarbons having carbon numbers predominantly higher than C25 and
	boiling above approximately 400°C (752°F).], Distillates (petroleum), solvent-dewaxed
	heavy paraffinic
	this product has a value of DMSO extract < 3 % wt, according to IP 346. According to the
	criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product must be regarded as non carcinogenic.
Reproductive toxicity :	Not classified (Based on available data, the classification criteria are not met)
Additional information :	(according to composition)
STOT-single exposure :	Not classified (Based on available data, the classification criteria are not met)
Additional information :	(according to composition)
· · ·	Not classified (Based on available data, the classification criteria are not met)
Additional information :	(according to composition)
Residual oils (petroleum,) solvent-refined (64	.742-01-4)
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	 > 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
Distillates (petroleum). solvent-dewaxed hea	vy paraffinic; Baseoil— unspecified; [A complex combination of
	I paraffins from a petroleum fraction by solvent crystallization. It consists
	on numbers predominantly in the range of C20 through C50 and produces a
finished oil with a viscosity not less than 100	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Not determined
LOAEL (dermal, rat/rabbit, 90 days)	100 mg/kg bodyweight/day
NOAEL (oral, rat, 90 days)	< 125 mg/kg bodyweight/day (CAS 64742-04-7, Mobil 1990) (OECD 408)
NOAEL (dermal, rat/rabbit, 90 days)	≈ 1000 mg/kg bodyweight Not determined
NOAEC (inhalation,rat, vapour, 90 days)	220 – 980 mg/m ³ (Dalbey W, Osimitz T, Kommineni C, Roy T, Feuston M and Yang J 1991 - OECD 412)

1991 - OECD 412)

Product Safety Information Sheet

A safety data sheet is not required for this product under Article 31 of REACH. This Product Safety Information Sheet has been created on a voluntary basis

Aspiration hazard Additional information	Not classified (Based on available data, the classification criteria are not met) (according to composition) Viscosity, kinematic: > 20,5 mm2/s (40 °C) (ASTM D 445)		
Eni Acer 150			
Viscosity, kinematic	150 mm²/s (40 °C) (ASTM D 445)		
Residual oils (petroleum,) solvent-refine	ed (64742-01-4)		
Viscosity, kinematic	490 mm²/s (40 °C) (ASTM D 445)		
hydrocarbons obtained by removal of n predominantly of hydrocarbons having	I heavy paraffinic; Baseoil— unspecified; [A complex combination of ormal paraffins from a petroleum fraction by solvent crystallization. It consists carbon numbers predominantly in the range of C20 through C50 and produces a n 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)		
Viscosity, kinematic	91 – 99 mm²/s (40 °C) (ASTM D 445)		
11.2. Information on other hazards			
Endocrine disrupting properties			
Adverse health effects caused by endocrine disrupting properties	The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) ar not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %		
Other information			
Potential adverse human health effects and symptoms Other information	 Contact with eyes may cause reddening and irritation, Avoid all eye and skin contact and c not breathe vapour and mist None 		

SECTION 12: Ecological information

12.1. Toxicity	
Ecology - general : Ecology - air :	The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment. An uncontrolled release to the environment may nevertheless produce a contamination of different environmental compartments (soil, underground, surface water bodies, aquifers). Handle according to general working hygiene practices to avoid pollution and release into the environment. This product has a low vapour pressure, and in normal conditions at ambient temperature the concentration in the air is negligible. A significant concentration may build up only in case of sprays and mists. In these cases overexposure to mists (e.g. through prolonged use in confined insufficiently ventilated spaces) may cause irritation to airways, nausea and dizziness.
Ecology - water :	This product is not soluble in water. It floats on water and forms a film on the surface. The damage to aquatic organisms is of mechanical kind (immobilization and entrapment)
Hazardous to the aquatic environment, short–term : (acute) Hazardous to the aquatic environment, long–term : (chronic)	Not classified (Based on available data, the classification criteria are not met)
Residual oils (petroleum,) solvent-refined (64	742-01-4)
LC50 fish 1	100 mg/l
EC50 Daphnia 1	10 g/l
Distillates (petroleum), solvent-dewaxed heav	/y paraffinic (64742-65-0)
LC50 fish 1	> 100 mg/l (LL 50, Exxon 1995 - OECD 203)
EC50 Daphnia 1	> 10000 mg/l (EL50, Shell 1988 - OECD 202)

Product Safety Information Sheet

Distillates (petroleum), solvent-dewaxed heav	y paraffinic (64742-65-0)		
NOEC (acute)	≥ 100 mg/l (Pseudokirchneriella subcapitata, 72h, OECD 201 - Petro-Canada 2008)		
NOEC chronic fish	≥ 1000 mg/l (Oncorhynchus mykiss, NOELR, 14d - QSAR, Redman, A. et al. 2010)		
NOEC chronic crustacea	≥ 1000 mg/l (21d, OECD 211 - Shell 1994)		
NOEC chronic algae	≥ 100 mg/l (Pseudokirchneriella subcapitata, 72h)		
12.2. Persistence and degradability			
Eni Acer 150			
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.		
Residual oils (petroleum,) solvent-refined (64	742-01-4)		
Persistence and degradability	Substance is complex UVCB, The test methods for this endpoint are not applicable to UVCB substances.		
Distillates (petroleum), solvent-dewaxed heav	y paraffinic (64742-65-0)		
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.		
Biodegradation	31 % (28d, Exxon 1995)		
12.3. Bioaccumulative potential			
Eni Acer 150			
Log Pow	Not applicable for mixtures		
Log Kow	Not applicable for mixtures		
Bioaccumulative potential	Not established.		
Residual oils (petroleum,) solvent-refined (64	742-01-4)		
Bioaccumulative potential	The test methods for this endpoint are not applicable to UVCB substances.		
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)			
BCF fish 1	0.4 – 6280 l/kg		
BCF fish 2	3.16 – 71100 l/kg		
Log Pow	1.99 – 18.02		
Log Kow	Not applicable (UVCB)		
Bioaccumulative potential	The test methods for this endpoint are not applicable to UVCB substances.		
12.4. Mobility in soil			
Eni Acer 150			
Ecology - soil	No data available.		
Residual oils (petroleum,) solvent-refined (64	742-01-4)		
Ecology - soil	The test methods for this endpoint are not applicable to UVCB substances.		
Distillates (petroleum), solvent-dewaxed heav	y paraffinic (64742-65-0)		
Log Koc	1.71 – 14.7		
Ecology - soil	The test methods for this endpoint are not applicable to UVCB substances.		
12/40/2024 (Devision date)			

Product Safety Information Sheet

12.5. Results of PBT and vPvB assessment				
Eni Acer 150				
This substance/mixture does not meet the PBT criteria	of REACH regulation, annex XIII			
This substance/mixture does not meet the vPvB criteria	a of REACH regulation, annex XIII			
Results of PBT-vPvB assessment The components in this formulation do not meet the criteria for classification as PBT vPvB. The product should be considered prudentially as "Persistent" in the environ according to the REACH Annex XIII criteria (point 1.1)				
Component				
Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	Residual oils (petroleum,) solvent-refined (64742-01-4), Distillates (petroleum), solvent- dewaxed heavy paraffinic (64742-65-0)			
Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	Residual oils (petroleum,) solvent-refined (64742-01-4), Distillates (petroleum), solvent- dewaxed heavy paraffinic (64742-65-0)			
12.6. Endocrine disrupting properties				
Adverse effects on the environment caused by : endocrine disrupting properties	The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.			
12.7. Other adverse effects				
	None. This product has no specific properties for inhibition of bacterial activity. In any case, wastewater containing this product should be treated in plants that are suited for the specific purpose.			

SECTION 13: Disposal considerations	
13.1. Waste treatment methods	
Regional waste regulation Waste treatment methods	 Disposal must be done according to official regulations. Do not dispose of the product, either new or used, by dumping on the ground, or discharging into sewers, tunnels, lakes or water courses. Deliver to a qualified official collector. Dispose of empty containers and wastes safely.
Sewage disposal recommendations	 Dispose of in a safe manner in accordance with local/national regulations. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.
Product/Packaging disposal recommendations	: European Waste Catalogue code(s) (Decision 2001/118/CE): 13 02 05* (mineral-based non-chlorinated engine, gear and lubricating oils). This EWC code is only a general indication, and takes into account the original composition of the product and its intended use. The user has the responsibility of choosing the right EWC code, considering the actual use of the product, alterations and contaminations.
Additional information	: Empty containers may contain combustible product residues. Do not cut, weld, bore, burn or incinerate emptied containers, unless they have been cleaned and declared safe.
Ecology - waste materials EURAL code (EWC)	 The product as it is does not contain halogenated substances. 13 02 05* - Mineral-based non-chlorinated engine, gear and lubricating oils

SECTION 14: Transport information				
In accordance with ADR / IMDG / IATA / ADN / RID				
ADR IMDG IATA ADN RID				
14.1. UN number or ID number				
Not regulated for transport				

Product Safety Information Sheet

A safety data sheet is not required for this product under Article 31 of REACH. This Product Safety Information Sheet has been created on a voluntary basis

ADR	IMDG	ΙΑΤΑ	ADN	RID
14.2. UN proper shipping	g name	·		
Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.3. Transport hazard c	lass(es)			
Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.4. Packing group				
Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.5. Environmental haz	ards			
Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
None.		· · · · · · · · · · · · · · · · · · ·		

14.6. Special precautions for user

Overland transport Not regulated.

Transport by sea Not regulated.

Air transport

Not regulated.

Inland waterway transport Not regulated.

Rail transport

Not regulated.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

Other information, restriction and prohibition Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 regulations December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). (et sequens). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (et sequens). Directives 89/391/CEE, 89/654/CEE, 89/655/CEE, 89/656/CEE, 90/269/CEE, 90/270/CEE, 90/394/CEE, 90/679/CEE, 93/88/CEE, 95/63/CE, 97/42/CE, 98/24/CE, 99/38/CE, 99/92/CE, 2001/45/CE, 2003/10/CE, 2003/18/CE (Health and safety on the workplace). Directive 2012/18/CE (Control of major-accident hazards involving dangerous substances). Directive 2004/42/CE (Limitation of emissions of Volatile Organic Compounds). Directive 98/24/EC (protection of the health and safety of workers from the risks related to chemical agents at work). Directive 92/85/CE (measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding). Substances Depleting the Ozone layer (1005/2009) - Annex I Substances (ODP). POP (2019/1021) - Persistent Organic Pollutants. Regulation EU (649/2012) -Export and Import of hazardous chemicals (PIC). Commission Delegated Regulation (EU) 2017/2100. Commission Regulation (EU) 2018/605.

Product Safety Information Sheet

A safety data sheet is not required for this product under Article 31 of REACH. This Product Safety Information Sheet has been created on a voluntary basis

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

No ingredients are included in the REACH Candidate list (> 0,1 % m/m).

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

National regulations

National adoption of EU Directives concerning health and safety on the workplace.

National adoption of EU Directives concerning control of major-accident hazards involving dangerous substances (2012/18/CE).

Relevant national laws on prevention of water pollution.

Relevant national laws on protection of the health of pregnant workers (National adoption of Dir. 92/85/EEC).

National adoption of Directive 2008/98/CE concerning disposal of used oils.

France

Maladies professionelles (F)				
Code	Description			
RG 36	Diseases caused by oils and fats of mineral or synthetic origin			
Germany				
Employment restrictions		: Employment prohibitions or restrictions on the protection of young people at work according to § 22 JArbSchG in the case of formation of hazardous substances have to be observed.		
National Rules and Recommendations		 TRGS 400: Hazard assessment for activities involving Hazardous Substances. TRGS 401: Risks resulting from skin contact - identification, assessment, measures. TRGS 402: Identification and Assessment of the Risks from Activities involving Hazardous Substances: Inhalation Exposure. TRGS 555: Working instruction and information for workers. TRGS 800: Fire protection measures. TRGS 900: Occupational Exposure Limits. 		
VbF class (D)		: Not applicable.		
Water hazard class (WGK) (D) WGK remark		 WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1). Classification is carried out on the basis of the Ordinance on facilities for handling substances that are hazardous to water (Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV)) of 18 April 2017 (BGBI 2017, Teil I, Nr. 22, Seite 905). 		
Hazardous Incident Ordinance (12. BImSchV)		: Is not subject to the Hazardous Incident Ordinance (12. BImSchV)		
Netherlands				
Saneringsinspanningen SZW-lijst van kankerverwekkende stoffen SZW-lijst van mutagene stoffen SZW-lijst van reprotoxische stoffen – Borstvoeding		 C - Minimize discharge None of the components are listed None of the components are listed None of the components are listed 		

Product Safety Information Sheet

A safety data sheet is not required for this product under Article 31 of REACH. This Product Safety Information Sheet has been created on a voluntary basis

- SZW-lijst van reprotoxische stoffen – Vruchtbaarheid	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling	: None of the components are listed
Denmark	
Danish National Regulations	: Young people under 18 years are not allowed to use the product
	Pregnant/breastfeeding women working with the product must not be in direct contact with i
Poland	
Polish National Regulations	: Act of 25 February 2011 on chemical substances and their mixtures (J. o L. No. 63, item 322 as amended; consolidated text J. o L. 2019, item 1225).
	Act of 14 December 2012 on waste (J. o L. 2013, item 322 as amended; consolidated text c o L. 2020, item 797).
	The announcement of Marshal of the Sejm of the Republic of Poland dated 19 October
	2016 concerning the consolidated text announcement of the decree on the management of
	packaging and packaging waste (J. o L. 2016, item 1863 as amended).
	Decree of the Minister of Environment of 14 December 2014 on the catalogue of waste (J. o L. 2014, item 1923).
	Act of 19 August 2011 on the Carriage of Dangerous Goods (J. o L. 2011 No. 227, item 1367 as amended; consolidated text J. o L. 2020, item 154).
	Regulation of the Minister of Family, Labour and Social Policy of 12 June 2018 on the
	highest permissible concentration and intensity of noxious agents for health at work environment (J. o L. item 1286 as amended).
	The announcement of Minister of Health dated 9 September 2016 concerning the
	consolidated text announcement of the decree of the Minister of Health of 30 December
	2004 on health and safety at work related to exposure to chemical agents at work (J. o L. o 16 September 2016, item 1488)
	Regulation of the Minister of Health of 2 February 2011 on tests and measurements of the noxious agents for health at work environment (J. o L. No. 33, item 166 as amended).
	Regulation of the Minister of Environment of 9 December 2003 on particularly hazardous substances to the environment (J. o L. No. 217, item 2141).
	ADR Agreement: Government Statement of 13 March 2023 on the entry into force of
	amendments to Annexes A and B to the Agreement concerning the International Carriage c
	Dangerous Goods by Road (ADR), signed in Geneva on 30 September 1957 (J. o. L. 2023, item 891)

15.2. Chemical safety assessment

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

No chemical safety assessment has been carried out

A chemical safety assessment has been carried out for the following components of this mixture::

Residual oils (petroleum,) solvent-refined

SECTION 16: Other information

Indication of changes				
Section	Changed item	Comments		
3.2	Comments	Modified		

Abbreviations and acronyms:			
	Complete text of the H phrases quoted in this Safety Data Sheet. These phrases are reported here for information only, and MAY NOT correspond to the classification of the product.		
	N/D = not available		
	N/A = not applicable		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways		

Product Safety Information Sheet

A safety data sheet is not required for this product under Article 31 of REACH. This Product Safety Information Sheet has been created on a voluntary basis

Abbreviations and acr	Abbreviations and acronyms:				
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road				
ATE	Acute Toxicity Estimate				
BCF	Bioconcentration factor				
CAS-No.	Chemical Abstract Service number				
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008				
DMEL	Derived Minimal Effect level				
DNEL	Derived-No Effect Level				
EC50	Effective concentration for 50 percent of test population (median effective concentration)				
EC-No.	European Community number				
ED	Endocrine disruptor				
IARC	International Agency for Research on Cancer				
ΙΑΤΑ	International Air Transport Association				
IMDG	International Maritime Dangerous Goods				
LC50	Lethal concentration for 50 percent of test population (median lethal concentration)				
LD50	Lethal dose for 50 percent of test population (median lethal dose)				
LOAEL	Lowest Observed Adverse Effect Level				
NOAEC	No-Observed Adverse Effect Concentration				
NOAEL	No-Observed Adverse Effect Level				
NOEC	No-Observed Effect Concentration				
OECD	Organisation for Economic Co-operation and Development				
OEL	Occupational Exposure Limit				
РВТ	Persistent Bioaccumulative Toxic				
PNEC	Predicted No-Effect Concentration				
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals, Regulation (EC) No 1907/2006				
RID	Regulation concerning the International Carriage of Dangerous Goods by Railways				
SDS	Safety Data Sheet				
STP	Sewage treatment plant				
VOC	Volatile Organic Compounds				
vPvB	Very Persistent and Very Bioaccumulative				
WGK	Water Hazard Class				

Data sources

: This Safety Data Sheet is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.

Training advice

Other information

Provide adequate training to professional operators for the use of PPEs, according to the information contained in this Safety Data Sheet.
Do not use the product for any purposes that have not been advised by the manufacturer.

Safety Data Sheet (SDS), EU