



Eni Ulex 100

Material number 700

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 14.4.2025
Version: 6.2
Replaces version: 6.1
Language: en-DE
Date of print: 16.7.2025

Page: 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Eni Ulex 100
UFI: 9J40-00DM-W003-WQ1A

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use: Metalworking fluid.

1.3 Details of the supplier of the safety data sheet

Company name: Enilive Schmiertechnik GmbH
Street/POB-No.: Paradiesstraße 14
Postal Code, city: 97080 Würzburg
Germany
E-mail: info.wuerzburg@enilive.com
Telephone: +49 (0)931-90098-0
Telefax: +49 (0)931-98442
Department responsible for information:
Application Engineering & Product Management (AEPM)
Telephone: +49 (0)931-90098-0
E-mail: technik.wuerzburg@enilive.com

1.4 Emergency telephone number

GIZ-Nord, Göttingen
Telephone: +49 (0)551-19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to EC regulation 1272/2008 (CLP)

Skin Sens. 1; H317 May cause an allergic skin reaction.
Aquatic Chronic 3; H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (CLP)



Signal word:

Warning

Hazard statements:

H317
H412

May cause an allergic skin reaction.
Harmful to aquatic life with long lasting effects.



Eni Ulex 100

Material number 700

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 14.4.2025
Version: 6.2
Replaces version: 6.1
Language: en-DE
Date of print: 16.7.2025

Page: 2 of 14

Precautionary statements:

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P261	Avoid breathing mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection.
P302+P352	IF ON SKIN: Wash with plenty of water/soap.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.

Special labelling

Text for labelling:

Contains:
3-Iodo-2-propynyl butylcarbamate
1,2-Benzisothiazol-3(2H)-one
2-Methyl-2H-isothiazol-3-one

2.3 Other hazards

Special danger of slipping by leaking/spilling product.

Endocrine disrupting properties, Results of PBT and vPvB assessment:

This product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% (w/w) or higher.

The product does not contain any substances classified as PBT or vPvB.

CAS No.	Designation	PBT/vPvB	ED Human	ED Environment
55406-53-6	3-Iodo-2-propynyl butylcarbamate			List II

SECTION 3: Composition/information on ingredients

3.1 Substances: not applicable

3.2 Mixtures

Chemical characterisation:

A mixture of base oils and additives



Eni Ulex 100

Material number 700

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 14.4.2025
Version: 6.2
Replaces version: 6.1
Language: en-DE
Date of print: 16.7.2025

Page: 3 of 14

Hazardous ingredients:

Identifiers	Designation Classification	Content
REACH 01-2119489407-26-xxxx EC No. 500-236-9 CAS 68920-66-1	Alcohols, C16-18, ethoxylated Skin Irrit. 2; H315. Aquatic Chronic 2; H411.	2,5 - 5 %
REACH 01-2119475104-44-xxxx EC No. 203-961-6 CAS 112-34-5	2-(2-Butoxyethoxy)ethanol Eye Irrit. 2; H319.	1 - < 5 %
REACH 01-2119527859-22-xxxx EC No. 271-781-5 CAS 68608-26-4	Sulfonic acids, petroleum, sodium salts Eye Irrit. 2; H319.	1 - < 5 %
EC No. 259-627-5 CAS 55406-53-6	3-Iodo-2-propynyl butylcarbamate Acute Tox. 4; H302. Acute Tox. 3; H331. Eye Dam. 1; H318. Skin Sens. 1; H317. STOT RE 1; H372. Aquatic Acute 1; H400. Aquatic Chronic 1; H410.	< 0,25 %
REACH 01-2120761540-60-xxxx EC No. 220-120-9 CAS 2634-33-5	1,2-Benzisothiazol-3(2H)-one Acute Tox. 4; H302. Acute Tox. 2; H330. Skin Irrit. 2; H315. Eye Dam. 1; H318. Skin Sens. 1A; H317. Aquatic Acute 1; H400. Aquatic Chronic 1; H410. Acute toxicity estimate (ATE): Oral: 450 mg/kg bw. Inhalative, dust/mist: 0,21 mg/L. Specific concentration limits (SCL): Skin Sens. 1A; H317: C ≥ 0,036 % M-factors: Aquatic Acute 1: M = 1. Aquatic Chronic 1: M = 1.	< 0,05 %
EC No. 220-239-6 CAS 2682-20-4	2-Methyl-2H-isothiazol-3-one Acute Tox. 3; H301. Acute Tox. 3; H311. Acute Tox. 2; H330. Skin Corr. 1B; H314. Eye Dam. 1; H318. Skin Sens. 1A; H317. Aquatic Acute 1; H400. Aquatic Chronic 1; H410. (EUH071). Specific concentration limits (SCL): Skin Sens. 1A; H317: C ≥ 0,0015 % M-factors: Aquatic Acute 1: M = 10. Aquatic Chronic 1: M = 1.	< 0,05 %

Full text of H- and EUH-statements: see section 16.

Additional information: The highly refined mineral oil contains <3% (w/w) DMSO extract, according to IP346.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: If medical advice is needed, have product container or label at hand.
Take off contaminated clothing and wash it before reuse.



Eni Ulex 100

Material number 700

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 14.4.2025
Version: 6.2
Replaces version: 6.1
Language: en-DE
Date of print: 16.7.2025

Page: 4 of 14

In case of inhalation:	Remove casualty to fresh air and keep warm and at rest. If breathing becomes irregular or ceases, apply rescue breathing or artificial respiration immediately, where required supply oxygen. If unconscious place in recovery position and seek medical advice.
Following skin contact:	Immediately clean with water and soap followed by thorough rinsing. In case of skin reactions, consult a physician.
After eye contact:	Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Subsequently consult an ophthalmologist.
After swallowing:	Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do not induce vomiting. Seek medical attention.

4.2 Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

4.3 Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:

Water spray jet, extinguishing powder, foam and carbon dioxide.

Extinguishing media which must not be used for safety reasons:

Full water jet.

5.2 Special hazards arising from the substance or mixture

May form dangerous gases and vapours in case of fire.

Furthermore, there may develop: Nitrogen oxides (NO_x), smoke, carbon monoxide and carbon dioxide.

5.3 Advice for firefighters

Special protective equipment for firefighters:

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information:

Do not inhale explosion and combustion gases. Remove persons to safety.

Use fine water spray to cool endangered containers. Move undamaged containers from immediate hazard area if it can be done safely.

Contaminated fire-fighting water must be collected separately. Do not allow water used to extinguish fire to enter drains, ground or waterways.

Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Do not breathe mist/vapours/spray. Avoid contact with the substance.

Eliminate all ignition sources if safe to do so. Provide adequate ventilation.

Keep unprotected people away.

Wear appropriate protective equipment. Take off contaminated clothing and wash it before reuse.



Eni Ulex 100

Material number 700

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 14.4.2025
Version: 6.2
Replaces version: 6.1
Language: en-DE
Date of print: 16.7.2025

Page: 5 of 14

6.2 Environmental precautions

Do not allow to enter into ground-water, surface water or drains. Do not allow to enter into soil/subsoil.

If necessary, notify appropriate authorities.

6.3 Methods and material for containment and cleaning up

Make sure spills can be contained, e.g. in sump pallets or kerbed areas. Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents) and place in closed containers for disposal.

Never return spills in original containers for re-use.

Additional information: Special danger of slipping by leaking/spilling product.

6.4 Reference to other sections

Refer additionally to section 8 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed. Do not breathe mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Wear appropriate protective equipment.
Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Do not put any product-impregnated cleaning rags into your trouser pockets. Take off contaminated clothing and wash it before reuse. Have eye wash bottle or eye rinse ready at work place.

Precautions against fire and explosion:
Keep away from sources of ignition - No smoking.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:
Keep container tightly closed in a cool, well-ventilated place.
Keep container dry. Keep only in the original container.
Protect from heat and direct sunlight. Protect from frost.
Storage temperature: 5 - 40 °C
Storage stability: 12 months

Hints on joint storage: Do not store together with: Strong oxidizing agents.
Keep away from food, drink and animal feedingstuffs.

Storage class: 10 = Combustible liquids that cannot be assigned to any of the above storage classes

7.3 Specific end use(s)

No information available.



Eni Ulex 100

Material number 700

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 14.4.2025
Version: 6.2
Replaces version: 6.1
Language: en-DE
Date of print: 16.7.2025

Page: 6 of 14

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
112-34-5	2-(2-Butoxyethoxy) ethanol	Europe: IOELV: STEL	101,2 mg/m ³ ; 15 ppm
		Europe: IOELV: TWA	67,5 mg/m ³ ; 10 ppm
		Germany: TRGS 900 Kurzzeit	100,5 mg/m ³ ; 15 ppm (Aerosol and vapour)
55406-53-6	3-Iodo-2-propynyl butylcarbamate	Germany: TRGS 900 Langzeit	67 mg/m ³ ; 10 ppm (Aerosol and vapour)
		Germany: TRGS 900 Kurzzeit	0,106 mg/m ³ ; 0,01 ppm (Aerosol and vapour)
		Germany: TRGS 900 Langzeit	0,058 mg/m ³ ; 0,005 ppm (Aerosol and vapour)

DNEL/DMEL: Information about Alcohols, C16-18, ethoxylated (CAS 68920-66-1):
DNEL workers, dermal, long-term, systemic: 2.080 mg/kg/bw/d
DNEL workers, inhalative, long-term, systemic: 294 mg/m³
Information about 2-(2-Butoxyethoxy)ethanol (CAS 112-34-5):
DNEL workers, dermal, long-term, systemic: 20 mg/kg/bw/d
DNEL workers, inhalative, long-term, systemic: 67,5 mg/m³

PNEC: Information about alcohols, C16-18, ethoxylated (CAS 68920-66-1):
PNEC water (freshwater): 0,002 mg/L
PNEC water (marine water): 0,002 mg/L
PNEC sediment (freshwater): 6,33 mg/kg
PNEC soil: 1 mg/kg
PNEC sewage treatment plant: 10.000 mg/L
Information about 2-(2-Butoxyethoxy)ethanol (CAS 112-34-5):
PNEC water (freshwater): 1 mg/L
PNEC water (marine water): 0,1 mg/L
PNEC sediment (freshwater): 4 mg/kg
PNEC sediment (marine water): 0,4 mg/kg
PNEC sewage treatment plant: 200 mg/L

8.2 Exposure controls

Provide for good ventilation or exhaust system or work with completely self-contained equipment.

Personal protection equipment

Occupational exposure controls

Respiratory protection: Respiratory protection must be worn whenever the WEL levels have been exceeded. The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.



Eni Ulex 100

Material number 700

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 14.4.2025
Version: 6.2
Replaces version: 6.1
Language: en-DE
Date of print: 16.7.2025

Page: 7 of 14

Hand protection:	Protective gloves according to DIN EN ISO 374-1. During full contact: Glove material: Nitrile rubber, polychloroprene, chloroprene rubber Breakthrough time: > 480 min Layer thickness: >= 0,7 mm During splash contact: Glove material: Nitrile rubber, polychloroprene, chloroprene rubber Breakthrough time: > 30 min Layer thickness: >= 0,4 mm Unsuitable material: Polyvinyl alcohol Observe glove manufacturer's instructions concerning penetrability and breakthrough time.
Eye protection:	Tightly sealed goggles according to DIN EN ISO 16321-1.
Body protection:	Wear suitable protective clothing.
General protection and hygiene measures:	Do not breathe mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not put any product-impregnated cleaning rags into your trouser pockets. Take off contaminated clothing and wash it before reuse. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Have eye wash bottle or eye rinse ready at work place.

Environmental exposure controls

Refer to "6.2 Environmental precautions".

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state at 20 °C and 101.3 kPa	liquid
Colour:	light brown
Odour:	Characteristic
Melting point/freezing point:	No data available
Boiling point or initial boiling point and boiling range:	> 100 °C (1013 hPa)
Flammability:	No data available
Lower and upper explosion limit:	No data available
Flash point:	> 100 °C (DIN EN ISO 2592)
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH:	at 20 °C, 5%: 8,9 (DIN 51369)
Kinematic viscosity:	at 20 °C: approx. 120 mm ² /s (DIN EN ISO 3104)
Water solubility:	at 20 °C: Miscible
Partition coefficient n-octanol/water (log value):	Not applicable
Vapour pressure:	No data available
Density:	at 15 °C: 0,909 g/mL (DIN EN ISO 12185)
Relative vapour density:	No data available
Particle characteristics:	Not applicable

9.2 Other information

Explosive properties:	No data available
Oxidizing characteristics:	No data available



Eni Ulex 100

Material number 700

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 14.4.2025
Version: 6.2
Replaces version: 6.1
Language: en-DE
Date of print: 16.7.2025

Page: 8 of 14

Auto-ignition temperature:

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Refer to subsection "Possibility of hazardous reactions".

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4 Conditions to avoid

Keep away from heat sources, sparks and open flames.
Protect from direct sunlight. Protect from frost.

10.5 Incompatible materials

Strong oxidizing agents.

10.6 Hazardous decomposition products

No hazardous decomposition products when regulations for storage and handling are observed.

Thermal decomposition: No data available



Eni Ulex 100

Material number 700

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 14.4.2025
Version: 6.2
Replaces version: 6.1
Language: en-DE
Date of print: 16.7.2025

Page: 9 of 14

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.

Acute toxicity (oral): Based on available data, the classification criteria are not met.

Acute toxicity (dermal): Based on available data, the classification criteria are not met.

Acute toxicity (inhalative): Based on available data, the classification criteria are not met.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/irritation: Based on available data, the classification criteria are not met.

Sensitisation to the respiratory tract: Lack of data.

Skin sensitisation: Skin Sens. 1; H317 = May cause an allergic skin reaction.

Germ cell mutagenicity/Genotoxicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure): Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties:

None

Other information:

Information about Alcohols, C16-18, ethoxylated (CAS 68920-66-1):
LD50 Rat, oral: > 2.000 mg/kg (OECD 401, no mortality occurred)
LD50 Rabbit, dermal: > 2.000 mg/kg (OECD 402, no mortality occurred)

Information about 2-(2-Butoxyethoxy)ethanol (CAS 112-34-5):
LD50 Mouse, oral: 2.410 mg/kg (OECD 401)
LD50 Rabbit, dermal: 2.764 mg/kg (OECD 402)



Eni Ulex 100

Material number 700

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 14.4.2025
Version: 6.2
Replaces version: 6.1
Language: en-DE
Date of print: 16.7.2025

Page: 10 of 14

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: Harmful to aquatic life with long lasting effects.
Information about Alcohols, C16-18, ethoxylated (CAS 68920-66-1):
Fish toxicity:
LC50 Danio rerio (zebrafish): 108 mg/L/96h (OECD 203)
Daphnia toxicity:
EL50 Daphnia magna (Big water flea): 51 mg/L/48 h (OECD 202)
Algae toxicity:
EL50 Pseudokirchneriella subcapitata (green algae): > 11,3 mg/L/72h (OECD 201)
Information about 2-(2-Butoxyethoxy)ethanol (CAS 112-34-5):
Fish toxicity:
LC50 Lepomis macrochirus (Bluegill): 1.300 mg/L/96h (OECD 203)
Daphnia toxicity:
EC50 Daphnia magna (Big water flea): > 100 mg/L/48 h (EU Method C.2)
Water Hazard Class: 2 = obviously hazardous to water (Self-classification (mixture).)

12.2 Persistence and degradability

Further details: Poorly eliminated from water.
Product is partially biodegradable.

12.3 Bioaccumulative potential

No indication of bioaccumulation potential.
Partition coefficient: n-octanol/water:
Not applicable

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

The product does not contain any substances classified as PBT or vPvB.

12.6 Endocrine disrupting properties

None

12.7 Other adverse effects

General information: Do not allow to enter into ground-water, surface water or drains.



Eni Ulex 100

Material number 700

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 14.4.2025
Version: 6.2
Replaces version: 6.1
Language: en-DE
Date of print: 16.7.2025

Page: 11 of 14

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Recommendation: Before intended use:
12 01 07* = Mineral-based machining oils free of halogens (except emulsions and solutions)

* = Evidence for disposal must be provided.

After intended use:

12 01 09* = Machining emulsions and solutions free of halogens

* = Evidence for disposal must be provided.

Dispose of waste according to applicable legislation.

Do not dispose of with household waste.

Package

Recommendation: Dispose of waste according to applicable legislation.
Handle contaminated packages in the same way as the substance itself.
Empty containers may contain flammable product residues. Do not cut, weld, bore, burn or incinerate emptied containers unless they have been cleaned and declared safe.
Empty containers should be disposed of in accordance with local regulations.

Section 14. Transport information

14.1 UN number or ID number

ADR/RID, IMDG, IATA-DGR:

not applicable

ADN:

ID 9006

14.2 UN proper shipping name

ADR/RID, IMDG, IATA-DGR:

Not restricted

ADN:

ID 9006, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

14.3 Transport hazard class(es)

ADR/RID, IMDG, IATA-DGR:

not applicable

ADN:

Class 9, Code: M12

14.4 Packing group

ADR/RID, ADN, IMDG, IATA-DGR:

not applicable

14.5 Environmental hazards

Dangerous for the environment:

Substance/mixture is not environmentally hazardous according to the criteria of the UN model regulations.

Marine pollutant - IMDG: no



Eni Ulex 100

Material number 700

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 14.4.2025
Version: 6.2
Replaces version: 6.1
Language: en-DE
Date of print: 16.7.2025

Page: 12 of 14

14.6 Special precautions for user

Inland waterway craft (ADN)

Hazard label: -
Transport permitted: T
Equipment necessary: PP

14.7 Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations - Germany

Storage class: 10 = Combustible liquids that cannot be assigned to any of the above storage classes

Water Hazard Class: 2 = obviously hazardous to water (Self-classification (mixture).)

Technical guidance air: 5.2.5

Information on working limitations:

Observe employment restrictions for young people.

Further regulations, limitations and legal requirements:

The product is subject to the restrictions on use according to TRGS 611.

National regulations - EC member states

Volatile organic compounds (VOC):

2,7 % by weight

Further regulations, limitations and legal requirements:

Use restriction according to REACH annex XVII, no.: 3, 55, 75

15.2 Chemical Safety Assessment

For this mixture a chemical safety assessment is not required.

SECTION 16: Other information

Classification procedure: Physical hazards: on basis of test data
Health hazards, environmental hazards: calculation method



Eni Ulex 100

Material number 700

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 14.4.2025
Version: 6.2
Replaces version: 6.1
Language: en-DE
Date of print: 16.7.2025

Page: 13 of 14

Wording of the H-phrases under paragraph 2 and 3:

H301 = Toxic if swallowed.
H302 = Harmful if swallowed.
H311 = Toxic in contact with skin.
H314 = Causes severe skin burns and eye damage.
H315 = Causes skin irritation.
H317 = May cause an allergic skin reaction.
H318 = Causes serious eye damage.
H319 = Causes serious eye irritation.
H330 = Fatal if inhaled.
H331 = Toxic if inhaled.
H372 = Causes damage to organs through prolonged or repeated exposure.
H400 = Very toxic to aquatic life.
H410 = Very toxic to aquatic life with long lasting effects.
H411 = Toxic to aquatic life with long lasting effects.
H412 = Harmful to aquatic life with long lasting effects.
EUH071 = Corrosive to the respiratory tract.

Reason of change: Changes in section 3: Composition / Information on ingredients
Changes in section 11: Endocrine disrupting properties
General revision

Date of first version: 1.4.2022

Department issuing data sheet:
see section 1: Department responsible for information



Eni Ulex 100

Material number 700

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 14.4.2025
Version: 6.2
Replaces version: 6.1
Language: en-DE
Date of print: 16.7.2025

Page: 14 of 14

Abbreviations and acronyms:

Acute Tox.: Acute toxicity
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
Aquatic Acute: Hazardous to the aquatic environment - acute
Aquatic Chronic: Hazardous to the aquatic environment - chronic
AS/NZS: Australian Standards/New Zealand Standards
Bw: Body weight
CAS: Chemical Abstracts Service
CFR: Code of Federal Regulations
CLP: Classification, Labelling and Packaging
DMEL: Derived minimal effect level
DNEL: Derived no-effect level
EC: European Community
EC50: Effective Concentration 50%
EL50: Effective loading rate 50%
EmS: Emergency Response Procedures for Ships Carrying Dangerous Goods
EN: European Standard
EQ: Excepted quantities
EU: European Union
Eye Dam.: Eye damage
Eye Irrit.: Eye irritation
IATA: International Air Transport Association
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations
IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IMDG Code: International Maritime Dangerous Goods Code
IMO: International Maritime Organization
LC50: Median lethal concentration
LD50: Lethal dose 50%
MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
M-factor: Multiplication factor
OECD: Organisation for Economic Co-operation and Development
OEL: Occupational Exposure Limit Value
OSHA: Occupational Safety and Health Administration
PBT: Persistent, bioaccumulative and toxic
PNEC: Predicted no-effect concentration
REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals
RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail
Skin Corr.: Skin corrosion
Skin Irrit.: Skin irritation
Skin Sens.: Skin sensitisation
STOT RE: Specific target organ toxicity - repeated exposure
TLV: Threshold Limit Value
TRGS: Technical Rules for Hazardous Substances
vPvB: Very persistent and very bioaccumulative
WEL: Workplace Exposure Limit

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.

Most recent product information is available at:
<https://sumdat.net/ykryekn0>

