

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878 Revision date: 11/4/2024 Supersedes: 7/25/2024 Version: 2.1

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **1.1. Product identifier** Product form : Mixture : Eni i-Sint tech P 0W-30 Trade name Product code : 1014 Type of product : Lubricant Formula : 0106-2024 Product group : Trade product 1.2. Relevant identified uses of the substance or mixture and uses advised against 1.2.1. Relevant identified uses Main use category : Industrial use, Professional use, Consumer use Industrial/Professional use spec : Used in closed systems Wide dispersive use Use of the substance/mixture : Lubricant for internal combustion engines Do not use the product for any purposes that have not been advised by the manufacturer. Function or use category : Lubricants and additives 1.2.2. Uses advised against

No additional information available

1.3. Details of t	he supplier o	of the safetv	data sheet

Manufacturer:

Enilive Iberia S.L.U.

Avenida de Europa, 24, Edificio Torona B - Planta 1ª, 28108 Alcobendas (Madrid) Tel: (+34) 917 277 878 Competent person responsible for the Safety Data Sheet (Reg. EC nr. 1907/2006): SDS.Enilive@enilive.com

Distributed by: Enilive Schmiertechnik GmbH, Paradiesstraße 14, 97080 Würzburg, GERMANY Department responsible for information: Application Engineering & Product Management (AEPM), Tel. +49 (0)931-900 98-0 e-mail: technik.wuerzburg@enilive.com

Poison Center

1.4. Emergency telephone number	
Emergency number	: CNIT +39 0382 24444 (24h) (IT + EN)

## **SECTION 2: Hazards identification**

2.1. Classification of the substance or mixture

## Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]

Not classified

## Adverse physicochemical, human health and environmental effects

Contact with eyes may cause temporary reddening and irritation. For specific information about the toxicological/ecotoxicological properties and classification of this product, see Sect. 11 and/or Sect. 12.

## 2.2. Label elements

## Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements

: EUH208 - Contains Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs, calcium salts, Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated. May produce an allergic reaction.

EUH210 - Safety data sheet available on request.

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

2.3. Other hazards (not relevant for classification)		
Other hazards not contributing to the classification	: This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels. Any substance, in case of accidents involving pressurized circuits and the like, may be accidentally injected under the skin, even without external damage. In such a case, the victim should be brought to an hospital as soon as possible, to get specialized medical treatment. Do not wait for symptoms to develop. A potential risk may arise from the release of hydrogen sulfide, when the product is stored or handled at high temperature. Hydrogen sulfide may accumulate in the tanks or other confined spaces, with danger to the workers that enter the spaces. In these cases overexposure to hydrogen sulfide may cause irritation to airways, nausea, dizziness, loss of consciousness and death.	

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII Contains no PBT and/or vPvB substances  $\geq$  0.1% assessed in accordance with REACH Annex XIII

Component			
Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7), Mineral base oil, severely refined, Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts (722503-68-6), Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated		
Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7), Mineral base oil, severely refined, Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts (722503-68-6), Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated		

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Component	
Substance(s) not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7), Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts (722503-68-6), Alkyl (C18- C28) toluenesulfonic acid, calcium salts, borated

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

### Not applicable

### 3.2. Mixtures

Comments

: Composition/ Information on ingredients: Mixture of hydrocarbons Polyolefins Additives

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]
Distillates (petroleum), hydrotreated heavy paraffinic (see note [*]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627- 25	20 - 30	Asp. Tox. 1, H304

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]
Mineral base oil, severely refined substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	REACH-no: N/D	8 - 11	Not classified
Benzenesulfonic acid, methyl-, mono-C20-24- branched alkyl derivs., calcium salts	CAS-No.: 722503-68-6 EC-No.: 682-816-2 EC Index-No.: N/A REACH-no: N/A	0,1 - 0,8	Skin Sens. 1B, H317 Aquatic Chronic 4, H413
Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated substance with national workplace exposure limit(s) (BE, IE)	EC-No.: 953-650-0 REACH-no: N/A	0,1 - 0,8	Skin Sens. 1B, H317 Repr. 2, H361d

Name	Product identifier	Specific concentration limits (%)	
Benzenesulfonic acid, methyl-, mono-C20-24- branched alkyl derivs., calcium salts	CAS-No.: 722503-68-6 EC-No.: 682-816-2 EC Index-No.: N/A REACH-no: N/A	(2 ≤ C < 100) Skin Sens. 1B, H317	
Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated	EC-No.: 953-650-0 REACH-no: N/A	(2 ≤ C < 100) Skin Sens. 1B, H317 (17.15 ≤ C < 100) Repr. 2, H361d	

Comments

: Note [\*]:

this product has a value of DMSO extract < 3 % wt, according to IP 346. According to the criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product must be regarded as non carcinogenic.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures				
4.1. Description of first aid measures				
First-aid measures after inhalation	: Remove to fresh air, keep the casualty warm and at rest. If breathing is difficult, give oxygen if possible, or assisted ventilation. If necessary, give external cardiac massage and obtain medical advice. See also section 4.3.			
First-aid measures after skin contact	: Remove contaminated clothing and shoes. Wash skin with soap and water. If skin irritation occurs: Get medical advice/attention. In case of burns, cool affected part with cold running water for at least 10 min. Cover with gauze or clean cloth. Ask for medical assistance or bring to a hospital. Do not apply salves or other substances, unless by doctor's advice.			
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do so. Rinse eyes thoroughly for at least 15 minutes. Keep eyelids well apart. Obtain medical attention if irritation persists. In case of burns, cool affected part with cold running water for at least 10 min. Cover with gauze or clean cloth. Ask for medical assistance or bring to a hospital. Do not apply salves or other substances, unless by doctor's advice.			
First-aid measures after ingestion	: Rinse mouth thoroughly with water. Give water to drink if victim completely conscious/alert. Do not induce vomiting.			
4.2. Most important symptoms and effects, both acute and delayed				
Symptoms/effects after inhalation	<ul> <li>Inhalation of fumes or oil mists produced at high temperatures may cause irritation of the respiratory tract. Symptoms of overexposure to vapours include drowsiness, weakness, headache, dizziness, nausea, vomiting, dimming of vision.</li> </ul>			
Symptoms/effects after skin contact Symptoms/effects after eye contact	<ul> <li>Contact with hot product may cause thermal burns.</li> <li>Contact with eyes may cause temporary reddening and irritation. Contact with hot product or vapours may cause burns.</li> </ul>			

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Symptoms/effects after ingestion Symptoms/effects upon intravenous administration Chronic symptoms	:	Accidental ingestion of small quantities of the product may cause nausea, discomfort and gastric disturbances. No information available. None to be reported, according to the present classification criteria.
4.3. Indication of any immediate medical at	te	ntion and special treatment needed

Obtain medical attention if casualty has an altered state of consciousness or if symptoms do not resolve. Seek medical attention in all cases of serious burns. If there is any suspicion of inhalation of H2S (hydrogen sulphide), Rescuers must wear breathing apparatus, belt and safety rope, and follow rescue procedures. Send patient to hospital. Immediately begin artificial respiration if breathing has ceased. Administer oxygen if necessary.

SECTION 5: Firefighting measures		
5.1. Extinguishing media		
Suitable extinguishing media Unsuitable extinguishing media	<ul> <li>Other extinguishing gases (according to regulations). Small-size fires: carbon dioxide, dry chemicals, foam, sand or earth. Large fires: foam or water fog (mist). These means should be used by trained personnel only.</li> <li>Do not use water jets. They could cause splattering, and spread the fire. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.</li> </ul>	
5.2. Special hazards arising from the substa	ance or mixture	
Fire hazard Explosion hazard Hazardous decomposition products in case of fire	<ul> <li>This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels.</li> <li>In case of losses from pressurized circuits, the sprays may form mists. Take into account that in this case the lower explosion limit for mists is about 45 g/m<sup>3</sup> of air. Vapours are heavier than air, spread along floors and form explosive mixtures with air.</li> <li>Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid</li> </ul>	
Hazardous decomposition products in case of me	particulates, gases, including carbon monoxide, NOx, H2S and SOx (harmful/toxic gases). Oxygenated compounds (aldehydes, etc.). POx. CaOx. ZnOx.	
5.3. Advice for firefighters		
Firefighting instructions	: Shut off source of product, if possible. If possible, move containers and drums away from the danger area, if safe to do so. Spilled product which is not burning should be covered with sand or foam. Use water sprays to cool containers and surfaces exposed to the flames. If the fire cannot be controlled, evacuate area.	
Special protective equipment for firefighters	: Wear personal protection equipment. (see chapter 8). In case of a large fire or in confined or poorly ventilated spaces, wear full fire resistant protective clothing and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. EN 443. EN 469. EN 659.	
Other information	: In case of fire, do not discharge residual product, waste materials and runoff water: collect separately and use a proper treatment.	

SECTION 6: Accidental release measures			
6.1. Personal precautions, protectiv	1. Personal precautions, protective equipment and emergency procedures		
General measures	: Stop or contain leak at the source, if safe to do so. Eliminate all ignition sources if safe to do so (e.g. electricity, sparks, fires, flares). Avoid accidental sprays on hot surfaces or electrical contacts. Avoid direct contact with released material. Keep upwind.		
6.1.1. For non-emergency personnel			
Protective equipment Emergency procedures	<ul> <li>See Section 8.</li> <li>Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency.</li> </ul>		

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

#### 6.1.2. For emergency responders

Protective equipment	Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters. Small spillages: normal antistatic working clothes are usually adequate. Large spillages: full body suit of chemically resistant and antistatic material. if necessary heat resistant and insulated. Work helmet. Antistatic non-skid safety shoes or boots.
	Goggles and /or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory protection: A half or full-face respirator with combined dust/organic vapour filter(s), or a Self-Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
Emergency procedures	If required, notify relevant authorities according to all applicable regulations.

### 6.2. Environmental precautions

Do not let the product accumulate in confined or underground spaces. Do not let the product flow into sewers or water courses, or in any way contaminate the environment. In case of contamination of environment compartments (soil, subsoil, surface or underground waters), remove contaminated soil when possible, and in any case treat all involved compartments in accordance with local regulations. The site should have a spill plan to ensure that adequate safeguards are in place to minimize the impact of episodic releases.

### 6.3. Methods and material for containment and cleaning up

For containment	: Contain spilled liquid with sand, earth or other suitable absorbents (non-flammable). Recover free liquid and waste materials in suitable waterproof and oil-resistant containers. Clean contaminated area. Dispose of according to local regulations. If in water: Confine the spillage. Remove from surface by skimming or suitable floating absorbents. Collect recovered product and other waste materials in suitable waterproof, oil resistant containers. Recover or dispose of according to local regulations. Do not use solvents or dispersants, unless specifically advised by an expert, and, if required, approved by local authorities.
Methods for cleaning up	<ul> <li>Transfer recovered product and other materials to suitable tanks or containers and store/dispose according to relevant regulations.</li> </ul>
Other information	: Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air/water temperature, wave/current direction and speed) may significantly influence the choice of appropriate actions. Local regulations may also prescribe or limit actions to be taken. For this reason, local experts should be consulted when necessary.

### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	: Ensure that proper housekeeping measures are in place. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Use and store only outdoors or in a well-ventilated area. Ensure good ventilation of the work station. Due to the extremely slippery nature of this material, more care than usual must be exercised in material handling practices to keep off all walking surfaces. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Before entering storage tanks and commencing any operation in a confined area (e.g. tunnels), carry out an adequate clean-up, and check the atmosphere for oxygen content, flammability, and the presence of sulphur compounds. The product may release Hydrogen Sulphide: a specific assessment of inhalation risks from the presence of hydrogen sulphide in tank headspaces, confined spaces, product residue, tank waste and waste water, and unintentional releases should be made to help determine controls appropriate to local circumstances.
Handling temperature Hygiene measures	<ul> <li>This product can be handled at ambient temperatures.</li> <li>Avoid contact with skin. Do not breathe fume/ mist/ vapours. Do not ingest. Do not smoke. Do not eat and do not drink during use. Do not clean hands with dirty or oil-soaked rags. Do not re-use clothes, if they are still contaminated. Keep away from food and beverages. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Contaminated work clothing should not be allowed out of the workplace. Separate working clothes from town clothes. Launder separately.</li> </ul>

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

7.2. Conditions for safe storage, in	cluding any incompatibilities
Storage conditions	: Store in dry, well-ventilated area. Keep away from open flames, hot surfaces and sources of ignition. Do not smoke.
Incompatible products	: Strong oxidizing agents.
Storage area	: Storage area layout, tank design, equipment and operating procedures must comply with the relevant European, national or local legislation. Storage installations/areas should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations.
Packages and containers:	: If the product is supplied in containers: Keep containers tightly closed and properly labelled. Keep only in the original container or in a suitable container for this kind of product.
Packaging materials	: For containers, or container linings use materials specifically approved for use with this product. Compatibility should be checked with the manufacturer.
Germany	
Storage class (LGK, TRGS 510)	: LGK 10 - Combustible liquids
Switzerland	
Storage class (LK)	: LK 10/12 - Liquids
7.3. Specific end use(s)	

No information available.

## SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

## 8.1.1 National occupational exposure and biological limit values

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Belgium - Occupational Exposure Limits		
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Denmark - Occupational Exposure Limits		
OEL TWA	1 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
OEL STEL	2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KGV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
WEL STEL (OEL STEL)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	

# Safety Data Sheet

Distillates (petroleum), hydrotreated heavy pa	araffinic (64742-54-7)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH OEL STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Mineral base oil, severely refined		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Belgium - Occupational Exposure Limits		
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Denmark - Occupational Exposure Limits		
OEL TWA	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
OEL STEL	2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KGV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
WEL STEL (OEL STEL)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH OEL STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Alkyl (C18-C28) toluenesulfonic acid, calcium	salts, borated	
Belgium - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
Ireland - Occupational Exposure Limits	·	
OEL TWA	4 mg/m³	
USA - ACGIH - Occupational Exposure Limits	·	
ACGIH OEL TWA	5 mg/m³	
8.1.2. Recommended monitoring procedures		
Monitoring methods		
Monitoring methods	Monitoring procedures should be chosen according to the indications set by national authorities or labour contracts. Refer to relevant legislation and in any case to the good practice of industrial hygiene.	

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### 8.1.3. Air contaminants formed

## No additional information available

814	DNFI	and	PNEC
0.1.4.	DITEL	and	INLO

Eni i-Sint tech P 0W-30	
DNEL/DMEL (additional information)	
Additional information	Not applicable
PNEC (additional information)	
Additional information	Not applicable
Distillates (petroleum), hydrotreated heavy pa	araffinic (64742-54-7)
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	1 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	2.7 mg/m <sup>3</sup>
Long-term - local effects, inhalation	5.6 mg/m³
DNEL/DMEL (General population)	
Long-term - systemic effects,oral	0.74 mg/kg bodyweight/day
Long-term - local effects, inhalation	1.2 mg/m³/day (DNEL, Mineral base oil mist, severely refined, DMSO extract <3% m/m)
PNEC (Oral)	
PNEC oral (secondary poisoning)	9.33 mg/kg food
reaction mass of isomers of: C7-9-alkyl 3-(3,5	-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)
DNEL/DMEL (Workers)	
Acute - systemic effects, dermal	20 mg/kg bodyweight/day
Acute - systemic effects, inhalation	1750 mg/m³
Acute - local effects, dermal	1 mg/cm <sup>2</sup>
Long-term - systemic effects, dermal	0.22 mg/kg bodyweight/day
Long-term - local effects, dermal	0.006 mg/cm <sup>2</sup>
Long-term - systemic effects, inhalation	3 mg/m <sup>3</sup>
DNEL/DMEL (General population)	
Acute - systemic effects, dermal	50 mg/kg bodyweight
Acute - systemic effects, inhalation	875 mg/m³
Acute - systemic effects, oral	50 mg/kg bodyweight/day
Acute - local effects, dermal	8.33 mg/cm <sup>2</sup>
Long-term - systemic effects,oral	0.43 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	0.74 mg/m³
Long-term - systemic effects, dermal	4.3 mg/kg bodyweight/day
Long-term - local effects, inhalation	875 mg/m³
PNEC (Water)	
PNEC aqua (freshwater)	4.3 μg/l
PNEC aqua (marine water)	1.8 µg/l
PNEC aqua (intermittent, freshwater)	43 μg/l

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

reaction mass of isomers of: C7-9-alkyl 3-	(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)
PNEC (Sediment)	
PNEC sediment (freshwater)	0.37 mg/kg dwt
PNEC sediment (marine water)	0.037 mg/kg dwt
PNEC (Soil)	
PNEC soil	0.632 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	33 µg/kg
PNEC (STP)	
PNEC sewage treatment plant	10 mg/l
Note	<ul> <li>The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a governmental regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH.</li> </ul>

### 8.1.5. Control banding

No additional information available

### 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

### Appropriate engineering controls:

Ensure good ventilation of the work station. Before entering storage tanks and commencing any operation in a confined area (e.g. tunnels), check the atmosphere for oxygen content, presence of hydrogen sulphide (H2S) and SOx, and flammability. see section(s) : 16. Other information.

### 8.2.2. Personal protection equipment

### Personal protective equipment (for industrial or professional use):

Gloves. Protective clothing. Safety glasses. Safety shoes or boots. Dust/aerosol mask with filter type P1.

Personal protective equipment symbol(s):



### 8.2.2.1. Eye and face protection

#### Eye protection:

When there is a risk of contact with the eyes, use safety goggles or other means of protection (face shield). If necessary, refer to national standards or to the EN 166 standard. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure

### 8.2.2.2. Skin protection

#### Skin and body protection:

Long-sleeved overalls. If necessary, refer to the EN 340 and related standards, for definition of characteristics and performance according to the risk rating of the area. Antistatic non-skid safety shoes or boots, chemical resistant, if necessary heat resistant and insulated.

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

#### Hand protection:

When there is a risk of contact with the skin, use waterproof gloves, resistant to chemical products. Gloves must be felt-lined. Use gloves respecting all the conditions and within the limits set by the manufacturer. Replace gloves immediately in case of cuts, holes or other signs of damages or degradation. If necessary, refer to the EN 374 standard. Adequate materials: nitrile (NBR) or PVC with a protection index > 5 (permeation time > 240 mins). Personal hygiene is a key element for an effective hand care. Gloves must be worn only with clean hands. After wearing gloves, hands must be carefully washed and dried.

### 8.2.2.3. Respiratory protection

### **Respiratory protection:**

Independently from other possible actions (technical modifications, operating procedures, and other means to limit the exposure of workers), personal protection equipment can be used according to necessity. Open or well ventilated spaces: if the product is handled without adequate containment: use full or half-face masks with adequate filter for organic vapours. (EN 136/140/145). Combination filter device (DIN EN 141). Approved respiratory protection equipment shall be used in spaces where hydrogen sulphide may accumulate: full face mask with cartridge/filter type "B" (grey for inorganic vapours including H2S) or self-contained breathing apparatus (SCBA). (EN 136/140/145). Closed or confined areas (e.g. tank interiors): the use of protection measures for airways (masks or self-contained breathing apparatus), must be assessed according to the specific activity, as well as level and duration of predicted exposure. (EN 136/140/145)

#### 8.2.2.4. Thermal hazards

### Thermal hazard protection:

None in normal use conditions.

#### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Do not discharge the product into the environment. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed. Prevent discharge of undissolved substance to or recover from onsite wastewater. Storage areas/installations should be designed with adequate bunds so as to prevent ground and water pollution in case of leaks or spills.

### Consumer exposure controls:

No special requirements.

SECTION 9: Physical and chemical properties			
9.1. Information on basic physical	9.1. Information on basic physical and chemical properties		
Physical state	: Liquid		
Colour	: brown.		
Appearance	: Liquid, bright & clear.		
Odour	: Characteristics.		
Odour threshold	: Not available		
Melting point	: Not determined		
Freezing point	: Not determined		
Boiling point	: Not determined		
Flammability	: Not flammable		
Lower explosion limit	: Not determined		
Upper explosion limit	: Not determined		
Flash point	: > 190 °C (ASTM D 93)		
Auto-ignition temperature	: Not determined		
Decomposition temperature	: Not determined		
рН	: Not available		
Viscosity, kinematic	: 51.5 mm²/s (40 °C) (ASTM D 445)		
Solubility	: Water: Immiscible and insoluble		
Log Kow	: Not applicable for mixtures		
Log Pow	: Not applicable for mixtures		
Vapour pressure	: 0.1 hPa (20 °C) (Mineral oil, ASTM D 5191) (CONCAWE, 2010)		
Vapour pressure at 50°C	: Not determined		
Density	: 845 kg/m³ (ASTM D 4052)		
Relative density	: Not determined		
Relative vapour density at 20°C	: Not determined		
Particle characteristics	: Not applicable		

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### 9.2. Other information

### 9.2.1. Information with regard to physical hazard classes

No additional information available

### 9.2.2. Other safety characteristics

Additional information

: No data available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This mixture does not offer any further hazard for reactivity, except what is reported in the following paragraphs.

### **10.2. Chemical stability**

Stable product, according to its intrinsic properties.

## 10.3. Possibility of hazardous reactions

None (in normal conditions of storage and handling). Contact with strong oxidizers (peroxides, chromates, etc.) may cause a fire hazard. Sensitivity to heat, friction or shock cannot be assessed in advance.

#### 10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition. Avoid the build-up of electrostatic charge.

### **10.5. Incompatible materials**

### Strong oxidants.

### **10.6. Hazardous decomposition products**

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition may produce : Carbon dioxide, Carbon monoxide, Nitrogen oxides (NOx) (as NO2). In exceptional cases (i.e prolonged storage in tanks contaminated with water, and presence of anaerobic sulfate-reducing microbial colonies), the product may undergo a degradation and generate small amounts of sulfur compounds, including H2S. See also Section 16, "Other information".

## **SECTION 11: Toxicological information**

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008		
Acute toxicity (oral) :	Not classified (Based on available data, the classification criteria are not met; Conclusive but not sufficient for classification)	
Acute toxicity (dermal) :	Not classified (Based on available data, the classification criteria are not met; Conclusive but not sufficient for classification)	
Acute toxicity (inhalation) :	Not classified (Based on available data, the classification criteria are not met; Conclusive but not sufficient for classification)	
Additional information :	(according to composition)	
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
LD50 oral rat	> 5000 mg/kg (OECD 401)	
LD50 dermal rat	> 5000 mg/kg (OECD 402)	
LC50 Inhalation - Rat	> 5 mg/l/4h (OECD 403)	
Mineral base oil, severely refined		
LD50 oral rat	> 5000 mg/kg (OECD 401)	
LD50 dermal rat	> 5000 mg/kg (OECD 402)	
LC50 Inhalation - Rat	> 5 mg/l/4h (OECD 403)	

# Safety Data Sheet

Alkyl (C18-C28) toluenesulfonic acid, calcium	salts, borated	
LD50 oral rat	3640 mg/kg bodyweight	
LD50 dermal rabbit	> 2000 mg/kg bodyweight	
	Not classified (Based on available data, the classification criteria are not met) (according to composition)	
Distillates (petroleum), hydrotreated heavy pa	raffinic (64742-54-7)	
рН	Not applicable	
Mineral base oil, severely refined		
рН	Not applicable	
	Not classified (Based on available data, the classification criteria are not met) (according to composition)	
Distillates (petroleum), hydrotreated heavy pa	raffinic (64742-54-7)	
рН	Not applicable	
Mineral base oil, severely refined	·	
рН	Not applicable	
Respiratory or skin sensitisation : Additional information :	Not classified (according to composition)	
Germ cell mutagenicity:Additional information:Carcinogenicity:Additional information:	Not classified (Based on available data, the classification criteria are not met) (according to composition) Not classified (Based on available data, the classification criteria are not met) (according to composition) All the mineral base oils contained in this product have a value < 3 % wt of DMSO extract, according to IP 346 (Nota L - Annex VI Reg (CE) 1272/2008, # 1.1.3) This product contains also the following substances : Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] this product has a value of DMSO extract < 3 % wt, according to IP 346. According to the criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product must be regarded as non carcinogenic. Not classified (Based on available data, the classification criteria are not met) (according to composition) Not classified (Based on available data, the classification criteria are not met) (according to composition) Not classified (Based on available data, the classification criteria are not met) (according to composition)	
Distillates (petroleum), hydrotreated heavy pa	rraffinic (64742-54-7)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)	
Mineral base oil, severely refined		
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)	
Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated		
NOAEL (oral, rat, 90 days)	300 mg/kg bodyweight/day	
Aspiration hazard : Additional information :	Not classified (Based on available data, the classification criteria are not met) (according to composition)	
Eni i-Sint tech P 0W-30		
Viscosity, kinematic	51.5 mm²/s (40 °C) (ASTM D 445)	

## Safety Data Sheet

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
Viscosity, kinematic 17.9 mm²/s (40 °C) (ASTM D 445)		
Mineral base oil, severely refined		
Viscosity, kinematic	9 mm²/s (40 °C) (ASTM D 445)	
11.2. Information on other hazards		
11.2.1. Endocrine disrupting properties		
Adverse health effects caused by endocrine disrupting properties	: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %	
11.2.2. Other information		
Potential adverse human health effects and symptoms	: Contact with eyes may cause temporary reddening and irritation.	
Other information	: None	

SECTION 12: Ecological information		
12.1. Toxicity		
Ecology - general	An uncontrolled release to the environment may produce a contamination of different environmental compartments (air, soil, underground, surface water bodies, aquifers). Handle according to general working hygiene practices to avoid pollution and release into the environment.	
Ecology - water	<ul> <li>This product is not soluble in water. It floats on water and forms a film on the surface. The damage to aquatic organisms is of mechanical kind (immobilization and entrapment)</li> <li>Not classified</li> </ul>	
Hazardous to the aquatic environment, short-term (acute)	Not classified	
Hazardous to the aquatic environment, long–term (chronic)	Not classified (Based on available data, the classification criteria are not met)	
Distillates (petroleum), hydrotreated heavy p	oaraffinic (64742-54-7)	
LC50 fish 1	> 100 mg/l (LL 50)	
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)	
Mineral base oil, severely refined		
LC50 fish 1	> 100 mg/l (LL 50)	
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)	
Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated		
LC50 fish 1	180 mg/l (Oryzias latipes)	
EC50 Daphnia 1	85.4 mg/l	
EC50 72h - Algae [1]	49.3 mg/l (Desmodesmus subspicatus)	
NOEC (chronic)	25 mg/l (21d)	
12.2. Persistence and degradability		
Eni i-Sint tech P 0W-30		
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.	

# Safety Data Sheet

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions	
Mineral base oil, severely refined		
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions	
Benzenesulfonic acid, methyl-, mono-C20-24-	branched alkyl derivs., calcium salts (722503-68-6)	
Persistence and degradability	Rapidly degradable	
Alkyl (C18-C28) toluenesulfonic acid, calcium	salts, borated	
Persistence and degradability	Readily biodegradable	
12.3. Bioaccumulative potential		
Eni i-Sint tech P 0W-30		
Log Pow	Not applicable for mixtures	
Log Kow	Not applicable for mixtures	
Bioaccumulative potential	Not established.	
Alkyl (C18-C28) toluenesulfonic acid, calcium	salts, borated	
Log Pow	2.7	
12.4. Mobility in soil		
Eni i-Sint tech P 0W-30		
Ecology - soil	No data available.	
12.5. Results of PBT and vPvB assessment		
Eni i-Sint tech P 0W-30		
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII		
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII		
Component		
Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7), Mineral base oil, severely refined, Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts (722503-68-6), Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated	
Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7), Mineral base oil, severely refined, Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts (722503-68-6), Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated	
12.6. Endocrine disrupting properties		
endocrine disrupting properties	The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.	
12.7. Other adverse effects		
Other adverse effects :	None.	

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Additional information

: No other effects known

SECTION 13: Disposal considerations	5
13.1. Waste treatment methods	
Regional waste regulation Waste treatment methods	<ul> <li>Disposal must be done according to official regulations.</li> <li>Dispose of empty containers and wastes safely. Do not dispose of the product, either new or used, by dumping on the ground, or discharging into sewers, tunnels, lakes or water courses. Deliver to a qualified official collector.</li> </ul>
Sewage disposal recommendations	Dispose of in a safe manner in accordance with local/national regulations. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.
Product/Packaging disposal recommendations	: European Waste Catalogue code(s) (Decision 2001/118/CE): 13 02 05* (mineral-based non-chlorinated engine, gear and lubricating oils). This EWC code is only a general indication, and takes into account the original composition of the product and its intended use. The user has the responsibility of choosing the right EWC code, considering the actual use of the product, alterations and contaminations.
EURAL code (EWC)	: 13 02 05* - Mineral-based non-chlorinated engine, gear and lubricating oils

## **SECTION 14: Transport information**

## In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	ΙΑΤΑ	ADN	RID
14.1. UN number or ID n	14.1. UN number or ID number			
Not regulated for transport				
14.2. UN proper shipping	g name			
Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.3. Transport hazard o	lass(es)			
Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.4. Packing group				
Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.5. Environmental hazards				
Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
None.				

## 14.6. Special precautions for user

**Overland transport** 

Not regulated.

Transport by sea Not regulated.

Air transport Not regulated.

**Inland waterway transport** Not regulated.

Rail transport Not regulated.

14.7. Maritime transport in bulk according to IMO instruments

### Not applicable

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Other information, restriction and prohibition regulations	<ul> <li>Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). (et sequens). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (et sequens). Directives 89/391/CEE, 89/654/CEE, 89/655/CEE, 89/656/CEE, 90/269/CEE, 90/270/CEE, 90/394/CEE, 90/679/CEE, 93/88/CEE, 95/63/CE, 97/42/CE, 98/24/CE, 99/38/CE, 99/92/CE, 2001/45/CE, 2003/10/CE, 2003/18/CE (Health and safety on the workplace). Directive 2012/18/CE (Control of major-accident hazards involving dangerous substances). Directive 2004/42/CE (Limitation of emissions of Volatile Organic Compounds). Directive 98/24/EC (protection of the health and safety of workers from the risks related to chemical agents at work). Directive 92/85/CE (measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are</li> </ul>
	, , , , , , , , , , , , , , , , , , , ,
	breastfeeding). Substances Depleting the Ozone layer (1005/2009) - Annex I Substances
	(ODP). Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29
	April 2004 on persistent organic pollutants and amending Directive 79/117/EEC. Regulation
	EU (649/2012) - Export and Import of hazardous chemicals (PIC).

### **REACH Annex XVII (Restriction List)**

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(b)	Distillates (petroleum), hydrotreated heavy paraffinic	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10

### **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

### **REACH Candidate List (SVHC)**

No ingredients are included in the REACH Candidate list (> 0,1 % m/m).

#### **PIC Regulation (Prior Informed Consent)**

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

#### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

#### Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

#### **Explosives Precursors Regulation (2019/1148)**

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

#### **Drug Precursors Regulation (273/2004)**

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

### 15.1.2. National regulations

National adoption of EU Directives concerning health and safety on the workplace.

National adoption of EU Directives concerning control of major-accident hazards involving dangerous substances (2012/18/CE). Relevant national laws on prevention of water pollution.

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Relevant national laws on protection of the health of pregnant workers (National adoption of Dir. 92/85/EEC). National adoption of Directive 2008/98/CE concerning disposal of used oils.

### Finland

Finnish National Regulations : Occupational Safety and Health Act No. 738/2002.

France

Maladies professionelles (F)		
Code Description	Description	
RG 36 Diseases caused	Diseases caused by oils and fats of mineral or synthetic origin	
Germany		
Employment restrictions National Rules and Recommendations	<ul> <li>Employment prohibitions or restrictions on the protection of young people at work according to § 22 JArbSchG in the case of formation of hazardous substances have to be observed.</li> <li>TRGS 900: Occupational Exposure Limits. TRGS 800: Fire protection measures. TRGS 555: Working instruction and information for workers. TRGS 402: Identification and Assessment of the Risks from Activities involving Hazardous Substances: Inhalation Exposure. TRGS 401: Risks resulting from skin contact - identification, assessment, measures. TRGS 400: Hazard assessment for activities involving Hazardous Substances. TRGS 500: Protective measures.</li> </ul>	
VbF class (D) Water hazard class (WGK) (D) WGK remark Hazardous Incident Ordinance (12. BImSchV)	<ul> <li>Not applicable.</li> <li>WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1).</li> <li>Classification based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS).</li> <li>Is not subject to the Hazardous Incident Ordinance (12. BImSchV)</li> </ul>	
Netherlands		
Saneringsinspanningen SZW-lijst van kankerverwekkende stoffen SZW-lijst van mutagene stoffen SZW-lijst van reprotoxische stoffen – Borstvoed SZW-lijst van reprotoxische stoffen – Vruchtbaarheid	<ul> <li>C - Minimize discharge</li> <li>None of the components are listed</li> </ul>	
SZW-lijst van reprotoxische stoffen – Ontwikkel	ing : None of the components are listed	
Denmark Danish National Regulations	: Young people under 18 years are not allowed to use the product Pregnant/breastfeeding women working with the product must not be in direct contact with i	
Norway		
Norwegian National Regulations	: Working Environment Act (LOV-2005-06-17 NO. 62). People under the age of 18 may not work with this product at all.	
Sweden		
Swedish National Regulations	: This product is in compliance with Ordinance 1998:944. Work Environment Act (1977: 1160). Chemical Hazards in the Working Environment (AFS 2011:19).	

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP] No chemical safety assessment has been carried out

A chemical safety assessment has been carried out for the following components of this mixture::

Distillates (petroleum), hydrotreated heavy paraffinic

Mineral base oil, severely refined

Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SECTION 16: Other information			
Indication of changes	3		
Section	Changed item	Change	Comments
2.2	EUH-statements	Modified	

Abbreviations	and acronyms:
	Complete text of the H phrases quoted in this Safety Data Sheet. These phrases are reported here for information only, and MAY NOT correspond to the classification of the product.
	N/D = not available
	N/A = not applicable
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Effective concentration for 50 percent of test population (median effective concentration)
IARC	International Agency for Research on Cancer
ΙΑΤΑ	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Lethal concentration for 50 percent of test population (median lethal concentration)
LD50	Lethal dose for 50 percent of test population (median lethal dose)
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
РВТ	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals, Regulation (EC) No 1907/2006
RID	Regulation concerning the International Carriage of Dangerous Goods by Railways
SDS	Safety Data Sheet
STP	Sewage treatment plant
vPvB	Very Persistent and Very Bioaccumulative

Data sources

Training advice

This Safety Data Sheet is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.
Provide adequate training to professional operators for the use of PPEs, according to the information contained in this Safety Data Sheet.

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Other information

: Do not use the product for any purposes that have not been advised by the manufacturer. In exceptional cases (i.e prolonged storage in tanks contaminated with water, and presence of anaerobic sulfate-reducing microbial colonies), the product may undergo a degradation and generate small amounts of sulfur compounds, including H2S. This situation is especially relevant in all those circumstances which require to enter a confined space, with direct exposure to the vapours. If there is any suspicion of inhalation of H2S (hydrogen sulphide), Rescuers must wear breathing apparatus, belt and safety rope, and follow rescue procedures. Send patient to hospital. Immediately begin artificial respiration if breathing has ceased. Administer oxygen if necessary. This situation is especially relevant for those operations which involve direct exposure to the vapours in the interior of tanks or other confined spaces. If this possibility is suspected, a specific assessment of inhalation risks from the presence of H2S in confined spaces must be made, to help determine prevention measures and controls (i.e. PPE) appropriate to local circumstances, and adequate emergency procedures.

Full text of H- and EUH-statements:		
Aquatic Chronic 4	Hazardous to the aquatic environment – Chronic Hazard, Category 4	
Asp. Tox. 1	Aspiration hazard, Category 1	
EUH208	Contains Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs, calcium salts, Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated. May produce an allergic reaction.	
EUH210	Safety data sheet available on request.	
H304	May be fatal if swallowed and enters airways.	
H317	May cause an allergic skin reaction.	
H361d	Suspected of damaging the unborn child.	
H413	May cause long lasting harmful effects to aquatic life.	
Repr. 2	Reproductive toxicity, Category 2	
Skin Sens. 1B	Skin sensitisation, category 1B	

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.