



# Eni i-Sint tech VK 0W-20

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878  
Revision date: 9/3/2025 Supersedes: 12/27/2024 Version: 2.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form	: Mixture
Trade name	: Eni i-Sint tech VK 0W-20
Product code	: 1058
Type of product	: Lubricants
Formula	: 0309-2025
Product group	: Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses

Main use category	: Industrial use, Professional use, Consumer use
Industrial/Professional use spec	: Used in closed systems Wide dispersive use
Use of the substance/mixture	: Lubricant for internal combustion engines ----- Do not use the product for any purposes that have not been advised by the manufacturer.
Function or use category	: Lubricants and additives

#### 1.3. Details of the supplier of the safety data sheet

Manufacturer: Enilive Iberia S.L.U. Avenida de Europa, 24, Edificio Torona B - Planta 1ª, 28108 Alcobendas (Madrid) Tel: (+34) 917 277 878  
Competent person responsible for the Safety Data Sheet (Reg. EC nr. 1907/2006): SDS.Enilive@enilive.com

Distributed by: Enilive Schmiertechnik GmbH, Paradiesstraße 14, 97080 Würzburg, GERMANY  
Department responsible for information: Application Engineering & Product Management (AEPM), Tel. +49 (0)931-900 98-0  
e-mail: technik.wuerzburg@enilive.com

#### 1.4. Emergency telephone number

Emergency number	: CNIT +39 0382 24444 (24h) (IT + EN) Poison Center
------------------	--

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]

Not classified

##### Adverse physicochemical, human health and environmental effects

Prolonged and repeated skin contact may cause reddening, irritation and dermatitis. May produce an allergic reaction. For specific information about the toxicological/ecotoxicological properties and classification of this product, see Sect. 11 and/or Sect. 12.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements	: EUH208 - Contains C14-16-18 Alkyl phenol. May produce an allergic reaction. EUH210 - Safety data sheet available on request.
----------------	---

#### 2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII  
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII  
Contains no PBT and/or vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

# Eni i-Sint tech VK 0W-20

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Component	
Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	1-Decene, Homopolymer, Hydrogenated (68037-01-4), Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified (72623-87-1), Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0), Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9), Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0), Paraffin oils (petroleum), catalytic dewaxed heavy, Baseoil - unspecified (64742-70-7), C14-16-18 Alkyl phenol
Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	1-Decene, Homopolymer, Hydrogenated (68037-01-4), Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified (72623-87-1), Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0), Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9), Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0), Paraffin oils (petroleum), catalytic dewaxed heavy, Baseoil - unspecified (64742-70-7), C14-16-18 Alkyl phenol

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Component	
Substance(s) not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0), Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9), Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0), Paraffin oils (petroleum), catalytic dewaxed heavy, Baseoil - unspecified (64742-70-7), C14-16-18 Alkyl phenol

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

Comments : Composition/ Information on ingredients:  
Polymers  
Mixture of hydrocarbons  
Additives

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (see note [*], see note [**]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627-25	50 – 70	Asp. Tox. 1, H304
1-Decene, Homopolymer, Hydrogenated (see note [*], see note [**])	CAS-No.: 68037-01-4 EC-No.: 500-183-1 REACH-no: 01-2119486452-34	20 – 30	Not classified

# Eni i-Sint tech VK 0W-20

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified (see note [*], see note [**]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	CAS-No.: 72623-87-1 EC-No.: 276-738-4 EC Index-No.: 649-483-00-5 REACH-no: 01-2119474889-13	2 – 2.5	Asp. Tox. 1, H304
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (see note [*], see note [**]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	CAS-No.: 72623-86-0 EC-No.: 276-737-9 EC Index-No.: 649-482-00-X REACH-no: 01-2119474878-16	2 – 2.5	Asp. Tox. 1, H304
Distillates (petroleum), solvent-dewaxed light paraffinic (see note [*], see note [**]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	CAS-No.: 64742-56-9 EC-No.: 265-159-2 EC Index-No.: 649-469-00-9 REACH-no: 01-2119480132-48	1 – 1.5	Asp. Tox. 1, H304
Distillates (petroleum), solvent-dewaxed heavy paraffinic (see note [*], see note [**]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	CAS-No.: 64742-65-0 EC-No.: 265-169-7 EC Index-No.: 649-474-00-6 REACH-no: 01-2119471299-27	1 – 1.5	Asp. Tox. 1, H304
Paraffin oils (petroleum), catalytic dewaxed heavy, Baseoil - unspecified (see note [*], see note [**])	CAS-No.: 64742-70-7 EC-No.: 265-174-4 EC Index-No.: 649-477-00-2 REACH-no: 01-2119487080-42	1 – 1.5	Asp. Tox. 1, H304
C14-16-18 Alkyl phenol	EC-No.: 931-468-2 REACH-no: NA	0.1 – 0.25	Skin Sens. 1B, H317 STOT RE 2, H373

### Comments

: Note [\*]:

this product has a value of DMSO extract < 3 % wt, according to IP 346. According to the criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product must be regarded as non carcinogenic.

Note [\*\*]:

substance with occupational exposure limits for some EU countries affecting the category of mineral oils (finely refined mineral base oil mists; see section 8.1)

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### First-aid measures after inhalation

: In case of disturbances owing to inhalation of vapours or mists, remove the victim from exposure; keep at rest; if necessary, seek medical attention. See also section 4.3.

#### First-aid measures after skin contact

: After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap. Take off contaminated clothing and wash it before reuse. If inflammation or irritation persists, seek medical advice. In case of burns, cool affected part with cold running water for at least 10 min. Cover with gauze or clean cloth. Ask for medical assistance or bring to a hospital. Do not apply salves or other substances, unless by doctor's advice. Body hypothermia must be avoided. Do not put ice on the burn.

# Eni i-Sint tech VK 0W-20

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

First-aid measures after eye contact	: Rinse eyes thoroughly for at least 15 minutes. Keep eyelids well apart. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation, blurred vision or swelling occurs and persists, obtain medical advice from a specialist. In case of burns, cool affected part with cold running water for at least 10 min. Cover with gauze or clean cloth. Ask for medical assistance or bring to a hospital. Do not apply salves or other substances, unless by doctor's advice.
First-aid measures after ingestion	: Do not induce vomiting. If the person is conscious, rinse mouth with water without swallowing. Keep at rest. Call for medical assistance or bring to an hospital. If the casualty is unconscious, place in the recovery position. In case of spontaneous vomiting, keep head low, to avoid the risk of aspiration into the lungs. Do not give anything by mouth to an unconscious person.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: This product has a low vapour pressure, and in normal conditions at ambient temperature the concentration in the air is negligible. A significant concentration may build up only if the product is used at high temperature, or in case of sprays and mists. In these cases overexposure to vapours may cause irritation to airways, nausea and dizziness.
Symptoms/effects after skin contact	: Prolonged and repeated skin contact may cause reddening, irritation and dermatitis. May cause an allergic skin reaction. Contact with hot product may cause thermal burns.
Symptoms/effects after eye contact	: Contact with eyes may cause temporary reddening and irritation. Contact with hot product or vapours may cause burns.
Symptoms/effects after ingestion	: Accidental ingestion of small quantities of the product may cause nausea, discomfort and gastric disturbances.
Symptoms/effects upon intravenous administration	: No information available.
Chronic symptoms	: None to be reported, according to the present classification criteria.

### 4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical attention if casualty has an altered state of consciousness or if symptoms do not resolve. Seek medical attention in all cases of serious burns.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Small-size fires: carbon dioxide, dry chemicals, foam, sand or earth. Large fires: foam or water fog (mist). These means should be used by trained personnel only. Other extinguishing gases (according to regulations).
Unsuitable extinguishing media	: Do not use water jets. They could cause splattering, and spread the fire. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels.
Explosion hazard	: In case of losses from pressurized circuits, the sprays may form mists. Take into account that in this case the lower explosion limit for mists is about 45 g/m <sup>3</sup> air.
Hazardous decomposition products in case of fire	: Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases. Oxygenated compounds (aldehydes, etc.). POx. ZnOx.

### 5.3. Advice for firefighters

Firefighting instructions	: Shut off source of product, if possible. Spilled product which is not burning should be covered with sand or foam. Move undamaged containers from immediate hazard area if it can be done safely. Use water sprays to cool containers and surfaces exposed to the flames. If the fire cannot be controlled, evacuate area.
Special protective equipment for firefighters	: Wear personal protection equipment. (see chapter 8). EN 443. EN 469. EN 659. In case of a large fire or in confined or poorly ventilated spaces, wear full fire resistant protective clothing and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
Other information	: In case of fire, do not discharge residual product, waste materials and runoff water: collect separately and use a proper treatment.

# Eni i-Sint tech VK 0W-20

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop or contain leak at the source, if safe to do so. Eliminate all ignition sources if safe to do so (e.g. electricity, sparks, fires, flares). Avoid accidental sprays on hot surfaces or electrical contacts. Avoid direct contact with released material. Keep upwind. Spill area may be slippery.

##### For non-emergency personnel

Protective equipment : See Section 8.  
Emergency procedures : Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency.

##### For emergency responders

Protective equipment : Small spillages: normal antistatic working clothes are usually adequate. Large spillages: full body suit of chemically resistant and antistatic material. If necessary heat resistant and insulated. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Gloves made of PVA are not water-resistant, and are not suitable for emergency use. If contact with hot product is possible or anticipated, gloves should be heat-resistant and thermally insulated. Antistatic non-skid safety shoes or boots, chemical resistant, if necessary heat resistant and insulated. Work helmet. Goggles and /or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory protection: a half or full-face respirator with filter(s) for organic vapours (AX), or a Self-contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.  
Emergency procedures : If required, notify relevant authorities according to all applicable regulations.

#### 6.2. Environmental precautions

Do not let the product accumulate in confined or underground spaces. Do not let the product flow into sewers or water courses, or in any way contaminate the environment. In case of contamination of environment compartments (soil, subsoil, surface or underground waters), remove contaminated soil when possible, and in any case treat all involved compartments in accordance with local regulations. The site should have a spill plan to ensure that adequate safeguards are in place to minimize the impact of episodic releases.

#### 6.3. Methods and material for containment and cleaning up

For containment : Contain spilled liquid with sand, earth or other suitable absorbents (non-flammable). Recover free liquid and waste materials in suitable waterproof and oil-resistant containers. Clean contaminated area. Dispose of according to local regulations. If in water: Confine the spillage. Remove from surface by skimming or suitable floating absorbents. Collect recovered product and other waste materials in suitable waterproof, oil resistant containers. Recover or dispose of according to local regulations. Do not use solvents or dispersants, unless specifically advised by an expert, and, if required, approved by local authorities.  
Other information : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air/water temperature, wave/current direction and speed) may significantly influence the choice of appropriate actions. Local regulations may also prescribe or limit actions to be taken. For this reason, local experts should be consulted when necessary.

#### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

# Eni i-Sint tech VK 0W-20

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : This material is combustible, but will not ignite readily. Provide adequate ventilation. Use adequate personal protective equipment as needed. Due to the extremely slippery nature of this material, more care than usual must be exercised in material handling practices to keep off all walking surfaces. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Avoid release to the environment. Emptied containers can contain combustible product residues. Do not cut, weld, drill, burn or incinerate empty containers or drums, unless they have been drained and cleaned. Before entering storage tanks and commencing any operation in a confined area (e.g. tunnels), carry out an adequate clean-up, and check the atmosphere for oxygen content and flammability. See also Section 16, "Other information".
- Hygiene measures : Ensure that proper housekeeping measures are in place. Avoid contact with skin. Do not breathe fume/ mist/ vapours. Do not ingest. Do not smoke. Do not eat and do not drink during use. Do not clean hands with dirty or oil-soaked rags. Do not re-use clothes, if they are still contaminated. Keep away from food and beverages. Take off immediately all contaminated clothing and wash it before reuse. Contaminated materials should not be allowed to accumulate in the workplaces and should never be kept inside the pockets. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in dry, well-ventilated area. Keep away from open flames, hot surfaces and sources of ignition. Do not smoke.
- Incompatible products : Keep away from strong oxidizers.
- Storage area : Storage area layout, tank design, equipment and operating procedures must comply with the relevant European, national or local legislation. Storage installations/areas should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations.
- Packages and containers: : If the product is supplied in containers: Keep containers tightly closed and properly labelled. Keep only in the original container or in a suitable container for this kind of product.
- Packaging materials : For containers, or container linings use materials specifically approved for use with this product. Compatibility should be checked with the manufacturer, according to the specific use conditions.

#### Germany

- Storage class (LGK, TRGS 510) : LGK 10 - Combustible liquids

#### Switzerland

- Storage class (LK) : LK 10/12 - Liquids

#### 7.3. Specific end use(s)

No information available.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### National occupational exposure and biological limit values

**Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)**

##### Austria - Occupational Exposure Limits

MAK (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
---------------	---

# Eni i-Sint tech VK 0W-20

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

**Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)**

### Belgium - Occupational Exposure Limits

OEL TWA	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
---------	---

### Denmark - Occupational Exposure Limits

OEL TWA	1 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
OEL STEL	2 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)

### Hungary - Occupational Exposure Limits

AK (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
--------------	---

### Netherlands - Occupational Exposure Limits

MAC TGG 8h (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
---------------------------------	---

### Spain - Occupational Exposure Limits

VLA-ED (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
VLA-EC (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)

### Sweden - Occupational Exposure Limits

NGV (OEL TWA)	1 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
KGV (OEL STEL)	3 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)

### United Kingdom - Occupational Exposure Limits

WEL TWA (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
WEL STEL (OEL STEL)	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)

### USA - ACGIH - Occupational Exposure Limits

ACGIH® TLV® TWA	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
ACGIH® TLV® STEL	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)

### Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified (72623-87-1)

### Austria - Occupational Exposure Limits

MAK (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
---------------	---

### Belgium - Occupational Exposure Limits

OEL TWA	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
---------	---

### Denmark - Occupational Exposure Limits

OEL TWA	1 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
OEL STEL	2 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)

### Hungary - Occupational Exposure Limits

AK (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
--------------	---

### Netherlands - Occupational Exposure Limits

MAC TGG 8h (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
---------------------------------	---

### Spain - Occupational Exposure Limits

VLA-ED (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
VLA-EC (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)



# Eni i-Sint tech VK 0W-20

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified (72623-87-1)	
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	1 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
KGV (OEL STEL)	3 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
WEL STEL (OEL STEL)	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
USA - ACGIH - Occupational Exposure Limits	
ACGIH® TLV® TWA	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
ACGIH® TLV® STEL	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)	
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Belgium - Occupational Exposure Limits	
OEL TWA	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Denmark - Occupational Exposure Limits	
OEL TWA	1 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
OEL STEL	2 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Netherlands - Occupational Exposure Limits	
MAC TGG 8h (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
VLA-EC (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	1 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
KGV (OEL STEL)	3 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
WEL STEL (OEL STEL)	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
USA - ACGIH - Occupational Exposure Limits	
ACGIH® TLV® TWA	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
ACGIH® TLV® STEL	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)	
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Belgium - Occupational Exposure Limits	
OEL TWA	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)



# Eni i-Sint tech VK 0W-20

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)	
<b>Denmark - Occupational Exposure Limits</b>	
OEL TWA	1 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
OEL STEL	2 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
<b>Hungary - Occupational Exposure Limits</b>	
AK (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
<b>Netherlands - Occupational Exposure Limits</b>	
MAC TGG 8h (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
<b>Spain - Occupational Exposure Limits</b>	
VLA-ED (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
VLA-EC (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
<b>Sweden - Occupational Exposure Limits</b>	
NGV (OEL TWA)	1 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
KGV (OEL STEL)	3 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
<b>United Kingdom - Occupational Exposure Limits</b>	
WEL TWA (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
WEL STEL (OEL STEL)	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH® TLV® TWA	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
ACGIH® TLV® STEL	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
<b>Austria - Occupational Exposure Limits</b>	
MAK (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
<b>Belgium - Occupational Exposure Limits</b>	
OEL TWA	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
<b>Denmark - Occupational Exposure Limits</b>	
OEL TWA	1 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
OEL STEL	2 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
<b>Hungary - Occupational Exposure Limits</b>	
AK (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
<b>Netherlands - Occupational Exposure Limits</b>	
MAC TGG 8h (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
<b>Spain - Occupational Exposure Limits</b>	
VLA-ED (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
VLA-EC (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
<b>Sweden - Occupational Exposure Limits</b>	
NGV (OEL TWA)	1 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
KGV (OEL STEL)	3 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
<b>United Kingdom - Occupational Exposure Limits</b>	
WEL TWA (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)

# Eni i-Sint tech VK 0W-20

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

WEL STEL (OEL STEL)	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
---------------------	--

### USA - ACGIH - Occupational Exposure Limits

ACGIH® TLV® TWA	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
ACGIH® TLV® STEL	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)

### Recommended monitoring procedures

#### Monitoring methods

Monitoring methods	Monitoring procedures should be chosen according to the indications set by national authorities or labour contracts. Refer to relevant legislation and in any case to the good practice of industrial hygiene.
--------------------	--

### DNEL and PNEC

#### Eni i-Sint tech VK 0W-20

##### DNEL/DMEL (additional information)

Additional information	Not applicable
------------------------	----------------

##### PNEC (additional information)

Additional information	Not applicable
------------------------	----------------

#### 1-Decene, Homopolymer, Hydrogenated (68037-01-4)

##### DNEL/DMEL (Workers)

Acute - local effects, inhalation	= 60 mg/m <sup>3</sup> (DNEL, 15 min)
-----------------------------------	---------------------------------------

##### DNEL/DMEL (General population)

Acute - local effects, inhalation	= 50 mg/m <sup>3</sup> (DNEL, 15 min)
-----------------------------------	---------------------------------------

#### Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)

##### DNEL/DMEL (Workers)

Long-term - systemic effects, dermal	1 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	2.73 mg/m <sup>3</sup>
Long-term - local effects, inhalation	5.4 mg/m <sup>3</sup>

##### DNEL/DMEL (General population)

Long-term - systemic effects, dermal	0.74 mg/kg bodyweight/day
Long-term - local effects, inhalation	1.2 mg/m <sup>3</sup>

#### Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)

##### DNEL/DMEL (Workers)

Long-term - systemic effects, dermal	0.97 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	2.73 mg/m <sup>3</sup>
Long-term - local effects, inhalation	5.58 mg/m <sup>3</sup>

##### DNEL/DMEL (General population)

Long-term - systemic effects, oral	0.74 mg/kg bodyweight/day
Long-term - local effects, inhalation	1.19 mg/m <sup>3</sup>

##### PNEC (Oral)

PNEC oral (secondary poisoning)	9.33 mg/kg food
---------------------------------	-----------------

# Eni i-Sint tech VK 0W-20

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)	
<b>DNEL/DMEL (Workers)</b>	
Long-term - systemic effects, dermal	0.97 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	2.73 mg/m³
Long-term - local effects, inhalation	5.4 mg/m³
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	0.74 mg/kg bodyweight/day
Long-term - local effects, inhalation	1.2 mg/m³
<b>PNEC (Oral)</b>	
PNEC oral (secondary poisoning)	9.33 mg/kg food
Paraffin oils (petroleum), catalytic dewaxed heavy, Baseoil - unspecified (64742-70-7)	
<b>DNEL/DMEL (Workers)</b>	
Long-term - systemic effects, dermal	0.97 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	2.73 mg/m³
Long-term - local effects, inhalation	5.58 mg/m³
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, oral	0.74 mg/kg bodyweight/day
Long-term - local effects, inhalation	1.19 mg/m³
<b>PNEC (Oral)</b>	
PNEC oral (secondary poisoning)	9.33 mg/kg food
C14-16-18 Alkyl phenol	
<b>DNEL/DMEL (Workers)</b>	
Long-term - systemic effects, dermal	0.3 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	1.17 mg/m³
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	100 µg/l
PNEC aqua (marine water)	10 µg/l
PNEC aqua (intermittent, freshwater)	1 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	4266.16 mg/kg dwt
PNEC sediment (marine water)	426.62 mg/kg dwt
<b>PNEC (Soil)</b>	
PNEC soil	852.58 mg/kg dwt
<b>PNEC (Oral)</b>	
PNEC oral (secondary poisoning)	3.3 mg/kg food
<b>PNEC (STP)</b>	
PNEC sewage treatment plant	100 mg/l

# Eni i-Sint tech VK 0W-20

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Note	: The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a governmental regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH.
------	--

## 8.2. Exposure controls

### Appropriate engineering controls

#### Appropriate engineering controls:

Before entering storage tanks and commencing any operation in a confined area (e.g. tunnels), carry out an adequate clean-up, and check the atmosphere for oxygen content and flammability. See also Section 16, "Other information".

### Personal protective equipment

#### Personal protective equipment (for industrial or professional use):

Gloves. Protective clothing. Safety glasses. Safety shoes or boots. Wear a face shield.

#### Personal protective equipment symbol(s):



### Eye and face protection

#### Eye protection:

When there is a risk of contact with the eyes, use safety goggles or other means of protection (face shield). If necessary, refer to national standards or to the EN 166 standard.

### Skin protection

#### Skin and body protection:

Long-sleeved overalls. If necessary, refer to the EN 340 and related standards, for definition of characteristics and performance according to the risk rating of the area. Antistatic non-skid safety shoes or boots, chemical resistant, if necessary heat resistant and insulated.

#### Hand protection:

Protective gloves. Adequate materials: nitrile (NBR) or PVC with a protection index > 5 (permeation time > 240 mins). Use gloves respecting all the conditions and within the limits set by the manufacturer. Replace gloves immediately in case of cuts, holes or other signs of damages or degradation. If necessary, refer to the EN 374 standard. Personal hygiene is a key element for an effective hand care. Gloves must be worn only with clean hands. After wearing gloves, hands must be carefully washed and dried.

### Respiratory protection

#### Respiratory protection:

Independently from other possible actions (technical modifications, operating procedures, and other means to limit the exposure of workers), personal protection equipment can be used according to necessity. Open or well ventilated spaces: in presence of mists and if the product is handled without adequate containment means: use full or half-face masks with filter for mists/aerosols. (EN 136/140/145). Combination filter device (DIN EN 141). Closed or confined areas (e.g. tank interiors): the use of protection measures for airways (masks or self-contained breathing apparatus), must be assessed according to the specific activity, as well as level and duration of predicted exposure.

### Thermal hazards

#### Thermal hazard protection:

If contact with hot product is possible or anticipated, gloves should be heat-resistant and thermally insulated.

### Environmental exposure controls

#### Environmental exposure controls:

Do not discharge the product into the environment. Storage areas/installations should be designed with adequate bunds so as to prevent ground and water pollution in case of leaks or spills. Prevent discharge of undissolved substance to or recover from onsite wastewater. Onsite wastewater treatment required. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

#### Consumer exposure controls:

No special requirements.

# Eni i-Sint tech VK 0W-20

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Yellow-brown.
Appearance	: Liquid, bright & clear.
Odour	: Slight odour of petroleum.
Odour threshold	: There are no data available on the preparation/mixture itself.
Melting point	: Not determined
Freezing point	: Not determined
Boiling point	: Not determined
Flammability	: Not flammable
Lower explosion limit	: Not determined
Upper explosion limit	: Not determined
Flash point	: 208 °C (closed cup)
Auto-ignition temperature	: Not determined
Decomposition temperature	: Not determined
pH	: Not applicable
Viscosity, kinematic	: 40.9 mm <sup>2</sup> /s (40°C, ASTM D 445)
Solubility	: Water: Immiscible and insoluble
Log Kow	: Not applicable for mixtures
Log Pow	: Not applicable for mixtures
Vapour pressure	: Not determined
Vapour pressure at 50°C	: Not determined
Critical pressure	: Not applicable for mixtures
Density	: 0.843 g/cm <sup>3</sup> ASTM D 4052
Relative density	: Not determined
Relative vapour density at 20°C	: Not determined
Particle characteristics	: Not applicable

#### 9.2. Other information

##### Information with regard to physical hazard classes

Critical temperature	: Not applicable for mixtures
----------------------	-------------------------------

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

This mixture does not offer any further hazard for reactivity, except what is reported in the following paragraphs.

#### 10.2. Chemical stability

Stable product, according to its intrinsic properties.

#### 10.3. Possibility of hazardous reactions

None (in normal conditions of storage and handling). Contact with strong oxidizers (peroxides, chromates, etc.) or alkali metals may cause a fire hazard.

#### 10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

#### 10.5. Incompatible materials

Strong oxidizing agents. Strong acids.

#### 10.6. Hazardous decomposition products

Thermal decomposition generates : Toxic fumes. Sulphur oxides. A potential risk may arise from the release of hydrogen sulfide, when the product is stored or handled at high temperature. Nitrogen oxides (NOx). Phosphorous oxide.

# Eni i-Sint tech VK 0W-20

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)
Additional information	: (according to composition)

**Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)**

LD50 oral rat	> 5000 mg/kg (OECD 401)
LD50 dermal rat	> 5000 mg/kg (OECD 402)
LC50 Inhalation - Rat	> 5 mg/l/4h (OECD 403)

#### **1-Decene, Homopolymer, Hydrogenated (68037-01-4)**

LD50 oral rat	≥ 5000 mg/kg
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	≥ 5.2 mg/l/4h (Inhalable aerosol)

#### **Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified (72623-87-1)**

LD50 oral rat	> 5000 mg/kg (OECD 401)
LD50 dermal rat	> 5000 mg/kg (OECD 402)
LC50 Inhalation - Rat	> 5 mg/l/4h (OECD 403)

#### **Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)**

LD50 oral rat	> 5000 mg/kg (OECD 401)
LD50 dermal rabbit	> 2000 mg/kg bodyweight (OECD 402)
LC50 Inhalation - Rat	> 5.53 mg/l/4h (OECD 403)

#### **Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)**

LD50 oral rat	> 5000 mg/kg (OECD 401)
LD50 dermal rat	> 5000 mg/kg (OECD 402)
LC50 Inhalation - Rat	> 5 mg/l/4h (OECD 403)

#### **Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)**

LD50 oral rat	> 5000 mg/kg (OECD 401)
LD50 dermal rat	> 5000 mg/kg (OECD 402)
LC50 Inhalation - Rat	> 5 mg/l/4h (OECD 403)

#### **Paraffin oils (petroleum), catalytic dewaxed heavy, Baseoil - unspecified (64742-70-7)**

LD50 oral rat	5000 mg/kg bodyweight
LD50 dermal rat	2000 – 5000 mg/kg bodyweight
LC50 Inhalation - Rat	2.18 – 5.53 mg/l/4h

Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met) pH: Not applicable
Additional information	: (according to composition)

# Eni i-Sint tech VK 0W-20

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

**Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)**

pH	Not applicable
----	----------------

**Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified (72623-87-1)**

pH	Not applicable
----	----------------

**Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)**

pH	Not applicable
----	----------------

**Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)**

pH	Not applicable
----	----------------

**Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)**

pH	Not applicable
----	----------------

Serious eye damage/irritation : Not classified (Based on available data, the classification criteria are not met)

pH: Not applicable

Additional information : (according to composition)

**Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)**

pH	Not applicable
----	----------------

**Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified (72623-87-1)**

pH	Not applicable
----	----------------

**Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)**

pH	Not applicable
----	----------------

**Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)**

pH	Not applicable
----	----------------

**Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)**

pH	Not applicable
----	----------------

Respiratory or skin sensitisation : Not classified (Based on available data, the classification criteria are not met)

Additional information : (according to composition)

Germ cell mutagenicity : Not classified (Based on available data, the classification criteria are not met)

Additional information : (according to composition)

Carcinogenicity : Not classified (Based on available data, the classification criteria are not met)

Additional information : (according to composition)

All the mineral base oils contained in this product have a value < 3 % wt of DMSO extract, according to IP 346 (Nota L - Annex VI Reg (CE) 1272/2008, # 1.1.3)

Reproductive toxicity : Not classified (Based on available data, the classification criteria are not met)

Additional information : (according to composition)

STOT-single exposure : Not classified (Based on available data, the classification criteria are not met)

Additional information : (according to composition)

STOT-repeated exposure : Not classified (Based on available data, the classification criteria are not met)

Additional information : (according to composition)



# Eni i-Sint tech VK 0W-20

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

**Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)**

LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)
----------------------------	--

### 1-Decene, Homopolymer, Hydrogenated (68037-01-4)

NOAEL (oral, rat, 90 days)	1000 – 6771 mg/kg bodyweight/day (Test OECD 408)
----------------------------	--

### Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified (72623-87-1)

LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)
----------------------------	--

### Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)

LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
LOAEL (dermal, rat/rabbit, 90 days)	100 mg/kg bodyweight/day (mouse, Chasey, K.L. and McKee, R.H. 1993 - OECD 453)
NOAEL (dermal, rat/rabbit, 90 days)	1000 – 2000 mg/kg bodyweight/day (API 1986, Mobil Environmental and Health Science Laboratory 1983 - OECD 410)
NOAEC (inhalation, rat, vapour, 90 days)	220 – 1500 mg/m <sup>3</sup> (Exxon Biomedical Sciences, Inc. 1991, Dalbey W, Osimitz T, Kommineni C, Roy T, Feuston M and Yang J 1991 - OECD 412)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

### Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)

LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)
----------------------------	--

### Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)
----------------------------	--

### Paraffin oils (petroleum), catalytic dewaxed heavy, Baseoil - unspecified (64742-70-7)

LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day
NOAEL (dermal, rat/rabbit, 90 days)	30 – 2000 mg/kg bodyweight/day
NOAEC (inhalation, rat, vapour, 90 days)	980 mg/m <sup>3</sup>

### C14-16-18 Alkyl phenol

NOAEL (oral, rat, 90 days)	30 – 100 mg/kg bodyweight/day
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)

Additional information : (according to composition)  
Viscosity, kinematic: > 20,5 mm<sup>2</sup>/s (40 °C) (ASTM D 445)

### Eni i-Sint tech VK 0W-20

Viscosity, kinematic	40.9 mm <sup>2</sup> /s (40°C, ASTM D 445)
----------------------	--

**Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)**

Viscosity, kinematic	27.2 – 29.2 mm <sup>2</sup> /s (40 °C) (ASTM D 445)
----------------------	---

### Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified (72623-87-1)

Viscosity, kinematic	12 mm <sup>2</sup> /s (40 °C) (ASTM D 445)
----------------------	--

# Eni i-Sint tech VK 0W-20

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)

Viscosity, kinematic	7.5 mm <sup>2</sup> /s (40 °C)
----------------------	--------------------------------

### Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)

Viscosity, kinematic	15 – 16.5 mm <sup>2</sup> /s (40 °C) (ASTM D 445)
----------------------	---

### Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

Viscosity, kinematic	< 20.5 mm <sup>2</sup> /s (40 °C) (ASTM D 445)
----------------------	--

## 11.2. Information on other hazards

### Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

### Other information

Potential adverse human health effects and symptoms : Prolonged and repeated skin contact may cause reddening, irritation and dermatitis, May cause an allergic skin reaction, Contact with eyes may cause temporary reddening and irritation, Avoid all eye and skin contact and do not breathe vapour and mist

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment. An uncontrolled release to the environment may nevertheless produce a contamination of different environmental compartments (air, soil, underground, surface water bodies, aquifers). Handle according to general working hygiene practices to avoid pollution and release into the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified (Based on available data, the classification criteria are not met)

Hazardous to the aquatic environment, long-term (chronic) : Not classified (Based on available data, the classification criteria are not met)

**Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)**

LC50 fish 1	> 100 mg/l (LL 50)
-------------	--------------------

EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)
----------------	-----------------------------------

### 1-Decene, Homopolymer, Hydrogenated (68037-01-4)

LC50 fish 1	≥ 1000 mg/l Oncorhynchus mykiss, Test EPA-660/3-75-009)
-------------	---

EC50 Daphnia 1	≥ 1000 mg/l (Test OECD 202)
----------------	-----------------------------

EC50 72h - Algae [1]	≥ 1000 mg/l (Test OECD 201)
----------------------	-----------------------------

ErC50 (algae)	≥ 1000 mg/l (72 h, Scenedesmus capricornutum)
---------------	---

NOEC (chronic)	125 mg/l (21 d, Daphnia magna)
----------------	--------------------------------

### Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified (72623-87-1)

LC50 fish 1	> 100 mg/l (LL 50)
-------------	--------------------

EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)
----------------	-----------------------------------

# Eni i-Sint tech VK 0W-20

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

<b>Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)</b>	
LC50 fish 1	> 100 mg/l (LL 50, Exxon 1995 - OECD 203)
EC50 Daphnia 1	> 10000 mg/l (WAF, 48 h, Shell 1988 - OECD 202)
NOEC chronic fish	≥ 1000 mg/l (Oncorhynchus mykiss, NOELR, 14d - QSAR, Redman, A. et al. 2010)
NOEC chronic crustacea	≥ 1000 mg/l (21d, OECD 211 - Shell 1994)
<b>Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)</b>	
LC50 fish 1	> 100 mg/l (LL 50)
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)
<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)</b>	
LC50 fish 1	> 100 mg/l (LL 50)
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)
<b>Paraffin oils (petroleum), catalytic dewaxed heavy, Baseoil - unspecified (64742-70-7)</b>	
LC50 fish 1	100 mg/l (LL50)
EC50 Daphnia 1	10 g/l (EL50)
NOEC chronic fish	1 g/l (NOELR, 14d)
<b>C14-16-18 Alkyl phenol</b>	
EC50 Daphnia 1	100 mg/l
<b>12.2. Persistence and degradability</b>	
<b>Eni i-Sint tech VK 0W-20</b>	
Persistence and degradability	No data available.
<b>Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)</b>	
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.
<b>1-Decene, Homopolymer, Hydrogenated (68037-01-4)</b>	
Persistence and degradability	Readily biodegradable.
Biodegradation	≥ 47.7 % (28d)
<b>Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified (72623-87-1)</b>	
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.
<b>Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)</b>	
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.

# Eni i-Sint tech VK 0W-20

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)

Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.
-------------------------------	--

### Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.
-------------------------------	--

### Paraffin oils (petroleum), catalytic dewaxed heavy, Baseoil - unspecified (64742-70-7)

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

### C14-16-18 Alkyl phenol

Persistence and degradability	Rapidly degradable
Biodegradation	24 % (Zahn-Wellens, 10-20 %)

## 12.3. Bioaccumulative potential

### Eni i-Sint tech VK 0W-20

Log Pow	Not applicable for mixtures
Log Kow	Not applicable for mixtures
Bioaccumulative potential	Not established.

### Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified (72623-87-1)

Log Kow	> 6
---------	-----

### Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)

Log Kow	> 6
Bioaccumulative potential	The test methods for this endpoint are not applicable to UVCB substances.

### C14-16-18 Alkyl phenol

Log Kow	4.5 (0.1 d, 10-20 %)
---------	----------------------

## 12.4. Mobility in soil

### Eni i-Sint tech VK 0W-20

Ecology - soil	No data available.
----------------	--------------------

### Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)

Ecology - soil	The test methods for this endpoint are not applicable to UVCB substances.
----------------	---

## 12.5. Results of PBT and vPvB assessment

### Eni i-Sint tech VK 0W-20

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII	
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
Results of PBT-vPvB assessment	The components in this formulation do not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)

# Eni i-Sint tech VK 0W-20

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Component	
Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	1-Decene, Homopolymer, Hydrogenated (68037-01-4), Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified (72623-87-1), Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0), Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9), Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0), Paraffin oils (petroleum), catalytic dewaxed heavy, Baseoil - unspecified (64742-70-7), C14-16-18 Alkyl phenol
Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	1-Decene, Homopolymer, Hydrogenated (68037-01-4), Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified (72623-87-1), Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0), Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9), Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0), Paraffin oils (petroleum), catalytic dewaxed heavy, Baseoil - unspecified (64742-70-7), C14-16-18 Alkyl phenol

### 12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

### 12.7. Other adverse effects

Other adverse effects : None.

**Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)**

Other information	This product has no specific properties for inhibition of bacterial activity. In any case, wastewater containing this product should be treated in plants that are suited for the specific purpose.
-------------------	---

#### Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified (72623-87-1)

Other information	This product has no specific properties for inhibition of bacterial activity. In any case, wastewater containing this product should be treated in plants that are suited for the specific purpose.
-------------------	---

#### Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)

Other information	This product has no specific properties for inhibition of bacterial activity. In any case, wastewater containing this product should be treated in plants that are suited for the specific purpose.
-------------------	---

#### Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)

Other information	This product has no specific properties for inhibition of bacterial activity. In any case, wastewater containing this product should be treated in plants that are suited for the specific purpose.
-------------------	---

#### Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

Other information	This product has no specific properties for inhibition of bacterial activity. In any case, wastewater containing this product should be treated in plants that are suited for the specific purpose.
-------------------	---

# Eni i-Sint tech VK 0W-20

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste treatment methods	: Do not dispose of the product, either new or used, by dumping on the ground, or discharging into sewers, tunnels, lakes or water courses. Deliver to a qualified official collector. Dispose of empty containers and wastes safely.
Sewage disposal recommendations	: Dispose of in a safe manner in accordance with local/national regulations. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.
Additional information	: Empty containers may contain combustible product residues. Emptied containers can contain combustible product residues. Do not cut, weld, drill, burn or incinerate empty containers or drums, unless they have been drained and cleaned.
EURAL code (EWC)	: 13 02 06* - Synthetic engine, gear and lubricating oils 15 01 10* - packaging containing residues of or contaminated by dangerous substances

### SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
Not regulated for transport				
<b>14.2. UN proper shipping name</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.3. Transport hazard class(es)</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.4. Packing group</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.5. Environmental hazards</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
None.				

#### 14.6. Special precautions for user

##### Overland transport

Not regulated

##### Transport by sea

Not regulated

##### Air transport

Not regulated

##### Inland waterway transport

Not regulated

##### Rail transport

Not regulated

#### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

# Eni i-Sint tech VK 0W-20

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU-Regulations

##### REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(b)	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil—unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] ; Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified ; Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based ; Distillates (petroleum), solvent-dewaxed light paraffinic ; Distillates (petroleum), solvent-dewaxed heavy paraffinic ; Paraffin oils (petroleum), catalytic dewaxed heavy, Baseoil - unspecified ; C14-16-18 Alkyl phenol	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10

##### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

##### REACH Candidate List (SVHC)

No ingredients are included in the REACH Candidate list (> 0,1 % m/m).

##### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

##### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

##### Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)



# Eni i-Sint tech VK 0W-20

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

### Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

### Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

### National regulations

#### France

Maladies professionnelles (F)	
Code	Description
RG 36	Diseases caused by oils and fats of mineral or synthetic origin

#### Germany

Employment restrictions	: Employment prohibitions or restrictions on the protection of young people at work according to § 22 JArbSchG in the case of formation of hazardous substances have to be observed.
National Rules and Recommendations	: TRGS 400: Hazard assessment for activities involving Hazardous Substances. TRGS 401: Risks resulting from skin contact - identification, assessment, measures. TRGS 402: Identification and Assessment of the Risks from Activities involving Hazardous Substances: Inhalation Exposure. TRGS 800: Fire protection measures. TRGS 900: Occupational Exposure Limits. TRGS 555: Working instruction and information for workers.
VbF class (D)	: Not applicable.
Water hazard class (WGK) (D)	: WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1).
WGK remark	: Classification based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS).
Major Accidents Ordinance (12. BImSchV)	: Is not subject to the Major Accidents Ordinance (12. BImSchV)

#### Netherlands

Saneringsinspanningen	: C - Minimize discharge
SZW-lijst van kankerverwekkende stoffen	: None of the components are listed
SZW-lijst van mutagene stoffen	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling	: None of the components are listed

#### Denmark

Danish National Regulations	: Young people under 18 years are not allowed to use the product Pregnant/breastfeeding women working with the product must not be in direct contact with it
-----------------------------	---

# Eni i-Sint tech VK 0W-20

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### Poland

Polish National Regulations

: Act of 25 February 2011 on chemical substances and their mixtures (J. o L. No. 63, item 322 as amended; consolidated text J. o L. 2019, item 1225).  
Act of 14 December 2012 on waste (J. o L. 2013, item 322 as amended; consolidated text J. o L. 2020, item 797).  
The announcement of Marshal of the Sejm of the Republic of Poland dated 19 October 2016 concerning the consolidated text announcement of the decree on the management of packaging and packaging waste (J. o L. 2016, item 1863 as amended).  
Decree of the Minister of Environment of 14 December 2014 on the catalogue of waste (J. o L. 2014, item 1923).  
Act of 19 August 2011 on the Carriage of Dangerous Goods (J. o L. 2011 No. 227, item 1367 as amended; consolidated text J. o L. 2020, item 154).  
Regulation of the Minister of Family, Labour and Social Policy of 12 June 2018 on the highest permissible concentration and intensity of noxious agents for health at work environment (J. o L. item 1286 as amended).  
The announcement of Minister of Health dated 9 September 2016 concerning the consolidated text announcement of the decree of the Minister of Health of 30 December 2004 on health and safety at work related to exposure to chemical agents at work (J. o L. of 16 September 2016, item 1488).  
Regulation of the Minister of Health of 2 February 2011 on tests and measurements of the noxious agents for health at work environment (J. o L. No. 33, item 166 as amended).  
Regulation of the Minister of Environment of 9 December 2003 on particularly hazardous substances to the environment (J. o L. No. 217, item 2141).  
ADR Agreement: Government Statement of 13 March 2023 on the entry into force of amendments to Annexes A and B to the Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), signed in Geneva on 30 September 1957 (J. o. L. 2023, item 891)

### 15.2. Chemical safety assessment

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

No chemical safety assessment has been carried out

**A chemical safety assessment has been carried out for the following components of this mixture::**

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.]

1-Decene, Homopolymer, Hydrogenated

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based

Distillates (petroleum), solvent-dewaxed light paraffinic

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Paraffin oils (petroleum), catalytic dewaxed heavy, Baseoil - unspecified

C14-16-18 Alkyl phenol

### SECTION 16: Other information

Indication of changes		
Section	Changed item	Comments
2.3	Other hazards not contributing to the classification	<b>Removed</b>
3	Composition/information on ingredients	<b>Modified</b>
9	Viscosity, kinematic	<b>Modified</b>
9	Boiling point	<b>Modified</b>
9	Molecular mass	<b>Removed</b>
9	Flash point	<b>Modified</b>

# Eni i-Sint tech VK 0W-20

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Indication of changes		
Section	Changed item	Comments
11.1	Other information	Removed
12.1	Ecology - water	Removed
12.1	Ecology - air	Removed
12.2	Persistence and degradability	Modified
12.7	Other information	Removed
13.1	Product/Packaging disposal recommendations	Removed
13.1	Ecology - waste materials	Removed
15.1	Other information, restriction and prohibition regulations	Removed
15.1	Regional legislation	Removed

Abbreviations and acronyms:	
	Complete text of the H phrases quoted in this Safety Data Sheet. These phrases are reported here for information only, and MAY NOT correspond to the classification of the product.
	N/D = not available
	N/A = not applicable
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Effective concentration for 50 percent of test population (median effective concentration)
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Lethal concentration for 50 percent of test population (median lethal concentration)
LD50	Lethal dose for 50 percent of test population (median lethal dose)
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals, Regulation (EC) No 1907/2006
RID	Regulation concerning the International Carriage of Dangerous Goods by Railways

# Eni i-Sint tech VK 0W-20

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### Abbreviations and acronyms:

SDS	Safety Data Sheet
STP	Sewage treatment plant
vPvB	Very Persistent and Very Bioaccumulative

Data sources	: This Safety Data Sheet is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.
Training advice	: Provide adequate training to professional operators for the use of PPEs, according to the information contained in this Safety Data Sheet.
Other information	: Do not use the product for any purposes that have not been advised by the manufacturer.

### Full text of H- and EUH-statements:

Asp. Tox. 1	Aspiration hazard, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H373	May cause damage to organs through prolonged or repeated exposure.
EUH208	Contains C14-16-18 Alkyl phenol. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.