

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878 Revision date: 8/23/2024 Supersedes: 12/27/2023 Version: 1.1

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **1.1. Product identifier** Product form : Mixture : Eni i-Sint tech F 0W-30 Trade name Product code : 1057 Type of product : Lubricant Formula : 0118-2017 Product group : Trade product 1.2. Relevant identified uses of the substance or mixture and uses advised against 1.2.1. Relevant identified uses Main use category : Industrial use, Professional use, Consumer use Industrial/Professional use spec : Used in closed systems Wide dispersive use Use of the substance/mixture : Lubricant for internal combustion engines Do not use the product for any purposes that have not been advised by the manufacturer. Function or use category : Lubricants and additives 1.2.2. Uses advised against No additional information available

### **1.3. Details of the supplier of the safety data sheet**

Enilive S.p.A, Viale Giorgio Ribotta 51, 00144 Rome, ITALY, Tel. +39 06 59821, www.eni.com

Competent person responsible for the safety data sheet (Reg. EC nr. 1907/2006): SDS.Enilive@eni.com

Distributed by: Enilive Schmiertechnik GmbH, Paradiesstraße 14, 97080 Würzburg, GERMANY, www.oilproducts.eni.com Department responsible for information: Application Engineering & Product Management (AEPM), Tel. +49 (0)931-900 98-0 e-mail: technik.wuerzburg@enilive.com

**1.4. Emergency telephone number** 

Emergency number

: CNIT +39 0382 24444 (24h) (IT + EN) Poison Center

## **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]

Hazardous to the aquatic environment – Chronic Hazard, H412

Category 3 Full text of H- and EUH-statements: see section 16

## Adverse physicochemical, human health and environmental effects

None to be reported, according to the present EU regulations. For specific information about the toxicological/ecotoxicological properties and classification of this product, see Sect. 11 and/or Sect. 12.

## 2.2. Label elements

### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

CLP Signal word	: -
Hazard statements (CLP)	: H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P273 - Avoid release to the environment.
	P501 - Dispose of contents/container to hazardous or special waste collection point, in
	accordance with local, regional, national and/or international regulation.
EUH-statements	: EUH208 - Contains Maleic anhydride. May produce an allergic reaction.

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

## 2.3. Other hazards (not relevant for classification)

Other hazards not contributing to the classification : None.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII Contains no PBT and/or vPvB substances  $\ge 0.1\%$  assessed in accordance with REACH Annex XIII

Component	
Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7), Dec-1-ene, trimers, hydrogenated (157707-86-3), Dodecylphenol, mixed isomers, branched (121158-58-5)( <sup>1</sup> ), 2,6-Di-tert-butylphenol (128-39-2), Calcium branched alkyl phenate sulphide (overbased) (N/D), Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)
Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7), Dec-1-ene, trimers, hydrogenated (157707-86-3), Dodecylphenol, mixed isomers, branched (121158-58-5)( <sup>1</sup> ), 2,6-Di-tert-butylphenol (128-39-2), Calcium branched alkyl phenate sulphide (overbased) (N/D), Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)

(1) Substance(s) in concentration below 0.1 % and displayed on a voluntary basis

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Component	
Substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	Dodecylphenol, mixed isomers, branched (121158-58-5)(¹)
Substance(s) not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7), Dec-1-ene, trimers, hydrogenated (157707-86-3), Calcium branched alkyl phenate sulphide (overbased) (N/D), 2,6-Di-tert-butylphenol (128-39-2)

(1) Substance(s) in concentration below 0.1 % and displayed on a voluntary basis

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

## Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]
Distillates (petroleum), hydrotreated heavy paraffinic (Main component, see note [**]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627- 25	60 - 70	Asp. Tox. 1, H304

## Safety Data Sheet

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]
Dec-1-ene, trimers, hydrogenated (Component)	CAS-No.: 157707-86-3 EC-No.: 500-393-3 REACH-no: 01-2119493949- 12-0000	15 - 20	Asp. Tox. 1, H304
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (see note [**]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	CAS-No.: 72623-87-1 EC-No.: 276-738-4 EC Index-No.: 649-483-00-5 REACH-no: 01-2119474889- 13	10 – 15	Not classified
Mineral base oil, severely refined (Component, For identification of the substance, see note [*]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	EC-No.: N/A	1 - 10	Not classified
Calcium branched alkyl phenate sulphide (overbased)	CAS-No.: N/D EC-No.: N/D EC Index-No.: N/A REACH-no: N/A	0.615 – 1.23	Aquatic Chronic 4, H413
2,6-Di-tert-butylphenol (Component)	CAS-No.: 128-39-2 EC-No.: 204-884-0 REACH-no: 01-2119490822- 33	0,01 - 0,13	Skin Irrit. 2, H315 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)
phenol, dodecyl-, branched; phenol, 2-dodecyl-, branched; phenol, 3-dodecyl-, branched Substance included in REACH Candidate List (Phenol, alkylation products (mainly in para position) with C12-rich branched alkyl chains from oligomerisation, covering any individual isomers and/ or combinations thereof (PDDP))	CAS-No.: 121158-58-5 EC-No.: 310-154-3 EC Index-No.: 604-092-00-9 REACH-no: 01-2119513207- 49	0.012 – 0.031	Skin Corr. 1C, H314 Eye Dam. 1, H318 Repr. 1B, H360F Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)
maleic anhydride (Component) substance with national workplace exposure limit(s) (AT, DE, ES, FR)	CAS-No.: 108-31-6 EC-No.: 203-571-6 EC Index-No.: 607-096-00-9	< 0,00012	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) STOT RE 1, H372 Skin Corr. 1B, H314 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1A, H317 EUH071

Specific concentration limits:		
Name	Product identifier	Specific concentration limits (%)
maleic anhydride (Component)	CAS-No.: 108-31-6 EC-No.: 203-571-6 EC Index-No.: 607-096-00-9	(0.001 ≤ C ≤ 100) Skin Sens. 1A, H317

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Comments	<ul> <li>[*] Note: this product may be formulated with one or more of the following severely refined mineral base oils (not classified as hazardous):</li> <li>CAS 101316-72-7/EC 309-877-7/REACH Reg. # 01-2119489969-06-xxxx; CAS 64742-54-7/EC 265-157-1/REACH Reg. # 01-2119484627-25-xxxx; CAS 64742-01-4/EC 265-101-6/REACH Reg. # 01-2119488707-21-xxxx; CAS 72623-87-1/EC 276-738-4/REACH Reg. # 01-2119474889-13-xxxx; CAS 64742-71-8/EC 265-176-5/REACH Reg. # 01-2119485040-48-xxxx; CAS 64742-65-0/EC 265-169-7/REACH Reg. # 01-2119471299-27-xxxx; CAS 64742-70-7/EC 265-174-4/REACH Reg. # 01-2119487080-42-xxxx.</li> <li>All these substances have a value &lt; 3 % wt of DMSO extract, according to IP 346 (Nota L - Annex VI Reg (CE) 1272/2008, # 1.1.3)</li> <li>Note [**]:</li> <li>this product has a value of DMSO extract &lt; 3 % wt, according to IP 346. According to the criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product</li> </ul>
	criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product must be regarded as non carcinogenic.

## Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general	: In case of spontaneous vomiting, transport the victim to a hospital, to verify the possibility that the product has been aspired into the lungs.
First-aid measures after inhalation	<ul> <li>In case of disturbances owing to inhalation of vapours or mists, remove the victim from exposure; keep at rest; if necessary, seek medical attention. See also section 4.3.</li> </ul>
First-aid measures after skin contact	: Take off contaminated clothing and shoes. Wash thoroughly with soap and water. If inflammation or irritation persists, seek medical advice. In case of burns, cool affected part with cold running water for at least 10 min. Cover with gauze or clean cloth. Ask for medical assistance or bring to a hospital. Do not apply salves or other substances, unless by doctor's advice. Do not put ice on the burn.
First-aid measures after eye contact	: Rinse eyes thoroughly for at least 15 minutes. Keep eyelids well apart. If irritation persists, seek medical advice. In case of burns, cool affected part with cold running water for at least 10 min. Cover with gauze or clean cloth. Ask for medical assistance or bring to a hospital. Do not apply salves or other substances, unless by doctor's advice.
First-aid measures after ingestion	: Do not induce vomiting to avoid aspiration into the lungs. Keep at rest. If the person is conscious, rinse mouth with water without swallowing. Keep at rest. Call for medical assistance or bring to an hospital. If the casualty is unconscious, place in the recovery position. In case of spontaneous vomiting, keep head low, to avoid the risk of aspiration into the lungs. Do not give anything by mouth to an unconscious person.
4.2. Most important symptoms and effects	both acute and delayed
Symptoms/effects after inhalation	: This product has a low vapour pressure, and in normal conditions at ambient temperature the concentration in the air is negligible. A significant concentration may build up only in case of sprays and mists. In these cases overexposure to mists (e.g. through prolonged use in confined insufficiently ventilated spaces) may cause irritation to airways, nausea and dizziness.
Symptoms/effects after skin contact	: Contact with hot product may cause thermal burns.
Symptoms/effects after eye contact Symptoms/effects after ingestion	<ul> <li>Contact with hot product or vapours may cause burns.</li> <li>Accidental ingestion of small quantities of the product may cause irritation, nausea and gastric disturbances. Taking into account the taste of the product, however, ingestion of dangerous quantites is very unlikely.</li> </ul>
Symptoms/effects upon intravenous administration Chronic symptoms	<ul><li>No information available.</li><li>None to be reported, according to the present classification criteria.</li></ul>

## 4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical attention if casualty has an altered state of consciousness or if symptoms do not resolve. Seek medical attention in all cases of serious burns. If there is any suspicion of inhalation of H2S (hydrogen sulphide), Rescuers must wear breathing apparatus, belt and safety rope, and follow rescue procedures. Send patient to hospital. Immediately begin artificial respiration if breathing has ceased. Administer oxygen if necessary. Send the casualty immediately to hospital. If breathing stops, give artificial respiration. Administer oxygen if necessary.

## Safety Data Sheet

SECTION 5: Firefighting measures		
5.1. Extinguishing media		
Suitable extinguishing media Unsuitable extinguishing media	<ul> <li>Small-size fires: carbon dioxide, dry chemicals, foam, sand or earth. Large fires: foam or water fog (mist). These means should be used by trained personnel only. Other extinguishing gases (according to regulations).</li> <li>Do not use water jets. They could cause splattering, and spread the fire. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.</li> </ul>	
5.2. Special hazards arising from the substance or mixture		
Fire hazard Explosion hazard	<ul> <li>This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels.</li> <li>In case of losses from pressurized circuits, the sprays may form mists. Take into account that in this case the lower explosion limit for mists is about 45 g/m<sup>3</sup> air.</li> </ul>	
5.3. Advice for firefighters		
Firefighting instructions Special protective equipment for firefighters	<ul> <li>Shut off source of product, if possible. If possible, move containers and drums away from the danger area, if safe to do so. Spilled product which is not burning should be covered with sand or foam. Use water sprays to cool containers and surfaces exposed to the flames. If the fire cannot be controlled, evacuate area.</li> <li>Wear personal protection equipment. (see chapter 8). EN 443. EN 469. EN 659. In case of a large fire or in confined or poorly ventilated spaces, wear full fire resistant protective electric and each act and the protection equipment. (SCRA) with a full face space approximation.</li> </ul>	
Other information	<ul> <li>clothing and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.</li> <li>In case of fire, do not discharge residual product, waste materials and runoff water: collect separately and use a proper treatment.</li> </ul>	

SECTION 6: Accidental release measures			
6.1. Personal precautions, protective equip	6.1. Personal precautions, protective equipment and emergency procedures		
General measures	: Stop or contain leak at the source, if safe to do so. Eliminate all ignition sources if safe to do so (e.g. electricity, sparks, fires, flares). Avoid direct contact with released material. Avoid accidental sprays on hot surfaces or electrical contacts. Keep upwind.		
6.1.1. For non-emergency personnel			
Protective equipment Emergency procedures	: See Section 8. : Keep non-involved personnel away from the area of spillage. Alert emergency personnel.		
	Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency.		
6.1.2. For emergency responders			
Protective equipment	: Small spillages: normal antistatic working clothes are usually adequate. Large spillages: full body suit of chemically resistant and antistatic material. if necessary heat resistant and insulated. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Gloves made of PVA are not water-resistant, and are not suitable for emergency use. If contact with hot product is possible or anticipated, gloves should be heat-resistant and thermally insulated. Antistatic non-skid safety shoes or boots, chemical resistant, if necessary heat resistant and insulated. Work helmet. Goggles and /or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory protection: A half or full-face respirator with filter(s) for organic vapours (A) (or A+B when applicable for H2S), or a Self-contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. A Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.		
Emergency procedures	: If required, notify relevant authorities according to all applicable regulations.		

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

C.2. Methode and meterial for containment and ale

### **6.2. Environmental precautions**

Do not let the product accumulate in confined or underground spaces. Do not let the product flow into sewers or water courses, or in any way contaminate the environment. In case of contamination of environment compartments (soil, subsoil, surface or underground waters), remove contaminated soil when possible, and in any case treat all involved compartments in accordance with local regulations. The site should have a spill plan to ensure that adequate safeguards are in place to minimize the impact of episodic releases.

0.5. Methous and material for containment a	ic cleaning up
For containment :	Contain spilled liquid with sand, earth or other suitable absorbents (non-flammable). Recover free liquid and waste materials in suitable waterproof and oil-resistant containers. Clean contaminated area. Dispose of according to local regulations. If in water: Confine the spillage. Remove from surface by skimming or suitable floating absorbents. Collect recovered product and other waste materials in suitable waterproof, oil resistant containers. Recover or dispose of according to local regulations. Do not use solvents or dispersants, unless specifically advised by an expert, and, if required, approved by local authorities.
Other information :	Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air/water temperature, wave/current direction and speed) may significantly influence the choice of appropriate actions. Local regulations may also prescribe or limit actions to be taken. For this reason, local experts should be consulted when necessary.

## 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	: Ensure that all relevant regulations regarding handling and storage facilities of flammable products are followed. Do not use compressed air for filling, discharging, or handling operations. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use and store only outdoors or in a well-ventilated area. During transfer operations, ensure that all equipment and containers are correctly grounded. Avoid the build-up of electric charges. Emptied containers can contain combustible product residues. Do not cut, weld, drill, burn or incinerate empty containers or drums, unless they have been drained and cleaned. Before entering storage tanks and commencing any operation in a confined area (e.g. tunnels), carry out an adequate clean-up, and check the atmosphere for oxygen content, flammability, and the presence of sulphur compounds. See also Section 16, "Other information".
Hygiene measures	: Avoid contact with skin. Do not breathe fume/ mist/ vapours. Do not ingest. Do not smoke. Do not eat and do not drink during use. Do not clean hands with dirty or oil-soaked rags. Do not re-use clothes, if they are still contaminated. Keep away from food and beverages.
7.2. Conditions for safe storage, including a	any incompatibilities
Storage conditions	: Store in dry, well-ventilated area. Keep away from open flames, hot surfaces and sources of ignition. Do not smoke.
Incompatible products Storage area	<ul> <li>Keep away from strong oxidizers.</li> <li>Storage area layout, tank design, equipment and operating procedures must comply with the relevant European, national or local legislation. Storage installations/areas should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and gualified personnel as defined by national, local or company regulations.</li> </ul>
Packages and containers:	: If the product is supplied in containers: Keep containers tightly closed and properly labelled. Keep only in the original container or in a suitable container for this kind of product.
Packaging materials	: For containers, or container linings use materials specifically approved for use with this product. Compatibility should be checked with the manufacturer, according to the specific use conditions.
Germany	
Storage class (LGK, TRGS 510)	: LGK 12 - Non-combustible liquids

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### Switzerland

Storage class (LK)

: LK 10/12 - Liquids

No information available.

7.3. Specific end use(s)

## **SECTION 8: Exposure controls/personal protection**

8.1. Control parameters

## 8.1.1 National occupational exposure and biological limit values

Austria - Occupational Exposure Limits       5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)         Belgium - Occupational Exposure Limits       5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)         Denmark - Occupational Exposure Limits       1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)         OEL TWA       1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)         OEL TWA       1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)         OEL STEL       2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)         Hungary - Occupational Exposure Limits          AK (OEL TWA)       5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)         Netherlands - Occupational Exposure Limits          MAC TGG 8h (mg/m³)       5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)         Spain - Occupational Exposure Limits          VLA-ED (OEL TWA)       6 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)         Swelen - Occupational Exposure Limits          NGV (OEL TWA)       1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)         Swelen - Occupational Exposure Limits          NGV (OEL TWA)       1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)         United Kingdom - Occ		
Belgium - Occupational Exposure Limits         5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)           Denmark - Occupational Exposure Limits         1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
OEL TWA       5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Denmark - Occupational Exposure Limits           OEL TWA         1 mg/m² (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
QEL TWA       1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
OEL STEL       2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Hungary - Occupational Exposure Limits         AK (OEL TWA)       5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
AK (OEL TWA)       5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Netherlands - Occupational Exposure Limits         MAC TGG 8h (mg/m³)       5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
MAC TGG 8h (mg/m³)       5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Spain - Occupational Exposure Limits         VLA-ED (OEL TWA)       5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
VLA-ED (OEL TWA)       5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
VLA-EC (mg/m³)       10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Sweden - Occupational Exposure Limits         NGV (OEL TWA)       1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
NGV (OEL TWA)1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)KGV (OEL STEL)3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
KGV (OEL STEL)       3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
United Kingdom - Occupational Exposure Limits         WEL TWA (OEL TWA)       5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
WEL TWA (OEL TWA)       5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
WEL STEL (OEL STEL)       10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
USA - ACGIH - Occupational Exposure Limits         ACGIH OEL TWA       5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
ACGIH OEL TWA       5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
ACGIH OEL STEL 10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Minoral base oil, soverely refined		
Mineral base oil, severely refined		
Austria - Occupational Exposure Limits		
MAK (OEL TWA) 5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Belgium - Occupational Exposure Limits		
OEL TWA 5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Denmark - Occupational Exposure Limits		
OEL TWA 1 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		

## Safety Data Sheet

Mineral base oil, severely refined		
OEL STEL	2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KGV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
WEL STEL (OEL STEL)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH OEL STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
maleic anhydride (108-31-6)		
Austria - Occupational Exposure Limits		
MAK [ppm]	0.1 ppm	
France - Occupational Exposure Limits		
VME (OEL TWA)	1 mg/m³	
Germany - Occupational Exposure Limits (TRGS 90	0)	
AGW (OEL TWA)	0.1 ppm	
Limitation of exposure peaks (ppm)	0.1 ppm	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA)	0.1 ppm	
USA - ACGIH - Occupational Exposure Limits		
ACGIH TLV®-TWA (ppm)	0.01 ppm	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Belgium - Occupational Exposure Limits		
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Denmark - Occupational Exposure Limits	·	
OEL TWA	1 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
I Contraction of the second		

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)		
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KGV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
WEL STEL (OEL STEL)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH OEL STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
8.1.2. Recommended monitoring procedures		

Monitoring methods	
Monitoring methods	Monitoring procedures should be chosen according to the indications set by national authorities or labour contracts. Refer to relevant legislation and in any case to the good practice of industrial hygiene.

## 8.1.3. Air contaminants formed

## No additional information available

## 8.1.4. DNEL and PNEC

Eni i-Sint tech F 0W-30	
DNEL/DMEL (additional information)	
Additional information	Not applicable
PNEC (additional information)	
Additional information	Not applicable
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	1 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	2.7 mg/m <sup>3</sup>
Long-term - local effects, inhalation	5.6 mg/m <sup>3</sup>
DNEL/DMEL (General population)	
Long-term - systemic effects,oral	0.74 mg/kg bodyweight/day
Long-term - local effects, inhalation	1.2 mg/m³/day (DNEL, Mineral base oil mist, severely refined, DMSO extract <3% m/m)

## Safety Data Sheet

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
PNEC (Oral)		
PNEC oral (secondary poisoning)	9.33 mg/kg food	
Dec-1-ene, trimers, hydrogenated (157707-86-	3)	
DNEL/DMEL (Workers)		
Acute - local effects, inhalation	60 mg/m³ (DNEL, 15 min)	
DNEL/DMEL (General population)		
Acute - local effects, inhalation	50 mg/m³ (DNEL, 15 min)	
PNEC (additional information)		
Additional information	Not derived - Not classified as hazardous for environment	
phenol, dodecyl-, branched; phenol, 2-dodecy	yl-, branched; phenol, 3-dodecyl-, branched (121158-58-5)	
DNEL/DMEL (Workers)		
Acute - systemic effects, dermal	166 mg/kg bodyweight/day	
Acute - systemic effects, inhalation	44.18 mg/m <sup>3</sup>	
Long-term - systemic effects, dermal	0.25 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	1.762 mg/m³	
DNEL/DMEL (General population)		
Acute - systemic effects, dermal	50 mg/kg bodyweight	
Acute - systemic effects, inhalation	13.26 mg/m <sup>3</sup>	
Acute - systemic effects, oral	1.26 mg/kg bodyweight	
Long-term - systemic effects,oral	0.075 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	0.79 mg/m³	
Long-term - systemic effects, dermal	0.075 mg/kg bodyweight/day	
PNEC (Water)		
PNEC aqua (freshwater)	0.074 µg/l	
PNEC aqua (marine water)	0.0074 μg/l	
PNEC aqua (intermittent, freshwater)	0.37 µg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	0.226 mg/kg dwt	
PNEC sediment (marine water)	0.0266 mg/kg dwt	
PNEC (Soil)		
PNEC soil	118 µg/kg dw	
PNEC (Oral)		
PNEC oral (secondary poisoning)	4 mg/kg food	
PNEC (STP)		
PNEC sewage treatment plant	100 mg/l	
2,6-Di-tert-butylphenol (128-39-2)		
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	11.25 mg/kg bodyweight/day	

## Safety Data Sheet

2,6-Di-tert-butylphenol (128-39-2)		
Long-term - systemic effects, inhalation	70.61 mg/m <sup>3</sup>	
DNEL/DMEL (General population)	1	
Long-term - systemic effects,oral	6.75 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	20.9 mg/m³	
Long-term - systemic effects, dermal	6.75 mg/kg bodyweight/day	
PNEC (Water)		
PNEC aqua (freshwater)	0.0007 mg/l	
PNEC aqua (marine water)	0.00007 mg/l	
PNEC aqua (intermittent, freshwater)	0.0045 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	0.317 mg/kg dwt	
PNEC sediment (marine water)	0.0317 mg/kg dwt	
PNEC (Soil)	·	
PNEC soil	0.697 mg/kg dwt	
PNEC (Oral)		
PNEC oral (secondary poisoning)	60 mg/kg food	
PNEC (STP)		
PNEC sewage treatment plant	10 mg/l	
Calcium branched alkyl phenate sulphide (overbased) (N/D)		
DNEL/DMEL (additional information)		
Additional information	Not derived - Not classified as hazardous for health	
PNEC (additional information)		
Additional information	Not yet determined.	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)		
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	0.97 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	2.73 mg/m³	
Long-term - local effects, inhalation	5.58 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	0.74 mg/kg bodyweight/day	
Long-term - local effects, inhalation	1.19 mg/m <sup>3</sup>	
PNEC (additional information)		
Additional information	Not applicable (UVCB)	
L	1	

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

: The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a governmental regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH.

### 8.1.5. Control banding

No additional information available

### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

### Appropriate engineering controls:

Before entering storage tanks and commencing any operation in a confined area (e.g. tunnels), carry out an adequate clean-up, and check the atmosphere for oxygen content and flammability. See also Section 16, "Other information".

#### 8.2.2. Personal protection equipment

### Personal protective equipment (for industrial or professional use):

Face shield. Gloves. Protective clothing. Safety glasses. Safety shoes or boots. Dust/aerosol mask.

#### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

#### Eye protection:

When there is a risk of contact with the eyes, use safety goggles or other means of protection (face shield). If necessary, refer to national standards or to the EN 166 standard.

#### 8.2.2.2. Skin protection

#### Skin and body protection:

Long-sleeved overalls. If necessary, refer to the EN 340 and related standards, for definition of characteristics and performance according to the risk rating of the area. Antistatic non-skid safety shoes or boots, chemical resistant, if necessary heat resistant and insulated.

#### Hand protection:

When there is a risk of contact with the skin, use waterproof gloves, resistant to chemical products. Gloves must be felt-lined. Adequate materials: nitrile (NBR) or PVC with a protection index > 5 (permeation time > 240 mins). Use gloves respecting all the conditions and within the limits set by the manufacturer. Replace gloves immediately in case of cuts, holes or other signs of damages or degradation. If necessary, refer to the EN 374 standard.

#### 8.2.2.3. Respiratory protection

### **Respiratory protection:**

Independently from other possible actions (technical modifications, operating procedures, and other means to limit the exposure of workers), personal protection equipment can be used according to necessity. Open or well ventilated spaces: in presence of oil mists and if the product is handled without adequate containment means: use full or half-face masks with filter for mists/aerosols (P). In case there is a significant presence of vapours (e.g. through handling at high temperature), use full or half-face masks with a filter for organic vapours (A), and H2S (B) where applicable. (EN 136/140/145). Combination filter device (DIN EN 141). Closed or confined areas (e.g. tank interiors): the use of protection measures for airways (masks or self-contained breathing apparatus), must be assessed according to the specific activity, as well as level and duration of predicted exposure. Approved respiratory protection equipment shall be used in spaces where hydrogen sulphide may accumulate: full face mask with cartridge/filter type "B" (grey for inorganic vapours including H2S) or self-contained breathing apparatus (SCBA). (EN 136/140/145)

### 8.2.2.4. Thermal hazards

## Thermal hazard protection:

If contact with hot product is possible or anticipated, gloves should be heat-resistant and thermally insulated.

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

#### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Do not discharge the product into the environment. Prevent discharge of undissolved substance to or recover from onsite wastewater. Storage areas/installations should be designed with adequate bunds so as to prevent ground and water pollution in case of leaks or spills. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

### Consumer exposure controls:

No special requirements.

## SECTION 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Yellow-brown.
Appearance	: Liquid, bright & clear.
Odour	: Slight odour of petroleum.
Odour threshold	: There are no data available on the preparation/mixture itself.
Melting point	: -48 °C (pour point) (ASTM D 97)
Freezing point	: Not determined
Boiling point	: Not determined
Flammability	: Not flammable
Lower explosion limit	: Not determined
Upper explosion limit	: Not determined
Flash point	: 225 °C (ASTM D 92)
Auto-ignition temperature	: Not determined
Decomposition temperature	: Not determined
рН	: Not applicable
Viscosity, kinematic	: 50.1 mm²/s (40 °C) (ASTM D 445)
Solubility	: Water: Immiscible and insoluble
Log Kow	: Not determined
Log Pow	: Not applicable for mixtures
Vapour pressure	: Not determined
Vapour pressure at 50°C	: Not determined
Density	: 845 kg/m³ (15 °C) (ASTM D 4052)
Relative density	: Not determined
Relative vapour density at 20°C	: Not determined
Particle characteristics	: Not applicable

## 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

Relative evaporation rate (butylacetate=1)	: Negligible.
Additional information	: No data available

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

This mixture does not offer any further hazard for reactivity, except what is reported in the following paragraphs.

## **10.2. Chemical stability**

Stable product, according to its intrinsic properties.

### **10.3. Possibility of hazardous reactions**

None (in normal conditions of storage and handling). Contact with strong oxidizers (peroxides, chromates, etc.) or alkali metals may cause a fire hazard.

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

## 10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition. Avoid the build-up of electrostatic charge.

### 10.5. Incompatible materials

Strong oxidizing agents.

## **10.6. Hazardous decomposition products**

Thermal decomposition may produce : Toxic fumes. In exceptional cases (i.e prolonged storage in tanks contaminated with water, and presence of anaerobic sulfate-reducing microbial colonies), the product may undergo a degradation and generate small amounts of sulfur compounds, including H2S.

SECTION 11: Toxicological information		
11.1. Information on hazard classes as defined	d in Regulation (EC) No 1272/2008	
Acute toxicity (oral):Acute toxicity (dermal):Acute toxicity (inhalation):Additional information:	Not classified (Based on available data, the classification criteria are not met) Not classified (Based on available data, the classification criteria are not met) Not classified (Based on available data, the classification criteria are not met) (according to composition)	
Distillates (petroleum), hydrotreated heavy pa	uraffinic (64742-54-7)	
LD50 oral rat	> 5000 mg/kg (OECD 401)	
LD50 dermal rat	> 5000 mg/kg (OECD 402)	
LC50 Inhalation - Rat	> 5 mg/l/4h (OECD 403)	
Dec-1-ene, trimers, hydrogenated (157707-86-	3)	
LD50 oral rat	> 2000 mg/kg (OECD 401-423)	
Mineral base oil, severely refined		
LD50 oral rat	> 5000 mg/kg bodyweight (OECD 401)	
LD50 dermal rat	> 5000 mg/kg bodyweight (OECD 402)	
LC50 Inhalation - Rat	> 5 mg/l/4h (OECD 403)	
phenol, dodecyl-, branched; phenol, 2-dodecyl-, branched; phenol, 3-dodecyl-, branched (121158-58-5)		
LD50 oral rat	2200 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)	
LD50 dermal rabbit	15000 mg/kg bodyweight	
2,6-Di-tert-butylphenol (128-39-2)		
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)	
LD50 dermal rabbit	> 0.5 ml/kg	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)		
LD50 oral rat	> 5000 mg/kg (OECD 401)	
LD50 dermal rat	> 5000 mg/kg (OECD 402)	
LC50 Inhalation - Rat	> 5 mg/l/4h (OECD 403)	
	Not classified (Based on available data, the classification criteria are not met) pH: Not applicable	
	(according to composition)	
	Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	
рН	Not applicable	

## Safety Data Sheet

Mineral base oil, severely refined		
рН	Not applicable	
Lubricating oils (petroleum), C20-50, hydrotr Baseoil - unspecified (72623-87-1)	eated neutral oil-based	
pН	Not applicable	
Serious eye damage/irritation :	Not classified (Based on available data, the classification criteria are not met) pH: Not applicable	
Additional information :	(according to composition)	
Distillates (petroleum), hydrotreated heavy p	araffinic (64742-54-7)	
рН	Not applicable	
Mineral base oil, severely refined		
рН	Not applicable	
Lubricating oils (petroleum), C20-50, hydrotr Baseoil - unspecified (72623-87-1)	eated neutral oil-based	
рН	Not applicable	
Respiratory or skin sensitisation       :         Germ cell mutagenicity       :         Additional information       :         Carcinogenicity       :         Additional information       :         Additional information       :         Reproductive toxicity       :         Additional information       :	Not classified Not classified (Based on available data, the classification criteria are not met) (according to composition) Not classified (Based on available data, the classification criteria are not met) (according to composition) This product contains : Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] this product has a value of DMSO extract < 3 % wt, according to IP 346. According to the criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product must be regarded as non carcinogenic. All the mineral base oils contained in this product have a value < 3 % wt of DMSO extract, according to IP 346 (Nota L - Annex VI Reg (CE) 1272/2008, # 1.1.3) Not classified (Based on available data, the classification criteria are not met) (according to composition)	
phenol, dodecyl-, branched; phenol, 2-dodecyl-, branched; phenol, 3-dodecyl-, branched (121158-58-5)		
NOAEL (animal/male, F1)	1.5 mg/kg	
NOAEL (animal/female, F1)	15 mg/kg (OECD 416)	
STOT-single exposure       :         Additional information       :         STOT-repeated exposure       :         Additional information       :	Not classified (Based on available data, the classification criteria are not met) (according to composition) Not classified (Based on available data, the classification criteria are not met) (according to composition)	
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)	
Mineral base oil, severely refined		
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)	
maleic anhydride (108-31-6)		
STOT-repeated exposure	Causes damage to organs (respiratory system) through prolonged or repeated exposure (inhalation).	

## Safety Data Sheet

2,6-Di-tert-butylphenol (128-39-2)		
NOAEL (subacute, oral, animal/male, 28 days)	> 100 mg/kg bodyweight (100 mg / d)	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)		
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)	
Aspiration hazard : Additional information :	Not classified (Based on available data, the classification criteria are not met) Viscosity, kinematic: > 20,5 mm2/s (40 °C) (ASTM D 445)	
Eni i-Sint tech F 0W-30		
Viscosity, kinematic	50.1 mm²/s (40 °C) (ASTM D 445)	
Distillates (petroleum), hydrotreated heavy pa	araffinic (64742-54-7)	
Viscosity, kinematic	17.9 mm²/s (40 °C) (ASTM D 445)	
Dec-1-ene, trimers, hydrogenated (157707-86	-3)	
Viscosity, kinematic	17.4 mm²/s (40°C)	
Mineral base oil, severely refined		
Viscosity, kinematic	> 21 mm²/s	
Hydrocarbon	Yes	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)		
Viscosity, kinematic	48 mm²/s (40°C) (ASTM D 445)	
11.2. Information on other hazards		
<b>11.2.1. Endocrine disrupting properties</b> Adverse health effects caused by endocrine         isrupting properties	The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %	
Component		
phenol, dodecyl-, branched; phenol, 2-dodecyl-, branched; phenol, 3-dodecyl-, branched (121158-58- 5)	The substance is identified for having endocrine disrupting properties but there is no additional data available (see section 2.3)	
11.2.2. Other information		
Potential adverse human health effects and : symptoms	None expected at ambient temperature,Prolonged and repeated skin contact may cause reddening, irritation and dermatitis,Contact with eyes may cause temporary reddening and irritation.	
Other information :	None	

SECTION 12: Ecological information	
12.1. Toxicity	
Ecology - general	: An uncontrolled release to the environment may nevertheless produce a contamination of different environmental compartments (air, soil, underground, surface water bodies, aquifers). Handle according to general working hygiene practices to avoid pollution and release into the environment.

## Safety Data Sheet

Ecology - air :	This product has a low vapour pressure, and in normal conditions at ambient temperature the concentration in the air is negligible. A significant concentration may build up only in case of sprays and mists. In these cases overexposure to mists (e.g. through prolonged use in confined insufficiently ventilated spaces) may cause irritation to airways, nausea and dizziness.
	This product is not soluble in water. It floats on water and forms a film on the surface. The damage to aquatic organisms is of mechanical kind (immobilization and entrapment)
Hazardous to the aquatic environment, short-term : (acute)	Not classified
	Harmful to aquatic life with long lasting effects.
Distillates (petroleum), hydrotreated heavy pa	araffinic (64742-54-7)
LC50 fish 1	> 100 mg/l (LL 50)
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)
Dec-1-ene, trimers, hydrogenated (157707-86-	3)
LC50 fish 1	≥ 1000 mg/l (96h, Oncorhynchus mykiss)
EC50 Daphnia 1	≥ 1000 mg/l (48 h)
EC50 72h - Algae [1]	> 1000 mg/l
ErC50 (algae)	≥ 1000 mg/l (72 h, Scenedesmus capricornutum)
NOEC (chronic)	125 mg/l (21 d, Daphnia magna)
NOEC chronic crustacea	125 mg/l (21d, NOELR WAF)
Mineral base oil, severely refined	
LC50 fish 1	> 100 mg/l (LL 50)
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)
Dodecylphenol, mixed isomers, branched (12	1158-58-5)
LC50 fish 1	40 mg/l (Pimephales promelas)
EC50 Daphnia 1	92.7 μg/l Test organisms (species): Daphnia magna
EC50 other aquatic organisms 1	> 0.58 mg/l (96h, Mysidopsis Bahia)
EC50 72h - Algae [1]	> 0.765 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	0.36 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
ErC50 (algae)	0.36 mg/l (21d)
LOEC (chronic)	0.012 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0.0037 mg/l (21d)
2,6-Di-tert-butylphenol (128-39-2)	
LC50 fish 1	1.4 mg/l Test organisms (species): Pimephales promelas
LC50 other aquatic organisms 1	0.45 mg/l
EC50 Daphnia 1	0.45 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	3.6 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	1.4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	3.9 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

## Safety Data Sheet

2,6-Di-tert-butylphenol (128-39-2)		
EC50 96h - Algae [2]	1.2 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names:	
	Raphidocelis subcapitata, Selenastrum capricornutum)	
LOEC (chronic)	0.086 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
NOEC (chronic)	0.035 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
NOEC chronic crustacea	0.035 mg/l (21d)	
Calcium branched alkyl phenate sulphide (ov	erbased) (N/D)	
LC50 fish 1	> 1000 mg/l (Pimephales promelas)	
EC50 Daphnia 1	> 1000 mg/l	
EC50 96h - Algae [1]	> 1000 mg/l (Selenastrum capricornutum)	
Lubricating oils (petroleum), C20-50, hydrotre Baseoil - unspecified (72623-87-1)	ated neutral oil-based	
LC50 fish 1	> 100 mg/l (LL 50)	
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)	
12.2. Persistence and degradability		
Eni i-Sint tech F 0W-30		
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.	
Distillates (petroleum), hydrotreated heavy pa	araffinic (64742-54-7)	
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions	
Dec-1-ene, trimers, hydrogenated (157707-86-	3)	
Persistence and degradability	Inherently biodegradable.	
Mineral base oil, severely refined		
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions	
Dodecylphenol, mixed isomers, branched (12	1158-58-5)	
Persistence and degradability	Rapidly degradable	
Biodegradation	25 % (28 d, OECD TG 301 B)	
maleic anhydride (108-31-6)		
Persistence and degradability	Rapidly degradable	
2,6-Di-tert-butylphenol (128-39-2)		
Persistence and degradability	Rapidly degradable	
Biodegradation	24 % (Zahn-Wellens, 10-20 %)	
Calcium branched alkyl phenate sulphide (overbased) (N/D)		
Persistence and degradability	Not readily biodegradable.	
5 5		

## Safety Data Sheet

Lubricating oils (petroleum), C20-50, hydrotre Baseoil - unspecified (72623-87-1)	ated neutral oil-based
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions
12.3. Bioaccumulative potential	
Eni i-Sint tech F 0W-30	
Log Pow	Not applicable for mixtures
Log Kow	Not determined
Bioaccumulative potential	Not established.
Dec-1-ene, trimers, hydrogenated (157707-86-	3)
Log Pow	> 10
Dodecylphenol, mixed isomers, branched (12	1158-58-5)
Bioconcentration factor (BCF REACH)	794.33
Log Kow	7.14
2,6-Di-tert-butylphenol (128-39-2)	
Log Kow	4.5 (0.1 d, 10-20 %)
Calcium branched alkyl phenate sulphide (ove	erbased) (N/D)
Bioconcentration factor (BCF REACH)	2.2
Log Kow	11.08
Lubricating oils (petroleum), C20-50, hydrotre Baseoil - unspecified (72623-87-1)	ated neutral oil-based
Log Kow	> 6
12.4. Mobility in soil	
Eni i-Sint tech F 0W-30	
Ecology - soil	No data available.
12.5. Results of PBT and vPvB assessment	
Eni i-Sint tech F 0W-30	
This substance/mixture does not meet the PBT criteria	of REACH regulation, annex XIII
This substance/mixture does not meet the vPvB criteria	of REACH regulation, annex XIII
Results of PBT-vPvB assessment	The components in this formulation do not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)
Component	
Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7), Dec-1-ene, trimers, hydrogenated (157707-86-3), Dodecylphenol, mixed isomers, branched (121158-58-5)( <sup>1</sup> ), 2,6-Di-tert-butylphenol (128-39-2), Calcium branched alkyl phenate sulphide (overbased) (N/D), Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Component		
Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7), Dec-1-ene, trimers, hydrogenated (157707-86-3), Dodecylphenol, mixed isomers, branched (121158-58-5)(1) 2,6-Di-tert-butylphenol (128-39-2), Calcium branched alkyl phenate sulphide (overbased) (N/D), Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)	
(1) Substance(s) in concentration below 0.1 % and displa	ayed on a voluntary basis	
12.6. Endocrine disrupting properties		
endocrine disrupting properties	The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set	

	out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.
Component	
Dodecylphenol, mixed isomers, branched (121158-58 5)	- Has an endocrine mode of action, i.e. it alters the function(s) of the endocrine system
12.7. Other adverse effects	
	None. This product has no specific properties for inhibition of bacterial activity. In any case, wastewater containing this product should be treated in plants that are suited for the specific

purpose.

SECTION 13: Disposal considerations	
13.1. Waste treatment methods	
Waste treatment methods	: Do not dispose of the product, either new or used, by dumping on the ground, or discharging into sewers, tunnels, lakes or water courses. Deliver to a qualified official collector.
Sewage disposal recommendations	: Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed. Dispose of in a safe manner in accordance with local/national regulations.
Product/Packaging disposal recommendations	: European Waste Catalogue code(s) (Decision 2001/118/CE): 13 02 05* (mineral-based non-chlorinated engine, gear and lubricating oils). This EWC code is only a general indication, and takes into account the original composition of the product and its intended use. The user has the responsibility of choosing the right EWC code, considering the actual use of the product, alterations and contaminations.
Additional information	: Empty containers may contain combustible product residues. Do not cut, weld, bore, burn or incinerate emptied containers, unless they have been cleaned and declared safe.
Ecology - waste materials EURAL code (EWC)	<ul> <li>The product as it is does not contain halogenated substances.</li> <li>13 02 05* - Mineral-based non-chlorinated engine, gear and lubricating oils</li> </ul>

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID				
ADR	IMDG IATA ADN RID			
14.1. UN number or ID number				
Not regulated for transport				
14.2. UN proper shipping name				
Not regulated.	Not regulated. Not regulated. Not regulated. Not regulated.			
14.3. Transport hazard class(es)				
Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

ADR	IMDG	ΙΑΤΑ	ADN	RID
14.4. Packing group				
Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.5. Environmental hazards				
Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
None.				

14.6. Special precautions for user

## Overland transport

Not regulated.

Transport by sea Not regulated.

### Air transport Not regulated.

**Inland waterway transport** Not regulated.

### Rail transport Not regulated.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.1.1. EU-Regulations

## **REACH Annex XVII (Restriction List)**

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(b)	Distillates (petroleum), hydrotreated heavy paraffinic ; Dec-1-ene, trimers, hydrogenated	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
30.	phenol, dodecyl-, branched; phenol, 2- dodecyl-, branched; phenol, 3-dodecyl-, branched	Substances which are classified as reproductive toxicant category 1A or 1B in Part 3 of Annex VI to Regulation (EC) No 1272/2008 and are listed in Appendix 5 or Appendix 6, respectively.

### **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

## **REACH Candidate List (SVHC)**

Contains substance(s) listed on the REACH Candidate List in concentrations  $\geq$  0.1 % or SCL: phenol, dodecyl-, branched; phenol, 2-dodecyl-, branched; phenol, 3-dodecyl-, branched (EC 310-154-3, CAS 121158-58-5)

### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### **POP Regulation (Persistent Organic Pollutants)**

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

### Dual-Use Regulation (428/2009)

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

#### **Explosives Precursors Regulation (2019/1148)**

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

#### **Drug Precursors Regulation (273/2004)**

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

#### 15.1.2. National regulations

National adoption of EU Directives concerning health and safety on the workplace.

National adoption of EU Directives concerning control of major-accident hazards involving dangerous substances (2012/18/CE). Relevant national laws on prevention of water pollution.

Relevant national laws on protection of the health of pregnant workers (National adoption of Dir. 92/85/EEC).

National adoption of Directive 2008/98/CE concerning disposal of used oils.

#### France

Maladies professionelles (F)	
Code Description	
RG 36 Diseases caused by oils and fats of mineral or synthetic origin	
RG 66 Occupational rhinitis and asthma	

#### Germany

VbF class (D) Water hazard class (WGK) (D) WGK remark Hazardous Incident Ordinance (12. BImSchV)	<ul> <li>Not applicable.</li> <li>WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1).</li> <li>Classification based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS).</li> <li>Is not subject to the Hazardous Incident Ordinance (12. BImSchV)</li> </ul>
Netherlands	
Saneringsinspanningen SZW-lijst van kankerverwekkende stoffen SZW-lijst van mutagene stoffen SZW-lijst van reprotoxische stoffen – Borstvoeding SZW-lijst van reprotoxische stoffen – Vruchtbaarheid SZW-lijst van reprotoxische stoffen – Ontwikkeling	<ul> <li>C - Minimize discharge</li> <li>None of the components are listed</li> <li>None of the components are listed</li> <li>None of the components are listed</li> <li>Dodecylphenol, mixed isomers, branched is listed</li> <li>None of the components are listed</li> </ul>
Denmark	
Danish National Regulations	: Young people under 18 years are not allowed to use the product Pregnant/breastfeeding women working with the product must not be in direct contact with it

### 15.2. Chemical safety assessment

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP] No chemical safety assessment has been carried out

### A chemical safety assessment has been carried out for the following components of this mixture::

Distillates (petroleum), hydrotreated heavy paraffinic

Dec-1-ene, trimers, hydrogenated 2,6-Di-tert-butylphenol

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based

Baseoil - unspecified

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SECTION 16: Other information				
Indication of changes				
Section	Changed item	Change	Comments	
1.3	Supplier information	Modified		

Abbreviations a	and acronyms:		
	N/A = not applicable		
	N/D = not available		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways		
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road		
ATE	Acute Toxicity Estimate		
BCF	Bioconcentration factor		
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008		
DMEL	Derived Minimal Effect level		
DNEL	Derived-No Effect Level		
EC50	Effective concentration for 50 percent of test population (median effective concentration)		
IARC	International Agency for Research on Cancer		
IATA	International Air Transport Association		
IMDG	International Maritime Dangerous Goods		
LC50	Lethal concentration for 50 percent of test population (median lethal concentration)		
LD50	Lethal dose for 50 percent of test population (median lethal dose)		
LOAEL	Lowest Observed Adverse Effect Level		
NOAEC	No-Observed Adverse Effect Concentration		
NOAEL	No-Observed Adverse Effect Level		
NOEC	No-Observed Effect Concentration		
OECD	Organisation for Economic Co-operation and Development		
PBT	Persistent Bioaccumulative Toxic		
PNEC	Predicted No-Effect Concentration		
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals, Regulation (EC) No 1907/2006		
RID	Regulation concerning the International Carriage of Dangerous Goods by Railways		
SDS	Safety Data Sheet		
STP	Sewage treatment plant		
vPvB	Very Persistent and Very Bioaccumulative		

#### Data sources

Training advice

This Safety Data Sheet is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.
Provide adequate training to professional operators for the use of PPEs, according to the information contained in this Safety Data Sheet.

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Other information

: Do not use the product for any purposes that have not been advised by the manufacturer. In exceptional cases (i.e prolonged storage in tanks contaminated with water, and presence of anaerobic sulfate-reducing microbial colonies), the product may undergo a degradation and generate small amounts of sulfur compounds, including H2S. This situation is especially relevant in all those circumstances which require to enter a confined space, with direct exposure to the vapours. If this possibility is suspected, a specific assessment of inhalation risks from the presence of H2S in confined spaces must be made, to help determine prevention measures and controls (i.e. PPE) appropriate to local circumstances, and adequate emergency procedures. If there is any suspicion of inhalation of H2S (hydrogen sulphide), Rescuers must wear breathing apparatus, belt and safety rope, and follow rescue procedures. Send patient to hospital. Immediately begin artificial respiration if breathing has ceased. Administer oxygen if necessary.

Full text of H- and EUH-statements:		
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4	
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1	
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1	
Aquatic Chronic 4	Hazardous to the aquatic environment – Chronic Hazard, Category 4	
Asp. Tox. 1	Aspiration hazard, Category 1	
EUH071	Corrosive to the respiratory tract.	
EUH208	Contains Maleic anhydride. May produce an allergic reaction.	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1	
H302	Harmful if swallowed.	
H304	May be fatal if swallowed and enters airways.	
H314	Causes severe skin burns and eye damage.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
H360F	May damage fertility.	
H372	Causes damage to organs through prolonged or repeated exposure.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
H412	Harmful to aquatic life with long lasting effects.	
H413	May cause long lasting harmful effects to aquatic life.	
Repr. 1B	Reproductive toxicity, Category 1B	
Resp. Sens. 1	Respiratory sensitisation, Category 1	
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B	
Skin Corr. 1C	Skin corrosion/irritation, Category 1, Sub-Category 1C	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
Skin Sens. 1A	Skin sensitisation, category 1A	
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1	

 Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

 Aquatic Chronic 3
 H412
 Calculation method

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.