

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878 Revision date: 7/16/2024 Supersedes: 3/11/2024 Version: 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Substance
Trade name : Eni Celtis 902

Chemical name : Distillates (petroleum), solvent-refined light paraffinic IUPAC name : Distillates (petroleum), solvent-refined light paraffinic

 EC Index-No.
 : 649-455-00-2

 EC-No.
 : 265-091-3

 CAS-No.
 : 64741-89-5

 REACH registration No.
 : 01-2119487067-30

Product code : 7259

Type of product : Mixture of hydrocarbons

Formula : UVCB

Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use, Consumer use

Industrial/Professional use spec : Used in closed systems

Non-dispersive use Wide dispersive use

Use resulting in inclusion into or onto a matrix

Use of the substance/mixture : General purpose lubricant

Hydraulic oil Metalworking fluid

Rubber production and processing Use in polymer processing Binder and release agent Functional fluids Explosives manufacture

Plasticizer

Function or use category : Lubricants and additives, Adhesives, binding agents, Anti-freezing agents, Construction

materials additives, Dust binding agents, Explosive substances and articles, Flotation agents, Heat transferring agents, Hydraulic fluids and additives, Insulating agents,

Intermediates, Laboratory chemicals, Viscosity adjusters

Title	Use descriptors
Rubber production and processing	SU3, SU10, SU11, PROC1, PROC2, PROC3, PROC3, PROC4, PROC5, PROC6, PROC7, PROC8a, PROC8b, PROC8b, PROC9, PROC13, PROC14, PROC15, PROC21, ERC4, ERC6d, ESVOC SPERC 4.19.v1
Distribution of substance	SU3, PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC9, PROC15, ERC1, ERC2, ERC3, ERC4, ERC5, ERC6a, ERC6b, ERC6c, ERC6d, ERC7, ESVOC SPERC 1.1b.v1
Formulation & (re)packing of substances and mixtures	SU3, SU10, PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC14, PROC15, ERC2, ESVOC SPERC 2.2.v1
Use in laboratories	SU3, PROC15, ERC4, (ERC)
Manufacture of substance	SU3, SU8, SU9, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15, ERC1, ERC4, ESVOC SPERC 1.1.v2
Use in Polymer processing	SU10, PROC1, PROC2, PROC4, PROC5, PROC6, PROC8a, PROC8b, PROC9, PROC13, PROC14, PROC21, ERC4, ESVOC SPERC 4.21a.v1
Uses in Coatings	SU3, PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC10, PROC13, PROC15, ERC4, ESVOC SPERC 4.3a.v1

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Title	Use descriptors
Use as an intermediate	SU3, SU8, SU9, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15, ERC6a, ESVOC SPERC 6.1a.v1
Use in Cleaning Agents	SU3, PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC10, PROC13, ERC4, ESVOC SPERC 4.4a.v1
Use in Oil and Gas field drilling and production operations	SU3, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, ERC4, (ENV)
Use in Metal working fluids / rolling oils	SU3, PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC17, ERC4, ESVOC SPERC 4.7a.v1
Use as binders and release agents	SU3, PROC1, PROC2, PROC3, PROC4, PROC6, PROC7, PROC8b, PROC10, PROC13, PROC14, ERC4, ESVOC SPERC 4.10a.v1
Use as a fuel	SU3, PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16, ERC7, ESVOC SPERC 7.12a.v1
Lubricants	SU3, PROC1, PROC2, PROC3, PROC4, PROC7, PROC8a, PROC8b, PROC9, PROC10, PROC13, PROC17, PROC18, ERC4, ERC7, ESVOC SPERC 4.6a.v1
Uses in mining operations	SU10, PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, ERC4, ESVOC SPERC 4.23.v1
Use in water treatment chemicals	SU10, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, ERC4, ESVOC SPERC 3.22a.v1
Use as Functional Fluids	SU3, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, ERC7, ESVOC SPERC 7.13a.v1
Use in laboratories	SU22, PROC15, ERC8a, ESVOC SPERC 8.17.v1
Use in Polymer processing	SU22, PROC1, PROC2, PROC6, PROC8a, PROC8b, PROC14, PROC21, ERC8a, ERC8d, ESVOC SPERC 8.21b.v1
Uses in Coatings	SU22, PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15, PROC19, ERC8a, ERC8d, ESVOC SPERC 8.3b.v1
Use in Cleaning Agents	SU22, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC10, PROC11, PROC13, ERC8a, ERC8d, ESVOC SPERC 8.4b.v1
Use in Oil and Gas field drilling and production operations	SU22, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, ERC8d
Use in Metal working fluids / rolling oils	SU22, PROC1, PROC2, PROC3, PROC5, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC17, ERC8a, ERC8d, ESVOC SPERC 8.7c.v1
Use as binders and release agents	SU22, PROC1, PROC2, PROC3, PROC4, PROC6, PROC8a, PROC8b, PROC10, PROC11, PROC14, ERC8a, ERC8d, ESVOC SPERC 8.10b.v1
Use in Agrochemicals	SU22, PROC1, PROC2, PROC4, PROC8a, PROC8b, PROC11, PROC13, ERC8a, ERC8d, ESVOC SPERC 8.11a.v1
Road and construction applications	SU22, PROC1, PROC2, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, ERC8d, ERC8f, ESVOC SPERC 8.15.v1
Use as a fuel	SU22, PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16, ERC9a, ERC9b, ESVOC SPERC 9.12b.v1
Use in water treatment chemicals	SU22, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC13, ERC8f, ESVOC SPERC 8.22b.v1
Explosives manufacture & use	SU22, PROC1, PROC3, PROC5, PROC8a, PROC8b, ERC8e, ESVOC SPERC 8.24.v1
Use as Functional Fluids	SU22, PROC1, PROC2, PROC3, PROC8a, PROC9, PROC20, ERC9a, ERC9b, ESVOC SPERC 9.13b.v1
Lubricants	SU22, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC17, PROC18, PROC20, ERC8a, ERC8d, ESVOC SPERC 8.6c.v1

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Title	Use descriptors
Lubricants	SU22, PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC10, PROC11, PROC13, PROC17, PROC18, PROC20, ERC9a, ERC9b, ESVOC SPERC 9.6b.v1
Uses in Coatings	SU21, PC1, PC4, PC8, PC9a, PC9b, PC9c, PC15, PC18, PC23, PC24, PC31, PC34, ERC8a, ERC8d, ESVOC SPERC 8.3c.v1
Use in Cleaning Agents	SU21, PC3, PC4, PC8, PC9a, PC24, PC35, PC38, ERC8a, ERC8d, ESVOC SPERC 8.4c.v1
Use in Agrochemicals	SU21, PC12, PC27, ERC8a, ERC8d, ESVOC SPERC 8.11b.v1
Use as a fuel	SU21, PC13, ERC9a, ESVOC SPERC 9.12c.v1
Lubricants	SU21, PC1, PC24, PC31, ERC8a, ERC8d, ESVOC SPERC 8.6e.v1
Lubricants	SU21, PC1, PC24, PC31, ERC9a, ERC9b, ESVOC SPERC 9.6d.v1
Use as Functional Fluids	SU21, PC16, PC17, ERC9a, ERC9b, ESVOC SPERC 9.13c.v1

Full text of use descriptors: see section 16

1.2.2. Uses advised against

Recommended use are listed above; other uses are not recommended unless an assessment has provided that risks are controlled.

1.3. Details of the supplier of the safety data sheet

Enilive S.p.A, Viale Giorgio Ribotta 51, 00144 Rome, ITALY, Tel. +39 06 59821

Competent person responsible for the safety data sheet (Reg. EC nr. 1907/2006): SDS.Enilive@enilive.com

Distributed by: Enilive Schmiertechnik GmbH, Paradiesstraße 14, 97080 Würzburg, GERMANY

Department responsible for information: Application Engineering & Product Management (AEPM), Tel. +49 (0)931-900 98-0

e-mail: technik.wuerzburg@enilive.com

1.4. Emergency telephone number

Emergency number : CNIT +39 0382 24444 (24h) (IT + EN)

Poison Center

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]

Aspiration hazard, Category 1 H304

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Aspiration into lungs can cause a chemical pneumonia. For specific information about the toxicological/ecotoxicological properties and classification of this product, see Sect. 11 and/or Sect. 12.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS08

CLP Signal word : Danger

Hazard statements (CLP) : H304 - May be fatal if swallowed and enters airways.

Precautionary statements (CLP) : P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER/doctor.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

P331 - Do NOT induce vomiting.

P501 - Dispose of contents/container to according to national or local regulations.

Nordic countries regulation

Denmark

MAL code : 00-1 (Executive Order No. 301 from 1993)

2.3. Other hazards (not relevant for classification)

Other hazards not contributing to the classification

: This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels. If the product is handled or used at high temperature, contact with hot product or vapours may cause burns. Do not wait for symptoms to develop.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

SECTION 3: Composition/information on ingredients

3.1. Substances

Name	Product identifier		Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]
Distillates (petroleum), solvent-refined light paraffinic	CAS-No.: 64741-89-5 EC-No.: 265-091-3 EC Index-No.: 649-455-00-2 REACH-no: 01-2119487067- 30	100	Asp. Tox. 1, H304

Full text of H- and EUH-statements: see section 16 Notes

this product has a value of DMSO extract < 3 % wt, according to IP 346. According to the criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product must be regarded as non carcinogenic.

3.2. Mixtures

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

First-aid measures after inhalation

- : In case of spontaneous vomiting, transport the victim to a hospital, to verify the possibility that the product has been aspired into the lungs.
- : Inhalation is unlikely because of the low vapour pressure of the substance at ambient temperature. Exposure to vapours may however occur when the substance is handled at high temperatures with poor ventilation. In case of symptoms arising from inhalation of product fumes, mists or vapour: Remove casualty to a quiet and well ventilated place if safe to do so. If casualty is unconscious and not breathing: ensure that there is no obstruction to breathing and give artificial respiration by trained personnel. If necessary, give external cardiac massage and obtain medical advice. If the casualty is breathing: Place in the recovery position. Administer oxygen if necessary. See also section 4.3.

7/16/2024 (Revision date) EN (English) 4/20

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

First-aid measures after skin contact

Take off contaminated clothing and shoes. Wash thoroughly with soap and water. Seek medical attention if skin irritation, swelling or redness develops and persists. In case of burns, cool affected part with cold running water for at least 10 min. Cover with gauze or clean cloth. Ask for medical assistance or bring to a hospital. Do not apply salves or other substances, unless by doctor's advice. Body hypothermia must be avoided. Do not put ice on the burn. DO NOT attempt to remove portions of clothing glued to burnt skin but cut

round them.

First-aid measures after eye contact : Rinse eyes thoroughly for at least 15 minutes. Keep eyelids well apart. Remove contact

lenses, if present and easy to do so. If irritation, blurred vision or swelling occurs and persists, obtain medical advice from a specialist. In case of burns, cool affected part with cold running water for at least 10 min. Cover with gauze or clean cloth. Ask for medical assistance or bring to a hospital. Do not apply salves or other substances, unless by doctor's advice. Immediately obtain specialist medical assessment and treatment for the

casualty

First-aid measures after ingestion : Do not induce vomiting to avoid aspiration into the lungs. Keep at rest. In case of spontaneous vomiting, keep head low, to avoid the risk of aspiration into the lungs. Do not

give anything by mouth to an unconscious person. If the person is conscious, rinse mouth with water without swallowing. Keep at rest. Call for medical assistance or bring to an $\frac{1}{2}$

hospital. If the casualty is unconscious, place in the recovery position.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms / injuries (general indications) : For all low-viscosity petroleum products (less than 20,5 mm2/s at 40 °C), there is the risk of aspiration into the lungs. This may occur directly after ingestion, or subsequently in case of

vomiting (spontaneous or induced). In this case there is the possibility of an inflamation of the lung tissues (chemical pneumonia). This is a serious condition requiring medical

treatment.

Symptoms/effects after inhalation : This product has a low vapour pressure, and in normal conditions at ambient temperature the concentration in the air is negligible. A significant concentration may build up only in case of sprays and mists. In these cases overexposure to mists (e.g. through prolonged

case of sprays and mists. In these cases overexposure to mists (e.g. through prolonged use in confined insufficiently ventilated spaces) may cause irritation to airways, nausea and dizziness.

Symptoms/effects after skin contact : Prolonged and repeated skin contact may cause reddening, irritation and dermatitis, due to a defatting effect. Contact with hot product may cause thermal burns.

Symptoms/effects after eye contact : Contact with eyes may cause a light transient irritation. Contact with hot product or vapours

may cause burns.

: Swallowing the liquid may cause aspiration into the lungs with the risk of chemical

pneumonitis.

Chronic symptoms : None to be reported, according to the present classification criteria.

: No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical attention if casualty has an altered state of consciousness or if symptoms do not resolve. In case of ingestion, always assume that aspiration has occurred. Send the casualty immediately to hospital. Do not wait for symptoms to develop. If necessary, drain stomach by gastric lavage ONLY under qualified medical supervision. Send the casualty immediately to hospital. If breathing stops, give artificial respiration. Administer oxygen if necessary. Seek medical attention in all cases of serious burns.

SECTION 5: Firefighting measures

Symptoms/effects upon intravenous administration

5.1. Extinguishing media

Symptoms/effects after ingestion

Suitable extinguishing media : Small-size fires: carbon dioxide, dry chemicals, foam, sand or earth. Large fires: foam or water fog (mist). These means should be used by trained personnel only. Other

extinguishing gases (according to regulations).

Unsuitable extinguishing media : Do not use water jets. They could cause splattering, and spread the fire. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

5.2. Special hazards arising from the substance or mixture

Fire hazard : This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels.

Explosion hazard : In case of losses from pressurized circuits, the sprays may form mists. Take into account that in this case the lower explosion limit for mists is about 45 g/m³ air.

7/16/2024 (Revision date) EN (English) 5/20

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Hazardous decomposition products in case of fire

: Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases. Oxygenated compounds (aldehydes, etc.).

5.3. Advice for firefighters

Firefighting instructions

Shut off source of product, if possible. If possible, move containers and drums away from the danger area, if safe to do so. Spilled product which is not burning should be covered with sand or foam. Use water sprays to cool containers and surfaces exposed to the flames. If the fire cannot be controlled, evacuate area.

Special protective equipment for firefighters

Advice for firefighters and protective measures. In case of a large fire or in confined or poorly ventilated spaces, wear full fire resistant protective clothing and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. EN 443. EN 469. EN 659.

Other information

: In case of fire, do not discharge residual product, waste materials and runoff water: collect separately and use a proper treatment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Stop or contain leak at the source, if safe to do so. Eliminate all ignition sources if safe to do so (e.g. electricity, sparks, fires, flares). Avoid direct contact with released material. Keep upwind.

6.1.1. For non-emergency personnel

Protective equipment Emergency procedures : See Section 8.

: Avoid direct contact with released material. Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency.

6.1.2. For emergency responders

Protective equipment

: Small spillages: normal antistatic working clothes are usually adequate. Large spillages: full body suit of chemically resistant and antistatic material. if necessary heat resistant and insulated. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Gloves made of PVA are not water-resistant, and are not suitable for emergency use. If contact with hot product is possible or anticipated, gloves should be heat-resistant and thermally insulated. Antistatic non-skid safety shoes or boots, chemical resistant. Work helmet. Goggles and /or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory protection: A half or full-face respirator with combined dust/organic vapour filter(s), or a Self-Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. A Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.

Emergency procedures

: If required, notify relevant authorities according to all applicable regulations.

6.2. Environmental precautions

Do not let the product accumulate in confined or underground spaces. Do not let the product flow into sewers or water courses, or in any way contaminate the environment. In case of contamination of environment compartments (soil, subsoil, surface or underground waters), remove contaminated soil when possible, and in any case treat all involved compartments in accordance with local regulations. The site should have a spill plan to ensure that adequate safeguards are in place to minimize the impact of episodic releases.

7/16/2024 (Revision date) EN (English) 6/20

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

6.3. Methods and material for containment and cleaning up

For containment

: Contain spilled liquid with sand, earth or other suitable absorbents (non-flammable). Recover free liquid and waste materials in suitable waterproof and oil-resistant containers. Clean contaminated area. Dispose of according to local regulations. Large spillages may be cautiously covered with foam, if available, to limit fire risk. Do not use direct jets. When inside buildings or confined spaces, ensure adequate ventilation. If in water: In case of small spillages in closed waters, contain product with floating barriers or other equipment. If possible, large spillages in open waters should be contained with floating barriers or other suitable mechanical means. Collect recovered product and other materials in suitable tanks or containers for recovery or safe disposal. Dispose of in accordance with relevant local regulations.

Other information

Do not use solvents or dispersants, unless specifically advised by an expert, and, if required, approved by local authorities. Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air/water temperature, wave/current direction and speed) may significantly influence the choice of appropriate actions. Local regulations may also prescribe or limit actions to be taken.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: This material is combustible, but will not ignite readily. Provide adequate ventilation. Use adequate personal protective equipment as needed. Due to the extremely slippery nature of this material, more care than usual must be exercised in material handling practices to keep off all walking surfaces. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Avoid release to the environment. Emptied containers can contain combustible product residues. Do not cut, weld, drill, burn or incinerate empty containers or drums, unless they have been drained and cleaned. If the product is stored in tanks: before entering storage tanks and commencing any operation in a confined area (e.g. tunnels), carry out an adequate clean-up, and check the atmosphere for oxygen content and flammability. See also Section 16, "Other information".

Hygiene measures

Ensure that proper housekeeping measures are in place. Avoid contact with skin. Do not breathe fume/ mist/ vapours. Do not ingest. Do not smoke. Do not eat and do not drink during use. Do not clean hands with dirty or oil-soaked rags. Keep away from food and beverages. Do not re-use clothes, if they are still contaminated. Contaminated materials should not be allowed to accumulate in the workplaces and should never be kept inside the pockets. Wash contaminated clothing before reuse. Separate working clothes from town clothes. Launder separately. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Store in dry, well-ventilated area. Keep away from open flames, hot surfaces and sources of ignition. Do not smoke.

Incompatible products

: Keep away from strong oxidizers.

Storage area

: Storage area layout, tank design, equipment and operating procedures must comply with the relevant European, national or local legislation. Storage installations/areas should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations.

Packages and containers:

: If the product is supplied in containers: Keep containers tightly closed and properly labelled. Keep only in the original container or in a suitable container for this kind of product. Empty containers may contain combustible product residues. Do not weld, solder, drill, cut or incinerate empty containers, unless they have been properly cleaned.

7/16/2024 (Revision date) EN (English) 7/20

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Packaging materials

: For containers, or container linings use materials specifically approved for use with this product. Recommended materials for containers, or container linings use mild steel, stainless steel. Some synthetic materials may be unsuitable for containers or container linings depending on the material specification and intended use. Compatibility should be checked with the manufacturer, according to the specific use conditions.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Distillates (petroleum), solvent-refined light paraffinic (64741-89-5)		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Belgium - Occupational Exposure Limits		
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
OEL STEL	2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KGV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
WEL STEL (OEL STEL)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH OEL STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	

8.1.2. Recommended monitoring procedures

Monitoring methods	
Monitoring methods	Monitoring procedures should be chosen according to the indications set by national authorities or labour contracts. Refer to relevant legislation and in any case to the good practice of industrial hygiene.

8.1.3. Air contaminants formed

No additional information available

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

8.1.4. DNEL and PNEC

Distillates (petroleum), solvent-refined light paraffinic (64741-89-5)		
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	0.97 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	2.79 mg/m³	
Long-term - local effects, inhalation	5.58 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	0.74 mg/kg bodyweight/day	
Long-term - local effects, inhalation	1.19 mg/m³	
PNEC (Oral)		
PNEC oral (secondary poisoning)	9.33 mg/kg food	
PNEC (additional information)		
Additional information	Not derived - Not classified as hazardous for environment	
Note	: The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived	

from toxicity data in accord with specific guidance within the European REACH regulation.

The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical.

OELs may be recommended by an individual company, a governmental regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH).

OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH.

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Before entering storage tanks and commencing any operation in a confined area (e.g. tunnels), carry out an adequate clean-up, and check the atmosphere for oxygen content and flammability. See also Section 16, "Other information".

8.2.2. Personal protection equipment

Personal protective equipment (for industrial or professional use):

Face shield. Gloves. Protective clothing. Safety glasses. Safety shoes or boots. Dust/aerosol mask.

Personal protective equipment symbol(s):











8.2.2.1. Eye and face protection

Eye protection:

When there is a risk of contact with the eyes, use safety goggles or other means of protection (face shield). If necessary, refer to national standards or to the EN 166 standard.

8.2.2.2. Skin protection

Skin and body protection:

Long-sleeved antistatic clothing, if necessary heat-resistant. If necessary, refer to the EN 340 and related standards, for definition of characteristics and performance according to the risk rating of the area. Antistatic non-skid safety shoes or boots, chemical resistant and insulated.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Hand protection:

When there is a risk of contact with the skin, use waterproof gloves, resistant to chemical products. Gloves must be felt-lined. Adequate materials: nitrile (NBR) or PVC with a protection index > 5 (permeation time > 240 mins). Use gloves respecting all the conditions and within the limits set by the manufacturer. Replace gloves immediately in case of cuts, holes or other signs of damages or degradation. If necessary, refer to the EN 374 standard. Personal hygiene is a key element for an effective hand care. Gloves must be worn only with clean hands. After wearing gloves, hands must be carefully washed and dried.

8.2.2.3. Respiratory protection

Respiratory protection:

Independently from other possible actions (technical modifications, operating procedures, and other means to limit the exposure of workers), personal protection equipment can be used according to necessity. Open or well ventilated spaces: in presence of mists and if the product is handled without adequate containment means: use full or half-face masks with filter for mists/aerosols. (EN 136/140/145). Combination filter device (DIN EN 141). Closed or confined areas (e.g. tank interiors): the use of protection measures for airways (masks or self-contained breathing apparatus), must be assessed according to the specific activity, as well as level and duration of predicted exposure.

8.2.2.4. Thermal hazards

Thermal hazard protection:

If contact with hot product is possible or anticipated, gloves should be heat-resistant and thermally insulated.

8.2.3. Environmental exposure controls

Environmental exposure controls:

Do not discharge the product into the environment. Storage areas/installations should be designed with adequate bunds so as to prevent ground and water pollution in case of leaks or spills. Prevent discharge of undissolved substance to or recover from onsite wastewater. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Consumer exposure controls:

Ensure adequate air ventilation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Colour : Yellow-brown.
Appearance : Liquid, bright & clear.
Molecular mass : Not applicable (UVCB)
Odour : Slight odour of petroleum.
Odour threshold : No data available

Melting point : -9 °C (pour point) (ASTM D 5950)

Freezing point : Not determined
Boiling point : Not determined
Flammability : Not flammable
Lower explosion limit : Not determined
Upper explosion limit : Not determined
Flash point : 200 °C (ASTM D 92)
Auto-ignition temperature : Not determined

Decomposition temperature : 280 °C (DSC N2), 153-209°C (DSC aria)

pH : Not applicable

Viscosity, kinematic : 14.5 – 16.5 mm²/s (40°C, ASTM D 445) Solubility : Water: Immiscible and insoluble

Log Kow : Not determined

Vapour pressure : < 0.1 hPa (20 °C)
Vapour pressure at 50 °C : Not determined

Density : 855 kg/m³ (15 °C) (ASTM D 4052)

Relative density : Not determined
Relative vapour density at 20°C : Not determined
Particle characteristics : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Explosion limits : ≥ 45 g/m³ (Aerosol)

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

9.2.2. Other safety characteristics

Relative evaporation rate (butylacetate=1) : Negligible.

Refractive index : 1.47 (20°C, ASTM 1218)

SECTION 10: Stability and reactivity

10.1. Reactivity

This substance does not offer any further hazard for reactivity, except what is reported in the following paragraphs.

10.2. Chemical stability

Stable product, according to its intrinsic properties.

10.3. Possibility of hazardous reactions

None (in normal conditions of storage and handling). Contact with strong oxidizers (peroxides, chromates, etc.) or alkali metals may cause a fire hazard. Sensitivity to heat, friction or shock cannot be assessed in advance.

10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition. Do not smoke. Avoid the build-up of electrostatic charge.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates: Toxic fumes.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified (Conclusive but not sufficient for classification)

Acute toxicity (dermal) : Not classified (Conclusive but not sufficient for classification)

Acute toxicity (inhalation) : Not classified (Conclusive but not sufficient for classification)

Distillates (petroleum), solvent-refined light paraffinic (64741-89-5)	
LD50 oral rat	> 5000 mg/kg (OECD 401)
LD50 dermal rat	> 5000 mg/kg (OECD 402)
LC50 Inhalation - Rat	> 5 mg/l/4h (OECD 403)

Skin corrosion/irritation : Not classified (Conclusive but not sufficient for classification)

pH: Not applicable

Additional information : Prolonged and repeated skin contact may cause reddening, irritation and dermatitis, due to

a defatting effect.

Serious eye damage/irritation : Not classified (Conclusive but not sufficient for classification)

pH: Not applicable

Additional information : Contact with eyes may cause temporary reddening and irritation.

(OECD 405)

Respiratory or skin sensitisation : Not classified (Conclusive but not sufficient for classification) Additional information : not sensitising.

: not sensitising. (OECD 406)

Germ cell mutagenicity : Not classified (Conclusive but not sufficient for classification)

Additional information : (OECD 471 - Ames test)

Carcinogenicity : Not classified (Conclusive but not sufficient for classification)

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Additional information	 Carcinogenicity tests results are negative. (OECD 453) this product has a value of DMSO extract < 3 % wt, according to IP 346. According to the criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product must be regarded as non carcinogenic.
Reproductive toxicity Additional information	 Not classified (Conclusive but not sufficient for classification) Tests results are negative. (OECD 414)
STOT-single exposure STOT-repeated exposure	: Not classified (Conclusive but not sufficient for classification) : Not classified (Conclusive but not sufficient for classification)
Distillatos (notroloum), solventar	refined light paraffinic (64741-89-5)

- : • : :- ::-: -:- ::-		
Distillates (petroleum), solvent-refined light paraffinic (64741-89-5)		
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)	
Aspiration hazard	: May be fatal if swallowed and enters airways.	
Additional information	 For all low-viscosity petroleum products (less than 20,5 mm2/s at 40 °C), there is the risk of aspiration into the lungs. This may occur directly after ingestion, or subsequently in case of vomiting (spontaneous or induced). In this case there is the possibility of an inflamation of the lung tissues (chemical pneumonia). This is a serious condition requiring medical treatment. Aspiration into lungs can cause a chemical pneumonia 	
Distillator (notucleum) coluent w	ofined light paraffinia (CA744 90 E)	

Distillates (petroleum), solvent-refined light paraffinic (64741-89-5)	
Viscosity, kinematic	14.5 – 16.5 mm²/s (40°C, ASTM D 445)

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties

: The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

11.2.2. Other information

Potential adverse human health effects and symptoms
Other information

: Aspiration into lungs can cause a chemical pneumonia, May be fatal if swallowed and enters airways.

: None

SECTION 12: Ecological information

12.1. Toxicity Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment. An uncontrolled release to the environment may nevertheless produce a contamination of different environmental compartments (air, soil, underground, surface water bodies, aquifers). Handle according to general working hygiene practices to avoid pollution and release into the environment. Ecology - air This product has a low vapour pressure, and in normal conditions at ambient temperature the concentration in the air is negligible. A significant concentration may build up only if the product is used at high temperature, or in case of sprays and mists. In these cases overexposure to vapours may cause irritation to airways, nausea and dizziness. Ecology - water This product is not soluble in water. It floats on water and forms a film on the surface. The damage to aquatic organisms is of mechanical kind (immobilization and entrapment) Hazardous to the aquatic environment, short-term : Not classified (Conclusive but not sufficient for classification) (acute) Hazardous to the aquatic environment, long-term : Not classified (Conclusive but not sufficient for classification) (chronic)

Distillates (petroleum), solvent-refined light paraffinic (64741-89-5)	
LC50 fish 1	> 100 mg/l (LL 50)
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

12.2. Persistence and degradability

Distillates (petroleum), solvent-refined light paraffinic (64741-89-5)	
Persistence and degradability The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent particularly in anaerobic conditions.	
Biodegradation	31 % (28d, Exxon 1995)

12.3. Bioaccumulative potential

Distillates (petroleum), solvent-refined light paraffinic (64741-89-5)		
Log Kow Not determined		
Bioaccumulative potential The test methods for this endpoint are not applicable to UVCB substances.		

12.4. Mobility in soil

Distillates (petroleum), solvent-refined light paraffinic (64741-89-5)	
Ecology - soil This product is not soluble in water. It floats on water and forms a film on the surface.	

12.5. Results of PBT and vPvB assessment

Distillates (petroleum), solvent-refined light paraffinic (64741-89-5)		
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII		
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII		
Results of PBT-vPvB assessment This substance does not meet the criteria for classification as PBT or vPvB. The production should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)		

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties

: The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

12.7. Other adverse effects

Other adverse effects Additional information : None.

: This product has no specific properties for inhibition of bacterial activity. In any case, wastewater containing this product should be treated in plants that are suited for the specific purpose.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Do not dispose of the product, either new or used, by dumping on the ground, or discharging into sewers, tunnels, lakes or water courses. Deliver to a qualified official collector.
Product/Packaging disposal recommendations	: European Waste Catalogue code(s) (Decision 2001/118/CE): 13 08 99* (oil wastes not otherwise specified - wastes not otherwise specified). This EWC code is only a general indication, and takes into account the original composition of the product and its intended use. The user has the responsibility of choosing the right EWC code, considering the actual use of the product, alterations and contaminations.
Additional information	: Empty containers may contain combustible product residues. Do not cut, weld, bore, burn or incinerate emptied containers, unless they have been cleaned and declared safe.
Ecology - waste materials	: The product as it is does not contain halogenated substances.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

EURAL code (EWC)

: 13 08 99* - wastes not otherwise specified

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID	
14.1. UN number or ID n	14.1. UN number or ID number				
Not regulated for transport					
Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.	
14.2. UN proper shippin	g name				
Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.	
14.3. Transport hazard o	class(es)				
Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.	
14.4. Packing group					
Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.	
14.5. Environmental hazards					
Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.	
No supplementary information available					

14.6. Special precautions for user

Overland transport

Not regulated.

Transport by sea

Not regulated.

Air transport

Not regulated.

Inland waterway transport

Not regulated.

Rail transport

Not regulated.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Other information, restriction and prohibition regulations

: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). (et sequens). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (et sequens). Directives 89/391/CEE, 89/654/CEE, 89/655/CEE, 89/656/CEE, 90/269/CEE, 90/270/CEE, 90/394/CEE, 90/679/CEE, 93/88/CEE, 95/63/CE, 97/42/CE, 98/24/CE, 99/38/CE, 99/92/CE, 2001/45/CE, 2003/10/CE, 2003/18/CE (Health and safety on the workplace). Directive 98/24/EC (protection of the health and safety of workers from the risks related to chemical agents at work). Directive 92/85/CE (measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding). Directive 2012/18/CE (Control of major-accident hazards involving dangerous substances). Directive 2004/42/CE (Limitation of emissions of Volatile Organic Compounds). Substances Depleting the Ozone layer (1005/2009) - Annex I Substances (ODP). Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC. Regulation EU (649/2012) - Export and Import of hazardous chemicals (PIC).

REACH Annex XVII (Restriction List)

Not listed on REACH Annex XVII

REACH Annex XIV (Authorisation List)

Not listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Not listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Not listed on the PIC list (Regulation EU 649/2012)

POP Regulation (Persistent Organic Pollutants)

Not listed on the POP list (Regulation EU 2019/1021)

Ozone Regulation (1005/2009)

Not listed on the Ozone Depletion list (Regulation EU 1005/2009)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

National adoption of EU Directives concerning health and safety on the workplace.

National adoption of EU Directives concerning control of major-accident hazards involving dangerous substances (2012/18/CE).

Relevant national laws on prevention of water pollution.

Relevant national laws on protection of the health of pregnant workers (National adoption of Dir. 92/85/EEC).

National adoption of Directive 2008/98/CE concerning disposal of used oils.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

France

Maladies professionelles (F)	
Code	Description
RG 36	Diseases caused by oils and fats of mineral or synthetic origin

Germany

Employment restrictions : Employment prohibitions or restrictions on the protection of young people at work according

to § 22 JArbSchG in the case of formation of hazardous substances have to be observed.

National Rules and Recommendations : TRGS 402: Identification and Assessment of the Risks from Activities involving Hazardous

Substances: Inhalation Exposure.

TRGS 401: Risks resulting from skin contact - identification, assessment, measures. TRGS 400: Hazard assessment for activities involving Hazardous Substances.

TRGS 500: Protective measures.

TRGS 555: Working instruction and information for workers.

TRGS 800: Fire protection measures.
TRGS 900: Occupational Exposure Limits.

VbF class (D) : Not applicable.

Water hazard class (WGK) (D) : WGK 1, Slightly hazardous to water.

WGK remark : Classification in compliance with Verwaltungsvorschriftwassergefährdender Stoffe (VwVwS)

of 27 July 2005.

Storage class (LGK, TRGS 510) : LGK 10 - Combustible liquids.

Hazardous Incident Ordinance (12. BImSchV) : Is not subject to the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

Saneringsinspanningen : C - Minimize discharge
SZW-lijst van kankerverwekkende stoffen : The substance is not listed
SZW-lijst van mutagene stoffen : The substance is not listed
SZW-lijst van reprotoxische stoffen – Borstvoeding : The substance is not listed
SZW-lijst van reprotoxische stoffen – : The substance is not listed

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen – Ontwikkeling : The substance is not listed

Denmark

MAL code : 00-1 (Executive Order No. 301 from 1993)

Danish National Regulations : Young people under 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct contact with it

Switzerland

Storage class (LK) : LK 6.1 - Toxic materials

15.2. Chemical safety assessment

A chemical safety assessment has been carried out.

SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Notes
2.3	Other hazards not contributing to the classification	Modified	
4.3	Other medical advice or treatment	Modified	
5.2	Hazardous decomposition products in case of fire	Modified	
6.1	Precautionary measures fire	Modified	
8.2	Respiratory protection	Modified	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Indication of changes			
Section	Changed item	Change	Notes
8.2	Personal protective equipment (for industrial or professional use)	Modified	
8.2	Appropriate engineering controls	Modified	
9.1	Decomposition temperature	Modified	
10.6	Hazardous decomposition products	Modified	

Abbreviations and acronyms:		
	N/A = not applicable	
	N/D = not available	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC50	Effective concentration for 50 percent of test population (median effective concentration)	
IARC	International Agency for Research on Cancer	
IATA	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Lethal concentration for 50 percent of test population (median lethal concentration)	
LD50	Lethal dose for 50 percent of test population (median lethal dose)	
LOAEL	Lowest Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
OECD	Organisation for Economic Co-operation and Development	
PBT	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals, Regulation (EC) No 1907/2006	
RID	Regulation concerning the International Carriage of Dangerous Goods by Railways	
SDS	Safety Data Sheet	
STP	Sewage treatment plant	
TLM	Median Tolerance Limit	
vPvB	Very Persistent and Very Bioaccumulative	

Data sources

: Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (et sequens). Chemical safety assessment.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Training advice : Provide adequate training to professional operators for the use of PPEs, according to the

information contained in this Safety Data Sheet. The hazard of asphyxiation is often

overlooked and must be stressed during operator training.

Other information : Do not use the product for any purposes that have not been advised by the manufacturer.

Full text of H- and EUH-statements:	
Asp. Tox. 1 Aspiration hazard, Category 1	
H304	May be fatal if swallowed and enters airways.

Full text of use descriptors		
(ENV)	Qualitative Assessment for Environment.	
(ERC)	Release fractions defined by ERC	
ERC1	Manufacture of the substance	
ERC2	Formulation of preparations	
ERC3	Formulation into solid matrix	
ERC4	Use of non-reactive processing aid at industrial site (no inclusion into or onto article)	
ERC5	Use at industrial site leading to inclusion into/onto article	
ERC6a	Use of intermediate	
ERC6b	Use of reactive processing aid at industrial site (no inclusion into or onto article)	
ERC6c	Use of monomer in polymerisation processes at industrial site (inclusion or not into/onto article)	
ERC6d	Use of reactive process regulators in polymerisation processes at industrial site (inclusion or not into/onto article)	
ERC7	Use of functional fluid at industrial site	
ERC8a	Wide dispersive indoor use of processing aids in open systems	
ERC8d	Wide dispersive outdoor use of processing aids in open systems	
ERC8e	Widespread use of reactive processing aid (no inclusion into or onto article, outdoor)	
ERC8f	Widespread use leading to inclusion into/onto article (outdoor)	
ERC9a	Wide dispersive indoor use of substances in closed systems	
ERC9b	Wide dispersive outdoor use of substances in closed systems	
ESVOC SPERC 1.1.v2	Manufacture of substances: Industrial (SU8, SU9)	
ESVOC SPERC 1.1b.v1	Distribution: Industrial (SU3)	
ESVOC SPERC 2.2.v1	Formulation & (re)packing of substances and mixtures: Industrial (SU10)	
ESVOC SPERC 3.22a.v1	Water treatment chemicals: Industrial (SU10)	
ESVOC SPERC 4.10a.v1	Use as binders and release agents: Industrial (SU3)	
ESVOC SPERC 4.19.v1	Rubber production and processing: Industrial (SU10)	
ESVOC SPERC 4.21a.v1	Polymer production: Industrial (SU10)	
ESVOC SPERC 4.23.v1	Uses in mining operations: Industrial (SU10)	
ESVOC SPERC 4.3a.v1	Uses in Coatings: Industrial (SU3)	
ESVOC SPERC 4.4a.v1	Use in Cleaning Agents: Industrial (SU3)	
ESVOC SPERC 4.6a.v1	Lubricants: Industrial (SU3)	
ESVOC SPERC 4.7a.v1	Use in Metal working fluids / rolling oils: Industrial (SU3)	
ESVOC SPERC 6.1a.v1	Manufacture of substance: Industrial (SU8, SU9)	
ESVOC SPERC 7.12a.v1	Use as a fuel: Industrial (SU3)	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Full text of use descriptors		
ESVOC SPERC 7.13a.v1	Use as Functional Fluids: Industrial (SU3)	
ESVOC SPERC 8.10b.v1	Use as binders and release agents: Professional (SU22)	
ESVOC SPERC 8.11a.v1	Use in Agrochemicals: Professional (SU22)	
ESVOC SPERC 8.11b.v1	Use in Agrochemicals: Consumer (SU21)	
ESVOC SPERC 8.15.v1	Road and construction applications: Professional (SU22)	
ESVOC SPERC 8.17.v1	Laboratory chemicals: Professional (SU22)	
ESVOC SPERC 8.21b.v1	Polymer production: Professional (SU22)	
ESVOC SPERC 8.22b.v1	Water treatment chemicals: Professional (SU22)	
ESVOC SPERC 8.24.v1	Explosives manufacture & use: Professional (SU22)	
ESVOC SPERC 8.3b.v1	Uses in Coatings: Professional (SU22)	
ESVOC SPERC 8.3c.v1	Uses in Coatings: Consumer (SU21)	
ESVOC SPERC 8.4b.v1	Use in Cleaning Agents: Professional (SU22)	
ESVOC SPERC 8.4c.v1	Use in Cleaning Agents: Consumer (SU21)	
ESVOC SPERC 8.6c.v1	Lubricants: Professional (SU22) - high environmental release	
ESVOC SPERC 8.6e.v1	Lubricants: Consumer (SU21) - high environmental release	
ESVOC SPERC 8.7c.v1	Use in Metal working fluids / rolling oils: Professional (SU22) - high environmental release	
ESVOC SPERC 9.12b.v1	Use as a fuel: Professional (SU 22)	
ESVOC SPERC 9.12c.v1	Use as a fuel: Consumer (SU21)	
ESVOC SPERC 9.13b.v1	Use as Functional Fluids: Professional (SU22)	
ESVOC SPERC 9.13c.v1	Use as Functional Fluids: Consumer (SU21)	
ESVOC SPERC 9.6b.v1	Lubricants: Professional (SU22) - low environmental release	
ESVOC SPERC 9.6d.v1	Lubricants: Consumer (SU21) - low environmental release	
PC1	Adhesives, sealants	
PC12	Fertilizers	
PC13	Fuels	
PC15	Non-metal-surface treatment products	
PC16	Heat Transfer Fluids	
PC17	Hydraulic Fluids	
PC18	Ink and Toners	
PC23	Leather treatment products	
PC24	Lubricants, greases, release products	
PC27	Plant protection products	
PC3	Air care products	
PC31	Polishes and wax blends	
PC34	Textile dyes, and impregnating products	
PC35	Washing and cleaning products	
PC38	Welding and soldering products, flux products	
PC4	Anti-Freeze and De-icing products	
PC8	Biocidal products	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Full text of use descriptors	
PC9a	Coatings and paints, thinners, paint removers
PC9b	Fillers, putties, plasters, modelling clay
PC9c	Finger paints
PROC1	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
PROC10	Roller application or brushing
PROC11	Non industrial spraying
PROC13	Treatment of articles by dipping and pouring
PROC14	Tabletting, compression, extrusion, pelettisation, granulation
PROC15	Use as laboratory reagent
PROC16	Use of fuels
PROC17	Lubrication at high energy conditions in metal working operations
PROC18	General greasing /lubrication at high kinetic energy conditions
PROC19	Manual activities involving hand contact
PROC2	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
PROC20	Use of functional fluids in small devices
PROC21	Low energy manipulation and handling of substances bound in/on materials or articles
PROC3	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
PROC4	Chemical production where opportunity for exposure arises
PROC5	Mixing or blending in batch processes
PROC6	Calendering operations
PROC7	Industrial spraying
PROC8a	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
PROC8b	Transfer of substance or mixture (charging and discharging) at dedicated facilities
PROC9	Transfer of substance or preparation into small containers (dedicated filling line, including weighing)
SU10	Formulation [mixing] of preparations and/or re-packaging (excluding alloys)
SU11	Manufacture of rubber products
SU21	Consumer uses: Private households (= general public = consumers)
SU22	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
SU3	Industrial uses: Uses of substances as such or in preparations at industrial sites
SU8	Manufacture of bulk, large scale chemicals (including petroleum products)
SU9	Manufacture of fine chemicals

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.