

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878 Revision date: 11/25/2024 Version: 1.0

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture

: Eni Grease CSX 2 TA Trade name

Product code

: Lubricant grease Type of product Formula : 1110-2022 Product group : Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Main use category : Professional use.Industrial use

Industrial/Professional use spec : Used in closed systems

Wide dispersive use

Use of the substance/mixture : General purpose lubricant

Do not use the product for any purposes that have not been advised by the manufacturer.

Function or use category : Lubricants and additives

#### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Enilive S.p.A, Viale Giorgio Ribotta 51, 00144 Rome, ITALY, Tel. +39 06 59821

Competent person responsible for the safety data sheet (Reg. EC nr. 1907/2006): SDS.Enilive@enilive.com

Distributed by: Enilive Schmiertechnik GmbH, Paradiesstraße 14, 97080 Würzburg, GERMANY

Department responsible for information: Application Engineering & Product Management (AEPM), Tel. +49 (0)931-900 98-0

e-mail: technik.wuerzburg@enilive.com

#### 1.4. Emergency telephone number

**Emergency number** : CNIT +39 0382 24444 (24h) (IT + EN)

Poison Center

#### **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]

Not classified

#### Adverse physicochemical, human health and environmental effects

Slightly irritant to eyes. Prolonged and repeated skin contact may cause reddening, irritation and dermatitis. For specific information about the toxicological/ecotoxicological properties and classification of this product, see Sect. 11 and/or Sect. 12.

#### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

**FUH-statements** : EUH208 - Contains Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with

phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched). May produce an

allergic reaction.

EUH210 - Safety data sheet available on request.

#### Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

# 2.3. Other hazards (not relevant for classification)

Other hazards not contributing to the classification

: Thermal decomposition generates toxic vapours. Prolonged and repeated skin contact may cause reddening, irritation and dermatitis. In case of contact with eyes, this product may cause irritation. Ingestion may cause nausea, vomiting and diarrhea. May cause long-term adverse effects in the environment. Any substance, in case of accidents involving pressurized circuits and the like, may be accidentally injected under the skin, even without external damage. In such a case, the victim should be brought to an hospital as soon as possible, to get specialized medical treatment. In exceptional cases (i.e prolunged storage in tanks contaminated with water, and presence of anaerobic sulfate-reducing microbial colonies), the product may undergo a degradation and generate small amounts of sulfur compounds, including H2S.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

# Component Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII Distillates (petroleum), solvent-refined heavy paraffinic, Baseoil - unspecified (64741-88-4), Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched), C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9) Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII Distillates (petroleum), solvent-refined heavy paraffinic, Baseoil - unspecified (64741-88-4), Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched), C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

#### Component

Substance(s) not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Distillates (petroleum), solvent-refined heavy paraffinic, Baseoil - unspecified (64741-88-4), Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched), C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)

#### **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Not applicable

# 3.2. Mixtures

Comments

: Composition/ Information on ingredients: Mixture of hydrocarbons Thickeners.

Additives

11/25/2024 (Revision date) EN (English) 2/25

# Safety Data Sheet

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]
Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least 100 SUS at 100 °F (19cSt at 40 °C).] (see note [*])	CAS-No.: 64741-88-4 EC-No.: 265-090-8 EC Index-No.: 649-454-00-7 REACH-no: 01-2119488706- 23	50 – 75	Asp. Tox. 1, H304
Residual oils (petroleum), solvent-dewaxed, Baseoil - unspecified (see note [*])	CAS-No.: 64742-62-7 EC-No.: 265-166-0 EC Index-No.: 649-471-00-X REACH-no: 01-2119480472- 38	35 – 50	Not classified
2-methylpentane-2,4-diol	CAS-No.: 107-41-5 EC-No.: 203-489-0 EC Index-No.: N/A REACH-no: 01-2119539582- 35	< 5	Skin Irrit. 2, H315 Eye Irrit. 2, H319
Alkaryl amine	CAS-No.: Supplier confidential EC-No.: Supplier confidential EC Index-No.: N/D REACH-no: N/D	< 5	Aquatic Chronic 4, H413
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)	EC-No.: 931-384-6 REACH-no: 01-2119493620- 38	< 5	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Eye Dam. 1, H318 Skin Sens. 1B, H317 Aquatic Chronic 2, H411
C16-18-(even numbered, saturated and unsaturated)-alkylamines	CAS-No.: 1213789-63-9 EC-No.: 627-034-4 REACH-no: 01-2119473797- 19	< 5	Acute Tox. 4 (Oral), H302 (ATE=1689 mg/kg bodyweight) Acute Tox. 4 (Dermal), H312 (ATE=2000 mg/kg bodyweight) Skin Corr. 1, H314 Eye Dam. 1, H318 STOT RE 1, H372 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)
Diphenylamine	CAS-No.: 122-39-4 EC-No.: 204-539-4 EC Index-No.: 612-026-00-5 REACH-no: N/D	< 5	Acute Tox. 3 (Inhalation), H331 (ATE=0.5 mg/l/4h) Acute Tox. 3 (Dermal), H311 (ATE=300 mg/kg bodyweight) Acute Tox. 3 (Oral), H301 (ATE=100 mg/kg bodyweight) STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

#### Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Specific concentration limits:		
Name	Product identifier	Specific concentration limits (%)
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)	EC-No.: 931-384-6 REACH-no: 01-2119493620- 38	(9.39 < C ≤ 100) Skin Sens. 1B, H317 (50 < C ≤ 100) Eye Irrit. 2, H319

Comments : Note [\*]:

this product has a value of DMSO extract < 3 % wt, according to IP 346. According to the criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product

must be regarded as non carcinogenic.

Full text of H- and EUH-statements: see section 16

#### **SECTION 4: First aid measures**

First-aid measures after ingestion

#### 4.1. Description of first aid measures

First-aid measures after inhalation : Remove to fresh air, keep the casualty warm and at rest. If breathing is difficult, give oxygen if possible, or assisted ventilation. Seek medical advice.

First-aid measures after skin contact : Take off contaminated clothing and shoes. Wash thoroughly with soap and water. If skin

irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse immediately with plenty of water. If irritation persists, seek medical advice.

: Do not induce vomiting to avoid aspiration into the lungs. If the person is conscious, rinse mouth with water without swallowing. Keep at rest. Call for medical assistance or bring to an hospital. If the casualty is inconscious, place in the recovery position. In case of spontaneous vomiting, transport the victim to a hospital, to verify the possibility that the product has been aspired into the lungs. Do not give anything by mouth to an unconscious

person.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : None under normal conditions at ambient temperatures.

Symptoms/effects after skin contact : Prolonged and repeated skin contact may cause reddening, irritation and dermatitis.

Contact with hot product may cause thermal burns.

Symptoms/effects after eye contact : Contact with eyes may cause temporary reddening and irritation. Contact with hot product or vapours may cause burns.

Symptoms/effects after ingestion : Accidental ingestion of small quantities of the product may cause irritation, nausea and gastric disturbances. Taking into account the taste of the product, however, ingestion of dangerous quantities is very unlikely.

Symptoms/effects upon intravenous administration : No information available.

Chronic symptoms : None known.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical attention if casualty has an altered state of consciousness or if symptoms do not resolve. Seek medical attention in all cases of serious burns.

#### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media : Dry chemical, CO2, or water spray or regular foam. Other extinguishing gases (according to

regulations).

Unsuitable extinguishing media : Do not use a heavy water stream. Use water stream to cool containers.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable aerosols are released in thermal decomposition.

Explosion hazard : No direct explosion hazard.

Hazardous decomposition products in case of fire : Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid

particulates, gases, including carbon monoxide, NOx (harmful/toxic gases). Oxygenated compounds (aldehydes, etc.).

11/25/2024 (Revision date) EN (English) 4/25

#### Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

#### 5.3. Advice for firefighters

Firefighting instructions

: Shut off source of product, if possible. Move undamaged containers from immediate hazard area if it can be done safely. Use water sprays to cool containers and surfaces exposed to the flames. If the fire cannot be controlled, evacuate area.

Special protective equipment for firefighters

: Personal protection equipment for firefighters (see also sect. 8). EN 443. EN 469. EN 659. In case of a large fire or in confined or poorly ventilated spaces, wear full fire resistant protective clothing and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Other information

: In case of fire, do not discharge residual product, waste materials and runoff water: collect separately and use a proper treatment.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures

: Stop or contain leak at the source, if safe to do so. Eliminate all ignition sources if safe to do so (e.g. electricity, sparks, fires, flares). Avoid direct contact with released material. Avoid accidental sprays on hot surfaces or electrical contacts. Keep upwind. Spill area may be slippery.

#### 6.1.1. For non-emergency personnel

Protective equipment Emergency procedures · See Section 8

: Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency.

#### 6.1.2. For emergency responders

Protective equipment

Do not attempt to take action without suitable protective equipment. Personal protective equipment Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters. If contact with hot product is possible or anticipated, gloves should be heat-resistant and thermally insulated. Antistatic non-skid safety shoes or boots, chemical resistant, if necessary heat resistant and insulated. Work helmet. Goggles and /or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory protection: a half or full-face respirator with filter(s) for organic vapours (AX), or a Self-contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. A Self Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.

Emergency procedures

: Notify local authorities according to relevant regulations.

## 6.2. Environmental precautions

Prevent product from entering sewers, rivers or other bodies of water, or underground spaces (tunnels, cellars, etc.). In case of contamination of environment compartments (soil, subsoil, surface or underground waters), remove contaminated soil when possible, and in any case treat all involved compartments in accordance with local regulations. The site should have a spill plan to ensure that adequate safeguards are in place to minimize the impact of episodic releases.

#### 6.3. Methods and material for containment and cleaning up

For containment

: Contain spilled liquid with sand, earth or other suitable absorbents (non-flammable). Recover free liquid and waste materials in suitable waterproof and oil-resistant containers. Clean contaminated area. Dispose of according to local regulations. Transfer collected product and other contaminated materials to suitable containers for recovery or safe disposal.

Other information

: Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air/water temperature, wave/current direction and speed) may significantly influence the choice of appropriate actions. Local regulations may also prescribe or limit actions to be taken. For this reason, local experts should be consulted when necessary.

#### Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

#### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Precautions for safe handling

This material is combustible, but will not ignite readily. Due to the extremely slippery nature of this material, more care than usual must be exercised in material handling practices to keep off all walking surfaces. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Avoid contact with skin, eyes and clothing. Do not use compressed air for filling, discharging, or handling operations. Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Use and store only outdoors or in a well-ventilated area. Emptied containers can contain combustible product residues. Do not cut, weld, drill, burn or incinerate empty containers or drums, unless they have been drained and cleaned.

Hygiene measures

Ensure that proper housekeeping measures are in place. Do not breathe fume/ mist/ vapours. Do not ingest. Do not smoke. Do not eat and do not drink during use. Do not clean hands with dirty or oil-soaked rags. Do not re-use clothes, if they are still contaminated. Keep away from food and beverages. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Separate working clothes from town clothes. Launder separately.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Store in dry, well ventilated area. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not smoke.

Incompatible products

: Keep away from: strong oxidants.

Storage area

: Storage area layout, tank design, equipment and operating procedures must comply with the relevant European, national or local legislation. Storage installations/areas should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations.

Packages and containers:

: If the product is supplied in containers: Keep containers tightly closed and properly labelled. Keep only in the original container or in a suitable container for this kind of product.

Packaging materials

: For containers, or container linings use materials specifically approved for use with this

product.

Germany

Storage class (LGK, TRGS 510) : LGK 11 - Combustible solids

**Switzerland** 

Storage class (LK) : NG - Non-hazardous

#### 7.3. Specific end use(s)

No information available.

#### **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least 100 SUS at 100 °F (19cSt at 40 °C).] (64741-88-4)

#### **Austria - Occupational Exposure Limits**

MAK (OEL TWA) 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)

#### Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least 100 SUS at 100 °F (19cSt at 40 °C).] (64741-88-4) **Belgium - Occupational Exposure Limits OEL TWA** 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) **Denmark - Occupational Exposure Limits** OFI TWA 1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) **OEL STEL** 2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) **Hungary - Occupational Exposure Limits** AK (OEL TWA) 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) **Netherlands - Occupational Exposure Limits** MAC TGG 8h (mg/m³) 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) **Spain - Occupational Exposure Limits** VLA-ED (OEL TWA) 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) VLA-EC (mg/m³) 10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) **Sweden - Occupational Exposure Limits** NGV (OEL TWA) 1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) KGV (OEL STEL) 3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) **United Kingdom - Occupational Exposure Limits** WEL TWA (OEL TWA) 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) WEL STEL (OEL STEL) 10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) **USA - ACGIH - Occupational Exposure Limits** ACGIH OEL TWA 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) ACGIH OEL STEL 10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) Residual oils (petroleum), solvent-dewaxed, Baseoil - unspecified (64742-62-7) **Austria - Occupational Exposure Limits** MAK (OEL TWA) 5 mg/m3 (Mineral base oil mist, severely refined, DMSO extract <3% m/m) **Belgium - Occupational Exposure Limits** OEL TWA 5 mg/m3 (Mineral base oil mist, severely refined, DMSO extract <3% m/m) **Denmark - Occupational Exposure Limits OEL TWA** 1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) OEL STEL 2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) **Hungary - Occupational Exposure Limits** AK (OEL TWA) 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) **Netherlands - Occupational Exposure Limits** MAC TGG 8h (mg/m³) 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) **Spain - Occupational Exposure Limits** VLA-ED (OEL TWA) 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) VLA-EC (mg/m³) 10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)

# Safety Data Sheet

Residual oils (petroleum), solvent-dewaxed, Baseoil - unspecified (64742-62-7)		
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KGV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
WEL STEL (OEL STEL)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH OEL STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
2-methylpentane-2,4-diol (107-41-5)		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	49 mg/m³	
MAK [ppm]	10 ppm	
MAK (OEL STEL)	49 mg/m³	
MAK Short time value [ppm]	10 ppm	
Belgium - Occupational Exposure Limits		
OEL TWA	123 mg/m³	
Limit value [ppm]	25 ppm	
Denmark - Occupational Exposure Limits		
OEL TWA	125 mg/m³	
	25 ppm	
OEL STEL	125 mg/m³	
Grænseværdi (kortvarig) (ppm)	25 ppm	
Finland - Occupational Exposure Limits		
HTP (OEL TWA)	120 mg/m³	
	25 ppm	
HTP (OEL STEL)	200 mg/m³	
HTP-arvo (15 min) (ppm)	40 ppm	
France - Occupational Exposure Limits		
VLE [mg/m³]	125 mg/m³	
VLE [ppm]	25 ppm	
Germany - Occupational Exposure Limits (TRGS 900)		
AGW (OEL TWA)	49 mg/m³	
	10 ppm	
Limitation of exposure peaks (mg/m³)	98 mg/m³	
Limitation of exposure peaks (ppm)	20 ppm	
Ireland - Occupational Exposure Limits		
OEL (15 min ref) (mg/m3)	125 mg/m³	

# Safety Data Sheet

Spain - Occupational Exposure Limits	1 mg/m³ Ceiling value 3 mg/m³		
IDSP (mg/m³)  Spain - Occupational Exposure Limits  /LA-EC (mg/m³)  123	3 mg/m³		
Spain - Occupational Exposure Limits  (LA-EC (mg/m³) 123	3 mg/m³		
/LA-EC (mg/m³) 123			
'LA-EC (ppm)   25 p			
	ppm		
Sweden - Occupational Exposure Limits			
	O mg/m³		
	ppm		
Inited Kingdom - Occupational Exposure Limits			
	3 mg/m³		
	ppm		
VEL STEL (OEL STEL) 123	3 mg/m³		
	ppm		
switzerland - Occupational Exposure Limits			
MAK (OEL TWA)	mg/m³		
10 p	ppm		
/LE [mg/m³] 98 r	mg/m³		
/LE [ppm] 20 p	ppm		
JSA - ACGIH - Occupational Exposure Limits			
ACGIH TLV®-STEL Ceiling (ppm) 25 p	ppm		
Diphenylamine (122-39-4)			
oustria - Occupational Exposure Limits			
MAK (OEL TWA) < 5	mg/m³		
MAK [ppm] 0.7	ppm		
MAK (OEL STEL) 10 r	mg/m³		
MAK Short time value [ppm] 1.4	ppm		
Belgium - Occupational Exposure Limits			
DEL TWA 10 r	mg/m³		
Denmark - Occupational Exposure Limits  OEL TWA 5 mg/m³  France - Occupational Exposure Limits  VLE [mg/m³] 10 mg/m³  Germany - Occupational Exposure Limits (TRGS 900)  AGW (OEL TWA) 5 mg/m³ (Inhalable aerosol)			
		imitation of exposure peaks (mg/m³) 10 r	mg/m³ (Inhalable aerosol)
		Ireland - Occupational Exposure Limits	
		DEL TWA 20 r	mg/m³
		DEL (15 min ref) (mg/m3) 10 r	mg/m³

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Diphenylamine (122-39-4)	
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	10 mg/m³
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	4 mg/m³
KGV (OEL STEL)	12 mg/m³
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	10 mg/m³
WEL STEL (OEL STEL)	20 mg/m³
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	10 mg/m³

## 8.1.2. Recommended monitoring procedures

Monitoring methods	
	Monitoring procedures should be chosen according to the indications set by national authorities or labour contracts. Refer to relevant legislation and in any case to the good practice of industrial hygiene.

#### 8.1.3. Air contaminants formed

No additional information available

#### 8.1.4. DNEL and PNEC

8.1.4. DNEL and PNEC		
Eni Grease CSX 2 TA		
DNEL/DMEL (additional information)		
Additional information	Not applicable	
PNEC (additional information)		
Additional information	Not applicable	
Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least 100 SUS at 100 °F (19cSt at 40 °C).] (64741-88-4)		
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	1 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	2.7 mg/m³	
Long-term - local effects, inhalation	5.6 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	0.74 mg/kg bodyweight/day	
Long-term - local effects, inhalation	1.2 mg/m³/day	
PNEC (Oral)		
PNEC oral (secondary poisoning)	9.33 mg/kg food	
Residual oils (petroleum), solvent-dewaxed, Baseoil - unspecified (64742-62-7)		
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	0.97 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	2.73 mg/m³	

# Safety Data Sheet

Residual oils (petroleum), solvent-dewaxed, Baseoil - unspecified (64742-62-7)		
Long-term - local effects, inhalation	5.58 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	0.74 mg/kg bodyweight/day	
Long-term - local effects, inhalation	1.19 mg/m³	
PNEC (additional information)		
Additional information	Not applicable (UVCB)	
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)		
DNEL/DMEL (Workers)		
Acute - local effects, dermal	160 μg/cm²	
Long-term - systemic effects, dermal	12.5 mg/kg bodyweight/day	
Long-term - local effects, dermal	160 μg/cm²	
Long-term - systemic effects, inhalation	4.28 mg/m³	
DNEL/DMEL (General population)		
Acute - local effects, dermal	160 μg/cm²	
Long-term - systemic effects,oral	0.25 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	1.09 mg/m³	
Long-term - systemic effects, dermal	6.25 mg/kg bodyweight/day	
Long-term - local effects, dermal	160 μg/cm²	
PNEC (Water)		
PNEC aqua (freshwater)	2.4 μg/l	
PNEC aqua (marine water)	0.24 μg/l	
PNEC aqua (intermittent, freshwater)	150 μg/l	
PNEC aqua (intermittent, marine water)	15 μg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	12.9 µg/kg dw	
PNEC sediment (marine water)	1.29 µg/kg dw	
PNEC (Soil)		
PNEC soil	1.17 µg/kg dw	
PNEC (Oral)		
PNEC oral (secondary poisoning)	10 mg/kg food	
PNEC (STP)		
PNEC sewage treatment plant 24.33 mg/l  C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)		
		DNEL/DMEL (Workers)
Acute - local effects, inhalation	1 mg/m³	
Long-term - systemic effects, dermal	0.09 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	0.38 mg/m³	
Long-term - local effects, inhalation	1 mg/m³	

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

C16-18-(even numbered, saturated and	unsaturated)-alkylamines (1213789-63-9)	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	40 μg/kg bodyweight/day	
Long-term - systemic effects, inhalation	0.035 mg/m³	
PNEC (Water)		
PNEC aqua (freshwater)	0.26 μg/l	
PNEC aqua (marine water)	0.026 μg/l	
PNEC aqua (intermittent, freshwater)	1.6 μg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	3.76 mg/kg dwt	
PNEC sediment (marine water)	0.376 mg/kg dwt	
PNEC (Soil)		
PNEC soil	10 mg/kg dwt	
PNEC (Oral)		
PNEC oral (secondary poisoning)	0.22 mg/kg food	
PNEC (STP)		
PNEC sewage treatment plant	550 μg/l	
Note	: The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived	

The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a governmental regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH.

### 8.1.5. Control banding

No additional information available

#### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

# Appropriate engineering controls:

Ensure good ventilation of the work station. Minimize exposure to mists/vapours/aerosol.

# 8.2.2. Personal protection equipment

#### Personal protective equipment (for industrial or professional use):

 ${\hbox{Gloves. Protective clothing. Safety glasses. Safety shoes or boots.}$ 

## Personal protective equipment symbol(s):









#### 8.2.2.1. Eye and face protection

#### Eye protection:

Not required for normal conditions of use. When there is a risk of contact with the skin, use waterproof gloves, resistant to chemical products. Gloves must be felt-lined.

#### Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

#### 8.2.2.2. Skin protection

#### Skin and body protection:

Non-skid safety shoes or boots, chemical resistant.

#### Hand protection:

Protective gloves. Adequate materials: nitrile (NBR) or neoprene with a protection index  $\geq$  5 (permeation time  $\geq$  240 mins). Use gloves respecting all the conditions and within the limits set by the manufacturer. Replace gloves immediately in case of cuts, holes or other signs of damages or degradation. If necessary, refer to the EN 374 standard.

#### Other skin protection

#### Materials for protective clothing:

Protective apron. DIN EN 465. DIN EN 466

#### 8.2.2.3. Respiratory protection

#### Respiratory protection:

Independently from other possible actions (technical modifications, operating procedures, and other means to limit the exposure of workers), personal protection equipment can be used according to necessity. Open or well ventilated spaces: in presence of oil mists and if the product is handled without adequate containment means: use full or half-face masks with filter for mists/aerosols. In case there is a significant presence of vapours (e.g. through handling at high temperature), use full or half-face masks with filter for hydrocarbon vapours. (EN 136/140/145). Combination filter device (DIN EN 141). Closed or confined areas (e.g. tank interiors): the use of protection measures for airways (masks or self-contained breathing apparatus), must be assessed according to the specific activity, as well as level and duration of predicted exposure. (EN 136/140/145)

#### 8.2.2.4. Thermal hazards

#### Thermal hazard protection:

None in normal use conditions.

#### 8.2.3. Environmental exposure controls

#### **Environmental exposure controls:**

Do not discharge the product into the environment. Prevent discharge of undissolved substance to or recover from onsite wastewater. Storage areas/installations should be designed with adequate bunds so as to prevent ground and water pollution in case of leaks or spills. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

#### Consumer exposure controls:

Not applicable.

#### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state : Solid
Colour : brown.
Odour : Characteristics.

Odour threshold : There are no data available on the preparation/mixture itself.

Melting point : Not determined
Freezing point : Not determined
Boiling point : Not determined
Flammability : Not flammable
Explosive properties : None.
Oxidising properties : None.

 Lower explosion limit
 : Not determined

 Upper explosion limit
 : Not determined

 Flash point
 : Not determined

 Auto-ignition temperature
 : Not determined

 Decomposition temperature
 : Not determined

pH : There are no data available on the preparation/mixture itself.

pH solution : Not available
Viscosity, kinematic : Not determined
Solubility : insoluble in water.

Water: Immiscible and insoluble

Log Kow : Not available

Log Pow : Not applicable for mixtures

#### Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Vapour pressure : Not determined
Vapour pressure at 50°C : Not determined
Density : Not determined
Relative density : Not determined
Relative vapour density at 20°C : Not determined
Particle size : Not available

#### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

Penetration : ((25°C) (ASTM D 217), Class NLGI: 2)

Drop point / drop range : > 300°C (ASTM D 566)

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

This mixture does not offer any further hazard for reactivity, except what is reported in the following paragraphs.

#### 10.2. Chemical stability

Stable product, according to its intrinsic properties (in normal conditions of storage and handling).

#### 10.3. Possibility of hazardous reactions

None (in normal conditions of storage and handling).

#### 10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

## 10.5. Incompatible materials

Strong oxidants.

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates: Toxic fumes.

#### **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

Additional information : (according to composition)

Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least 100 SUS at 100 °F (19cSt at 40 °C).] (64741-88-4)

LD50 oral rat	5000 mg/kg bodyweight
LD50 dermal rabbit	2000 - 5000 mg/kg bodyweight
LC50 Inhalation - Rat	2.18 – 5.53 mg/l/4h

#### Residual oils (petroleum), solvent-dewaxed, Baseoil - unspecified (64742-62-7)

	LD50 oral rat	5000 mg/kg bodyweight

# Safety Data Sheet

	,	
Residual oils (petroleum), solvent-dewaxed, Baseoil - unspecified (64742-62-7)		
LD50 dermal rabbit	2000 – 5000 mg/kg bodyweight	
LC50 Inhalation - Rat	2.18 – 5.53 mg/l/4h	
2-methylpentane-2,4-diol (107-41-5)		
LD50 oral rat	2000 mg/kg bodyweight	
LD50 dermal rat	2000 mg/kg bodyweight	
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)		
LD50 oral rat	≈ 2000 mg/kg bodyweight	
C16-18-(even numbered, saturated and unsa	iturated)-alkylamines (1213789-63-9)	
LD50 oral rat	1689 mg/kg bodyweight (OECD 401)	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)	
LD50 dermal rabbit	2000 mg/kg bodyweight	
Skin corrosion/irritation  Additional information	Not classified (Based on available data, the classification criteria are not met) pH: There are no data available on the preparation/mixture itself. (according to composition)	
C16-18-(even numbered, saturated and unsa		
рН	11.7 Temp.: 20 °C	
	Not classified (Based on available data, the classification criteria are not met) pH: There are no data available on the preparation/mixture itself.	
Additional information : (according to composition)  C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)		
pH	11.7 Temp.: 20 °C	
Respiratory or skin sensitisation Additional information	Not classified (Based on available data, the classification criteria are not met) (according to composition)	
Germ cell mutagenicity	Not classified (Based on available data, the classification criteria are not met)	
Additional information  Carcinogenicity	: (according to composition) : Not classified (Based on available data, the classification criteria are not met)	
Additional information	: (according to composition)  This product contains: Residual oils (petroleum), solvent-dewaxed; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of ong, branched chain hydrocarbons from a residual oil by solvent crystalli zation. It consists of hydrocarbons having carbon numbers predominantly greater than C25 and boiling above approxi mately 400 °C (752 °F).]  this product has a value of DMSO extract < 3 % wt, according to IP 346. According to the criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product must be regarded as non carcinogenic.	
Reproductive toxicity	Not classified (Based on available data, the classification criteria are not met)	
Additional information STOT-single exposure	: (according to composition) : Not classified (Based on available data, the classification criteria are not met)	
Additional information	(according to composition)	
Residual oils (petroleum), solvent-dewaxed, Baseoil - unspecified (64742-62-7)		
LOAEL (oral, rat)	125 mg/kg bw/day	
NOAEL (dermal, rat/rabbit)	1000 – 2000 mg/kg bodyweight	
NOAEC (inhalation, rat, vapour)	980 mg/m³	

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

2-methylpentane-2,4-diol (107-41-5)		
NOAEL (oral, rat, 90 days)	450 mg/kg bodyweight/day	
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)		
NOAEL (subacute, oral, animal/male, 28 days)	150 mg/kg bodyweight	
NOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat	
C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)		
NOAEL (oral, rat, 90 days)	3.25 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.	
Diphenylamine (122-39-4)		
NOAEL (oral, rat, 90 days)	3 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 452 (Chronic Toxicity Studies)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.	
Aspiration hazard : Additional information :	Not classified (Based on available data, the classification criteria are not met) (according to composition)	
Eni Grease CSX 2 TA		
Viscosity, kinematic	Not determined	
C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)		
Viscosity, kinematic	5.245 mm²/s	

#### 11.2. Information on other hazards

#### 11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

# 11.2.2. Other information

Potential adverse human health effects and symptoms

: Irritation: may cause irritation to the respiratory system, Contact with eyes may cause temporary reddening and irritation, Prolonged and repeated skin contact may cause reddening, irritation and dermatitis.

Other information : None

#### **SECTION 12: Ecological information**

#### 12.1. Toxicity

Ecology - general

: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment. An uncontrolled release to the environment may nevertheless produce a contamination of different environmental compartments (soil, underground, surface water bodies, aquifers). Handle according to general working hygiene practices to avoid pollution and release into the environment.

Ecology - water

This product is not soluble in water. It floats on water and forms a film on the surface.

Hazardous to the aquatic environment, short-term (acute)

: Not classified (Based on available data, the classification criteria are not met)

Hazardous to the aquatic environment, long-term (chronic)

: Not classified (Based on available data, the classification criteria are not met)

11/25/2024 (Revision date) EN (English) 16/25

# Safety Data Sheet

Distillates (petroleum), solvent-refined heavy	paraffinic, Baseoil - unspecified (64741-88-4)		
LC50 fish 1	100 mg/l		
EC50 Daphnia 1	10 g/l		
Residual oils (petroleum), solvent-dewaxed, Baseoil - unspecified (64742-62-7)			
LC50 fish 1	100 mg/l		
EC50 Daphnia 1	> 1000 mg/l		
NOEC chronic crustacea	10 mg/l (Test Organism: Daphnia magna)		
2-methylpentane-2,4-diol (107-41-5)			
LC50 fish 1	8.51 – 13.5 g/l		
EC50 Daphnia 1	5.41 g/l		
EC50 72h - Algae [1]	429 mg/l		
Reaction products of bis(4-methylpentan-2-yl amines, C12-14-alkyl (branched)	dithiophosphoric acid with phosphorus oxide, propylene oxide and		
LC50 fish 1	24 mg/l (Rainbow Trout)		
LC50 fish 2	8.5 mg/l (Fathead Minnow)		
EC50 Daphnia 1	91.4 mg/l		
EC50 96h - Algae [1]	6.4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)		
EC50 96h - Algae [2]	15 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)		
NOEC (acute)	1.7 – 3.3		
NOEC chronic fish	3.2 mg/l (Rainbow Trout - 4d)		
IOEC chronic crustacea 0.12 mg/l (Daphnia magna - 21 d)			
C16-18-(even numbered, saturated and unsat	urated)-alkylamines (1213789-63-9)		
LC50 fish 1	0.84 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)		
LC50 fish 2	4.21 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)		
EC50 Daphnia 1	0.32 mg/l Test organisms (species): Daphnia magna		
EC50 Daphnia 2	0.98 mg/l Test organisms (species): Daphnia magna		
EC50 72h - Algae [1]	0.46 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)		
EC50 72h - Algae [2]	0.38 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)		
LOEC (chronic)	0.032 mg/l Test organisms (species): Daphnia magna Duration: '21 d'		
NOEC (chronic)	0.013 mg/l Test organisms (species): Daphnia magna Duration: '21 d'		
NOEC chronic crustacea	0.013 mg/l (21d)		
NOEC chronic algae	0.01 mg/l (3d)		
Diphenylamine (122-39-4)			
LC50 fish 1	3.79 mg/l (96h; Pimephales promelas)		
LC50 fish 2	5.1 mg/l (48h; Oryzias latipes)		
EC50 Daphnia 1	2 mg/l Test organisms (species): Daphnia magna		

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Diphenylamine (122-39-4)		
EC50 72h - Algae [1]	2.17 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)	
ErC50 (algae)	0.18 mg/l (72h)	

#### 12.2. Persistence and degradability

•			
Eni Grease CSX 2 TA			
Persistence and degradability  A fraction of the constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately p particularly in anaerobic conditions.			
Distillates (petroleum), solvent-refined heavy	paraffinic, Baseoil - unspecified (64741-88-4)		
Persistence and degradability	Rapidly degradable		
Residual oils (petroleum), solvent-dewaxed, E	Baseoil - unspecified (64742-62-7)		
Persistence and degradability Rapidly degradable			
2-methylpentane-2,4-diol (107-41-5)			
Persistence and degradability Rapidly degradable			
Alkaryl amine (Supplier confidential)			
Persistence and degradability Rapidly degradable			
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)			
Persistence and degradability	Rapidly degradable		
Biodegradation	3.6 – 7.4 % (28d - OECD 301 B)		
C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)			
Persistence and degradability Readily biodegradable			
Biodegradation	66 % (28d) (OECD 301B)		
Diphenylamine (122-39-4)			
Persistence and degradability	Rapidly degradable		
Biodegradation	26 % (28d)		

# 12.3. Bioaccumulative potential

Eni Grease CSX 2 TA		
Log Pow	Not applicable for mixtures	
Bioaccumulative potential	Not established. According to the characteristics of the components, the product has a low biodegradability in anaerobic conditions, and may be persistent. Some of the chemical compounds that are present in the product have a potential for bioaccumulation, and may be harmful to aquatic organisms.	
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)		
og Kow 5.14 (25°C)		
C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)		
Bioconcentration factor (BCF REACH) > 500		
og Kow 4.33		

#### Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

#### 12.4. Mobility in soil

#### **Eni Grease CSX 2 TA**

Ecology - soil Product adsorbs onto the soil.

#### 12.5. Results of PBT and vPvB assessment

#### **Eni Grease CSX 2 TA**

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

Results of PBT-vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)

#### Component

Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII

Distillates (petroleum), solvent-refined heavy paraffinic, Baseoil - unspecified (64741-88-4), Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched), C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)

Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII

Distillates (petroleum), solvent-refined heavy paraffinic, Baseoil - unspecified (64741-88-4), Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched), C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)

#### 12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

#### 12.7. Other adverse effects

Other adverse effects : None.

Additional information : No other effects known

#### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Waste treatment methods

: Do not dispose of the product, either new or used, by discharging into sewers, tunnels, lakes or water courses. Deliver to a qualified official collector.

Sewage disposal recommendations

: Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed. Dispose of in a safe manner in accordance with local/national regulations.

Product/Packaging disposal recommendations

: European Waste Catalogue code(s) (Decision 2001/118/CE): 13 08 99\* (oil wastes not otherwise specified - wastes not otherwise specified). This EWC code is only a general indication, and takes into account the original composition of the product and its intended use. The user has the responsibility of choosing the right EWC code, considering the actual use of the product, alterations and contaminations.

Additional information

: Empty containers may contain combustible product residues. Do not cut, weld, drill, burn or incinerate empty containers or drums, unless they have been cleaned, and declared safe.

Ecology - waste materials EURAL code (EWC)

: The product as it is does not contain halogenated substances.

: 13 08 99\* - wastes not otherwise specified

#### **SECTION 14: Transport information**

In accordance with ADR / IMDG / IATA / ADN / RID

11/25/2024 (Revision date) EN (English) 19/25

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

ADR	IMDG	IATA	ADN	RID	
14.1. UN number or ID n	14.1. UN number or ID number				
Not regulated for transport					
14.2. UN proper shipping name					
Not regulated.	Not regulated.	Not regulated. Not regulated. Not regulated. Not regulated.			
14.3. Transport hazard class(es)					
Not regulated.	Not regulated. Not regulated. Not regulated. Not regulated.				
14.4. Packing group					
Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.	
14.5. Environmental hazards					
Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.	
None.					

# 14.6. Special precautions for user

#### **Overland transport**

Not regulated.

## Transport by sea

Not regulated.

#### Air transport

Not regulated.

#### **Inland waterway transport**

Not regulated.

#### Rail transport

Not regulated.

# 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

#### Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

#### **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Other information, restriction and prohibition regulations

: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). (et sequens). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (et sequens). Directives 89/391/CEE, 89/654/CEE, 89/655/CEE, 89/656/CEE, 90/269/CEE, 90/270/CEE, 90/394/CEE, 90/679/CEE, 93/88/CEE, 95/63/CE, 97/42/CE, 98/24/CE, 99/38/CE, 99/92/CE, 2001/45/CE, 2003/10/CE, 2003/18/CE (Health and safety on the workplace). Directive 2012/18/CE (Control of major-accident hazards involving dangerous substances). Directive 2004/42/CE (Limitation of emissions of Volatile Organic Compounds). Directive 98/24/EC (protection of the health and safety of workers from the risks related to chemical agents at work). Directive 92/85/CE (measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding). Substances Depleting the Ozone layer (1005/2009) - Annex I Substances (ODP). Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC. Regulation EU (649/2012) - Export and Import of hazardous chemicals (PIC).

#### **REACH Annex XVII (Restriction List)**

EU restriction list (REA	EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description	
3(b)	Distillates (petroleum), solvent-refined heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity of at least 100 SUS at 100 °F (19cSt at 40 °C).]; 2-methylpentane-2,4-diol; Reaction products of bis(4-methylpentan-2-yl)dithiophosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched); C16-18-(even numbered, saturated and unsaturated)-alkylamines	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(c)	Alkaryl amine; Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched); C16-18-(even numbered, saturated and unsaturated)-alkylamines	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1

#### **REACH Annex XIV (Authorisation List)**

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

#### **REACH Candidate List (SVHC)**

No ingredients are included in the REACH Candidate list (> 0,1 % m/m).

#### **PIC Regulation (Prior Informed Consent)**

Contains substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals): Diphenylamine (122-39-4)

#### **POP Regulation (Persistent Organic Pollutants)**

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

#### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

## Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

#### **Explosives Precursors Regulation (2019/1148)**

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

#### **Drug Precursors Regulation (273/2004)**

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

#### 15.1.2. National regulations

National adoption of EU Directives concerning health and safety on the workplace.

National adoption of EU Directives concerning control of major-accident hazards involving dangerous substances (2012/18/CE).

Relevant national laws on prevention of water pollution.

Relevant national laws on protection of the health of pregnant workers (National adoption of Dir. 92/85/EEC).

National adoption of Directive 2008/98/CE concerning disposal of used oils.

#### **France**

Maladies professionelles (F)		
Code Description		
RG 15	Diseases caused by aromatic amines, their salts and derivatives, especially hydroxylated, halogenated, nitrated, nitrosated and sulphonated	
RG 15 BIS	Allergic mechanism disorders caused by aromatic amines, their salts, their derivatives, especially hydroxylated, halogenated, nitrated, nitrosated, sulphonated and products containing them in the free state	
RG 36	Diseases caused by oils and fats of mineral or synthetic origin	

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid
	hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons;
	alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters;
	dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and
	dimethylsulfoxide

#### Germany

**Employment restrictions** : Employment prohibitions or restrictions on the protection of young people at work according

to § 22 JArbSchG in the case of formation of hazardous substances have to be observed.

National Rules and Recommendations TRGS 900: Occupational Exposure Limits.

TRGS 800: Fire protection measures.

TRGS 555: Working instruction and information for workers.

TRGS 402: Identification and Assessment of the Risks from Activities involving Hazardous

Substances: Inhalation Exposure.

TRGS 401: Risks resulting from skin contact - identification, assessment, measures. TRGS 400: Hazard assessment for activities involving Hazardous Substances.

TRGS 905: List of mutagenic, carcinogenic or teratogenic substances.

VbF class (D) : Not applicable.

Water hazard class (WGK) (D) WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1). WGK remark

Classification based on the components in compliance with Verwaltungsvorschrift

wassergefährdender Stoffe (VwVwS).

Hazardous Incident Ordinance (12. BImSchV) Is not subject to the Hazardous Incident Ordinance (12. BlmSchV)

#### **Netherlands**

Saneringsinspanningen : C - Minimize discharge

SZW-lijst van kankerverwekkende stoffen : None of the components are listed SZW-lijst van mutagene stoffen : None of the components are listed SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed : None of the components are listed

SZW-lijst van reprotoxische stoffen -Vruchtbaarheid

SZW-lijst van reprotoxische stoffen - Ontwikkeling

: None of the components are listed

#### **Denmark**

**Danish National Regulations** : Pregnant/breastfeeding women working with the product must not be in direct contact with it

#### 15.2. Chemical safety assessment

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

No chemical safety assessment has been carried out

#### A chemical safety assessment has been carried out for the following components of this mixture::

Residual oils (petroleum), solvent-dewaxed, Baseoil - unspecified

2-methylpentane-2.4-diol

Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)

C16-18-(even numbered, saturated and unsaturated)-alkylamines

#### **SECTION 16: Other information**

Indication of changes			
Section Changed item Change Comments			
	First issue.		

Abbreviations and acronyms:		
N/A = not applicable		
N/D = not available		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE Acute Toxicity Estimate		

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Abbreviations and acronyms:		
BCF	Bioconcentration factor	
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC50	Effective concentration for 50 percent of test population (median effective concentration)	
IARC	International Agency for Research on Cancer	
IATA	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Lethal concentration for 50 percent of test population (median lethal concentration)	
LD50	Lethal dose for 50 percent of test population (median lethal dose)	
LOAEL	Lowest Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
OECD	Organisation for Economic Co-operation and Development	
PBT	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals, Regulation (EC) No 1907/2006	
RID	Regulation concerning the International Carriage of Dangerous Goods by Railways	
SDS	Safety Data Sheet	
STP	Sewage treatment plant	
vPvB	Very Persistent and Very Bioaccumulative	

Data sources

: This Safety Data Sheet is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.

Training advice

: Provide adequate training to professional operators for the use of PPEs, according to the information contained in this Safety Data Sheet.

Other information

: Do not use the product for any purposes that have not been advised by the manufacturer.

Full text of H- and EUH-statements:		
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3	
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3	
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4	
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1	
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2	
Aquatic Chronic 4	Hazardous to the aquatic environment – Chronic Hazard, Category 4	
Asp. Tox. 1	Aspiration hazard, Category 1	
EUH208	Contains Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched). May produce an allergic reaction.	

# Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Full text of H- and EUH-statements:		
EUH210	Safety data sheet available on request.	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
H301	Toxic if swallowed.	
H302	Harmful if swallowed.	
H304	May be fatal if swallowed and enters airways.	
H311	Toxic in contact with skin.	
H312	Harmful in contact with skin.	
H314	Causes severe skin burns and eye damage.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H319	Causes serious eye irritation.	
H331	Toxic if inhaled.	
H372	Causes damage to organs through prolonged or repeated exposure.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
H411	Toxic to aquatic life with long lasting effects.	
H413	May cause long lasting harmful effects to aquatic life.	
Skin Corr. 1	Skin corrosion/irritation, Category 1	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
Skin Sens. 1B	Skin sensitisation, category 1B	
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1	
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2	

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.