

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878 Revision date: 6/12/2024 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

: Eni i-Sint tech P 0W-20 Trade name

Product code : 1116 Type of product : Lubricant Formula : 0072-2024 Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use, Consumer use

Industrial/Professional use spec : Wide dispersive use

Used in closed systems

Use of the substance/mixture : Lubricant for two-stroke engines

Do not use the product for any purposes that have not been advised by the manufacturer.

Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer:

Enilive Iberia S.L.U.

Avenida de Europa, 24, Edificio Torona B - Planta 1ª, 28108 Alcobendas (Madrid) Tel: (+34) 917 277 878 Competent person responsible for the Safety Data Sheet (Reg. EC nr. 1907/2006): SDS.Enilive@enilive.com

Distributed by: Enilive Schmiertechnik GmbH, Paradiesstraße 14, 97080 Würzburg, GERMANY, www.oilproducts.eni.com Department responsible for information: Application Engineering & Product Management (AEPM), Tel. +49 (0)931-900 98-0 e-mail: technik.wuerzburg@enilive.com

1.4. Emergency telephone number

: CNIT +39 0382 24444 (24h) (IT + EN) **Emergency number**

Poison Center

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]

Not classified

Adverse physicochemical, human health and environmental effects

For specific information about the toxicological/ecotoxicological properties and classification of this product, see Sect. 11 and/or Sect. 12.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH210 - Safety data sheet available on request.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

2.3. Other hazards (not relevant for classification)

Other hazards not contributing to the classification

: This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels. In case of contact with eyes, this product may cause irritation. If the product is handled or used at high temperature, contact with hot product or vapours may cause burns. Any substance, in case of accidents involving pressurized circuits and the like, may be accidentally injected under the skin, even without external damage. In such a case, the victim should be brought to an hospital as soon as possible, to get specialized medical treatment. Do not wait for symptoms to develop.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

Component	
1-Decene, Homopolymer, Hydrogenated (68037-01-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Mineral base oil, severely refined	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) (4259-15-8)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Component		
Distillates (petroleum), hydrotreated heavy paraffinic(64742-54-7)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	
1-Decene, Homopolymer, Hydrogenated(68037-01-4)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	
Distillates (petroleum), hydrotreated heavy paraffinic(64742-54-7)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)(4259-15-8)	The substance is not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Notes

: Composition/information on ingredients

Mixture of hydrocarbons

Additives

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]
Distillates (petroleum), hydrotreated heavy paraffinic (see note [*]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627- 25	50 – 60	Asp. Tox. 1, H304
1-Decene, Homopolymer, Hydrogenated	CAS-No.: 68037-01-4 EC-No.: 500-183-1 REACH-no: 01-2119486452- 34	60 - 70	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated heavy paraffinic (see note [*]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627- 25	10 – 15	Not classified
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (see note [*]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	CAS-No.: 72623-87-1 EC-No.: 276-738-4 EC Index-No.: 649-483-00-5 REACH-no: 01-2119474889- 13	5 - 10	Not classified
Mineral base oil, severely refined (see note [**], see note [*]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	-	2 - 4	Asp. Tox. 1, H304
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	CAS-No.: 4259-15-8 EC-No.: 224-235-5 EC Index-No.: N/A REACH-no: 01-2119493635- 27	0,6 - 1,4	Eye Dam. 1, H318 Aquatic Chronic 2, H411
salicylic acid	CAS-No.: 69-72-7 EC-No.: 200-712-3 EC Index-No.: 607-732-00-5 REACH-no: 01-2119486984- 17	0.014 – 0.139	Acute Tox. 4 (Oral), H302 (ATE=891 mg/kg bodyweight) Eye Dam. 1, H318 Repr. 2, H361d

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Specific concentration limits:		
Name	Product identifier	Specific concentration limits (%)
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	CAS-No.: 4259-15-8 EC-No.: 224-235-5 EC Index-No.: N/A REACH-no: 01-2119493635- 27	(50 < C ≤ 100) Eye Dam. 1, H318

Notes : Note [*]:

this product has a value of DMSO extract < 3 % wt, according to IP 346. According to the criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product must be regarded as non carcinogenic.

Note [**]:

this product may be formulated with one or more of the following severely refined mineral

base oils:

EC N. 265-157-1, REACH-nr:01- 2119484627-25; EC N. 265-169-7, REACH-nr:01- 2119471299-27, EC N. 265-158-7, REACH-nr:01-2119487077-29,; EC N. 265-159-2,

REACH-nr:01-2119480132-48.

All these substances have a value < 3 % wt of DMSO extract, according to IP 346 (Nota L -

Annex VI Reg (CE) 1272/2008, # 1.1.3)

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove to fresh air, keep the casualty warm and at rest.

First-aid measures after skin contact : Wash skin with soap and water. If skin irritation or rash occurs, get medical advice/attention. In case of burns, cool affected part with cold running water for at least 10 min. Cover with

gauze or clean cloth. Ask for medical assistance or bring to a hospital. Do not apply salves

or other substances, unless by doctor's advice.
First-aid measures after eye contact : Remove contact lenses, if present and easy to

: Remove contact lenses, if present and easy to do so. Rinse eyes thoroughly for at least 15 minutes. Keep eyelids well apart. If irritation, blurred vision or swelling occurs and persists,

obtain medical advice from a specialist.

First-aid measures after ingestion : Rinse mouth thoroughly with water. Give water to drink if victim completely conscious/alert.

Do not induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact : Prolonged and repeated skin contact may cause reddening, irritation and dermatitis.

Symptoms/effects after eye contact : Contact with eyes may cause temporary reddening and irritation.

Symptoms/effects after ingestion : Accidental ingestion of small quantities of the product may cause nausea, discomfort and

gastric disturbances.

Symptoms/effects upon intravenous administration : No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Small-size fires: carbon dioxide, dry chemicals, alcohol-resistant foam, sand or earth. Large fires: alcohol-resistant foam or water fog (mist). These means should be used by trained

personnel only.

Unsuitable extinguishing media : Do not use water jets. They could cause splattering, and spread the fire. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

6/12/2024 (Revision date) EN (English) 4/22

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

5.2. Special hazards arising from the substance or mixture

Fire hazard : Not flammable. The vapours are heavier than air and will accumulate in closed areas and at ground level, with backfire hazard.

Explosion hazard : In case of losses from pressurized circuits, the sprays may form mists. Take into account

that in this case the lower explosion limit for mists is about 45 g/m³ air. Vapours are heavier

than air and may spread along floors.

Hazardous decomposition products in case of fire : Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other

toxic gases.

5.3. Advice for firefighters

Firefighting instructions : Shut off source of product, if possible, move containers and drums away from

the danger area, if safe to do so. Spilled product which is not burning should be covered with sand or foam. Use water sprays to cool containers and surfaces exposed to the flames.

If the fire cannot be controlled, evacuate area.

Special protective equipment for firefighters : Wear personal protection equipment. (see chapter 8). In case of a large fire or in confined or poorly ventilated spaces, wear full fire resistant protective clothing and self-contained

poorly ventilated spaces, wear full fire resistant protective clothing and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. EN

443. EN 469. EN 659.

Other information : In case of fire, do not discharge residual product, waste materials and runoff water: collect

separately and use a proper treatment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop or contain leak at the source, if safe to do so. Eliminate all ignition sources if safe to do so (e.g. electricity, sparks, fires, flares). Avoid accidental sprays on hot surfaces or electrical

contacts. Avoid direct contact with released material. Keep upwind.

6.1.1. For non-emergency personnel

Protective equipment : See Section 8.

Emergency procedures : Keep non-involved personnel away from the area of spillage. Alert emergency personnel.

Except in case of small spillages, the feasibility of any actions should always be assessed

and advised, if possible, by a trained, competent person in charge of managing the

emergency.

6.1.2. For emergency responders

Protective equipment : Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters. Small spillages: normal antistatic working clothes are usually adequate.

Large spillages: full body suit of chemically resistant and antistatic material. if necessary heat resistant and insulated. Work helmet. Antistatic non-skid safety shoes or boots. Goggles and /or face shield, if splashes or contact with eyes is possible or anticipated. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only

SCBA's should be used.

Emergency procedures : If required, notify relevant authorities according to all applicable regulations.

6.2. Environmental precautions

Prevent liquid from entering sewers, watercourses, underground or low areas. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain spilled liquid with sand, earth or other suitable absorbents (non-flammable).

Recover free liquid and waste materials in suitable waterproof and oil-resistant containers. Clean contaminated area. Dispose of according to local regulations. If in water: Confine the spillage. Remove from surface by skimming or suitable floating absorbents. Collect recovered product and other waste materials in suitable waterproof, oil resistant containers. Recover or dispose of according to local regulations. Do not use solvents or dispersants,

unless specifically advised by an expert, and, if required, approved by local authorities.

Methods for cleaning up : Transfer recovered product and other materials to suitable tanks or containers and store/dispose according to relevant regulations.

6/12/2024 (Revision date) EN (English) 5/22

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Other information

: Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air/water temperature, wave/current direction and speed) may significantly influence the choice of appropriate actions. Local regulations may also prescribe or limit actions to be taken. For this reason, local experts should be consulted when necessary.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: This material is combustible, but will not ignite readily. Provide adequate ventilation. Use adequate personal protective equipment as needed. Due to the extremely slippery nature of this material, more care than usual must be exercised in material handling practices to keep off all walking surfaces. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Avoid release to the environment. Emptied containers can contain combustible product residues. Do not cut, weld, drill, burn or incinerate empty containers or drums, unless they have been drained and cleaned.

Handling temperature

: This product can be handled at ambient temperatures.

Hygiene measures

Ensure that proper housekeeping measures are in place. Avoid contact with skin. Do not breathe fume/ mist/ vapours. Do not ingest. Do not smoke. Do not eat and do not drink during use. Do not clean hands with dirty or oil-soaked rags. Do not re-use clothes, if they are still contaminated. Keep away from food and beverages. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Contaminated work clothing should not be allowed out of the workplace. Separate working clothes from town clothes. Launder separately.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Store in dry, well-ventilated area. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Incompatible products

Storage area

: Strong oxidizing agents.

Storage area layout, tank design, equipment and operating procedures must comply with the relevant European, national or local legislation. Storage installations/areas should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations.

Packages and containers:

If the product is supplied in containers: Keep containers tightly closed and properly labelled. Keep only in the original container or in a suitable container for this kind of product.

Packaging materials

: For containers, or container linings use materials specifically approved for use with this product. Compatibility should be checked with the manufacturer, according to the specific use conditions.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
Austria - Occupational Exposure Limits		
MAK (OEL TWA) 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Belgium - Occupational Exposure Limits		
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	

6/12/2024 (Revision date) EN (English) 6/22

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)			
Denmark - Occupational Exposure Limits	Denmark - Occupational Exposure Limits		
OEL TWA [1]	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
OEL STEL	2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Hungary - Occupational Exposure Limits			
AK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Netherlands - Occupational Exposure Limits			
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Spain - Occupational Exposure Limits			
VLA-ED (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Sweden - Occupational Exposure Limits			
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
KGV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
United Kingdom - Occupational Exposure Limits			
WEL TWA (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
WEL STEL (OEL STEL)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
USA - ACGIH - Occupational Exposure Limits			
ACGIH OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
ACGIH OEL STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)			
Austria - Occupational Exposure Limits			
MAK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Belgium - Occupational Exposure Limits			
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Denmark - Occupational Exposure Limits			
OEL TWA [1]	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
OEL STEL	2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Hungary - Occupational Exposure Limits	Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Netherlands - Occupational Exposure Limits			
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Spain - Occupational Exposure Limits			
VLA-ED (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
Sweden - Occupational Exposure Limits			
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
KGV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)		

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)		
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
WEL STEL (OEL STEL)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH OEL STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Mineral base oil, severely refined		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Belgium - Occupational Exposure Limits		
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
OEL STEL	2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KGV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
WEL STEL (OEL STEL)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH OEL STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Belgium - Occupational Exposure Limits		
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Denmark - Occupational Exposure Limits		
OEL TWA [1]	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
OEL STEL	2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KGV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
WEL STEL (OEL STEL)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH OEL STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	

Exposure limit values for the other components

8.1.2. Recommended monitoring procedures

Monitoring methods	
Monitoring methods	Monitoring procedures should be chosen according to the indications set by national authorities or labour contracts. Refer to relevant legislation and in any case to the good practice of industrial hygiene.

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

Eni i-Sint tech P 0W-20		
DNEL/DMEL (additional information)		
Additional information	Not applicable	
PNEC (additional information)		
Additional information	Not applicable	
1-Decene, Homopolymer, Hydrogenated (68037-01-4)		
DNEL/DMEL (additional information)		
Additional information	not derived	
PNEC (additional information)		
Additional information	Not derived - Not classified as hazardous for environment	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Note

: The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a governmental regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH.

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment (for industrial or professional use):

Gloves. Safety glasses.

Personal protective equipment symbol(s):





8.2.2.1. Eye and face protection

Eye protection:

When there is a risk of contact with the eyes, use safety goggles or other means of protection (face shield). If necessary, refer to national standards or to the EN 166 standard.

8.2.2.2. Skin protection

Skin and body protection:

Long-sleeved overalls. If necessary, refer to the EN 340 and related standards, for definition of characteristics and performance according to the risk rating of the area. Antistatic non-skid safety shoes or boots, chemical resistant, if necessary heat resistant and insulated.

Hand protection:

When there is a risk of contact with the skin, use waterproof gloves, resistant to chemical products. Gloves must be felt-lined. Adequate materials: nitrile (NBR) or PVC with a protection index > 5 (permeation time > 240 mins). Use gloves respecting all the conditions and within the limits set by the manufacturer. Replace gloves immediately in case of cuts, holes or other signs of damages or degradation. If necessary, refer to the EN 374 standard. Personal hygiene is a key element for an effective hand care. Gloves must be worn only with clean hands. After wearing gloves, hands must be carefully washed and dried.

8.2.2.3. Respiratory protection

Respiratory protection:

Independently from other possible actions (technical modifications, operating procedures, and other means to limit the exposure of workers), personal protection equipment can be used according to necessity. Open or well ventilated spaces: if the product is handled without adequate containment means for the vapours: use full or half-face masks with filter for hydrocarbon vapours (AX). (EN 136/140/145). Combined gas/dust mask with filter type: EN 14387. Closed or confined areas (e.g. tank interiors): the use of protection measures for airways (masks or self-contained breathing apparatus), must be assessed according to the specific activity, as well as level and duration of predicted exposure.

8.2.2.4. Thermal hazards

Thermal hazard protection:

If contact with hot product is possible or anticipated, gloves should be heat-resistant and thermally insulated.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

8.2.3. Environmental exposure controls

Environmental exposure controls:

Do not discharge the product into the environment. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed. Prevent discharge of undissolved substance to or recover from onsite wastewater. Storage areas/installations should be designed with adequate bunds so as to prevent ground and water pollution in case of leaks or spills.

Consumer exposure controls:

Wear protective gloves. Ensure adequate air ventilation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid : Light brown. Colour : Characteristics. Odour Odour threshold : Not available Melting point : Not determined : Not determined Freezing point Boiling point Not determined Flammability : Not flammable Lower explosion limit : Not determined Upper explosion limit : Not determined Flash point : > 190 °C (ASTM D 93) Auto-ignition temperature Not determined Decomposition temperature : Not determined

: Not determined рΗ

Viscosity, kinematic 42 mm²/s (40 °C) ;6,9-9,2 mm²/s (100 °C) (ASTM D 445)

Solubility This product is not soluble in water.

Log Kow Not applicable for mixtures

Vapour pressure : Not determined Vapour pressure at 50°C : Not determined Density Not determined Relative density Not determined Relative vapour density at 20°C : Not determined Particle characteristics : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

Additional information : No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

This mixture does not offer any further hazard for reactivity, except what is reported in the following paragraphs.

10.2. Chemical stability

Stable product, according to its intrinsic properties.

10.3. Possibility of hazardous reactions

None (in normal conditions of storage and handling).

10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition may produce : Carbon dioxide, Carbon monoxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met) Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met) Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

Additional information	: (according to composition)	
1-Decene, Homopolymer, Hydroger	nated (68037-01-4)	
LD50 oral rat	≥ 5000 mg/kg (OECD 401-423)	
LD50 dermal rabbit	≥ 2000 mg/kg bodyweight (OECD 402)	
LC50 Inhalation - Rat	≥ 5.2 mg/l/4h (Inhalable aerosol) (OECD 403)	
Distillates (petroleum), hydrotreate	d heavy paraffinic (64742-54-7)	
LD50 oral rat	> 5000 mg/kg (OECD 401)	
LD50 dermal rabbit	> 2000 mg/kg bodyweight (OECD 402)	
LC50 Inhalation - Rat	> 5.53 mg/l/4h (OECD 403) (EBSI, 1988)	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)		
LD50 oral rat	> 5000 mg/kg (OECD 401)	
LD50 dermal rat	> 5000 mg/kg (OECD 402)	
LC50 Inhalation - Rat	> 5 mg/l/4h (OECD 403)	
Mineral base oil, severely refined		
LD50 oral rat	> 5000 mg/kg (OECD 401)	
LD50 dermal rat	> 5000 mg/kg (OECD 402)	
LC50 Inhalation - Rat	> 5 mg/l/4h (OECD 403)	
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) (4259-15-8)	
LD50 oral rat	3100 mg/kg bodyweight	
LD50 dermal rabbit	5000 mg/kg bodyweight	
salicylic acid (69-72-7)		
LD50 oral rat	891 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 699 - 1140	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)	
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
LD50 oral rat	> 5000 mg/kg (OECD 401)	
LD50 dermal rat	> 5000 mg/kg (OECD 402)	
LD50 dermal rabbit	> 2000 mg/kg bodyweight	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Distillates (petroleum), hydrotreated heavy p	araffinic (64742-54-7)
LC50 Inhalation - Rat	> 5.53 mg/l/4h (EBSI, 1988)
Skin corrosion/irritation :	Not classified (Based on available data, the classification criteria are not met)
Additional information :	pH: Not determined (according to composition)
Distillates (petroleum), hydrotreated heavy p	araffinic (64742-54-7)
рН	Not applicable
Lubricating oils (petroleum), C20-50, hydrotro Baseoil - unspecified (72623-87-1)	eated neutral oil-based
рН	Not applicable
Mineral base oil, severely refined	
рН	Not applicable
Distillates (petroleum), hydrotreated heavy p	araffinic (64742-54-7)
рН	Not applicable
Serious eye damage/irritation	Not classified (Based on available data, the classification criteria are not met) pH: Not determined
Additional information :	(according to composition)
Distillates (petroleum), hydrotreated heavy p	araffinic (64742-54-7)
рН	Not applicable
Lubricating oils (petroleum), C20-50, hydrotro Baseoil - unspecified (72623-87-1)	eated neutral oil-based
рН	Not applicable
Mineral base oil, severely refined	
рН	Not applicable
Distillates (petroleum), hydrotreated heavy p	araffinic (64742-54-7)
рН	Not applicable
Respiratory or skin sensitisation : Additional information :	Not classified (Based on available data, the classification criteria are not met) (according to composition)
Germ cell mutagenicity :	Not classified (Based on available data, the classification criteria are not met)
Additional information : Carcinogenicity :	(according to composition) Not classified (Based on available data, the classification criteria are not met)
Additional information :	(according to composition)
	All the mineral base oils contained in this product have a value < 3 % wt of DMSO extract, according to IP 346 (Nota L - Annex VI Reg (CE) 1272/2008, # 1.1.3)
	This product contains: Lubricating oils (petroleum), C24-50, solvent-extd, dewaxed,
	hydrogenated; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by
	solvent extraction and hydrogenation of atmospheric distillation residues. It consists
	predominantly of hydrocarbons having carbon numbers predominantly in the range of C24 through C50 and produces a finished oil with a viscosity in the order of 16cSt to 75cSt at 40
	°C (104 °F).], Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified;
	[A complex combination of hydrocarbons obtained by treating a petroleum fraction with
	hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100
	SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated
	hydrocarbons.]
	this product has a value of DMSO extract < 3 % wt, according to IP 346. According to the criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product
Penraduative toxicity	must be regarded as non carcinogenic.
Reproductive toxicity :	Not classified (Based on available data, the classification criteria are not met)

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) NOAEL (animalmale, F0P) 1000 mg/kg bodyweight STOT-single exposure	Additional information :	(according to composition)				
Distillates (potroleum), hydrotreated heavy paraffinic (64742-54-7) NOAEL (animalmale, F0/P) 1000 mg/kg bodyweight STOT-single exposure Not classified (Based on available data, the classification criteria are not met) Additional information (according to composition) STOT-speaked exposure Not classified (Based on available data, the classification criteria are not met) Additional information (according to composition) Distillates (potroleum), hydrotreated heavy paraffinic (64742-54-7) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day (OECD TG 408) Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Basooil - unspecified (72623-87-1) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day (OECD TG 408) Minoral base oil, severely refined LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day (OECD TG 408) Zinc bis(D,O-bis(2-ethylhexyl)) bis(dithlophosphate) (4259-15-8) NOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day (OECD TG 408) Zinc bis(D,O-bis(2-ethylhexyl)) bis(dithlophosphate) (4259-15-8) NOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day (OECD TG 408) Zinc bis(D,O-bis(2-ethylhexyl)) 50 mg/kg bodyweight/day (OECD TG 408) Zinc bis(D,O-bis(2-ethylhexyl)) 125 mg/kg bodyweigh	Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)					
NOAEL (animal/male, F0/P) 1000 mg/kg bodyweight STOT-ingle exposure	NOAEL (animal/male, F0/P)	1000 mg/kg bodyweight				
STOT-single exposure Additional information STOT-single exposure Additional information STOT-repeated exposure Additional information STOT-repeated exposure STOT-repeated exposure Additional information STOT-repeated exposure STOT-repated exposure STOT-repeated exposure STOT-repeated exposure STOT	Distillates (petroleum), hydrotreated heavy pa	raffinic (64742-54-7)				
Additional information : (according to composition) : (STOT-repeated exposure : Not classified (Based on available data, the classification criteria are not met) : (according to composition)	NOAEL (animal/male, F0/P)	1000 mg/kg bodyweight				
STOT-repeated exposure Additional information : (according to composition) Distillatos (petroleum), hydrotreated heavy paraffinic (64742-54-7) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day (OECD TG 408) Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day (OECD TG 408) Mineral base oil, severely refined LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day (OECD TG 408) Mineral base oil, severely refined LOAEL (oral, rat, 90 days) 25 mg/kg bodyweight/day (OECD TG 408) Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) (4259-15-8) NOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day Salicylic acid (69-72-7) NOAEL (oral, rat, 90 days) 50 mg/kg bodyweight/day Salicylic acid (69-72-7) NOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day (OECD TG 408) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day (OECD TG 408) Aspiration hazard Not classified (Based on available data, the classification criteria are not met) Additional information (according to composition) Eni i-Sint tech P OW-20 Viscosity, kinematic 42 mm²/s (40 °C); 6,9-9,2 mm2/s (100 °C) (ASTM D 445) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 17.9 mm²/s (40 °C) (ASTM D 445) Mineral base oil, severely refined Viscosity, kinematic 18 mm²/s (40 °C) (ASTM D 445) Distillates (petroleum), hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1) Viscosity, kinematic 15 – 16.5 mm²/s (40 °C) (ASTM D 445) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 15 – 16.5 mm²/s (40 °C) (ASTM D 445) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 15 – 16.5 mm²/s (40 °C) (ASTM D 445)		,				
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day (OECD TG 408) Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day (OECD TG 408) Mineral base oil, severely refined LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day (OECD TG 408) Mineral base oil, severely refined LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day (OECD TG 408) Zinc bis[O,O-bis[2-ethylhexyl)] bis(dithiophosphate) (4259-15-8) NOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day Sol mg/kg bodyweight/day Salicylic acid (69-72-7) NOAEL (oral, rat, 90 days) 50 mg/kg bodyweight/day (OECD TG 408) Aspiration hazard 125 mg/kg bodyweight/day Sol mg/kg bodyweight/d	STOT-repeated exposure :	Not classified (Based on available data, the classification criteria are not met)				
LOAEL (oral, rat, 90 days) Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1) LOAEL (oral, rat, 90 days) I25 mg/kg bodyweight/day (OECD TG 408) Mineral base oil, severely refined LOAEL (oral, rat, 90 days) = 125 mg/kg bodyweight/day (OECD TG 408) Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) (4259-15-8) NOAEL (oral, rat, 90 days) I25 mg/kg bodyweight/day Salicylic acid (69-72-7) NOAEL (oral, rat, 90 days) 50 mg/kg bodyweight Animal: rat Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) LOAEL (oral, rat, 90 days) I25 mg/kg bodyweight/day (OECD TG 408) Aspiration hazard Shot classified (Based on available data, the classification criteria are not met) Additional information Eni I-Sint tech P 0W-20 Viscosity, kinematic 42 mm²/s (40 °C) (6.9-9.2 mm2/s (100 °C) (ASTM D 445) Lubricating oils (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 17.9 mm²/s (40 °C) (ASTM D 445) Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1) Viscosity, kinematic 48 mm²/s (40 °C) (ASTM D 445) Mineral base oil, severely refined Viscosity, kinematic 15 – 16.5 mm²/s (40 °C) (ASTM D 445) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)						
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day (OECD TG 408) Mineral base oil, severely refined LOAEL (oral, rat, 90 days) 2 inc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) (4259-15-8) NOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day 2 inc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) (4259-15-8) NOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day 3 incylic acid (69-72-7) NOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day (OECD TG 408) 2 incylic acid (69-72-7) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day (OECD TG 408) Aspiration hazard 1 incylic acid (69-72-7) Not classified (Based on available data, the classification criteria are not met) Additional information 2 incylic acid (69-72-7) Viscosity, kinematic 4 2 mm²/s (40 °C) (8-9-9.2 mm2/s (100 °C) (ASTM D 445) 1-Decene, Homopolymer, Hydrogenated (68037-01-4) Viscosity, kinematic 17.9 mm²/s (40 °C) (ASTM D 445) Lubricating oils (petroleum), hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1) Viscosity, kinematic 48 mm²/s (40 °C) (ASTM D 445) Mineral base oil, severely refined Viscosity, kinematic 15 – 16.5 mm²/s (40 °C) (ASTM D 445) Distillates (petroleum), hydrotreated heavy parafffinic (64742-54-7)						
Baseoil - unspecified (72623-87-1) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day (OECD TG 408) Mineral base oil, severely refined LOAEL (oral, rat, 90 days) = 125 mg/kg bodyweight/day (OECD TG 408) Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) (4259-15-8) NOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day salicylic acid (69-72-7) NOAEL (oral, rat, 90 days) 50 mg/kg bodyweight Animal: rat Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day (OECD TG 408) Aspiration hazard : Not classified (Based on available data, the classification criteria are not met) Additional information : (according to composition) Eni I-Sint tech P 0W-20 Viscosity, kinematic 42 mm²/s (40 °C); 6,9-9,2 mm2/s (100 °C) (ASTM D 445) 1-Decene, Homopolymer, Hydrogenated (68037-01-4) Viscosity, kinematic 16 mm²/s (37.8 °C) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 17.9 mm²/s (40 °C) (ASTM D 445) Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1) Viscosity, kinematic 48 mm²/s (40 °C) (ASTM D 445) Mineral base oil, severely refined Viscosity, kinematic 15 – 16.5 mm²/s (40 °C) (ASTM D 445) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		,				
Mineral base oil, severely refined LOAEL (oral, rat, 90 days) = 125 mg/kg bodyweight/day (OECD TG 408) Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) (4259-15-8) NOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day salicylic acid (69-72-7) NOAEL (oral, rat, 90 days) 50 mg/kg bodyweight Animal: rat Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day (OECD TG 408) Aspiration hazard : Not classified (Based on available data, the classification criteria are not met) Additional information : (according to composition) Eni i-Sint tech P 0W-20 Viscosity, kinematic 42 mm²/s (40 °C) :6,9-9.2 mm2/s (100 °C) (ASTM D 445) 1-Decene, Homopolymer, Hydrogenated (68037-01-4) Viscosity, kinematic 17.9 mm²/s (40 °C) (ASTM D 445) Lubricating oils (petroleum), c20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1) Viscosity, kinematic 15 – 16.5 mm²/s (40 °C) (ASTM D 445) Mineral base oil, severely refined Viscosity, kinematic 15 – 16.5 mm²/s (40 °C) (ASTM D 445) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		ated neutral oil-based				
LOAEL (oral, rat, 90 days) = 125 mg/kg bodyweight/day (OECD TG 408) Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) (4259-15-8) NOAEL (oral, rat, 90 days)	LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)				
Zinc bis[O,O-bis[2-ethylhexyl]] bis(dithiophosphate) (4259-15-8) NOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day salicylic acid (69-72-7) NOAEL (oral, rat, 90 days) 50 mg/kg bodyweight Animal: rat Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day (OECD TG 408) Aspiration hazard : Not classified (Based on available data, the classification criteria are not met) Additional information : (according to composition) Eni i-Sint tech P 0W-20 Viscosity, kinematic 42 mm²/s (40 °C) ;6,9-9,2 mm²/s (100 °C) (ASTM D 445) 1-Decene, Homopolymer, Hydrogenated (68037-01-4) Viscosity, kinematic 16 mm²/s (37,8°C) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 17.9 mm²/s (40 °C) (ASTM D 445) Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1) Viscosity, kinematic 48 mm²/s (40 °C) (ASTM D 445) Mineral base oil, severely refined Viscosity, kinematic 15 – 16.5 mm²/s (40 °C) (ASTM D 445) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	Mineral base oil, severely refined					
NOAEL (oral, rat, 90 days) salicylic acid (69-72-7) NOAEL (oral, rat, 90 days) 50 mg/kg bodyweight/day 125 mg/kg bodyweight Animal: rat bistillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day (OECD TG 408) Aspiration hazard : Not classified (Based on available data, the classification criteria are not met) Additional information : (according to composition) Eni i-Sint tech P 0W-20 Viscosity, kinematic 42 mm²/s (40 °C) :6,9-9,2 mm2/s (100 °C) (ASTM D 445) 1-Decene, Homopolymer, Hydrogenated (68037-01-4) Viscosity, kinematic 16 mm²/s (37,8°C) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 17.9 mm²/s (40 °C) (ASTM D 445) Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1) Viscosity, kinematic 48 mm²/s (40 °C) (ASTM D 445) Mineral base oil, severely refined Viscosity, kinematic 15 – 16.5 mm²/s (40 °C) (ASTM D 445) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	LOAEL (oral, rat, 90 days)	= 125 mg/kg bodyweight/day (OECD TG 408)				
Salicylic acid (69-72-7) NOAEL (oral, rat, 90 days) 50 mg/kg bodyweight Animal: rat Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day (OECD TG 408) Aspiration hazard : Not classified (Based on available data, the classification criteria are not met) Additional information : (according to composition) Eni i-Sint tech P 0W-20 Viscosity, kinematic 42 mm²/s (40 °C) ;6,9-9,2 mm2/s (100 °C) (ASTM D 445) 1-Decene, Homopolymer, Hydrogenated (68037-01-4) Viscosity, kinematic 16 mm²/s (37,8°C) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 17.9 mm²/s (40 °C) (ASTM D 445) Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1) Viscosity, kinematic 48 mm²/s (40 °C) (ASTM D 445) Mineral base oil, severely refined Viscosity, kinematic 15 – 16.5 mm²/s (40 °C) (ASTM D 445) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophos	Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) (4259-15-8)				
NOAEL (oral, rat, 90 days) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day (OECD TG 408) Aspiration hazard : Not classified (Based on available data, the classification criteria are not met) Additional information : (according to composition)	NOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day				
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) LOAEL (oral, rat, 90 days) Aspiration hazard Shot classified (Based on available data, the classification criteria are not met) Additional information Eni i-Sint tech P 0W-20 Viscosity, kinematic 42 mm²/s (40 °C); 6,9-9,2 mm2/s (100 °C) (ASTM D 445) 1-Decene, Homopolymer, Hydrogenated (68037-01-4) Viscosity, kinematic 16 mm²/s (37,8°C) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 17.9 mm²/s (40 °C) (ASTM D 445) Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1) Viscosity, kinematic 48 mm²/s (40 °C) (ASTM D 445) Mineral base oil, severely refined Viscosity, kinematic 15 – 16.5 mm²/s (40 °C) (ASTM D 445) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	salicylic acid (69-72-7)					
LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day (OECD TG 408) Aspiration hazard Additional information Eni i-Sint tech P 0W-20 Viscosity, kinematic 42 mm²/s (40 °C) ;6,9-9,2 mm2/s (100 °C) (ASTM D 445) 1-Decene, Homopolymer, Hydrogenated (68037-01-4) Viscosity, kinematic 16 mm²/s (37,8°C) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 17.9 mm²/s (40 °C) (ASTM D 445) Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1) Viscosity, kinematic 48 mm²/s (40 °C) (ASTM D 445) Mineral base oil, severely refined Viscosity, kinematic 15 – 16.5 mm²/s (40 °C) (ASTM D 445) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	NOAEL (oral, rat, 90 days)	50 mg/kg bodyweight Animal: rat				
Aspiration hazard : Not classified (Based on available data, the classification criteria are not met) Additional information : (according to composition) Eni i-Sint tech P 0W-20 Viscosity, kinematic	Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)					
Additional information : (according to composition) Eni i-Sint tech P 0W-20 Viscosity, kinematic	LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)				
Viscosity, kinematic 1-Decene, Homopolymer, Hydrogenated (68037-01-4) Viscosity, kinematic 16 mm²/s (37,8°C) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 17.9 mm²/s (40 °C) (ASTM D 445) Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1) Viscosity, kinematic 48 mm²/s (40°C) (ASTM D 445) Mineral base oil, severely refined Viscosity, kinematic 15 – 16.5 mm²/s (40 °C) (ASTM D 445) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)						
1-Decene, Homopolymer, Hydrogenated (68037-01-4) Viscosity, kinematic	Eni i-Sint tech P 0W-20					
Viscosity, kinematic Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 17.9 mm²/s (40 °C) (ASTM D 445) Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1) Viscosity, kinematic 48 mm²/s (40 °C) (ASTM D 445) Mineral base oil, severely refined Viscosity, kinematic 15 – 16.5 mm²/s (40 °C) (ASTM D 445) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	Viscosity, kinematic	42 mm²/s (40 °C) ;6,9-9,2 mm2/s (100 °C) (ASTM D 445)				
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic 17.9 mm²/s (40 °C) (ASTM D 445) Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1) Viscosity, kinematic 48 mm²/s (40 °C) (ASTM D 445) Mineral base oil, severely refined Viscosity, kinematic 15 – 16.5 mm²/s (40 °C) (ASTM D 445) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	1-Decene, Homopolymer, Hydrogenated (6803	37-01-4)				
Viscosity, kinematic 17.9 mm²/s (40 °C) (ASTM D 445) Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1) Viscosity, kinematic 48 mm²/s (40 °C) (ASTM D 445) Mineral base oil, severely refined Viscosity, kinematic 15 – 16.5 mm²/s (40 °C) (ASTM D 445) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	Viscosity, kinematic	16 mm²/s (37,8°C)				
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1) Viscosity, kinematic 48 mm²/s (40°C) (ASTM D 445) Mineral base oil, severely refined Viscosity, kinematic 15 – 16.5 mm²/s (40 °C) (ASTM D 445) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)					
Baseoil - unspecified (72623-87-1) Viscosity, kinematic 48 mm²/s (40°C) (ASTM D 445) Mineral base oil, severely refined Viscosity, kinematic 15 – 16.5 mm²/s (40 °C) (ASTM D 445) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	Viscosity, kinematic	17.9 mm²/s (40 °C) (ASTM D 445)				
Mineral base oil, severely refined Viscosity, kinematic 15 – 16.5 mm²/s (40 °C) (ASTM D 445) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		ated neutral oil-based				
Viscosity, kinematic 15 – 16.5 mm²/s (40 °C) (ASTM D 445) Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	Viscosity, kinematic	48 mm²/s (40°C) (ASTM D 445)				
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	Mineral base oil, severely refined					
	Viscosity, kinematic	15 – 16.5 mm²/s (40 °C) (ASTM D 445)				
Viscosity, kinematic 36.82 mm²/s (40 °C) (ASTM D 445)	Distillates (petroleum), hydrotreated heavy pa	raffinic (64742-54-7)				
	Viscosity, kinematic	36.82 mm²/s (40 °C) (ASTM D 445)				

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

11.2.2. Other information

Potential adverse human health effects and

symptoms

symptoms

Other information : None

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general

: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment. An uncontrolled release to the environment may nevertheless produce a contamination of different environmental compartments (soil, underground, surface water bodies, aquifers). Handle according to general working hygiene practices to avoid pollution and release into the environment.

Hazardous to the aquatic environment, short–term (acute)

: Not classified (Based on available data, the classification criteria are not met)

: Contact with eyes may cause temporary reddening and irritation.

Hazardous to the aquatic environment, long-term

: Not classified (Based on available data, the classification criteria are not met)

(chronic)			
1-Decene, Homopolymer, Hydrogenated (68037-01-4)			
LC50 fish 1	≥ 1000 mg/l (96h, Oncorhynchus mykiss)		
EC50 Daphnia 1	≥ 1000 mg/l (48 h)		
EC50 72h - Algae [1]	> 1000 mg/l		
ErC50 (algae)	≥ 1000 mg/l (72 h, Scenedesmus capricornutum)		
NOEC (chronic)	125 mg/l (21 d, Daphnia magna)		
Distillates (petroleum), hydrotreated heavy pa	raffinic (64742-54-7)		
LC50 fish 1	> 100 mg/l (LL 50)		
C50 Daphnia 1 > 10000 mg/l WAF, 48 h (OECD 202)			
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)			
LC50 fish 1	> 100 mg/l (LL 50)		
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)		
Mineral base oil, severely refined			
LC50 fish 1	> 100 mg/l (LL 50)		
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)		
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) (4259-15-8)			
LC50 fish 1	46 mg/l		
EC50 Daphnia 1	75 mg/l (OECD 202)		
EC50 72h - Algae [1]	240 – 410 mg/l (EL50)		
NOEC chronic crustacea	0.4 mg/l		

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

salicylic acid (69-72-7)			
LC50 fish 1	1370 mg/l Test organisms (species): Pimephales promelas		
EC50 Daphnia 1	870 mg/l Test organisms (species): Daphnia magna		
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)		
NOEC (chronic)	10 mg/l Test organisms (species): Daphnia magna Duration: '21 d'		
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)			
LC50 fish 1	> 100 mg/l (LL 50)		
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)		

12.2. Persistence and degradability

Eni i-Sint tech P 0W-20				
Persistence and degradability	Not available.			
1-Decene, Homopolymer, Hydrogenated (6803	37-01-4)			
Persistence and degradability	Inherently biodegradable.			
Biodegradation	≥ 47.7 % (28d)			
Distillates (petroleum), hydrotreated heavy pa	raffinic (64742-54-7)			
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.			
Lubricating oils (petroleum), C20-50, hydrotre Baseoil - unspecified (72623-87-1)	ated neutral oil-based			
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.			
Mineral base oil, severely refined				
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.			
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophos	phate) (4259-15-8)			
Biodegradation	5 % (28d) (OECD 301 D)			
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)				
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.			

12.3. Bioaccumulative potential

Eni i-Sint tech P 0W-20			
Log Kow Not applicable for mixtures			
Bioaccumulative potential Not established.			
1-Decene, Homopolymer, Hydrogenated (68037-01-4)			
Log Pow > 6.5			

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)			
Log Kow > 6			
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) (4259-15-8)			
Log Kow 3.6 (Octanol Water Coefficient test - 0,1 days)			

12.4. Mobility in soil

Eni i-Sint tech P 0W-20	
Mobility in soil	Not determined
Ecology - soil	No data available.

12.5. Results of PBT and vPvB assessment

Eni i-Sint tech P 0W-20

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

<i>~</i>	100	-	_	-	_	-	4
Uι	m	Ю	o	п	е	п	L

Component	
1-Decene, Homopolymer, Hydrogenated (68037-01-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Baseoil - unspecified (72623-87-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Mineral base oil, severely refined	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)
Zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate) (4259-15-8)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII This substance does not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

12.7. Other adverse effects

Other adverse effects : None.

Additional information : No other effects known

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation

: Disposal must be done according to official regulations.

Waste treatment methods

Do not dispose of the product, either new or used, by dumping on the ground, or discharging into sewers, tunnels, lakes or water courses. Deliver to a qualified official collector. Dispose of empty containers and wastes safely.

Sewage disposal recommendations

Dispose of in a safe manner in accordance with local/national regulations. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Product/Packaging disposal recommendations

European Waste Catalogue code(s) (Decision 2001/118/CE): 13 02 05* (mineral-based non-chlorinated engine, gear and lubricating oils), 13 02 06* (synthetic engine, gear and lubricating oils). This EWC code is only a general indication, and takes into account the original composition of the product and its intended use. The user has the responsibility of choosing the right EWC code, considering the actual use of the product, alterations and contaminations.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA ADI		RID		
14.1. UN number or ID n	14.1. UN number or ID number					
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable		
14.2. UN proper shippin	g name					
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable		
14.3. Transport hazard o	14.3. Transport hazard class(es)					
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable		
14.4. Packing group						
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable		
14.5. Environmental hazards						
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable		
None.						

14.6. Special precautions for user

Overland transport

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

Rail transport

Not applicable

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Other information, restriction and prohibition regulations

: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). (et sequens). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (et sequens). Directives 89/391/CEE, 89/654/CEE, 89/655/CEE, 89/656/CEE, 90/269/CEE, 90/270/CEE, 90/394/CEE, 90/679/CEE, 93/88/CEE, 95/63/CE, 97/42/CE, 98/24/CE, 99/38/CE, 99/92/CE, 2001/45/CE, 2003/10/CE, 2003/18/CE (Health and safety on the workplace). Directive 2012/18/CE (Control of major-accident hazards involving dangerous substances). Directive 2004/42/CE (Limitation of emissions of Volatile Organic Compounds). Directive 98/24/EC (protection of the health and safety of workers from the risks related to chemical agents at work). Directive 92/85/CE (measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding). Substances Depleting the Ozone layer (1005/2009) - Annex I Substances (ODP). Regulation EU (649/2012) - Export and Import of hazardous chemicals (PIC). POP (2019/1021) - Persistent Organic Pollutants.

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

No ingredients are included in the REACH Candidate list (> 0,1 % m/m).

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

National adoption of EU Directives concerning health and safety on the workplace.

National adoption of EU Directives concerning control of major-accident hazards involving dangerous substances (2012/18/CE).

Relevant national laws on prevention of water pollution.

Relevant national laws on protection of the health of pregnant workers (National adoption of Dir. 92/85/EEC).

National adoption of Directive 2008/98/CE concerning disposal of used oils.

Finland

Finnish National Regulations : Occupational Safety and Health Act No. 738/2002.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

France

Maladies professionelles	(F)
Code	Description
RG 36	Diseases caused by oils and fats of mineral or synthetic origin

Germany

Employment restrictions : Employment prohibitions or restrictions on the protection of young people at work according

to § 22 JArbSchG in the case of formation of hazardous substances have to be observed.

National Rules and Recommendations TRGS 400: Hazard assessment for activities involving Hazardous Substances.

> TRGS 401: Risks resulting from skin contact - identification, assessment, measures. TRGS 402: Identification and Assessment of the Risks from Activities involving Hazardous

Substances: Inhalation Exposure. TRGS 500: Protective measures.

TRGS 555: Working instruction and information for workers.

TRGS 800: Fire protection measures. TRGS 900: Occupational Exposure Limits.

VbF class (D) : Not applicable.

Water hazard class (WGK) (D) WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1).

WGK remark Classification is carried out on the basis of the Ordinance on facilities for handling substances that are hazardous to water (Verordnung über Anlagen zum Umgang mit

wassergefährdenden Stoffen (AwSV)) of 18 April 2017 (BGBI 2017, Teil I, Nr. 22, Seite

Storage class (LGK, TRGS 510) LGK 10 - Combustible liquids.

Hazardous Incident Ordinance (12. BlmSchV) Is not subject to the Hazardous Incident Ordinance (12. BlmSchV)

Netherlands

Saneringsinspanningen : C - Minimize discharge

SZW-lijst van kankerverwekkende stoffen None of the components are listed SZW-lijst van mutagene stoffen None of the components are listed SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed : None of the components are listed

SZW-lijst van reprotoxische stoffen -

Vruchtbaarheid SZW-lijst van reprotoxische stoffen - Ontwikkeling

: salicylic acid is listed

Denmark

Danish National Regulations : Young people under 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct contact with it

Norway

: Working Environment Act (LOV-2005-06-17 NO. 62). Norwegian National Regulations

People under the age of 18 may not work with this product at all.

Sweden

Swedish National Regulations : This product is in compliance with Ordinance 1998:944.

Work Environment Act (1977: 1160).

Chemical Hazards in the Working Environment (AFS 2011:19).

Switzerland

Storage class (LK) : LK 10/12 - Liquids

15.2. Chemical safety assessment

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

No chemical safety assessment has been carried out

A chemical safety assessment has been carried out for the following components of this mixture::

1-Decene, Homopolymer, Hydrogenated

Distillates (petroleum), hydrotreated heavy paraffinic

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based

Baseoil - unspecified

Mineral base oil, severely refined

Distillates (petroleum), hydrotreated heavy paraffinic

6/12/2024 (Revision date) EN (English) 20/22

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SECTION 16: Other information

Indication of changes				
Section Changed item Change Notes				
	First issue.			

Abbreviations and acronyms:	
	Complete text of the H phrases quoted in this Safety Data Sheet. These phrases are reported here for information only, and MAY NOT correspond to the classification of the product.
	N/D = not available
	N/A = not applicable
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Effective concentration for 50 percent of test population (median effective concentration)
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Lethal concentration for 50 percent of test population (median lethal concentration)
LD50	Lethal dose for 50 percent of test population (median lethal dose)
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals, Regulation (EC) No 1907/2006
RID	Regulation concerning the International Carriage of Dangerous Goods by Railways
SDS	Safety Data Sheet
STP	Sewage treatment plant
vPvB	Very Persistent and Very Bioaccumulative

Data sources

: This Safety Data Sheet is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.

Training advice

Other information

: Provide adequate training to professional operators for the use of PPEs, according to the information contained in this Safety Data Sheet.

· Do no

: Do not use the product for any purposes that have not been advised by the manufacturer.

6/12/2024 (Revision date) EN (English) 21/22

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Full text of H- and EUH-statements:		
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2	
Asp. Tox. 1	Aspiration hazard, Category 1	
EUH210	Safety data sheet available on request.	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1	
H302	Harmful if swallowed.	
H304	May be fatal if swallowed and enters airways.	
H318	Causes serious eye damage.	
H361d	Suspected of damaging the unborn child.	
H411	Toxic to aquatic life with long lasting effects.	
Repr. 2	Reproductive toxicity, Category 2	

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.