

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: AUTOL DESOLITE K

This safety data sheet pertains to the following products:

11900 = AUTOL DESOLITE K

11980 = AUTOL DESOLITE K

UFI: PWP9-VEAK-Y30C-H325

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use: Fuel additive.

1.3 Details of the supplier of the safety data sheet

Company name: Enilive Schmiertechnik GmbH

Street/POB-No.: Paradiesstraße 14

Postal Code, city: 97080 Würzburg

Germany

E-mail: info.wuerzburg@enilive.com

Telephone: +49 (0)931-90098-0

Telefax: +49 (0)931-98442

Department responsible for information:

Application Engineering & Product Management (AEPM)

Telephone: +49 (0)931-90098-0

E-mail: technik.wuerzburg@enilive.com

1.4 Emergency telephone number

GIZ-Nord, Göttingen

Telephone: +49 (0)551-19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to EC regulation 1272/2008 (CLP)

Asp. Tox. 1; H304 May be fatal if swallowed and enters airways.

(EUH066) Repeated exposure may cause skin dryness or cracking.

2.2 Label elements

Labelling (CLP)



Signal word: **Danger**

Hazard statements: H304

May be fatal if swallowed and enters airways.

EUH066

Repeated exposure may cause skin dryness or cracking.



AUTOL DESOLITE K

Material number 11900_11980

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 27.3.2025
Version: 4.3
Replaces version: 4.2
Language: en-DE
Date of print: 30.4.2025

Page: 2 of 11

Precautionary statements:

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P405	Store locked up.
P501	Dispose of contents/container to hazardous or special waste collection point.

Special labelling

Text for labelling: Contains Distillates (petroleum), hydrotreated light

2.3 Other hazards

Special danger of slipping by leaking/spilling product.

Endocrine disrupting properties, Results of PBT and vPvB assessment:

The product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances: not applicable

3.2 Mixtures

Chemical characterisation: Mixture of hydrocarbons

Hazardous ingredients:

Identifiers	Designation Classification	Content
REACH 01-2119456620-43-xxxx list no. 926-141-6 CAS 64742-47-8	Distillates (petroleum), hydrotreated light Asp. Tox. 1; H304. (EUH066).	>= 90 %

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:	If medical advice is needed, have product container or label at hand. Take off contaminated clothing and wash it before reuse.
In case of inhalation:	Remove person to fresh air and keep comfortable for breathing. Seek medical attention if problems persist.
Following skin contact:	Immediately clean with water and soap followed by thorough rinsing. In case of skin reactions, consult a physician.
After eye contact:	Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Remove contact lenses, if present and easy to do. Continue rinsing. Subsequently consult an ophthalmologist.
After swallowing:	Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do not induce vomiting. Caution if victim vomits: Risk of aspiration! Keep airway open. Immediately get medical attention.

4.2 Most important symptoms and effects, both acute and delayed

May be fatal if swallowed and enters airways.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Aspiration hazard: in case of swallowing or vomiting danger of penetration into the lungs.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:

Water mist, foam, extinguishing powder and carbon dioxide.

Extinguishing media which must not be used for safety reasons:

Full water jet

5.2 Special hazards arising from the substance or mixture

Combustible. May form dangerous gases and vapours in case of fire.

Furthermore, there may develop: carbon monoxide and carbon dioxide.

5.3 Advice for firefighters

Special protective equipment for firefighters:

Wear self-contained positive pressure breathing apparatus and fire fighter's clothing conforming to European standard EN 469.

Additional information:

Do not allow fire water to penetrate into surface or ground water.

Fire residuals and contaminated extinguishing water must be disposed of in accordance with the regulations of the local authorities.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Do not breathe mist/vapours/spray. Avoid contact with the substance.

If possible, eliminate leakage. Provide adequate ventilation.

Wear appropriate protective equipment. Take off contaminated clothing and wash it before reuse. Keep unprotected people away.

6.2 Environmental precautions

Do not allow to enter into ground-water, surface water or drains.

If necessary, notify appropriate authorities.

6.3 Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents) and place in closed containers for disposal.

Never return spills in original containers for re-use.

Additional information:

Special danger of slipping by leaking/spilling product.

6.4 Reference to other sections

Refer additionally to section 8 and 13.



AUTOL DESOLITE K

Material number 11900_11980

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 27.3.2025
Version: 4.3
Replaces version: 4.2
Language: en-DE
Date of print: 30.4.2025

Page: 4 of 11

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed. Do not breathe mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Wear appropriate protective equipment.
Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Take off contaminated clothing and wash it before reuse.
Have eye wash bottle or eye rinse ready at work place.

Precautions against fire and explosion:
Keep away from heat.
When handling larger quantities, take precautionary measures against electrostatic charging.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:
Keep container tightly closed and in a well-ventilated place.
Keep container dry. Keep only in the original container.
Protect from heat and direct sunlight.
Store containers in upright position.

Hints on joint storage: Keep away from food, drink and animal feedingstuffs.

Storage class: 10 = Combustible liquids that cannot be assigned to any of the above storage classes

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values:

CAS No.	Designation	Type	Limit value
64742-47-8	Distillates (petroleum), hydrotreated light	Germany: DFG Kurzzeit	20 mg/m ³ (Aerosol, respirable fraction)
		Germany: DFG Langzeit	5 mg/m ³ (Aerosol, respirable fraction)
		Germany: TRGS 900 Kurzzeit	600 mg/m ³ (hydrocarbons, aliphatic, C9-C14)
		Germany: TRGS 900 Langzeit	300 mg/m ³ (hydrocarbons, aliphatic, C9-C14)

8.2 Exposure controls

Provide good ventilation and/or an exhaust system in the work area.



AUTOL DESOLITE K

Material number 11900_11980

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 27.3.2025
Version: 4.3
Replaces version: 4.2
Language: en-DE
Date of print: 30.4.2025

Page: 5 of 11

Personal protection equipment

Occupational exposure controls

- Respiratory protection: Respiratory protection must be worn whenever the WEL levels have been exceeded. The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection: Protective gloves according to DIN EN ISO 374-1. Observe glove manufacturer's instructions concerning penetrability and breakthrough time.
- Eye protection: Tightly sealed goggles according to DIN EN ISO 16321-1.
- Body protection: Wear suitable protective clothing.
- General protection and hygiene measures:
Do not breathe mist/vapours/spray. Do not get in eyes, on skin, or on clothing.
Take off contaminated clothing and wash it before reuse.
Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.
Have eye wash bottle or eye rinse ready at work place.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.
In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state at 20 °C and 101.3 kPa	liquid
Colour:	colourless
Odour:	No data available
Odour threshold:	No data available
Melting point/freezing point:	≤ -39 °C
Initial boiling point and boiling range:	190 - 280 °C (Distillates (petroleum), hydrotreated light)
Flammability:	No data available
Upper/lower flammability or explosive limits:	LEL (Lower Explosion Limit): 0,50 Vol-% (Distillates (petroleum), hydrotreated light) UEL (Upper Explosive Limit): 8,00 Vol-% (Distillates (petroleum), hydrotreated light)
Flash point/flash point range:	80 °C (c.c.)
Decomposition temperature:	No data available
pH:	Not applicable
Viscosity, kinematic:	at 40 °C: 1,7 mm ² /s
Water solubility:	Insoluble
Partition coefficient: n-octanol/water:	6 - 8 log P(o/w) (Distillates (petroleum), hydrotreated light) Based on the n-octanol/water partition coefficient accumulation in organisms is possible.
Vapour pressure:	at 20 °C: $\leq 0,05$ kPa (Distillates (petroleum), hydrotreated light)
Density:	at 15 °C: 0,805 g/mL
Vapour density:	≥ 1 (Air =1; Distillates (petroleum), hydrotreated light)



AUTOL DESOLITE K

Material number 11900_11980

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 27.3.2025
Version: 4.3
Replaces version: 4.2
Language: en-DE
Date of print: 30.4.2025

Page: 6 of 11

Particle characteristics:

Not applicable

9.2 Other information

Explosive properties:

No data available

Oxidizing characteristics:

No data available

Auto-ignition temperature:

> 230 °C (Distillates (petroleum), hydrotreated light)

Evaporation rate:

600 (Ether (anhydrous)) = 1; Distillates (petroleum), hydrotreated light)

Additional information:

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Refer to subsection "Possibility of hazardous reactions".

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4 Conditions to avoid

Keep away from heat sources, sparks and open flames.
Protect from direct sunlight.

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

No hazardous decomposition products when regulations for storage and handling are observed.

Thermal decomposition:

No data available



AUTOL DESOLITE K

Material number 11900_11980

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 27.3.2025
Version: 4.3
Replaces version: 4.2
Language: en-DE
Date of print: 30.4.2025

Page: 7 of 11

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological effects: The statements are derived from the properties of the single components. No toxicological data is available for the product as such.

Acute toxicity (oral): Based on available data, the classification criteria are not met.
ATEmix (calculated): ATE > 5.000 mg/kg

Acute toxicity (dermal): Based on available data, the classification criteria are not met.
ATEmix (calculated): ATE > 5.000 mg/kg

Acute toxicity (inhalative): Based on available data, the classification criteria are not met.
ATEmix (calculated): ATE > 50 mg/L

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/irritation: Based on available data, the classification criteria are not met.

Sensitisation to the respiratory tract: Based on available data, the classification criteria are not met.

Skin sensitisation: Lack of data.

Germ cell mutagenicity/Genotoxicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): Lack of data.

Specific target organ toxicity (repeated exposure): Lack of data.

Aspiration hazard: Asp. Tox. 1; H304 = May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties:

No data available

Other information:

Information about Distillates (petroleum), hydrotreated light:
LD50, Rat, oral: > 5.000 mg/kg (OECD 401)
LD50, Rabbit, dermal: > 5.000 mg/kg (OECD 402)
LC50, Rat, inhalative: > 5.000 mg/m³/8h (vapour; OECD 403)

Symptoms

In case of ingestion: Nausea, vomiting.
After contact with skin:
Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

SECTION 12: Ecological information

12.1 Toxicity

Water Hazard Class: 1 = slightly hazardous to water (Self-classification (mixture).)



AUTOL DESOLITE K

Material number 11900_11980

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 27.3.2025
Version: 4.3
Replaces version: 4.2
Language: en-DE
Date of print: 30.4.2025

Page: 8 of 11

12.2 Persistence and degradability

Further details: Information about Distillates (petroleum), hydrotreated light: 69 %/28d
Readily biodegradable (according to OECD criteria) (OECD 301F).

12.3 Bioaccumulative potential

Partition coefficient: n-octanol/water:
6 - 8 log P(o/w) (Distillates (petroleum), hydrotreated light)
Based on the n-octanol/water partition coefficient accumulation in organisms is possible.

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

The product does not contain any substances classified as PBT or vPvB.

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

General information: Do not allow to enter into ground-water, surface water or drains.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste key number: 13 07 03* = Other fuels (including mixtures)
* = Evidence for disposal must be provided.
Recommendation: Dispose of waste according to applicable legislation.
Do not dispose of with household waste.

Package

Recommendation: Dispose of waste according to applicable legislation.
Handle contaminated packages in the same way as the substance itself.

Section 14. Transport information

14.1 UN number or ID number

ADR/RID, IMDG, IATA-DGR:
not applicable
ADN: ID 9003

14.2 UN proper shipping name

ADR/RID, IMDG, IATA-DGR:
Not restricted
ADN: ID 9003,
SUBSTANCES WITH A FLASH-POINT ABOVE 60 °C AND NOT MORE THAN 100 °C



AUTOL DESOLITE K

Material number 11900_11980

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 27.3.2025
Version: 4.3
Replaces version: 4.2
Language: en-DE
Date of print: 30.4.2025

Page: 9 of 11

14.3 Transport hazard class(es)

ADR/RID, IMDG, IATA-DGR:

not applicable

ADN:

Class 9, Code: M12

14.4 Packing group

ADR/RID, ADN, IMDG, IATA-DGR:

not applicable

14.5 Environmental hazards

Dangerous for the environment:

Substance/mixture is not environmentally hazardous according to the criteria of the UN model regulations.

Marine pollutant - IMDG:

no

14.6 Special precautions for user

Inland waterway craft (ADN)

Hazard label:

-

Transport permitted:

T

Equipment necessary:

PP

14.7 Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations - Germany

Storage class: 10 = Combustible liquids that cannot be assigned to any of the above storage classes

Water Hazard Class: 1 = slightly hazardous to water (Self-classification (mixture).)

Technical guidance air: 5.2.5

Information on working limitations:

Observe employment restrictions for young people.

Observe employment restrictions for expectant or nursing mothers.

Further regulations, limitations and legal requirements:

The product is not subject to the Chemicals Prohibition Ordinance (ChemVerbotsV).

National regulations - EC member states

Further regulations, limitations and legal requirements:

Use restriction according to REACH annex XVII, no.: 3



AUTOL DESOLITE K

Material number 11900_11980

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 27.3.2025
Version: 4.3
Replaces version: 4.2
Language: en-DE
Date of print: 30.4.2025

Page: 10 of 11

Further regulations, limitations and legal requirements

Inventory of chemical substances Australia (AIIC): All ingredients are listed or exempt from listing.

Inventory of chemical substances Canada: All ingredients are listed or exempt from listing.

Inventory of chemical substances China (IECSC): All ingredients are listed or exempt from listing.

Inventory of chemical substances European Union: All ingredients are listed or exempt from listing.

Inventory of chemical substances Japan (ENCS): All ingredients are listed or exempt from listing.

Inventory of chemical substances Japan (ISHL): All ingredients are listed or exempt from listing.

Inventory of chemical substances Korea (KECI): All ingredients are listed or exempt from listing.

Inventory of chemical substances New Zealand (NZIoC): All ingredients are listed or exempt from listing.

Inventory of chemical substances the Philippines (PICCS): All ingredients are listed or exempt from listing.

Inventory of chemical substances Taiwan (TCSI):

All ingredients are listed or exempt from listing.

Toxic and Concerned Chemical Substance Control Act (TCCSCA): Not listed.

Inventory of chemical substances USA (TSCA): All ingredients are listed or exempt from listing.

15.2 Chemical Safety Assessment

For this mixture a chemical safety assessment is not required.

SECTION 16: Other information

Classification procedure: Health hazards: Calculation method

Wording of the H-phrases under paragraph 2 and 3:

H304 = May be fatal if swallowed and enters airways.

EUH066 = Repeated exposure may cause skin dryness or cracking.

Reason of change: Changes in section 1: Changes of product list

Date of first version: 18.1.2021

Department issuing data sheet:

see section 1: Department responsible for information



AUTOL DESOLITE K

Material number 11900_11980

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Revision date: 27.3.2025
Version: 4.3
Replaces version: 4.2
Language: en-DE
Date of print: 30.4.2025

Page: 11 of 11

Abbreviations and acronyms:

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
AS/NZS: Australian Standards/New Zealand Standards
Asp. Tox.: Aspiration toxicity
ATE: Acute toxicity estimate
ATEmix: Acute Toxicity Estimate of mixture
CAS: Chemical Abstracts Service
CFR: Code of Federal Regulations
CLP: Classification, Labelling and Packaging
DMEL: Derived minimal effect level
DNEL: Derived no-effect level
EC: European Community
EmS: Emergency Response Procedures for Ships Carrying Dangerous Goods
EN: European Standard
EQ: Excepted quantities
EU: European Union
IATA: International Air Transport Association
IATA-DGR: International Air Transport Association – Dangerous Goods Regulations
IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IMDG Code: International Maritime Dangerous Goods Code
IMO: International Maritime Organization
LC50: Median lethal concentration
LD50: Lethal dose 50%
LEL: Lower Explosion Limit
log P(o/w): Partition coefficient: octanol/water
MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD: Organisation for Economic Co-operation and Development
OEL: Occupational Exposure Limit Value
OSHA: Occupational Safety and Health Administration
PBT: Persistent, bioaccumulative and toxic
PICCS: Philippine Inventory of Chemicals and Chemical Substances
PNEC: Predicted no-effect concentration
REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals
RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail
TLV: Threshold Limit Value
TRGS: Technical Rules for Hazardous Substances
vPvB: Very persistent and very bioaccumulative
WEL: Workplace Exposure Limit

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.

Most recent product information is available at:
<http://sumdat.net/yvbyk91t>

