

Material number 600

Revision date: 20.3.2024
Version: 5.0
Replaces version: 4.0
Language: en-DE
Date of print: 4.4.2024

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU)

2020/878 Page: 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Eni i-care superclean winter -30° gebrauchsfertig

UFI: GY00-R0DY-100A-3CJM

1.2 Relevant identified uses of the substance or mixture and uses advised against

General use: Antifreeze and/or cleaning additive for windscreen wiper unit.

1.3 Details of the supplier of the safety data sheet

Company name: Enilive Schmiertechnik GmbH

Street/POB-No.: Paradiesstraße 14
Postal Code, city: 97080 Würzburg

Germany

E-mail: info.wuerzburg@enilive.com

Telephone: +49 (0)931-90098-0 Telefax: +49 (0)931-98442

Department responsible for information:

Application Engineering & Product Management (AEPM)

Telephone: +49 (0)931-90098-0 E-mail: technik.wuerzburg@enilive.com

1.4 Emergency telephone number

GIZ-Nord, Göttingen

Telephone: +49 (0)551-19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to EC regulation 1272/2008 (CLP)

Flam. Liq. 3; H226 Flammable liquid and vapour.

2.2 Label elements

Labelling (CLP)



Signal word: Warning

Hazard statements: H226 Flammable liquid and vapour.

printed by Eni Schmiertechnik GmbH



Material number 600

Revision date: 20.3.2024
Version: 5.0
Replaces version: 4.0
Language: en-DE
Date of print: 4.4.2024

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU)

2020/878 Page: 2 of 13

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P280 Wear protective gloves/protective clothing/eye protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse

skin with water or shower.

P403+P235 Store in a well-ventilated place. Keep cool.

Special labelling

Text for labelling:

Labelling for contents according to regulation (EC) No 648/2004, annex VII:

Contains:

- Dyestuff, perfumes

2.3 Other hazards

Potentially explosive mixtures may form if adequate ventilation is not provided. Inhaling can lead to irritations of the respiratory tract and mucous membrane. Higher doses may lead to a narcotic effect.

Special danger of slipping by leaking/spilling product.

Endocrine disrupting properties, Results of PBT and vPvB assessment:

CAS No.	Designation	PBT/vPvB	ED Human	ED Environment
78-93-3	Butanone		List II	

SECTION 3: Composition/information on ingredients

3.1 Substances: not applicable

3.2 Mixtures

Chemical characterisation: Aqueous solution

Hazardous ingredients:

Identifiers	Designation Classification	Content
REACH 01-2119457610-43-xxxx	Ethanol	< 50 %
EC No. 200-578-6 CAS 64-17-5	Flam. Liq. 2; H225. Eye Irrit. 2; H319.	
	Specific concentration limits (SCL): Eye Irrit. 2; H319: C ≥ 50 %	
EC No. 201-159-0	Butanone	< 1 %
CAS 78-93-3	Flam. Liq. 2; H225. Eye Irrit. 2; H319. STOT SE 3; H336. (EUH066).	

Full text of H- and EUH-statements: see section 16.



Material number 600

Revision date: 20.3.2024
Version: 5.0
Replaces version: 4.0
Language: en-DE
Date of print: 4.4.2024

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU)

78 Page: 3 of 13

Additional information: Contains

Contains Denatonium benzoate.

Labelling for contents according to regulation (EC) No 648/2004, annex VII:

Contains:

- Dyestuff, perfumes

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: If medical advice is needed, have product container or label at hand. Take off

contaminated clothing and wash it before reuse. First aider: Pay attention to self-protection!

In case of inhalation: Remove person to fresh air and keep comfortable for breathing. In the event of discomfort

seek medical treatment.

Following skin contact: Immediately clean with water and soap followed by thorough rinsing. In case of skin

reactions, consult a physician.

After eye contact: Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids

apart. Remove contact lenses, if present and easy to do. Continue rinsing.

In case of eye irritation consult an ophthalmologist.

After swallowing: Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an

unconscious person. Do not induce vomiting. Seek medical attention.

4.2 Most important symptoms and effects, both acute and delayed

In case of inhalation:

Inhaling can lead to irritations of the respiratory tract and mucous membrane.

Higher doses may lead to a narcotic effect.

After contact with skin:

Frequently or prolonged contact with skin may cause dermal irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:

Water spray jet, alcohol resistant foam, extinguishing powder.

Extinguishing media which must not be used for safety reasons:

Full water jet.

5.2 Special hazards arising from the substance or mixture

Flammable liquid and vapour. Air combined with vapours may form potentially explosive mixtures that are heavier than air. Vapours may proceed on the ground over great distances and cause fire and backflashes.

May form dangerous gases and vapours in case of fire.

Furthermore, there may develop: Carbon monoxide and carbon dioxide.



Material number 600

Revision date: 20.3.2024
Version: 5.0
Replaces version: 4.0
Language: en-DE
Date of print: 4.4.2024

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU)

Page: 4 of 13

5.3 Advice for firefighters

Special protective equipment for firefighters:

Wear self-contained positive pressure breathing apparatus and fire fighter's clothing

conforming to European standard EN 469.

Additional information: Heating will lead to pressure increase: Danger of bursting and explosion. Keep containers

cool with water spray.

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the

risk of explosion.

Do not allow fire water to penetrate into surface or ground water.

Fire residuals and contaminated extinguishing water must be disposed of in accordance

with the regulations of the local authorities.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid breathing mist/vapours/spray. Avoid contact with the substance. In case of leakage, eliminate all ignition sources. If possible, eliminate leakage. Provide adequate ventilation. Wear appropriate protective equipment. Keep unprotected people away.

Cordon off downwind area at risk and warn inhabitants.

Take off contaminated clothing and wash it before reuse.

6.2 Environmental precautions

Do not allow to enter into ground-water, surface water or drains. Danger of explosion! In case of release, notify competent authorities.

6.3 Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

Beware of reignition. Thoroughly clean surrounding area. In case of greater quantities: Collect mechanically (use only explosion-proof equipment when pumping out). Never

return spills in original containers for re-use.

Additional information: Use explosion-proof equipment and non-sparking tools/utensils.

Special danger of slipping by leaking/spilling product.

6.4 Reference to other sections

Refer additionally to section 8 and 13.



Material number 600

Revision date: 20.3.2024
Version: 5.0
Replaces version: 4.0
Language: en-DE
Date of print: 4.4.2024

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU) 2020/878

Page: 5 of 13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling: Provide adequate ventilation, and local exhaust as needed. Avoid breathing

mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Wear appropriate

protective equipment.

Do not eat, drink or smoke when using this product. Wash hands thoroughly after

handling. Take off contaminated clothing and wash it before reuse.

Guarantee sufficient ventilation during and after use, in order to prevent vapour

accumulation.

When handling large quantities, supply emergency spray.

Precautions against fire and explosion:

Keep away from sources of ignition - No smoking. Take action to prevent static discharges.

Use only explosion-protected equipment/instruments. Do not weld.

In partially filled containers explosive mixtures may form.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:

Keep container tightly closed and in a well-ventilated place. Keep container dry. Keep only in the original container.

Protect from heat and direct sunlight. Store containers in upright position.

Hints on joint storage: Keep away from food, drink and animal feedingstuffs.

Storage class: 3 = Flammable liquids

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values:

CAS No.	Designation	Туре	Limit value
64-17-5	Ethanol	Germany: TRGS 900 Kurzzeit Germany: TRGS 900 Langzeit	1.520 mg/m³; 800 ppm 380 mg/m³; 200 ppm
78-93-3	Butanone	Europe: IOELV: STEL Europe: IOELV: TWA Germany: TRGS 900 Kurzzeit	900 mg/m³; 300 ppm 600 mg/m³; 200 ppm 600 mg/m³; 200 ppm (may be absorbed through the skin)
		Germany: TRGS 900 Langzeit	600 mg/m³; 200 ppm (may be absorbed through the skin)

Biological limit values:

CAS No.	Designation	Туре	Limit value	Parameter	Sampling
78-93-3	Butanone	Germany: TRGS 903,	2 mg/L	2-Butanone	end of exposure or end of
		urine			shift



Material number 600

Revision date: 20.3.2024
Version: 5.0
Replaces version: 4.0
Language: en-DE
Date of print: 4.4.2024

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU)

0/878 Page: 6 of 13

DNEL/DMEL: Contains Ethanol:

DNEL workers, long-term, systemic, inhalative: 380 mg/m³ DNEL workers, long-term, systemic, dermal: 343 mg/kg bw/d DNEL consumers, long-term, systemic, inhalative: 114 mg/m³ DNEL consumers, short-term, local, inhalative: 950 mg/m³ DNEL consumers, long-term, systemic, dermal: 206 mg/kg bw/d DNEL consumers, long-term, systemic, oral: 87 mg/kg bw/d

PNEC: Contains Ethanol:

PNEC water (freshwater): 0,96 mg/L PNEC water (marine water): 0,79 mg/L PNEC sewage treatment plant: 580 mg/L PNEC sediment (freshwater): 3,6 mg/kg dw PNEC sediment (marine water): 2,9 mg/kg dw

PNEC soil: 0,63 mg/kg dw PNEC oral: 0,38 g/kg Food

8.2 Exposure controls

Provide good ventilation and/or an exhaust system in the work area.

Personal protection equipment

Occupational exposure controls

Respiratory protection: Respiratory protection must be worn whenever the WEL levels have been exceeded.

Use filter type A (= against vapours of organic substances) according to BS EN 14387.

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

Hand protection: Protective gloves according to DIN EN 374.

Glove material:

Permanent contact: Butyl caoutchouc (butyl rubber), fluoro rubber

Splash guard: Nitrile rubber, chloroprene rubber

Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

Eye protection: Tightly sealed goggles according to DIN EN ISO 16321-1:2022.

Body protection: Flame retardant, antistatic and chemical resistant protective clothing.

General protection and hygiene measures:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

Avoid breathing mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Take off

contaminated clothing and wash it before reuse.

Contaminated work clothing should not be allowed out of the workplace. When using do not eat or drink. Wash hands thoroughly after handling.

When handling large quantities, supply emergency spray.

Environmental exposure controls

Refer to "6.2 Environmental precautions".



Material number 600

Revision date: 20.3.2024
Version: 5.0
Replaces version: 4.0
Language: en-DE
Date of print: 4.4.2024

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU)

2020/878 Page: 7 of 13

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state at 20 °C and 101.3 kPa liquid
Colour: blue
Clear

Odour: Citrus

Odour threshold:

Melting point/freezing point:

No data available

No data available

No data available
approx. 76 °C

Flammable liquid and vapour.

Upper/lower flammability or explosive limits: LEL (Lower Explosion Limit): 2,50 Vol-%

UEL (Upper Explosive Limit): 13,50 Vol-%

Flash point/flash point range: approx. 25 °C

Auto-ignition temperature: > 363 °C

Decomposition temperature:

PH:

at 20 °C: approx. 7

Viscosity, kinematic:

No data available

Water solubility:

Completely miscible

Partition coefficient: n-octanol/water:

Vapour pressure:

No data available

at 20 °C: 59 hPa

Density: at 20 °C: approx. 0,94 g/mL

Vapour density: No data available
Particle characteristics: Not applicable

9.2 Other information

Explosive properties: Vapours can form explosive mixtures with air.

Oxidizing characteristics: No data available

Auto-ignition temperature: Not self-igniting

Evaporation rate: No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Flammable liquid and vapour.

Vapours can form explosive mixtures with air.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Heating will lead to pressure increase: Danger of bursting and explosion.

printed by Eni Schmiertechnik GmbH



Material number 600

Revision date: 20.3.2024
Version: 5.0
Replaces version: 4.0
Language: en-DE
Date of print: 4.4.2024

8 of 13

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU)

2020/878 Page:

10.4 Conditions to avoid

Keep away from heat sources, sparks and open flames. Protect from direct sunlight.

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

No decomposition when used properly.

Thermal decomposition: No data available

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological effects:

The statements are derived from the properties of the single components. No toxicological data is available for the product as such.

Acute toxicity (oral): Based on available data, the classification criteria are not met.

Acute toxicity (dermal): Based on available data, the classification criteria are not met.

Acute toxicity (inhalative): Based on available data, the classification criteria are not met.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/irritation: Based on available data, the classification criteria are not

Sensitisation to the respiratory tract: Based on available data, the classification criteria

Skin sensitisation: Based on available data, the classification criteria are not met.

Germ cell mutagenicity/Genotoxicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure): Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties:

This product contains a substance that has endocrine disrupting properties with respect

to humans.

Other information: Information about Ethanol:

LD50 Rat, oral: 10.470 mg/kg (OECD 401)

LD50 Rabbit, dermal: 17.100 mg/kg

LC50 Rat, inhalative (vapour): 116,9 mg/L/4h (OECD 403)



Material number 600

Revision date: 20.3.2024
Version: 5.0
Replaces version: 4.0
Language: en-DE
Date of print: 4.4.2024

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU)

B Page: 9 of 13

Symptoms

In case of inhalation:

Inhaling can lead to irritations of the respiratory tract and mucous membrane.

Higher doses may lead to a narcotic effect.

After contact with skin:

Frequently or prolonged contact with skin may cause dermal irritation.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: Information about Ethanol:

Fish toxicity:

LC50 Lepomis macrochirus (bluegill): 12.700 mg/L/96h

Daphnia toxicity:

EC50 Daphnia magna (Big water flea): > 10.000 mg/L/48h

Algae toxicity:

EC50 Pseudokirchneriella subcapitata (green algae): 22.000 mg/L/96h

Water Hazard Class: 1 = slightly hazardous to water (Self-classification (mixture).)

12.2 Persistence and degradability

Further details: Product is biodegradable.

12.3 Bioaccumulative potential

Does not accumulate in organisms.

Partition coefficient: n-octanol/water:

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

General information: Do not allow to enter into ground-water, surface water or drains.

printed by Eni Schmiertechnik GmbH



Material number 600

Revision date: 20.3.2024
Version: 5.0
Replaces version: 4.0
Language: en-DE
Date of print: 4.4.2024

10 of 13

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU)

020/878 Page:

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Recommendation: 07 01 04*= Other organic solvents, washing liquids and mother liquors

16 05 08*= Discarded organic chemicals consisting of or containing hazardous substances

* = Evidence for disposal must be provided.

Dispose of waste according to applicable legislation.

Package

Recommendation: Dispose of waste according to applicable legislation. Handle empty containers with care.

Incineration may cause explosion.

Handle contaminated packages in the same way as the substance itself.

Non-contaminated packages may be recycled.

SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID, ADN, IMDG, IATA-DGR:

UN 1170

14.2 UN proper shipping name

ADR/RID, ADN, IMDG: UN 1170, ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

IATA-DGR: UN 1170, ETHANOL SOLUTION

14.3 Transport hazard class(es)

ADR/RID, ADN: Class 3, Code: F1
IMDG: Class 3, Subrisk -

IATA-DGR: Class 3

14.4 Packing group

ADR/RID, ADN, IMDG, IATA-DGR:

Ш

14.5 Environmental hazards

Dangerous for the environment:

Substance/mixture is not environmentally hazardous according to the criteria of the UN

model regulations.

Marine pollutant - IMDG: no





Material number 600

Revision date: 20.3.2024
Version: 5.0
Replaces version: 4.0
Language: en-DE
Date of print: 4.4.2024

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU)

2020/878 Page: 11 of 13

14.6 Special precautions for user

Land transport (ADR/RID)

Warning board: ADR/RID: Kemmler-number 30, UN number UN 1170

Hazard label: 3
Special Provisions: 144 601
Limited quantities: 5 L
EQ: E1

Package - Instructions: P001 IBC03 LP01 R001

Special provisions for packing together: MP19
Portable tanks - Instructions: T2
Portable tanks - Special Provisions: TP1
Tank coding: LGBF
Tunnel restriction code: (D/E)

Remarks: ADR/RID: Transport as "limited quantity" according to chapter 3.4 ADR/RID

(> 8.000 kg total gross mass): Tunnel restriction code (E)

Inland waterway craft (ADN)

Hazard label: 3
Special Provisions: 144 601
Limited quantities: 5 L
EQ: E1
Transport permitted: T

Equipment necessary: PP - EX - A

ventilation: VE01

Sea transport (IMDG)

EmS: F-E, S-D
Special Provisions: 144 223
Limited quantities: 5 L
Excepted quantities: E1

Package - Instructions: P001, LP01
IBC - Instructions: IBC03
IBC - Provisions: -

Tank instructions - IMO:

Tank instructions - UN:

Tank instructions - Provisions:

TP1

Stowage and handling: Category A.

Properties and observations: Colourless, volatile liquids. Pure ETHANOL: Flashpoint 13°C c.c. Explosive

limits: 3,3% to 19%. Miscible with water.

Segregation group: none

Air transport (IATA)

Hazard label: Flamm. liquid

Excepted Quantity Code: E1

Passenger and Cargo Aircraft: Ltd.Qty.:

Passenger and Cargo Aircraft:

Pack.Instr. Y344 - Max. Net Qty/Pkg. 10 L

Pack.Instr. 355 - Max. Net Qty/Pkg. 60 L

Pack.Instr. 366 - Max. Net Qty/Pkg. 220 L

Special Provisions: A3 A58 A180

Emergency Response Guide-Code (ERG): 3L



Material number 600

Revision date: 20.3.2024
Version: 5.0
Replaces version: 4.0
Language: en-DE
Date of print: 4.4.2024

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU)

)20/878 Page: 12 of 13

14.7 Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations - Germany

Storage class: 3 = Flammable liquids

Water Hazard Class: 1 = slightly hazardous to water (Self-classification (mixture).)

Incident regulation: Richtlinie 2012/18/EU (Seveso III):

Physikalische Gefahren: Ziffer 1.2.5.3 = Code P5c, Mengenschwelle 5 000 000kg /

50 000 000kg

Technical guidance air: 5.2.5 Information on working limitations:

Observe employment restrictions for young people.

Further regulations, limitations and legal requirements:

No data available

National regulations - EC member states

Volatile organic compounds (VOC):

45,34 % by weight

Labelling of packaging with <= 125mL content



Signal word: Warning

Hazard statements: not applicable

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Wear protective gloves/protective clothing/eye protection.

Further regulations, limitations and legal requirements:

Directive 2012/18/EU on the control of major-accident hazards involving dangerous

substances [Seveso-III-Directive] refer to Germany, 12. BlmSchV

Use restriction according to REACH annex XVII, no.: 3, 40, 75

15.2 Chemical Safety Assessment

For this mixture a chemical safety assessment is not required.

printed by Eni Schmiertechnik GmbH with Qualisys SUMDAT



Revision date: 20.3.2024 Version: 4.0 Replaces version: Language: en-DE Date of print: 4.4.2024

Safety Data Sheet

according to Regulation (EC) No 1907/2006 (REACH) and Regulation (EU)

Page: 13 of 13

SECTION 16: Other information

Wording of the H-phrases under paragraph 2 and 3:

H225 = Highly flammable liquid and vapour. H226 = Flammable liquid and vapour. H319 = Causes serious eye irritation.

H336 = May cause drowsiness or dizziness. EUH066 = Repeated exposure may cause skin dryness or cracking.

Changes in section 1: Details of the supplier of the safety data sheet Reason of change:

General revision

Date of first version: 25.6.2021

Department issuing data sheet:

see section 1: Department responsible for information

Abbreviations and acronyms:

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

AS/NZS: Australian Standards/New Zealand Standards

CAS: Chemical Abstracts Service CFR: Code of Federal Regulations

CLP: Classification, Labelling and Packaging

DMEL: Derived minimal effect level DNEL: Derived no-effect level EC: European Community EC50: Effective Concentration 50%

EN: European Standard EQ: Excepted quantities EU: European Union Eve Irrit .: Eve irritation Flam. Liq.: Flammable liquid

IATA: International Air Transport Association

IATA-DGR: International Air Transport Association - Dangerous Goods Regulations

IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk

IMDG Code: International Maritime Dangerous Goods Code

LC50: Median lethal concentration

LD50: Lethal dose 50%

LEL: Lower Explosion Limit

MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships

OECD: Organisation for Economic Co-operation and Development

OEL: Occupational Exposure Limit Value

OSHA: Occupational Safety and Health Administration PBT: Persistent, bioaccumulative and toxic

PNEC: Predicted no-effect concentration

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Regulations Concerning the International Carriage of Dangerous Goods by Rail

STOT SE: Specific target organ toxicity - single exposure

TLV: Threshold Limit Value

TRGS: Technical Rules for Hazardous Substances

UN: United Nations

vPvB: Very persistent and very bioaccumulative

WEL: Workplace Exposure Limit

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.

> Most recent product information is available at: http://sumdat.net/1arp38rz

