

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878 Revision date: 7/4/2025 Supersedes: 11/25/2024 Version: 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : Eni Rotra ATF HD Plus

Product code : 4738

Type of product : Lubricants

Formula : 0209-2020

Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category : Industrial use, Professional use

Industrial/Professional use spec : Used in closed systems

Wide dispersive use

Use of the substance/mixture : Gearbox lubricant

Do not use the product for any purposes that have not been advised by the manufacturer.

Function or use category : Lubricants and additives

1.3. Details of the supplier of the safety data sheet

Enilive S.p.A, Viale Giorgio Ribotta 51, 00144 Rome, ITALY, Tel. +39 06 59821

Competent person responsible for the safety data sheet (Reg. EC nr. 1907/2006): SDS.Enilive@enilive.com

Distributed by: Enilive Schmiertechnik GmbH, Paradiesstraße 14, 97080 Würzburg, GERMANY

Department responsible for information: Application Engineering & Product Management (AEPM), Tel. +49 (0)931-900 98-0

e-mail: technik.wuerzburg@enilive.com

1.4. Emergency telephone number

Emergency number : CNIT +39 0382 24444 (24h) (IT + EN)

Poison Center

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]

Hazardous to the aquatic environment – Chronic Hazard, H411

Category 2

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Toxic to aquatic life with long lasting effects. For specific information about the toxicological/ecotoxicological properties and classification of this product, see Sect. 11 and/or Sect. 12.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



CLP Signal word : -

Hazard statements (CLP) : H411 - Toxic to aquatic life with long lasting effects.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Precautionary statements (CLP)

: P273 - Avoid release to the environment.

P391 - Collect spillage.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards (not relevant for classification)

Other hazards not contributing to the classification

This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels. In case of contact with eyes, this product may cause irritation. If the product is handled or used at high temperature, contact with hot product or vapours may cause burns. Any substance, in case of accidents involving pressurized circuits and the like, may be accidentally injected under the skin, even without external damage. In such a case, the victim should be brought to an hospital as soon as possible, to get specialized medical treatment. Do not wait for symptoms to develop. A potential risk may arise from the release of hydrogen sulfide, when the product is stored or handled at high temperature. Hydrogen sulfide may accumulate in the tanks or other confined spaces, with danger to the workers that enter the spaces. In these cases overexposure to hydrogen sulfide may cause irritation to airways, nausea, dizziness, loss of consciousness and death.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

Component

Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7), Distillates (petroleum), hydrotreated light paraffinic (64742-55-8), reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0), Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified (72623-87-1), Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9), Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0), Alkyl phosphites, C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)

Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7), Distillates (petroleum), hydrotreated light paraffinic (64742-55-8), reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0), Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified (72623-87-1), Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9), Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0), Alkyl phosphites, C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Component

Substance(s) not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7), Distillates (petroleum), hydrotreated light paraffinic (64742-55-8), reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0), Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified (72623-87-1), Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9), Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0), Alkyl phosphites, C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Comments : Composition/ Information on ingredients:

Mixture of hydrocarbons

Polymers Additives

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (see note [*], see note [**]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627- 25	40 – 50	Asp. Tox. 1, H304
Thiophene, tetrahydro-, 1,1-dioxide, 3-(C9-11 branched alkyloxy) derivs., C10-rich	CAS-No.: 398141-87-2 EC-No.: 800-172-4 EC Index-No.: N/A REACH-no: 01-2119969520- 35	0.2 - 1	Aquatic Chronic 2, H411
Distillates (petroleum), hydrotreated light paraffinic (see note [*], see note [**]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	CAS-No.: 64742-55-8 EC-No.: 265-158-7 EC Index-No.: 649-468-00-3 REACH-no: 01-2119487077- 29	0.1 - 1	Asp. Tox. 1, H304
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate	CAS-No.: 125643-61-0 EC-No.: 406-040-9 EC Index-No.: 607-530-00-7 REACH-no: 01-0000015551-	0.1 - 1	Aquatic Chronic 4, H413
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified (see note [*], see note [**]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	CAS-No.: 72623-87-1 EC-No.: 276-738-4 EC Index-No.: 649-483-00-5 REACH-no: 01-2119474889- 13	0.1 - 1	Asp. Tox. 1, H304
Distillates (petroleum), solvent-dewaxed light paraffinic (see note [*], see note [**]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	CAS-No.: 64742-56-9 EC-No.: 265-159-2 EC Index-No.: 649-469-00-9 REACH-no: 01-2119480132-	0.1 - 1	Asp. Tox. 1, H304
Distillates (petroleum), solvent-dewaxed heavy paraffinic (see note [*], see note [**]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	CAS-No.: 64742-65-0 EC-No.: 265-169-7 EC Index-No.: 649-474-00-6 REACH-no: 01-2119471299- 27	0.1 - 1	Asp. Tox. 1, H304

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]
Alkyl phosphites (Additive)	EC-No.: 424-820-7 EC Index-No.: N/A REACH-no: 01-0000017126- 75	0.1 - 0.25	Acute Tox. 4 (Dermal), H312 (ATE=1100 mg/kg bodyweight) Skin Corr. 1B, H314 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)
C16-18-(even numbered, saturated and unsaturated)-alkylamines (Additive)	CAS-No.: 1213789-63-9 EC-No.: 627-034-4 REACH-no: 01-2119473797- 19	0.01 - 1	Acute Tox. 4 (Oral), H302 (ATE=1689 mg/kg bodyweight) Skin Corr. 1B, H314 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)
N,N-bis(2-hydroxyethyl)-3-[(C16-18)alkoxy]-1- propanamine (Additive)	CAS-No.: N/D EC-No.: 930-859-5 EC Index-No.: N/A REACH-no: 01-2120763467- 44	0.01 - 1	Skin Corr. 1C, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411

Comments : Note [*]:

this product has a value of DMSO extract < 3 % wt, according to IP 346. According to the criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product must be regarded as non carcinogenic.

Note [**]:

substance with occupational exposure limits for some EU countries affecting the category of mineral oils (finely refined mineral base oil mists; see section 8.1)

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation

First-aid measures after skin contact

First-aid measures after eye contact

First-aid measures after ingestion

- : In case of disturbances owing to inhalation of vapours or mists, remove the victim from exposure; keep at rest; if necessary, seek medical attention. See also section 4.3.
- : After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. In case of burns, cool affected part with cold running water for at least 10 min. Cover with gauze or clean cloth. Ask for medical assistance or bring to a hospital. Do not apply salves or other substances,
- : Rinse eyes thoroughly for at least 15 minutes. Keep eyelids well apart. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation, blurred vision or swelling occurs and persists, obtain medical advice from a specialist. In case of burns, cool affected part with cold running water for at least 10 min. Cover with gauze or clean cloth. Ask for medical assistance or bring to a hospital. Do not apply salves or other substances, unless by doctor's advice.

unless by doctor's advice. Body hypothermia must be avoided. Do not put ice on the burn.

: Do NOT induce vomiting. If the person is conscious, rinse mouth with water without swallowing. Keep at rest. Call for medical assistance or bring to an hospital. If the casualty is unconscious, place in the recovery position. In case of spontaneous vomiting, transport the victim to a hospital, to verify the possibility that the product has been aspired into the lungs. Do not give anything by mouth to an unconscious person.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : This product has a low vapour pressure, and in normal conditions at ambient temperature

the concentration in the air is negligible. A significant concentration may build up only in case of sprays and mists. In these cases overexposure to mists (e.g. through prolonged use in confined insufficiently ventilated spaces) may cause irritation to airways, nausea and

dizziness.

Symptoms/effects after skin contact : Contact with hot product may cause thermal burns.

Symptoms/effects after eye contact : Contact with eyes may cause temporary reddening and irritation. Contact with hot product

or vapours may cause burns.

Symptoms/effects after ingestion : Accidental ingestion of small quantities of the product may cause nausea, discomfort and

gastric disturbances.

Symptoms/effects upon intravenous administration : No information available.

Chronic symptoms : None to be reported, according to the present classification criteria.

4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical attention if casualty has an altered state of consciousness or if symptoms do not resolve. Seek medical attention in all cases of serious burns. If there is any suspicion of inhalation of H2S (hydrogen sulphide), Rescuers must wear breathing apparatus, belt and safety rope, and follow rescue procedures. Send patient to hospital. Immediately begin artificial respiration if breathing has ceased. Administer oxygen if necessary.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Small-size fires: carbon dioxide, dry chemicals, foam, sand or earth. Large fires: foam or

water fog (mist). These means should be used by trained personnel only. Other

extinguishing gases (according to regulations).

Unsuitable extinguishing media : Do not use water jets. They could cause splattering, and spread the fire. Simultaneous use

of foam and water on the same surface is to be avoided as water destroys the foam.

5.2. Special hazards arising from the substance or mixture

Fire hazard : This product is combustible, but not classified as Flammable. The creation of flammable

vapour mixtures takes place at temperatures which are higher than normal ambient levels.

: Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Explosion hazard : Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Hazardous decomposition products in case of fire : Incomplete combustion is likely to give rise to a complex mixture of airborne solid and liquid

particulates, gases, including carbon monoxide, NOx, H2S and SOx (harmful/toxic gases).

Oxygenated compounds (aldehydes, etc.). POx.

5.3. Advice for firefighters

Firefighting instructions : Shut off source of product, if possible. Move undamaged containers from immediate hazard area if it can be done safely. Spilled product which is not burning should be covered with sand or foam. Use water sprays to cool containers and surfaces exposed to the flames. If

the fire cannot be controlled, evacuate area.

Special protective equipment for firefighters : Wear personal protection equipment. (see chapter 8). In case of a large fire or in confined or poorly ventilated spaces, wear full fire resistant protective clothing and self-contained

breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. EN

Other information 443. EN 469. EN 659.

: In case of fire, do not discharge residual product, waste materials and runoff water: collect separately and use a proper treatment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures Stop or contain leak at the source

: Stop or contain leak at the source, if safe to do so. Eliminate all ignition sources if safe to do so (e.g. electricity, sparks, fires, flares). Avoid accidental sprays on hot surfaces or electrical contacts. Avoid direct contact with released material. Keep upwind. Spill area may be slippery.

7/4/2025 (Revision date) EN (English) 5/33

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

For non-emergency personnel

Protective equipment

See Section 8

Emergency procedures

Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency.

For emergency responders

Protective equipment

: Small spillages: normal antistatic working clothes are usually adequate. Large spillages: full body suit of chemically resistant and antistatic material. if necessary heat resistant and insulated. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Gloves made of PVA are not water-resistant, and are not suitable for emergency use. If contact with hot product is possible or anticipated, gloves should be heat-resistant and thermally insulated. Antistatic non-skid safety shoes or boots, chemical resistant, if necessary heat resistant and insulated. Work helmet. Goggles and /or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory protection: A half or full-face respirator with filter(s) for organic vapours (A) (or A+B when applicable for H2S), or a Self-contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.

Emergency procedures

: If required, notify relevant authorities according to all applicable regulations.

6.2. Environmental precautions

Do not let the product accumulate in confined or underground spaces. Do not let the product flow into sewers or water courses, or in any way contaminate the environment. In case of contamination of environment compartments (soil, subsoil, surface or underground waters), remove contaminated soil when possible, and in any case treat all involved compartments in accordance with local regulations. The site should have a spill plan to ensure that adequate safeguards are in place to minimize the impact of episodic releases.

6.3. Methods and material for containment and cleaning up

For containment

Contain spilled liquid with sand, earth or other suitable absorbents (non-flammable). Recover free liquid and waste materials in suitable waterproof and oil-resistant containers. Clean contaminated area. Dispose of according to local regulations. If in water: Confine the spillage. Remove from surface by skimming or suitable floating absorbents. Collect recovered product and other waste materials in suitable waterproof, oil resistant containers. Recover or dispose of according to local regulations. Do not use solvents or dispersants, unless specifically advised by an expert, and, if required, approved by local authorities.

Other information

Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air/water temperature, wave/current direction and speed) may significantly influence the choice of appropriate actions. Local regulations may also prescribe or limit actions to be taken. For this reason, local experts should be consulted when necessary.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

7/4/2025 (Revision date) EN (English) 6/33

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: This material is combustible, but will not ignite readily. Provide adequate ventilation. Use adequate personal protective equipment as needed. Due to the extremely slippery nature of this material, more care than usual must be exercised in material handling practices to keep off all walking surfaces. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Avoid release to the environment. Emptied containers can contain combustible product residues. Do not cut, weld, drill, burn or incinerate empty containers or drums, unless they have been drained and cleaned. The product may release Hydrogen Sulphide: a specific assessment of inhalation risks from the presence of hydrogen sulphide in tank headspaces, confined spaces, product residue, tank waste and waste water, and unintentional releases should be made to help determine controls appropriate to local circumstances. Before entering storage tanks and commencing any operation in a confined area (e.g. tunnels), carry out an adequate clean-up, and check the atmosphere for oxygen content, flammability, and the presence of sulphur compounds. See also Section 16, "Other information".

Hygiene measures

: Ensure that proper housekeeping measures are in place. Avoid contact with skin. Do not breathe fume/ mist/ vapours. Do not ingest. Do not smoke. Do not eat and do not drink during use. Do not clean hands with dirty or oil-soaked rags. Do not re-use clothes, if they are still contaminated. Keep away from food and beverages. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Contaminated work clothing should not be allowed out of the workplace. Separate working clothes from town clothes. Launder separately.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Store in dry, well-ventilated area. Keep away from open flames, hot surfaces and sources of ignition. Do not smoke.

Incompatible products

: Keep away from: strong acids and strong oxidants.

Storage area

Storage area layout, tank design, equipment and operating procedures must comply with the relevant European, national or local legislation. Storage installations/areas should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations.

Packages and containers:

: If the product is supplied in containers: Keep containers tightly closed and properly labelled. Keep only in the original container or in a suitable container for this kind of product.

Packaging materials

For containers, or container linings use materials specifically approved for use with this product. Compatibility should be checked with the manufacturer, according to the specific use conditions.

ι

Germany

Storage class (LGK, TRGS 510) : LGK 10 - Combustible liquids

Switzerland

Storage class (LK) : LK 10/12 - Liquids

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7) **Austria - Occupational Exposure Limits** MAK (OEL TWA) 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) **Belgium - Occupational Exposure Limits** OFI TWA 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) **Denmark - Occupational Exposure Limits** OFI TWA 1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) OEL STEL 2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) **Hungary - Occupational Exposure Limits** AK (OEL TWA) 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) **Netherlands - Occupational Exposure Limits** MAC TGG 8h (mg/m³) 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) **Spain - Occupational Exposure Limits** VLA-ED (OEL TWA) 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) VLA-EC (mg/m³) 10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) **Sweden - Occupational Exposure Limits** NGV (OEL TWA) 1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) KGV (OEL STEL) 3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) **United Kingdom - Occupational Exposure Limits** WEL TWA (OEL TWA) 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) WEL STEL (OEL STEL) 10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) **USA - ACGIH - Occupational Exposure Limits** ACGIH® TLV® TWA 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) ACGIH® TLV® STEL 10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) **Austria - Occupational Exposure Limits** MAK (OEL TWA) 5 mg/m3 (Mineral base oil mist, severely refined, DMSO extract <3% m/m) **Belgium - Occupational Exposure Limits OEL TWA** 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) **Denmark - Occupational Exposure Limits OEL TWA** 1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) OFL STEL 2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) **Hungary - Occupational Exposure Limits** AK (OEL TWA) 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m) **Netherlands - Occupational Exposure Limits** MAC TGG 8h (mg/m3) 5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)

Safety Data Sheet

Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)		
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KGV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
WEL STEL (OEL STEL)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH® TLV® TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH® TLV® STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Lubricating oils (petroleum), C20-50, hydrotre	eated neutral oil-based, Baseoil - unspecified (72623-87-1)	
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Belgium - Occupational Exposure Limits		
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Denmark - Occupational Exposure Limits		
OEL TWA	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
OEL STEL	2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KGV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
WEL STEL (OEL STEL)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH® TLV® TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH® TLV® STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	

Safety Data Sheet

Distillates (petroleum), solvent-dewaxed light	paraffinic (64742-56-9)	
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Belgium - Occupational Exposure Limits		
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Denmark - Occupational Exposure Limits		
OEL TWA	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
OEL STEL	2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KGV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
WEL STEL (OEL STEL)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH® TLV® TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH® TLV® STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)		
Austria - Occupational Exposure Limits		
MAK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Belgium - Occupational Exposure Limits		
OEL TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Denmark - Occupational Exposure Limits		
OEL TWA	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
OEL STEL	2 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Netherlands - Occupational Exposure Limits		
MAC TGG 8h (mg/m³)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
VLA-EC (mg/m³)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)		
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	1 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
KGV (OEL STEL)	3 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA)	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
WEL STEL (OEL STEL)	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH® TLV® TWA	5 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	
ACGIH® TLV® STEL	10 mg/m³ (Mineral base oil mist, severely refined, DMSO extract <3% m/m)	

Recommended monitoring procedures

Monitoring methods	
Monitoring methods	Monitoring procedures should be chosen according to the indications set by national authorities or labour contracts. Refer to relevant legislation and in any case to the good practice of industrial hygiene.

DNEL and **PNEC**

DNEL and PNEC		
Eni Rotra ATF HD Plus		
DNEL/DMEL (additional information)		
Not applicable		
Not applicable		
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)		
0.97 mg/kg bodyweight/day		
2.73 mg/m³		
5.58 mg/m³		
DNEL/DMEL (General population)		
0.74 mg/kg bodyweight/day		
1.2 mg/m³/day (DNEL, Mineral base oil mist, severely refined, DMSO extract <3% m/m)		
PNEC (Oral)		
9.33 mg/kg food		
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)		
DNEL/DMEL (Workers)		
0.97 mg/kg bodyweight/day		
2.73 mg/m³		
5.58 mg/m³		

Safety Data Sheet

Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)			
DNEL/DMEL (General population)			
Long-term - systemic effects,oral	0.74 mg/kg bodyweight/day		
Long-term - local effects, inhalation	1.19 mg/m³		
PNEC (Oral)			
PNEC oral (secondary poisoning)	9.33 mg/kg food		
Lubricating oils (petroleum), C20-50, hydrotre	eated neutral oil-based, Baseoil - unspecified (72623-87-1)		
DNEL/DMEL (Workers)			
Long-term - systemic effects, dermal	0.97 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation	2.73 mg/m³		
Long-term - local effects, inhalation	5.4 mg/m³		
DNEL/DMEL (General population)			
Long-term - systemic effects,oral	0.74 mg/kg bodyweight/day		
Long-term - local effects, inhalation	1.2 mg/m³		
PNEC (Oral)			
PNEC oral (secondary poisoning)	9.33 mg/kg food		
Distillates (petroleum), solvent-dewaxed light	paraffinic (64742-56-9)		
DNEL/DMEL (Workers)			
Long-term - systemic effects, dermal	0.97 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation	2.73 mg/m³		
Long-term - local effects, inhalation	5.58 mg/m³		
DNEL/DMEL (General population)			
Long-term - systemic effects,oral	0.74 mg/kg bodyweight/day		
Long-term - local effects, inhalation	1.19 mg/m³		
PNEC (Oral)			
PNEC oral (secondary poisoning)	9.33 mg/kg food		
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)			
DNEL/DMEL (Workers)			
Long-term - systemic effects, dermal	0.97 mg/kg bodyweight/day		
Long-term - systemic effects, inhalation	2.73 mg/m³		
Long-term - local effects, inhalation	5.4 mg/m³		
DNEL/DMEL (General population)			
Long-term - systemic effects,oral	0.74 mg/kg bodyweight/day		
Long-term - local effects, inhalation	1.2 mg/m³		
PNEC (Oral)			
PNEC oral (secondary poisoning)	9.33 mg/kg food		
Alkyl phosphites			
DNEL/DMEL (Workers)			
Long-term - systemic effects, dermal	0.5 mg/kg bodyweight/day		

Safety Data Sheet

Alkyl phosphites		
Long-term - systemic effects, inhalation	1.76 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	0.25 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	430 μg/m³	
Long-term - systemic effects, dermal	0.25 mg/kg bodyweight/day	
PNEC (Water)		
PNEC aqua (freshwater)	0.036 mg/l	
PNEC aqua (marine water)	90 ng/l	
PNEC aqua (intermittent, freshwater)	0.9 μg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	0.128 mg/kg dwt	
PNEC sediment (marine water)	15.9 µg/kg dw	
PNEC (Soil)		
PNEC soil	0.104 mg/kg dwt	
PNEC (Oral)		
PNEC oral (secondary poisoning)	10 mg/kg food	
PNEC (STP)		
PNEC sewage treatment plant	5 mg/l	
C16-18-(even numbered, saturated and unsat	urated)-alkylamines (1213789-63-9)	
DNEL/DMEL (Workers)		
Acute - local effects, inhalation	1 mg/m³	
Long-term - systemic effects, dermal	0.09 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	0.38 mg/m³	
Long-term - local effects, inhalation	1 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	40 μg/kg bodyweight/day	
Long-term - systemic effects, inhalation	0.035 mg/m³	
PNEC (Water)		
PNEC aqua (freshwater)	0.26 μg/l	
PNEC aqua (marine water)	0.026 μg/l	
PNEC aqua (intermittent, freshwater)	1.6 µg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	3.76 mg/kg dwt	
PNEC sediment (marine water)	0.376 mg/kg dwt	
PNEC (Soil)		
PNEC soil	10 mg/kg dwt	
PNEC (Oral)		
PNEC oral (secondary poisoning)	0.22 mg/kg food	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

PNEC (STP)	
PNEC sewage treatment plant	550 µg/l
Note	: The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a governmental regulatory body o an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH.

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Ensure that there is a suitable ventilation system. Before entering storage tanks and commencing any operation in a confined area (e.g. tunnels), carry out an adequate clean-up, and check the atmosphere for oxygen content, flammability, and the presence of sulphur compounds. See also Section 16, "Other information".

Personal protection equipment

Personal protective equipment (for industrial or professional use):

Gloves. Protective clothing. Safety glasses. Safety shoes or boots. Dust/aerosol mask.

Personal protective equipment symbol(s):









Eye and face protection

Eye protection:

When there is a risk of contact with the skin, use waterproof gloves, resistant to chemical products. Gloves must be felt-lined.

Skin protection

Skin and body protection:

Long-sleeved overalls. If necessary, refer to the EN 340 and related standards, for definition of characteristics and performance according to the risk rating of the area. Antistatic non-skid safety shoes or boots, chemical resistant, if necessary heat resistant and insulated.

Hand protection:

When there is a risk of contact with the skin, use waterproof gloves, resistant to chemical products. Gloves must be felt-lined. Adequate materials: nitrile (NBR) or PVC with a protection index > 5 (permeation time > 240 mins). Use gloves respecting all the conditions and within the limits set by the manufacturer. Replace gloves immediately in case of cuts, holes or other signs of damages or degradation. If necessary, refer to the EN 374 standard. Personal hygiene is a key element for an effective hand care. Gloves must be worn only with clean hands. After wearing gloves, hands must be carefully washed and dried.

Respiratory protection

Respiratory protection:

Independently from other possible actions (technical modifications, operating procedures, and other means to limit the exposure of workers), personal protection equipment can be used according to necessity. Open or well ventilated spaces: in presence of oil mists and if the product is handled without adequate containment means: use full or half-face masks with filter for mists/aerosols. In case there is a significant presence of vapours (e.g. through handling at high temperature), use full or half-face masks with filter for hydrocarbon vapours. (EN 136/140/145). Combined gas/dust mask with filter type: EN 14387. Closed or confined areas (e.g. tank interiors): the use of protection measures for airways (masks or self-contained breathing apparatus), must be assessed according to the specific activity, as well as level and duration of predicted exposure. (EN 136/140/145). Approved respiratory protection equipment shall be used in spaces where hydrogen sulphide may accumulate: full face mask with cartridge/filter type "B" (grey for inorganic vapours including H2S) or self-contained breathing apparatus (SCBA). (EN 136/140/145)

Thermal hazards

Thermal hazard protection:

If contact with hot product is possible or anticipated, gloves should be heat-resistant and thermally insulated.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Environmental exposure controls

Environmental exposure controls:

Do not discharge the product into the environment. Storage areas/installations should be designed with adequate bunds so as to prevent ground and water pollution in case of leaks or spills. Prevent discharge of undissolved substance to or recover from onsite wastewater. Onsite wastewater treatment required. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Consumer exposure controls:

Not applicable.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Colour : Pale yellow.

Appearance : Liquid, bright & clear.
Odour : Characteristics.

Odour threshold : There are no data available on the preparation/mixture itself.

Melting point : Not applicable
Freezing point : Not determined
Softening point : -48 °C (ASTM D 5950)
Boiling point : > 200 °C (ASTM D 1160)

Flammability : Not flammable
Lower explosion limit : Not determined
Upper explosion limit : Not determined
Flash point : 205 °C (ASTM D 92)
Auto-ignition temperature : Not determined
Decomposition temperature : Not determined

pH : Lack of data (on mixture / components of the mixture) - Data not available

Viscosity, kinematic : 7,2 mm2/s (100 °C) (ASTM D 445)
Viscosity, dynamic : 13000 mPa·s (-40°C, ASTM D 2983)
Solubility : Water: Immiscible and insoluble
Log Kow : Not applicable for mixtures
Log Pow : Not applicable for mixtures

Vapour pressure : < 0.1 hPa (20°C) Vapour pressure at 50°C : Not determined

Critical pressure : Not applicable for mixtures

Density : 845 kg/m³ (15°C, (ASTM D 4052)

Relative density : Not determined Relative vapour density at 20°C : Not determined Particle characteristics : Not applicable

9.2. Other information

Information with regard to physical hazard classes

Critical temperature : Not applicable for mixtures

Other safety characteristics

Additional information : No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

This mixture does not offer any further hazard for reactivity, except what is reported in the following paragraphs.

10.2. Chemical stability

Stable product, according to its intrinsic properties.

10.3. Possibility of hazardous reactions

None (in normal conditions of storage and handling). Contact with strong oxidizers (peroxides, chromates, etc.) may cause a fire hazard.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Strong oxidants and strong acids.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition generates: Toxic fumes. In exceptional cases (i.e prolonged storage in tanks contaminated with water, and presence of anaerobic sulfate-reducing microbial colonies), the product may undergo a degradation and generate small amounts of sulfur compounds, including H2S.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)
Additional information : (according to composition)

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)

LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rat	> 5000 mg/kg (OECD 402)
LC50 Inhalation - Rat	> 5 mg/l/4h (OECD 403)

Thiophene, tetrahydro-, 1,1-dioxide, 3-(C9-11 branched alkyloxy) derivs., C10-rich (398141-87-2)	
LD50 oral rat	10 ml/kg
LD50 dermal rabbit	4000 – 8000 mg/kg bodyweight

Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)	
LD50 oral rat	> 5000 mg/kg (OECD 401)
LD50 dermal rat	> 5000 mg/kg (OECD 402)

	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)	
	LD50 oral rat 500 – 2000 mg/kg bodyweight	
LD50 dermal rat 2000 mg/kg bodyweight		2000 mg/kg bodyweight
ı		

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified (72623-87-1)	
LD50 oral rat > 5000 mg/kg (OECD 401)	
LD50 dermal rat	> 5000 mg/kg (OECD 402)
LC50 Inhalation - Rat > 5 mg/l/4h (OECD 403)	
Distillates (natural course) solvent devised light navoffinis (C4742 EC 0)	

LC50 Innalation - Rat	> 5 mg/l/4h (OECD 403)
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)	
LD50 oral rat	> 5000 mg/kg (OECD 401)
LD50 dermal rat	> 5000 mg/kg (OECD 402)
LC50 Inhalation - Rat	> 5 mg/l/4h (OECD 403)

Safety Data Sheet

<u> </u>		
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)		
LD50 oral rat	> 5000 mg/kg (OECD 401)	
LD50 dermal rat	> 5000 mg/kg (OECD 402)	
LC50 Inhalation - Rat	> 5 mg/l/4h (OECD 403)	
Alkyl phosphites		
LD50 oral rat	> 2000 mg/kg bodyweight	
LD50 dermal rabbit	> 500 mg/kg bodyweight	
C16-18-(even numbered, saturated and unsat	urated)-alkylamines (1213789-63-9)	
LD50 oral rat	1689 mg/kg bodyweight (OECD 401)	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)	
LD50 dermal rabbit	2000 mg/kg bodyweight	
N,N-bis(2-hydroxyethyl)-3-[(C16-18)alkoxy]-1-	propanamine (N/D)	
LD50 oral rat	> 2000 mg/kg bodyweight (OECD 401)	
LD50 dermal rabbit	> 2000 mg/kg bodyweight (OECD 402)	
Skin corrosion/irritation :	Not classified (Based on available data, the classification criteria are not met)	
Additional information :	pH: Lack of data (on mixture / components of the mixture) - Data not available (according to composition)	
carbon numbers predominantly in the range	h hydrogen in the presence of a catalyst. It consists of hydrocarbons having of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F proportion of saturated hydrocarbons.] (64742-54-7)	
рН	Not applicable	
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)		
рН	Not applicable	
Lubricating oils (petroleum), C20-50, hydrotre	eated neutral oil-based, Baseoil - unspecified (72623-87-1)	
рН	Not applicable	
Distillates (petroleum), solvent-dewaxed light	paraffinic (64742-56-9)	
рН	Not applicable	
Distillates (petroleum), solvent-dewaxed heav	yy paraffinic (64742-65-0)	
рН	Not applicable	
C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)		
рН	11.7 Temp.: 20 °C	
Serious eye damage/irritation : Additional information :	Not classified (Based on available data, the classification criteria are not met) pH: Lack of data (on mixture / components of the mixture) - Data not available (according to composition)	
	araffinic; Baseoil— unspecified; [A complex combination of hydrocarbons	
obtained by treating a petroleum fraction with carbon numbers predominantly in the range of	hydrogen in the presence of a catalyst. It consists of hydrocarbons having of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F proportion of saturated hydrocarbons.] (64742-54-7)	
pH	Not applicable	
L		

Safety Data Sheet

Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)			
рН	Not applicable		
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified (72623-87-1)			
рН	Not applicable		
Distillates (petroleum), solvent-dewaxed light	t paraffinic (64742-56-9)		
рН	Not applicable		
Distillates (petroleum), solvent-dewaxed heav	vy paraffinic (64742-65-0)		
рН	Not applicable		
C16-18-(even numbered, saturated and unsat	urated)-alkylamines (1213789-63-9)		
рН	11.7 Temp.: 20 °C		
Respiratory or skin sensitisation : Additional information :	Not classified (Based on available data, the classification criteria are not met) (according to composition)		
Germ cell mutagenicity :	Not classified (Based on available data, the classification criteria are not met)		
Additional information :	(according to composition)		
Carcinogenicity : Additional information :	Not classified (Based on available data, the classification criteria are not met) (according to composition)		
Additional information .	All the mineral base oils contained in this product have a value < 3 % wt of DMSO extract,		
	according to IP 346 (Nota L - Annex VI Reg (CE) 1272/2008, # 1.1.3)		
Reproductive toxicity : Additional information :	Not classified (Based on available data, the classification criteria are not met) (according to composition)		
Alkyl phosphites			
NOAEL (animal/male, F1)	150 mg/kg (OECD TG 421)		
N,N-bis(2-hydroxyethyl)-3-[(C16-18)alkoxy]-1-propanamine (N/D)			
NOAEL (animal/male, F0/P)	100 mg/kg bodyweight		
NOAEL (animal/male, F1)	100 mg/kg bodyweight (OECD TG 421)		
STOT-single exposure : Additional information :	Not classified (Based on available data, the classification criteria are not met) (according to composition)		
reaction mass of isomers of: C7-9-alkyl 3-(3,5	i-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)		
LOAEL (oral, rat)	5 mg/kg bw/day (28 d)		
C16-18-(even numbered, saturated and unsat	urated)-alkylamines (1213789-63-9)		
STOT-single exposure	May cause respiratory irritation.		
STOT-repeated exposure : Additional information :	Not classified (Based on available data, the classification criteria are not met) (according to composition)		
Distillates (petroleum), hydrotreated heavy pa	araffinic; Baseoil— unspecified; [A complex combination of hydrocarbons		
obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having			
carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F			
(19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)			
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)		
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	> 0.98 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)		
Distillates (petroleum), hydrotreated light par	raffinic (64742-55-8)		
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)		
(, , , , , , , , , , , , , , , , , , ,	3 3 7 3 7 7 7 7 2 2 2 2 2 2 2 2 2 2 2 2		

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)				
NOAEL (oral, rat, 90 days)	5 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)			
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified (72623-87-1)				
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)			
Distillates (petroleum), solvent-dewaxed light	paraffinic (64742-56-9)			
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)			
Distillates (petroleum), solvent-dewaxed heav	y paraffinic (64742-65-0)			
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day (OECD TG 408)			
C16-18-(even numbered, saturated and unsat	urated)-alkylamines (1213789-63-9)			
NOAEL (oral, rat, 90 days)	3.25 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)			
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.			
N,N-bis(2-hydroxyethyl)-3-[(C16-18)alkoxy]-1-	propanamine (N/D)			
NOAEL (oral, rat, 90 days)	250 mg/kg bodyweight/day			
Aspiration hazard : Additional information :	Not classified (Based on available data, the classification criteria are not met) (according to composition) Viscosity, kinematic: > 20,5 mm2/s (40 °C) (ASTM D 445)			
Eni Rotra ATF HD Plus				
Viscosity, kinematic	7,2 mm2/s (100 °C) (ASTM D 445)			
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil of at least 100 SUS at 100°F (19cSt at 40°C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-54-7)				
Viscosity, kinematic	17.9 mm²/s (40 °C) (ASTM D 445)			
Distillates (petroleum), hydrotreated light par	affinic (64742-55-8)			
Viscosity, kinematic	6.5 – 9 mm²/s (40 °C) (ASTM D 445)			
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified (72623-87-1)				
Viscosity, kinematic	9 mm²/s (40 °C) (ASTM D 445)			
Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)				
Viscosity, kinematic	15 – 16.5 mm²/s (40 °C) (ASTM D 445)			
Distillates (petroleum), solvent-dewaxed heav	y paraffinic (64742-65-0)			
Viscosity, kinematic	< 20.5 mm²/s (40 °C) (ASTM D 445)			
C16-18-(even numbered, saturated and unsat	urated)-alkylamines (1213789-63-9)			
Viscosity, kinematic	5.245 mm²/s			

11.2. Information on other hazards

Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Other information

Potential adverse human health effects and

symptoms

Other information

None

: Contact with eyes may cause temporary reddening and irritation, Avoid all eye and skin contact and do not breathe vapour and mist

SECTION 12: Ecological information

7	-1	α			ч
12		 U,	МL	UIL	w

Ecology - general

Ecology - water

: Handle according to general working hygiene practices to avoid pollution and release into

the environment. Notify authorities if product enters sewers or public waters.

Ecology - air

This product has a low vapour pressure, and in normal conditions at ambient temperature the concentration in the air is negligible. A significant concentration may build up only if the

product is used at high temperature, or in case of sprays and mists.

This product is not soluble in water. It floats on water and forms a film on the surface. The damage to aquatic organisms is of mechanical kind (immobilization and entrapment)

Hazardous to the aquatic environment, short-term

Not classified (Based on available data, the classification criteria are not met)

Hazardous to the aquatic environment, long-term

: Toxic to aquatic life with long lasting effects.

(chronic)		
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
LC50 fish 1	> 100 mg/l (LL 50)	
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)	
Thiophene, tetrahydro-, 1,1-dioxide, 3-(C9-11	branched alkyloxy) derivs., C10-rich (398141-87-2)	
LC50 fish 1	2.4 mg/l	
EC50 Daphnia 1	4.6 mg/l	
Distillates (petroleum), hydrotreated light para	affinic (64742-55-8)	
LC50 fish 1	100 – 10000 mg/l (LL 50)	
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)	
EC50 72h - Algae [1]	100 mg/l (EL0, Pseudokirchneriella subcapitata)	
NOEC (chronic)	10 – 1000 mg/l (NOELR, Daphnia Magna)	
NOEC chronic algae	100 mg/l (72h, Pseudokirchneriella subcapitata)	
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)		
LC50 fish 1	> 74 mg/l (Brachydanio rerio, OECD 203)	
LC50 fish 2	> 2 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)	
EC50 Daphnia 1	> 100 mg/l (24h, OECD 202)	
EC50 Daphnia 2	> 1000 mg/l Test organisms (species): Daphnia magna	
EC50 72h - Algae [1]	> 3 mg/l (Scenedesmus sp, OECD 201)	
ErC50 (algae)	> 33.7 mg/l (OECD 201, 72 h, Pseudokirchnerella subspicata)	
NOEC (acute)	33.7 mg/l (72 h, Pseudokirchnerella subspicata)	
NOEC (chronic)	≤ 0.01 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
NOEC chronic crustacea	≥ 1 mg/l (21d, Daphnia magna)	
Lubricating oils (petroleum), C20-50, hydrotre	eated neutral oil-based, Baseoil - unspecified (72623-87-1)	
LC50 fish 1	> 100 mg/l (LL 50)	
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)	

Safety Data Sheet

Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)			
LC50 fish 1	> 100 mg/l (LL 50)		
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)		
Distillates (petroleum), solvent-dewaxed heav	y paraffinic (64742-65-0)		
LC50 fish 1	> 100 mg/l (LL 50)		
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)		
Alkyl phosphites			
LC50 fish 1	1.5 mg/l (Oncorhynchus mykiss, OECD 203)		
EC50 Daphnia 1	0.09 mg/l (EL50, OECD TG 202)		
EC50 72h - Algae [1]	0.31 mg/l (Pseudokirchneriella subcapitata)		
NOEC chronic crustacea	0.14 mg/l (21d)		
C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)			
LC50 fish 1	0.84 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)		
LC50 fish 2	4.21 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)		
EC50 Daphnia 1	0.32 mg/l Test organisms (species): Daphnia magna		
EC50 Daphnia 2	0.98 mg/l Test organisms (species): Daphnia magna		
EC50 72h - Algae [1]	0.46 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)		
EC50 72h - Algae [2]	0.38 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)		
LOEC (chronic)	0.032 mg/l Test organisms (species): Daphnia magna Duration: '21 d'		
NOEC (chronic)	0.013 mg/l Test organisms (species): Daphnia magna Duration: '21 d'		
NOEC chronic crustacea	0.013 mg/l (21d)		
NOEC chronic algae	0.01 mg/l (3d)		
N,N-bis(2-hydroxyethyl)-3-[(C16-18)alkoxy]-1-propanamine (N/D)			
LC50 fish 1	690 (≥ 10) mg/l (Cyprinodon variegatus, OECD 203)		
EC50 Daphnia 1	> 4 mg/l (OECD TG 202)		
EC50 72h - Algae [1]	0.72 mg/l (EL50)		
NOEC chronic algae	0.25 mg/l (NOELR, Pseudokirchneriella subcapitata, OECD TG 201)		
12.2. Persistence and degradability			

Eni Rotra ATF HD Plus		
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.	
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
Persistence and degradability The most significant constituents of the product should be considered as "inhered biodegradable", but not "readily biodegradable", and they may be moderately preparticularly in anaerobic conditions.		
Thiophene, tetrahydro-, 1,1-dioxide, 3-(C9-11 branched alkyloxy) derivs., C10-rich (398141-87-2)		
Persistence and degradability	Rapidly degradable	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Thiophene, tetrahydro-, 1,1-dioxide, 3-(C9-11 branched alkyloxy) derivs., C10-rich (398141-87-2)			
Biodegradation 9.6 % (28d, OECD TG 301 C)			
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)			
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.		
Biodegradation	< 60 % (28d)		
reaction mass of isomers of: C7-9-alkyl 3-(3,5	-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)		
Persistence and degradability	Not biodegradable.		
Lubricating oils (petroleum), C20-50, hydrotre	eated neutral oil-based, Baseoil - unspecified (72623-87-1)		
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.		
Distillates (petroleum), solvent-dewaxed light	paraffinic (64742-56-9)		
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.		
Distillates (petroleum), solvent-dewaxed heav	/y paraffinic (64742-65-0)		
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.		
Alkyl phosphites			
Persistence and degradability	Rapidly degradable		
Biodegradation	52.9 % (60d, OECD TG 301 B)		
C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)			
Persistence and degradability	Readily biodegradable.		
Biodegradation	66 % (28d) (OECD 301B)		
N,N-bis(2-hydroxyethyl)-3-[(C16-18)alkoxy]-1-propanamine (N/D)			
Persistence and degradability	Rapidly degradable		
Biodegradation	56.8 % (28d, OECD TG 301 B)		
12.3. Bioaccumulative potential			
Eni Rotra ATF HD Plus			
Log Pow	Not applicable for mixtures		
Log Kow	Not applicable for mixtures		
Bioaccumulative potential	Not established.		

7/4/2025 (Revision date)	EN (English)	22/33

Thiophene, tetrahydro-, 1,1-dioxide, 3-(C9-11 branched alkyloxy) derivs., C10-rich (398141-87-2)

4.1

< 1

Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)

27.54

Bioconcentration factor (BCF REACH)

Log Kow

Log Kow

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)	
Bioconcentration factor (BCF REACH)	260 (35 d, Oncorhynchus mykiss, OECD 305)
C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)	
Bioconcentration factor (BCF REACH) > 500	
N,N-bis(2-hydroxyethyl)-3-[(C16-18)alkoxy]-1-propanamine (N/D)	
Log Pow > 5.2 (25°C)	

12.4. Mobility in soil

Eni Rotra ATF HD Plus	
Ecology - soil	No data available.

12.5. Results of PBT and vPvB assessment		
Eni Rotra ATF HD Plus		
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII		
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII		
Results of PBT-vPvB assessment The components in this formulation do not meet the criteria for classification as PBT or vPvB. The product should be considered prudentially as "Persistent" in the environment, according to the REACH Annex XIII criteria (point 1.1)		

according to the REACH Annex XIII criteria (point 1.1)	
Component	
Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7), Distillates (petroleum), hydrotreated light paraffinic (64742-55-8), reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0), Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified (72623-87-1), Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9), Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0), Alkyl phosphites, C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)
Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7), Distillates (petroleum), hydrotreated light paraffinic (64742-55-8), reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0), Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified (72623-87-1), Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9), Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0), Alkyl phosphites, C16-18-(even numbered,

saturated and unsaturated)-alkylamines (1213789-63-9)

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

12.7. Other adverse effects

Other adverse effects : None.

Eni Rotra ATF HD Plus	
Other information	This product has no specific properties for inhibition of bacterial activity. In any case, wastewater containing this product should be treated in plants that are suited for the specific purpose.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
Other information	This product has no specific properties for inhibition of bacterial activity. In any case, wastewater containing this product should be treated in plants that are suited for the specific purpose.	
Distillates (petroleum), hydrotreated light para	affinic (64742-55-8)	
Other information	This product has no specific properties for inhibition of bacterial activity. In any case, wastewater containing this product should be treated in plants that are suited for the specific purpose.	
Lubricating oils (petroleum), C20-50, hydrotre	ated neutral oil-based, Baseoil - unspecified (72623-87-1)	
Other information	This product has no specific properties for inhibition of bacterial activity. In any case, wastewater containing this product should be treated in plants that are suited for the specific purpose.	
Distillates (petroleum), solvent-dewaxed light	paraffinic (64742-56-9)	
Other information	This product has no specific properties for inhibition of bacterial activity. In any case, wastewater containing this product should be treated in plants that are suited for the specific purpose.	
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)		
Other information	This product has no specific properties for inhibition of bacterial activity. In any case, wastewater containing this product should be treated in plants that are suited for the specific purpose.	

SECTION 13: Disposal considerations

13.1. Waste treatment methods

: Do not dispose of the product, either new or used, by dumping on the ground, or Waste treatment methods discharging into sewers, tunnels, lakes or water courses. Deliver to a qualified official collector. Dispose of empty containers and wastes safely. Sewage disposal recommendations : Dispose of in a safe manner in accordance with local/national regulations. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed. European Waste Catalogue code(s) (Decision 2001/118/CE): 13 02 05* (mineral-based Product/Packaging disposal recommendations non-chlorinated engine, gear and lubricating oils). This EWC code is only a general indication, and takes into account the original composition of the product and its intended use. The user has the responsibility of choosing the right EWC code, considering the actual use of the product, alterations and contaminations. Additional information : Empty containers may contain combustible product residues. Do not cut, weld, bore, burn or incinerate emptied containers, unless they have been cleaned and declared safe. Ecology - waste materials The product as it is does not contain halogenated substances. EURAL code (EWC) 13 02 05* - Mineral-based non-chlorinated engine, gear and lubricating oils

: HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one

SECTION 14: Transport information

HP Code

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 3082	UN 3082	UN 3082	UN 3082	UN 3082

or more sectors of the environment

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
14.2. UN proper shippin	g name			
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	Environmentally hazardous substance, liquid, n.o.s.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Transport document descr	iption			
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Alkyl phosphites), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Alkyl phosphites), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (Alkyl phosphites), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Alkyl phosphites), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Alkyl phosphites), 9, III
14.3. Transport hazard o	class(es)			
9	9	9	9	9
**************************************	**************************************	2	**************************************	**************************************
14.4. Packing group				
III	III	III	III	III
14.5. Environmental haz	ards			
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes EmS-No. (Fire): F-A EmS-No. (Spillage): S-F	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
None.	1			1

14.6. Special precautions for user

Overland transport

Transport regulations (ADR) : Not subject

Classification code (UN) : M6

Special provisions (ADR) : 274, 335, 375, 601, 650

Limited quantities (ADR) : 5I Excepted quantities (ADR) : E1

Packing instructions (ADR) : P001, IBC03, LP01, R001

Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T4
Portable tank and bulk container special provisions : TP1, TP29

(ADR)

Tank code (ADR) : LGBV
Vehicle for tank carriage : AT
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Loading, unloading : CV13

and handling (ADR)

Hazard identification number (Kemler No.) : 96

Orange plates



Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Tunnel restriction code : EAC code : •3Z

Transport by sea

Transport regulations (IMDG) : Not subject Limited quantities (IMDG) : 5 L Excepted quantities (IMDG) : E1 Stowage category (IMDG) : A

Air transport

Transport regulations (IATA) : Not subject PCA Excepted quantities (IATA) : E1 PCA Limited quantities (IATA) : Y964 PCA limited quantity max net quantity (IATA) : 30kgG PCA packing instructions (IATA) : 964 PCA max net quantity (IATA) : 450L CAO packing instructions (IATA) : 964 CAO max net quantity (IATA) : 450L

Special provisions (IATA) : A97, A158, A197, A215

ERG code (IATA) : 9L

Inland waterway transport

Transport regulations (ADN) : Not subject

Classification code (ADN) : M6

Special provisions (ADN) : 274, 335, 375, 601, 650

Limited quantities (ADN) : 5 L

Excepted quantities (ADN) : E1

Carriage permitted (ADN) : T

Equipment required (ADN) : PP

Number of blue cones/lights (ADN) : 0

Rail transport

Transport regulations (RID) : Not subject

Classification code (RID) : M6

Special provisions (RID) : 274, 335, 375, 601, 650

Limited quantities (RID) : 5L Excepted quantities (RID) : E1

Packing instructions (RID) : P001, IBC03, LP01, R001

Special packing provisions (RID) : PP1
Mixed packing provisions (RID) : MP19
Portable tank and bulk container instructions (RID) : T4
Portable tank and bulk container special provisions : TP1, TP29

(RID)

Tank codes for RID tanks (RID) : LGBV

Transport category (RID) : 3

Special provisions for carriage – Packages (RID) : W12

Special provisions for carriage - Loading and : CW13, CW31

unloading (RID)

Colis express (express parcels) (RID) : CE8
Hazard identification number (RID) : 90

14.7. Maritime transport in bulk according to IMO instruments

IBC code : Not applicable.

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description	
3(b)	Distillates (petroleum), hydrotreated heavy paraffinic; Distillates (petroleum), hydrotreated light paraffinic; Lubricating oils (petroleum), C20-50, hydrotreated neutral oilbased, Baseoil - unspecified; Distillates (petroleum), solvent-dewaxed light paraffinic; Distillates (petroleum), solvent-dewaxed heavy paraffinic; Alkyl phosphites; C16-18-(even numbered, saturated and unsaturated)-alkylamines; N,N-bis(2-hydroxyethyl)-3-[(C16-18)alkoxy]-1-propanamine	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	
3(c)	Eni Rotra ATF HD Plus; Thiophene, tetrahydro-, 1,1-dioxide, 3-(C9-11 branched alkyloxy) derivs., C10-rich; reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate; Alkyl phosphites; C16-18-(even numbered, saturated and unsaturated)-alkylamines; N,N-bis(2-hydroxyethyl)-3-[(C16-18)alkoxy]-1-propanamine	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

No ingredients are included in the REACH Candidate list (> 0,1 % m/m).

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

Seveso Directive (Disaster Risk Reduction)

Seveso Additional information · F2

Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

National regulations

France

Maladies professionelles (F)	
Code	Description
RG 36	Diseases caused by oils and fats of mineral or synthetic origin

Germany

Employment restrictions : Employment prohibitions or restrictions on the protection of young people at work according

to § 22 JArbSchG in the case of formation of hazardous substances have to be observed.

National Rules and Recommendations TRGS 400: Hazard assessment for activities involving Hazardous Substances.

> TRGS 401: Risks resulting from skin contact - identification, assessment, measures. TRGS 402: Identification and Assessment of the Risks from Activities involving Hazardous

Substances: Inhalation Exposure.

TRGS 555: Working instruction and information for workers.

TRGS 800: Fire protection measures. TRGS 900: Occupational Exposure Limits.

VbF class (D) Not applicable.

Water hazard class (WGK) (D) WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1). WGK remark

Classification is carried out on the basis of the Ordinance on facilities for handling substances that are hazardous to water (Verordnung über Anlagen zum Umgang mit

wassergefährdenden Stoffen (AwSV)) of 18 April 2017 (BGBI 2017, Teil I, Nr. 22, Seite

Major Accidents Ordinance (12. BlmSchV) : Is not subject to the Major Accidents Ordinance (12. BImSchV)

Netherlands

Waterbezwaarlijkheid : 7 - Toxic to aquatic organisms

6 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment

Saneringsinspanningen C - Minimize discharge

SZW-lijst van kankerverwekkende stoffen None of the components are listed SZW-lijst van mutagene stoffen None of the components are listed

SZW-lijst van reprotoxische stoffen - Borstvoeding : None of the components are listed SZW-lijst van reprotoxische stoffen -: None of the components are listed

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen - Ontwikkeling : None of the components are listed

Denmark

Danish National Regulations : Pregnant/breastfeeding women working with the product must not be in direct contact with it

7/4/2025 (Revision date) EN (English) 28/33

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Poland

Polish National Regulations

: Act of 25 February 2011 on chemical substances and their mixtures (J. o L. No. 63, item 322 as amended; consolidated text J. o L. 2019, item 1225).

Act of 14 December 2012 on waste (J. o L. 2013, item 322 as amended; consolidated text J. o L. 2020, item 797).

The announcement of Marshal of the Sejm of the Republic of Poland dated 19 October 2016 concerning the consolidated text announcement of the decree on the management of packaging and packaging waste (J. o L. 2016, item 1863 as amended).

Decree of the Minister of Environment of 14 December 2014 on the catalogue of waste (J. o L. 2014, item 1923).

Act of 19 August 2011 on the Carriage of Dangerous Goods (J. o L. 2011 No. 227, item 1367 as amended; consolidated text J. o L. 2020, item 154).

Regulation of the Minister of Family, Labour and Social Policy of 12 June 2018 on the highest permissible concentration and intensity of noxious agents for health at work environment (J. o L. item 1286 as amended).

The announcement of Minister of Health dated 9 September 2016 concerning the consolidated text announcement of the decree of the Minister of Health of 30 December 2004 on health and safety at work related to exposure to chemical agents at work (J. o L. of 16 September 2016, item 1488)

Regulation of the Minister of Health of 2 February 2011 on tests and measurements of the noxious agents for health at work environment (J. o L. No. 33, item 166 as amended). Regulation of the Minister of Environment of 9 December 2003 on particularly hazardous substances to the environment (J. o L. No. 217, item 2141).

ADR Agreement: Government Statement of 13 March 2023 on the entry into force of amendments to Annexes A and B to the Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), signed in Geneva on 30 September 1957 (J. o. L. 2023, item 891)

15.2. Chemical safety assessment

For this mixture a chemical safety assessment has been not carried out

A chemical safety assessment has been carried out for the following components of this mixture::

Distillates (petroleum), hydrotreated heavy paraffinic

Thiophene, tetrahydro-, 1,1-dioxide, 3-(C9-11 branched alkyloxy) derivs., C10-rich

Distillates (petroleum), hydrotreated light paraffinic

reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, Baseoil - unspecified

Distillates (petroleum), solvent-dewaxed light paraffinic

Distillates (petroleum), solvent-dewaxed heavy paraffinic

Alkyl phosphites

C16-18-(even numbered, saturated and unsaturated)-alkylamines

N,N-bis(2-hydroxyethyl)-3-[(C16-18)alkoxy]-1-propanamine

SECTION 16: Other information

Indication of changes		
Section Changed item		Comments
	Number of blue cones/lights (ADN)	Added
	Equipment required (ADN)	Added
	Carriage permitted (ADN)	Added
	Colis express (express parcels) (RID)	Added
	Special provisions for carriage - Loading and unloading (RID)	Added
Special provisions for carriage – Packages (RID)		Added
	Tank codes for RID tanks (RID)	Added

Safety Data Sheet

Indication of changes			
Section	Changed item	Comments	
	Portable tank and bulk container special provisions (RID)	Added	
	Portable tank and bulk container instructions (RID)	Added	
	Mixed packing provisions (RID)	Added	
	Special packing provisions (RID)	Added	
	Packing instructions (RID)	Added	
	Special provisions (RID)	Added	
	ERG code (IATA)	Added	
	Special provisions (IATA)	Added	
	CAO packing instructions (IATA)	Added	
	PCA packing instructions (IATA)	Added	
	PCA Limited quantities (IATA)	Added	
	Special provisions for carriage - Loading, unloading and handling (ADR)	Added	
	Special provisions for carriage - Packages (ADR)	Added	
	Tank code (ADR)	Added	
	Portable tank and bulk container special provisions (ADR)	Added	
	Portable tank and bulk container instructions (ADR)	Added	
	Mixed packing provisions (ADR)	Added	
	Special packing provisions (ADR)	Added	
	Packing instructions (ADR)	Added	
	Vehicle for tank carriage	Added	
	Adverse health effects caused by endocrine disrupting properties	Added	
5.3	EAC code	Added	
9	Upper explosive limit (UEL)	Added	
9	Lower explosive limit (LEL)	Added	
9	Oxidising properties	Removed	
9	Explosive properties	Removed	
9	Relative evaporation rate (butylacetate=1)	Removed	
9	Flash point	Modified	
9	Viscosity, kinematic	cosity, kinematic Modified	
9	Flammability (solid, gas)	Added	
9	Vapour pressure at 50°C	Vapour pressure at 50°C Modified	
9	Relative density	tive density Modified	
9	Freezing point	Modified	
1	l .	4	

Safety Data Sheet

Indication of changes			
Section	Changed item	Comments	
9	Auto-ignition temperature Modified		
9	Relative vapour density at 20°C Modified		
9	Flammability (solid, gas) Removed		
9.1	Explosive limits (vol %) Removed		
9.1	Decomposition temperature Modified		
11.1	Additional information Modified		
12.6	Adverse effects on the environment caused by endocrine disrupting properties Added		
14.6	Special provisions (ADN)	Added	
14.6	Special provisions (ADR)	Added	
15.1	Other information, restriction and prohibition regulations	Removed	
15.1	Regional legislation	Removed	

Abbreviations and acronyms:		
	Complete text of the H phrases quoted in this Safety Data Sheet. These phrases are reported here for information only, and MAY NOT correspond to the classification of the product.	
	N/D = not available	
	N/A = not applicable	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC50	Effective concentration for 50 percent of test population (median effective concentration)	
IARC	International Agency for Research on Cancer	
IATA	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Lethal concentration for 50 percent of test population (median lethal concentration)	
LD50	Lethal dose for 50 percent of test population (median lethal dose)	
LOAEL	Lowest Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
OECD	Organisation for Economic Co-operation and Development	
PBT	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Abbreviations and acronyms:		
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals, Regulation (EC) No 1907/2006	
RID	Regulation concerning the International Carriage of Dangerous Goods by Railways	
SDS	Safety Data Sheet	
STP	Sewage treatment plant	
vPvB	Very Persistent and Very Bioaccumulative	

Data sources

Training advice

Other information

- : This Safety Data Sheet is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.
- : Provide adequate training to professional operators for the use of PPEs, according to the information contained in this Safety Data Sheet.
- Do not use the product for any purposes that have not been advised by the manufacturer. In exceptional cases (i.e prolonged storage in tanks contaminated with water, and presence of anaerobic sulfate-reducing microbial colonies), the product may undergo a degradation and generate small amounts of sulfur compounds, including H2S. This situation is especially relevant in all those circumstances which require to enter a confined space, with direct exposure to the vapours. The product may release Hydrogen Sulphide: a specific assessment of inhalation risks from the presence of hydrogen sulphide in tank headspaces, confined spaces, product residue, tank waste and waste water, and unintentional releases should be made to help determine controls appropriate to local circumstances. If there is any suspicion of inhalation of H2S (hydrogen sulphide), Rescuers must wear breathing apparatus, belt and safety rope, and follow rescue procedures. Send patient to hospital. Immediately begin artificial respiration if breathing has ceased. Administer oxygen if necessary. This situation is especially relevant for those operations which involve direct exposure to the vapours in the interior of tanks or other confined spaces. Therefore, it is very important to follow the above mentioned precautionary measures also with used oils.

Full text of H- and EUH-statements:		
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4	
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1	
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2	
Aquatic Chronic 4	Hazardous to the aquatic environment – Chronic Hazard, Category 4	
Asp. Tox. 1	Aspiration hazard, Category 1	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1	
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B	
Skin Corr. 1C	Skin corrosion/irritation, Category 1, Sub-Category 1C	
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	
H302	Harmful if swallowed.	
H304	May be fatal if swallowed and enters airways.	
H312	Harmful in contact with skin.	
H314	Causes severe skin burns and eye damage.	
H318	Causes serious eye damage.	
H335	May cause respiratory irritation.	
H373	May cause damage to organs through prolonged or repeated exposure.	

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Full text of H- and EUH-statements:		
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
H411	Toxic to aquatic life with long lasting effects.	
H413	May cause long lasting harmful effects to aquatic life.	

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Aquatic Chronic 2	H411	Calculation method

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.