



# Eni Rotra FE 75W-80

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878  
Revision date: 24/12/2025 Supersedes: 14/05/2025 Version: 1.2

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : Eni Rotra FE 75W-80  
Product code : 1314  
Type of product : Lubricants  
Formula : 0115-2015  
Product group : Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses

Main use category : Industrial use, Professional use, Consumer use  
Industrial/Professional use spec : Used in closed systems  
Wide dispersive use  
Use of the substance/mixture : Gearbox lubricant  
----  
Do not use the product for any purposes that have not been advised by the manufacturer.  
Function or use category : Lubricants and additives

#### 1.3. Details of the supplier of the safety data sheet

Manufacturer:

Enilive Iberia S.L.U.

Avenida de Europa, 24, Edificio Torona B - Planta 1ª, 28108 Alcobendas (Madrid) Tel: (+34) 917 277 878

Competent person responsible for the Safety Data Sheet (Reg. EC nr. 1907/2006): SDS.Enilive@enilive.com

Distributed by: Enilive Schmiertechnik GmbH, Paradiesstraße 14, 97080 Würzburg, GERMANY

Department responsible for information: Application Engineering & Product Management (AEPM), Tel. +49 (0)931-900 98-0

e-mail: technik.wuerzburg@enilive.com

#### 1.4. Emergency telephone number

Emergency number : CNIT +39 0382 24444 (24h) (IT + EN)  
Poison Center

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]

Hazardous to the aquatic environment – Chronic Hazard, H411

Category 2

Full text of H- and EUH-statements: see section 16

##### Adverse physicochemical, human health and environmental effects

Prolonged and repeated skin contact may cause reddening, irritation and dermatitis. May produce an allergic reaction. For specific information about the toxicological/ecotoxicological properties and classification of this product, see Sect. 11 and/or Sect. 12.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS09

# Eni Rotra FE 75W-80

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

CLP Signal word	: -
Hazard statements (CLP)	: H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P273 - Avoid release to the environment. P391 - Collect spillage. P501 - Dispose of contents/container to according to national or local regulations.
EUH-statements	: EUH208 - Contains Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched). May produce an allergic reaction.

### 2.3. Other hazards

Other hazards not contributing to the classification	: This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels. In case of contact with eyes, this product may cause irritation. Any substance, in case of accidents involving pressurized circuits and the like, may be accidentally injected under the skin, even without external damage. In such a case, the victim should be brought to an hospital as soon as possible, to get specialized medical treatment. Do not wait for symptoms to develop.
--	---

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

Contains no PBT and/or vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

Component	
Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	1-Decene, Trimer, Hydrogenated (157707-86-3), Distillates (petroleum), hydrotreated light naphthenic (64742-53-6), Mineral base oil, severely refined (N/A), Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5), Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched), C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9), Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)
Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	1-Decene, Trimer, Hydrogenated (157707-86-3), Distillates (petroleum), hydrotreated light naphthenic (64742-53-6), Mineral base oil, severely refined (N/A), Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5), Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched), C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9), Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

# Eni Rotra FE 75W-80

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Component	
Substance(s) not included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605	Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0), 1-Decene, Trimer, Hydrogenated (157707-86-3), Distillates (petroleum), hydrotreated light naphthenic (64742-53-6), Mineral base oil, severely refined (N/A), Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5), Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched), C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

Comments : Composition/ Information on ingredients:  
Mixture of hydrocarbons  
Polymers  
Additives

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (see note [**], see note [***], see note [****]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	CAS-No.: 64742-65-0 EC-No.: 265-169-7 EC Index-No.: 649-474-00-6 REACH-no: 01-2119471299-27	60 – 70	Not classified
1-Decene, Trimer, Hydrogenated	CAS-No.: 157707-86-3 EC-No.: 500-393-3 REACH-no: 01-2119486452-34	10 - 15	Asp. Tox. 1, H304
Distillates (petroleum), solvent-refined light paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C).] (see note [**], see note [***]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	CAS-No.: 64742-53-6 EC-No.: 265-156-6 EC Index-No.: 649-466-00-2 REACH-no: 01-2119480375-34	1 - 5	Asp. Tox. 1, H304
Mineral base oil, severely refined (For identification of the substance, see note [*], see note [***]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	CAS-No.: N/A EC-No.: N/A	1 - 5	Asp. Tox. 1, H304

# Eni Rotra FE 75W-80

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [EU-GHS / CLP]
Distillates (petroleum), hydrotreated heavy naphthenic (see note [**], see note [***]) substance with national workplace exposure limit(s) (AT, BE, DK, ES, GB, HU, NL, SE)	CAS-No.: 64742-52-5 EC-No.: 265-155-0 EC Index-No.: 649-465-00-7 REACH-no: 01-2119467170-45	1 - 5	Not classified
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) (Additive)	EC-No.: 931-384-6 REACH-no: 01-2119493620-38	0,5 - 0,9	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Chronic 2, H411
C16-18-(even numbered, saturated and unsaturated)-alkylamines (Additive)	CAS-No.: 1213789-63-9 EC-No.: 627-034-4 REACH-no: 01-2119473797-19	0,2 – 0,4	Acute Tox. 4 (Oral), H302 (ATE=1689 mg/kg bodyweight) Skin Corr. 1B, H314 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)

### Specific concentration limits:

Name	Product identifier	Specific concentration limits (%)
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) (Additive)	EC-No.: 931-384-6 REACH-no: 01-2119493620-38	(9,39 < C ≤ 100) Skin Sens. 1B; H317 (50 < C ≤ 100) Eye Irrit. 2; H319

### Comments

: [\*] Note: this product may be formulated with one or more of the following severely refined mineral base oils:  
CAS 64742-54-7/EC 265-157-1/REACH Reg. # 01-2119484627-25-xxxx; CAS 64742-65-0/EC 265-169-7/REACH Reg. # 01-2119471299-27-xxxx; CAS 64742-70-7/EC 265-174-4/REACH Reg. # 01-2119487080-42-xxxx; CAS 64742-56-9/EC 265-159-2/ REACH Reg. # 01-2119480132-48-xxxx.  
All these substances have a value < 3 % wt of DMSO extract, according to IP 346 (Nota L - Annex VI Reg (CE) 1272/2008, # 1.1.3)  
Note [\*\*]:  
this product has a value of DMSO extract < 3 % wt, according to IP 346. According to the criteria laid out by the EU (note L, Annex VI of Regulation (CE) 1272/2008), this product must be regarded as non carcinogenic.  
Note [\*\*\*]:  
substance with occupational exposure limits for some EU countries affecting the category of mineral oils (finely refined mineral base oil mists; see section 8.1)  
Note [\*\*\*\*]:  
this product may be formulated with one or more of the following base oils: CAS: 64742-54-7, EC 265-157-1, REACH Reg. 01-2119484627-25-0033/ CAS: 74869-22-0, EC: 278-012-2 REACH Reg. 01-2119495601-36

Full text of H- and EUH-statements: see section 16

# Eni Rotra FE 75W-80

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures after inhalation : Remove to fresh air, keep the casualty warm and at rest. If breathing is difficult, give oxygen if possible, or assisted ventilation. If necessary, give external cardiac massage and obtain medical advice. See also section 4.3.
- First-aid measures after skin contact : Remove contaminated clothing and shoes. Wash skin with soap and water. If skin irritation or rash occurs, get medical advice/attention. In case of contact with hot product, cool affected part with plenty of cold water, and cover with gauze or clean cloth. Call a doctor or bring to a hospital. Do not use salves or ointments, unless directed by doctor.
- First-aid measures after eye contact : Remove contact lenses, if present and easy to do so. Rinse eyes thoroughly for at least 15 minutes. Keep eyelids well apart. If irritation, blurred vision or swelling occurs and persists, obtain medical advice from a specialist. In case of burns, cool affected part with cold running water for at least 10 min. Cover with gauze or clean cloth. Ask for medical assistance or bring to a hospital. Do not apply salves or other substances, unless by doctor's advice.
- First-aid measures after ingestion : Rinse mouth thoroughly with water. Give water to drink if victim completely conscious/alert. Do not induce vomiting.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects after inhalation : Inhalation of fumes or oil mists produced at high temperatures may cause irritation of the respiratory tract. Symptoms of overexposure to vapours include drowsiness, weakness, headache, dizziness, nausea, vomiting, dimming of vision.
- Symptoms/effects after skin contact : Prolonged and repeated skin contact may cause reddening, irritation and dermatitis, due to a defatting effect. May cause an allergic skin reaction. Contact with hot product may cause thermal burns.
- Symptoms/effects after eye contact : Contact with eyes may cause temporary reddening and irritation. Contact with hot product or vapours may cause burns.
- Symptoms/effects after ingestion : Accidental ingestion of small quantities of the product may cause nausea, discomfort and gastric disturbances.
- Symptoms/effects upon intravenous administration : No information available.
- Chronic symptoms : None to be reported, according to the present classification criteria.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical attention if casualty has an altered state of consciousness or if symptoms do not resolve. Seek medical attention in all cases of serious burns.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Small-size fires: carbon dioxide, dry chemicals, foam, sand or earth. Large fires: foam or water fog (mist). These means should be used by trained personnel only. Other extinguishing gases (according to regulations).
- Unsuitable extinguishing media : Do not use water jets. They could cause splattering, and spread the fire. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : This product is combustible, but not classified as Flammable. The creation of flammable vapour mixtures takes place at temperatures which are higher than normal ambient levels.
- Explosion hazard : In case of losses from pressurized circuits, the sprays may form mists. Take into account that in this case the lower explosion limit for mists is about 45 g/m<sup>3</sup> air. Vapours are heavier than air, spread along floors and form explosive mixtures with air.
- Hazardous decomposition products in case of fire : Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases. Oxygenated compounds (aldehydes, etc.). POx.

# Eni Rotra FE 75W-80

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### 5.3. Advice for firefighters

- Firefighting instructions : Shut off source of product, if possible. Move undamaged containers from immediate hazard area if it can be done safely. Spilled product which is not burning should be covered with sand or foam. Use water sprays to cool containers and surfaces exposed to the flames. If the fire cannot be controlled, evacuate area.
- Special protective equipment for firefighters : Wear personal protection equipment. (see chapter 8). In case of a large fire or in confined or poorly ventilated spaces, wear full fire resistant protective clothing and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. EN 443. EN 469. EN 659.
- Other information : In case of fire, do not discharge residual product, waste materials and runoff water: collect separately and use a proper treatment.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Stop or contain leak at the source, if safe to do so. Eliminate all ignition sources if safe to do so (e.g. electricity, sparks, fires, flares). Avoid accidental sprays on hot surfaces or electrical contacts. Avoid direct contact with released material. Keep upwind.

#### For non-emergency personnel

- Protective equipment : See Section 8.
- Emergency procedures : Keep non-involved personnel away from the area of spillage. Alert emergency personnel. Except in case of small spillages, the feasibility of any actions should always be assessed and advised, if possible, by a trained, competent person in charge of managing the emergency.

#### For emergency responders

- Protective equipment : Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters. Small spillages: normal antistatic working clothes are usually adequate. Large spillages: full body suit of chemically resistant and antistatic material. if necessary heat resistant and insulated. Work helmet. Antistatic non-skid safety shoes or boots. Goggles and /or face shield, if splashes or contact with eyes is possible or anticipated. Respiratory protection: a half or full-face respirator with filter(s) for organic vapours (AX), or a Self-contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA's should be used.
- Emergency procedures : If required, notify relevant authorities according to all applicable regulations.

### 6.2. Environmental precautions

Do not let the product accumulate in confined or underground spaces. Do not let the product flow into sewers or water courses, or in any way contaminate the environment. In case of contamination of environment compartments (soil, subsoil, surface or underground waters), remove contaminated soil when possible, and in any case treat all involved compartments in accordance with local regulations. The site should have a spill plan to ensure that adequate safeguards are in place to minimize the impact of episodic releases.

### 6.3. Methods and material for containment and cleaning up

- For containment : Contain spilled liquid with sand, earth or other suitable absorbents (non-flammable). Recover free liquid and waste materials in suitable waterproof and oil-resistant containers. Clean contaminated area. Dispose of according to local regulations. If in water: Confine the spillage. Remove from surface by skimming or suitable floating absorbents. Collect recovered product and other waste materials in suitable waterproof, oil resistant containers. Recover or dispose of according to local regulations. Do not use solvents or dispersants, unless specifically advised by an expert, and, if required, approved by local authorities.
- Methods for cleaning up : Transfer recovered product and other materials to suitable tanks or containers and store/dispose according to relevant regulations.
- Other information : Recommended measures are based on the most likely spillage scenarios for this material; however, local conditions (wind, air/water temperature, wave/current direction and speed) may significantly influence the choice of appropriate actions. Local regulations may also prescribe or limit actions to be taken. For this reason, local experts should be consulted when necessary.

# Eni Rotra FE 75W-80

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling	: This material is combustible, but will not ignite readily. Provide adequate ventilation. Use adequate personal protective equipment as needed. Due to the extremely slippery nature of this material, more care than usual must be exercised in material handling practices to keep off all walking surfaces. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Avoid release to the environment. Emptied containers can contain combustible product residues. Do not cut, weld, drill, burn or incinerate empty containers or drums, unless they have been drained and cleaned. Before entering storage tanks and commencing any operation in a confined area (e.g. tunnels), carry out an adequate clean-up, and check the atmosphere for oxygen content and flammability.
Handling temperature	: This product can be handled at ambient temperatures.
Hygiene measures	: Ensure that proper housekeeping measures are in place. Avoid contact with skin. Do not breathe fume/ mist/ vapours. Do not ingest. Do not smoke. Do not eat and do not drink during use. Do not clean hands with dirty or oil-soaked rags. Do not re-use clothes, if they are still contaminated. Keep away from food and beverages. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Contaminated work clothing should not be allowed out of the workplace. Separate working clothes from town clothes. Launder separately.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store in dry, well ventilated area. Keep away from open flames, hot surfaces and sources of ignition. Do not smoke.
Incompatible products	: Strong oxidizing agents.
Storage area	: Storage area layout, tank design, equipment and operating procedures must comply with the relevant European, national or local legislation. Storage installations/areas should be designed with adequate bunds in case of leaks or spills. Cleaning, inspection and maintenance of internal structure of storage tanks must be done only by properly equipped and qualified personnel as defined by national, local or company regulations.
Packages and containers:	: If the product is supplied in containers: Keep containers tightly closed and properly labelled. Keep only in the original container or in a suitable container for this kind of product.
Packaging materials	: For containers, or container linings use materials specifically approved for use with this product. Compatibility should be checked with the manufacturer.

#### Germany

Storage class (LGK, TRGS 510) : LGK 10 - Combustible liquids

#### Switzerland

Storage class (LK) : LK 10/12 - Liquids

### 7.3. Specific end use(s)

No information available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### National occupational exposure and biological limit values

# Eni Rotra FE 75W-80

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

**Distillates (petroleum), solvent-refined light paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-53-6)**

### Austria - Occupational Exposure Limits

MAK (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
---------------	---

### Belgium - Occupational Exposure Limits

OEL TWA	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
---------	---

### Denmark - Occupational Exposure Limits

OEL TWA	1 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
---------	---

OEL STEL	2 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
----------	---

### Hungary - Occupational Exposure Limits

AK (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
--------------	---

### Netherlands - Occupational Exposure Limits

MAC TGG 8h (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
---------------------------------	---

### Spain - Occupational Exposure Limits

VLA-ED (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
------------------	---

VLA-EC (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
-----------------------------	--

### Sweden - Occupational Exposure Limits

NGV (OEL TWA)	1 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
---------------	---

KGV (OEL STEL)	3 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
----------------	---

### United Kingdom - Occupational Exposure Limits

WEL TWA (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
-------------------	---

WEL STEL (OEL STEL)	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
---------------------	--

### USA - ACGIH - Occupational Exposure Limits

ACGIH® TLV® TWA	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
-----------------	---

ACGIH® TLV® STEL	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
------------------	--

### Mineral base oil, severely refined (N/A)

### Austria - Occupational Exposure Limits

MAK (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
---------------	---

### Belgium - Occupational Exposure Limits

OEL TWA	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
---------	---

### Denmark - Occupational Exposure Limits

OEL TWA	1 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
---------	---

OEL STEL	2 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
----------	---

### Hungary - Occupational Exposure Limits

AK (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
--------------	---

### Netherlands - Occupational Exposure Limits

MAC TGG 8h (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
---------------------------------	---

# Eni Rotra FE 75W-80

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

<b>Mineral base oil, severely refined (N/A)</b>	
<b>Spain - Occupational Exposure Limits</b>	
VLA-ED (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
VLA-EC (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
<b>Sweden - Occupational Exposure Limits</b>	
NGV (OEL TWA)	1 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
KGV (OEL STEL)	3 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
<b>United Kingdom - Occupational Exposure Limits</b>	
WEL TWA (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
WEL STEL (OEL STEL)	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH® TLV® TWA	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
ACGIH® TLV® STEL	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
<b>Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)</b>	
<b>Austria - Occupational Exposure Limits</b>	
MAK (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
<b>Belgium - Occupational Exposure Limits</b>	
OEL TWA	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
<b>Denmark - Occupational Exposure Limits</b>	
OEL TWA	1 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
OEL STEL	2 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
<b>Hungary - Occupational Exposure Limits</b>	
AK (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
<b>Netherlands - Occupational Exposure Limits</b>	
MAC TGG 8h (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
<b>Spain - Occupational Exposure Limits</b>	
VLA-ED (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
VLA-EC (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
<b>Sweden - Occupational Exposure Limits</b>	
NGV (OEL TWA)	1 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
KGV (OEL STEL)	3 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
<b>United Kingdom - Occupational Exposure Limits</b>	
WEL TWA (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
WEL STEL (OEL STEL)	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH® TLV® TWA	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
ACGIH® TLV® STEL	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)

# Eni Rotra FE 75W-80

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

**Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)**

### Austria - Occupational Exposure Limits

MAK (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
---------------	---

### Belgium - Occupational Exposure Limits

OEL TWA	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
---------	---

### Denmark - Occupational Exposure Limits

OEL TWA	1 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
---------	---

OEL STEL	2 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
----------	---

### Hungary - Occupational Exposure Limits

AK (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
--------------	---

### Netherlands - Occupational Exposure Limits

MAC TGG 8h (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
---------------------------------	---

### Spain - Occupational Exposure Limits

VLA-ED (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
------------------	---

VLA-EC (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
-----------------------------	--

### Sweden - Occupational Exposure Limits

NGV (OEL TWA)	1 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
---------------	---

KGV (OEL STEL)	3 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
----------------	---

### United Kingdom - Occupational Exposure Limits

WEL TWA (OEL TWA)	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
-------------------	---

WEL STEL (OEL STEL)	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
---------------------	--

### USA - ACGIH - Occupational Exposure Limits

ACGIH® TLV® TWA	5 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
-----------------	---

ACGIH® TLV® STEL	10 mg/m <sup>3</sup> (Mineral base oil mist, severely refined, DMSO extract <3% m/m)
------------------	--

### Recommended monitoring procedures

#### Monitoring methods

Monitoring methods	Monitoring procedures should be chosen according to the indications set by national authorities or labour contracts. Refer to relevant legislation and in any case to the good practice of industrial hygiene.
--------------------	--

### DNEL and PNEC

#### Eni Rotra FE 75W-80

##### DNEL/DMEL (additional information)

Additional information	Not applicable
------------------------	----------------

##### PNEC (additional information)

Additional information	Not applicable
------------------------	----------------

# Eni Rotra FE 75W-80

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

**Distillates (petroleum), solvent-refined light paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-53-6)**

### DNEL/DMEL (Workers)

Long-term - systemic effects, dermal	0,97 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	2,73 mg/m <sup>3</sup>
Long-term - local effects, inhalation	5,58 mg/m <sup>3</sup>

### DNEL/DMEL (General population)

Long-term - systemic effects, oral	0,74 mg/kg bodyweight/day
Long-term - local effects, inhalation	1,19 mg/m <sup>3</sup>

### Mineral base oil, severely refined (N/A)

### DNEL/DMEL (Workers)

Long-term - systemic effects, inhalation	= 5,4 mg/m <sup>3</sup> /day (DNEL, Mineral base oil mist, severely refined, DMSO extract <3% m/m)
--	--

### DNEL/DMEL (General population)

Long-term - local effects, inhalation	= 1,2 mg/m <sup>3</sup> /day (DNEL, Mineral base oil mist, severely refined, DMSO extract <3% m/m)
---------------------------------------	--

### Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)

### DNEL/DMEL (Workers)

Long-term - systemic effects, dermal	0,97 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	2,73 mg/m <sup>3</sup>
Long-term - local effects, inhalation	5,58 mg/m <sup>3</sup>

### DNEL/DMEL (General population)

Long-term - systemic effects, oral	0,74 mg/kg bodyweight/day
Long-term - local effects, inhalation	1,19 mg/m <sup>3</sup>

### PNEC (Oral)

PNEC oral (secondary poisoning)	9,33 mg/kg food
---------------------------------	-----------------

### Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)

### DNEL/DMEL (Workers)

Acute - local effects, dermal	160 µg/cm <sup>2</sup>
Long-term - systemic effects, dermal	12,5 mg/kg bodyweight/day
Long-term - local effects, dermal	160 µg/cm <sup>2</sup>
Long-term - systemic effects, inhalation	4,28 mg/m <sup>3</sup>

### DNEL/DMEL (General population)

Acute - local effects, dermal	160 µg/cm <sup>2</sup>
Long-term - systemic effects, oral	0,25 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	1,09 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	6,25 mg/kg bodyweight/day
Long-term - local effects, dermal	160 µg/cm <sup>2</sup>

# Eni Rotra FE 75W-80

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)

#### PNEC (Water)

PNEC aqua (freshwater)	2,4 µg/l
PNEC aqua (marine water)	0,24 µg/l
PNEC aqua (intermittent, freshwater)	150 µg/l
PNEC aqua (intermittent, marine water)	15 µg/l

#### PNEC (Sediment)

PNEC sediment (freshwater)	12,9 µg/kg dw
PNEC sediment (marine water)	1,29 µg/kg dw

#### PNEC (Soil)

PNEC soil	1,17 µg/kg dw
-----------	---------------

#### PNEC (Oral)

PNEC oral (secondary poisoning)	10 mg/kg food
---------------------------------	---------------

#### PNEC (STP)

PNEC sewage treatment plant	24,33 mg/l
-----------------------------	------------

### C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)

#### DNEL/DMEL (Workers)

Acute - local effects, inhalation	1 mg/m <sup>3</sup>
Long-term - systemic effects, dermal	0,09 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	0,38 mg/m <sup>3</sup>
Long-term - local effects, inhalation	1 mg/m <sup>3</sup>

#### DNEL/DMEL (General population)

Long-term - systemic effects, oral	40 µg/kg bodyweight/day
Long-term - systemic effects, inhalation	0,035 mg/m <sup>3</sup>

#### PNEC (Water)

PNEC aqua (freshwater)	0,26 µg/l
PNEC aqua (marine water)	0,026 µg/l
PNEC aqua (intermittent, freshwater)	1,6 µg/l

#### PNEC (Sediment)

PNEC sediment (freshwater)	3,76 mg/kg dwt
PNEC sediment (marine water)	0,376 mg/kg dwt

#### PNEC (Soil)

PNEC soil	10 mg/kg dwt
-----------	--------------

#### PNEC (Oral)

PNEC oral (secondary poisoning)	0,22 mg/kg food
---------------------------------	-----------------

#### PNEC (STP)

PNEC sewage treatment plant	550 µg/l
-----------------------------	----------

# Eni Rotra FE 75W-80

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Note : The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accord with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a governmental regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH.

## 8.2. Exposure controls

### Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station. Before entering storage tanks and commencing any operation in a confined area (e.g. tunnels), carry out an adequate clean-up, and check the atmosphere for oxygen content and flammability. See also Section 16, "Other information".

### Personal protection equipment

#### Personal protective equipment (for industrial or professional use):

Gloves. Protective clothing. Safety glasses. Safety shoes or boots.

#### Personal protective equipment symbol(s):



### Eye and face protection

#### Eye protection:

When there is a risk of contact with the eyes, use safety goggles or other means of protection (face shield). If necessary, refer to national standards or to the EN 166 standard.

### Skin protection

#### Skin and body protection:

Long-sleeved overalls. If necessary, refer to the EN 340 and related standards, for definition of characteristics and performance according to the risk rating of the area. Antistatic non-skid safety shoes or boots, chemical resistant, if necessary heat resistant and insulated.

#### Hand protection:

When there is a risk of contact with the skin, use waterproof gloves, resistant to chemical products. Gloves must be felt-lined. Adequate materials: nitrile (NBR) or PVC with a protection index > 5 (permeation time > 240 mins). Use gloves respecting all the conditions and within the limits set by the manufacturer. Replace gloves immediately in case of cuts, holes or other signs of damages or degradation. If necessary, refer to the EN 374 standard. Personal hygiene is a key element for an effective hand care. Gloves must be worn only with clean hands. After wearing gloves, hands must be carefully washed and dried.

### Respiratory protection

#### Respiratory protection:

Independently from other possible actions (technical modifications, operating procedures, and other means to limit the exposure of workers), personal protection equipment can be used according to necessity. Open or well ventilated spaces: if the product is handled without adequate containment, use full or half-face masks with adequate filter for dusts. (EN 136/140/145). Combined gas/dust mask with filter type: EN 14387. Closed or confined areas (e.g. tank interiors): the use of protection measures for airways (masks or self-contained breathing apparatus), must be assessed according to the specific activity, as well as level and duration of predicted exposure. (EN 136/140/145)

### Thermal hazards

#### Thermal hazard protection:

If contact with hot product is possible or anticipated, gloves should be heat-resistant and thermally insulated.

### Environmental exposure controls

#### Environmental exposure controls:

Do not discharge the product into the environment. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed. Prevent discharge of undissolved substance to or recover from onsite wastewater. Storage areas/installations should be designed with adequate bunds so as to prevent ground and water pollution in case of leaks or spills.

#### Consumer exposure controls:

No special requirements.

# Eni Rotra FE 75W-80

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Amber.
Appearance	: Liquid, bright & clear.
Odour	: Characteristics.
Odour threshold	: There are no data available on the preparation/mixture itself.
Melting point	: Not applicable
Freezing point	: Not determined
Softening point	: -45 °C (ASTM D5950)
Boiling point	: $\geq 200$ (ASTM D1160)
Flammability	: Not flammable
Lower explosion limit	: Not determined
Upper explosion limit	: Not determined
Flash point	: 215 °C (ASTM D 92)
Auto-ignition temperature	: Not determined
Decomposition temperature	: Not determined
pH	: Lack of data (on mixture / components of the mixture) - Data not available
Viscosity, kinematic	: 54 mm <sup>2</sup> /s (40 °C) (ASTM D 445)
Viscosity, dynamic	: 75000 mPa·s (-40°C, ASTM D2983)
Solubility	: Water: Immiscible and insoluble
Log Kow	: Not applicable for mixtures
Log Pow	: Not applicable for mixtures
Vapour pressure	: Not determined
Vapour pressure at 50°C	: Not determined
Density	: 875 kg/m <sup>3</sup> (15°C) (ASTM D 4052)
Relative density	: Not determined
Relative vapour density at 20°C	: Not determined
Particle characteristics	: Not applicable

#### 9.2. Other information

##### Information with regard to physical hazard classes

Explosion limits :  $\geq 45$  g/m<sup>3</sup> (Aerosol)

##### Other safety characteristics

Additional information : No data available

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

This mixture does not offer any further hazard for reactivity, except what is reported in the following paragraphs.

#### 10.2. Chemical stability

Stable product, according to its intrinsic properties.

#### 10.3. Possibility of hazardous reactions

None (in normal conditions of storage and handling). Contact with strong oxidizers (peroxides, chromates, etc.) may cause a fire hazard. Sensitivity to heat, friction or shock cannot be assessed in advance.

#### 10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

#### 10.5. Incompatible materials

Strong oxidants.

# Eni Rotra FE 75W-80

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Thermal decomposition may produce : Carbon dioxide, Carbon monoxide.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met; Conclusive but not sufficient for classification)
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met; Conclusive but not sufficient for classification)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met; Conclusive but not sufficient for classification)
Additional information	: (according to composition)

#### 1-Decene, Trimer, Hydrogenated (157707-86-3)

LD50 oral rat	≥ 5000 mg/kg (OECD 401-423)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	≥ 2000 mg/kg bodyweight (OECD 402)
LC50 Inhalation - Rat	≥ 5,2 mg/l/4h (Inhalable aerosol) (OECD 403)

#### Distillates (petroleum), solvent-refined light paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-53-6)

LD50 oral rat	> 5000 mg/kg bodyweight
LD50 dermal rat	> 5000 mg/kg bodyweight
LD50 dermal rabbit	2000 – 5000 mg/kg bodyweight
LC50 Inhalation - Rat	> 5 mg/l/4h

#### Mineral base oil, severely refined (N/A)

LD50 oral rat	≥ 5000 mg/kg bodyweight (OECD 401)
LD50 dermal rat	≥ 5000 mg/kg bodyweight (OECD 402)

#### Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)

LD50 oral rat	> 5000 mg/kg (OECD 401)
LD50 dermal rabbit	2000 – 5000 mg/kg bodyweight (OECD 402)
LC50 Inhalation - Rat	2,18 – 5,53 mg/l/4h (OECD 403)

#### Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)

LD50 oral rat	≈ 2000 mg/kg bodyweight
---------------	-------------------------

#### C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)

LD50 oral rat	1689 mg/kg bodyweight (OECD 401)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	2000 mg/kg bodyweight

# Eni Rotra FE 75W-80

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)</b>	
LD50 oral rat	> 5000 mg/kg (API 1982, UBTL 1983 - OECD 401)
LD50 dermal rabbit	2000 – 5000 mg/kg bodyweight (API 1982, UBTL 1984 - OECD 402)
LC50 Inhalation - Rat	3,9 – 5,3 mg//4h (Bio-Research Laboratories, Ltd. 1984 - OECD 403)
Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met) pH: Lack of data (on mixture / components of the mixture) - Data not available
Additional information	: (according to composition)
<b>Mineral base oil, severely refined (N/A)</b>	
pH	Not applicable
<b>Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)</b>	
pH	Not applicable
<b>C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)</b>	
pH	11,7 Temp.: 20 °C
<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)</b>	
pH	Not applicable
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met) pH: Lack of data (on mixture / components of the mixture) - Data not available
Additional information	: (according to composition) This product contains components with a Specific Concentration Limit (SCL).
<b>Mineral base oil, severely refined (N/A)</b>	
pH	Not applicable
<b>Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)</b>	
pH	Not applicable
<b>C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)</b>	
pH	11,7 Temp.: 20 °C
<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)</b>	
pH	Not applicable
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Additional information	: (according to composition)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Additional information	: (according to composition)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Additional information	: (according to composition) All the mineral base oils contained in this product have a value < 3 % wt of DMSO extract, according to IP 346 (Nota L - Annex VI Reg (CE) 1272/2008, # 1.1.3)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
Additional information	: (according to composition)
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)

# Eni Rotra FE 75W-80

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Additional information : (according to composition)

### C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)

STOT-single exposure : May cause respiratory irritation.

STOT-repeated exposure : Not classified (Based on available data, the classification criteria are not met)

Additional information : (according to composition)

**Distillates (petroleum), solvent-refined light paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-53-6)**

LOAEL (oral, rat, 90 days) : 125 mg/kg bodyweight/day

NOAEL (dermal, rat/rabbit, 90 days) : 30 – 2000 mg/kg bodyweight/day

NOAEC (inhalation, rat, vapour, 90 days) : 980 mg/m<sup>3</sup>

### Mineral base oil, severely refined (N/A)

LOAEL (oral, rat, 90 days) : 125 mg/kg bodyweight/day (OECD TG 408)

### Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)

LOAEL (oral, rat, 90 days) : 125 mg/kg bodyweight/day (OECD TG 408)

NOAEL (dermal, rat/rabbit, 90 days) : 30 – 2000 mg/kg bodyweight/day

NOAEC (inhalation, rat, vapour, 90 days) : 980 mg/m<sup>3</sup>

### Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)

NOAEL (subacute, oral, animal/male, 28 days) : 150 mg/kg bodyweight

NOAEL (oral, rat, 90 days) : 150 mg/kg bodyweight Animal: rat

### C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)

NOAEL (oral, rat, 90 days) : 3,25 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 407 (Repeated Dose 28-Day Oral Toxicity Study in Rodents)

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

**Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)**

LOAEL (oral, rat, 90 days) : 125 mg/kg bodyweight/day (CAS 64742-04-7, Mobil 1990) (OECD 408)

LOAEL (dermal, rat/rabbit, 90 days) : 100 mg/kg bodyweight/day

NOAEL (oral, rat, 90 days) : < 125 mg/kg bodyweight/day (CAS 64742-04-7, Mobil 1990) (OECD 408)

NOAEL (dermal, rat/rabbit, 90 days) : 1000 – 2000 mg/kg bodyweight/day (API 1982, Mobil Environmental and Health Science Laboratory 1983 - OECD 410)

NOAEC (inhalation, rat, vapour, 90 days) : 220 – 980 mg/m<sup>3</sup> (Dalbey W, Osimitz T, Kommineni C, Roy T, Feuston M and Yang J 1991 - OECD 412)

Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)

Additional information : (according to composition)

Viscosity, kinematic: > 20,5 mm<sup>2</sup>/s (40 °C) (ASTM D 445)

### Eni Rotra FE 75W-80

Viscosity, kinematic : 54 mm<sup>2</sup>/s (40 °C) (ASTM D 445)

# Eni Rotra FE 75W-80

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

<b>1-Decene, Trimer, Hydrogenated (157707-86-3)</b>	
Viscosity, kinematic	17,4 mm <sup>2</sup> /s (40°C)
<b>Distillates (petroleum), solvent-refined light paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained as the raffinate from a solvent extraction process. It consists predominantly of saturated hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-53-6)</b>	
Viscosity, kinematic	< 20,5 mm <sup>2</sup> /s
<b>Mineral base oil, severely refined (N/A)</b>	
Viscosity, kinematic	> 21 mm <sup>2</sup> /s
Hydrocarbon	Yes
<b>Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)</b>	
Viscosity, kinematic	9 mm <sup>2</sup> /s (40 °C) (ASTM D 445)
<b>C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)</b>	
Viscosity, kinematic	5,245 mm <sup>2</sup> /s
<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)</b>	
Viscosity, kinematic	30 – 32 mm <sup>2</sup> /s (40 °C) (ASTM D 445)

### 11.2. Information on other hazards

#### Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

#### Other information

Potential adverse human health effects and symptoms : Contact with eyes may cause temporary reddening and irritation, Prolonged and repeated skin contact may cause reddening, irritation and dermatitis, May produce an allergic reaction, Avoid all eye and skin contact and do not breathe vapour and mist

Other information : None

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : An uncontrolled release to the environment may nevertheless produce a contamination of different environmental compartments (air, soil, underground, surface water bodies, aquifers). Handle according to general working hygiene practices to avoid pollution and release into the environment.

Ecology - air : This product has a low vapour pressure, and in normal conditions at ambient temperature the concentration in the air is negligible. A significant concentration may build up only if the product is used at high temperature, or in case of sprays and mists.

Ecology - water : This product is not soluble in water. It floats on water and forms a film on the surface. The damage to aquatic organisms is of mechanical kind (immobilization and entrapment)

Hazardous to the aquatic environment, short-term (acute) : Not classified (Based on available data, the classification criteria are not met)

Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

# Eni Rotra FE 75W-80

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

<b>1-Decene, Trimer, Hydrogenated (157707-86-3)</b>	
LC50 fish 1	≥ 1000 mg/l (96h, Salmo gairdneri)
EC50 Daphnia 1	190 mg/l (48 h, Daphnia magna)
NOEC (chronic)	125 mg/l (21 d, Daphnia magna)
<b>Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)</b>	
LC50 fish 1	> 100 mg/l (Pimephales promelas)
LC50 other aquatic organisms 1	> 10 g/l (LL50)
EC50 Daphnia 1	> 10 g/l
NOEC chronic fish	> 5000 mg/l (7d)
NOEC chronic crustacea	> 1000 mg/l (21d)
<b>Mineral base oil, severely refined (N/A)</b>	
LC50 fish 1	> 100 mg/l (LL 50)
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)
<b>Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)</b>	
LC50 fish 1	> 100 mg/l (LL 50)
EC50 Daphnia 1	> 10000 mg/l WAF, 48 h (OECD 202)
<b>Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)</b>	
LC50 fish 1	24 mg/l (Rainbow Trout)
LC50 fish 2	8,5 mg/l (Fathead Minnow)
EC50 Daphnia 1	91,4 mg/l
EC50 96h - Algae [1]	6,4 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [2]	15 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
NOEC (acute)	1,7 – 3,3
NOEC chronic fish	3,2 mg/l (Rainbow Trout - 4d)
NOEC chronic crustacea	0,12 mg/l (Daphnia magna - 21 d)
<b>C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)</b>	
LC50 fish 1	0,84 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
LC50 fish 2	4,21 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 Daphnia 1	0,32 mg/l Test organisms (species): Daphnia magna
EC50 Daphnia 2	0,98 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	0,46 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h - Algae [2]	0,38 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
LOEC (chronic)	0,032 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC (chronic)	0,013 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic crustacea	0,013 mg/l (21d)
NOEC chronic algae	0,01 mg/l (3d)

# Eni Rotra FE 75W-80

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)</b>	
LC50 fish 1	> 100 mg/l (LL 50, Exxon 1995 - OECD 203)
EC50 Daphnia 1	> 10000 mg/l (EL50, Shell 1988 - OECD 202)
NOEC (acute)	≥ 100 mg/l (Pseudokirchneriella subcapitata, 72h, OECD 201 - Petro-Canada 2008)
NOEC chronic fish	≥ 1000 mg/l (Oncorhynchus mykiss, NOELR, 14d - QSAR, Redman, A. et al. 2010)
NOEC chronic crustacea	≥ 1000 mg/l (21d, OECD 211 - Shell 1994)
NOEC chronic algae	≥ 100 mg/l (Pseudokirchneriella subcapitata, 72h)

### 12.2. Persistence and degradability

<b>Eni Rotra FE 75W-80</b>	
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.
<b>1-Decene, Trimer, Hydrogenated (157707-86-3)</b>	
Persistence and degradability	Inherently biodegradable.
Biodegradation	≥ 47,7 % (28d)
<b>Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)</b>	
Persistence and degradability	Rapidly degradable
<b>Mineral base oil, severely refined (N/A)</b>	
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.
<b>Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)</b>	
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.
<b>Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)</b>	
Persistence and degradability	Rapidly degradable
Biodegradation	3,6 – 7,4 % (28d - OECD 301 B)
<b>C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)</b>	
Persistence and degradability	Readily biodegradable.
Biodegradation	66 % (28d) (OECD 301B)
<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)</b>	
Persistence and degradability	The most significant constituents of the product should be considered as "inherently biodegradable", but not "readily biodegradable", and they may be moderately persistent, particularly in anaerobic conditions.
Biodegradation	31 % (28d, Exxon 1995)

# Eni Rotra FE 75W-80

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### 12.3. Bioaccumulative potential

#### Eni Rotra FE 75W-80

Log Pow	Not applicable for mixtures
Log Kow	Not applicable for mixtures
Bioaccumulative potential	Not established.

#### 1-Decene, Trimer, Hydrogenated (157707-86-3)

Log Pow	> 6,5
---------	-------

#### Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)

Log Kow	5,14 (25°C)
---------	-------------

#### C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)

Bioconcentration factor (BCF REACH)	> 500
-------------------------------------	-------

**Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)**

BCF fish 1	0,4 – 6280 l/kg
BCF fish 2	3,16 – 71100 l/kg
Log Pow	1,99 – 18,02
Log Kow	Not applicable (UVCB)
Bioaccumulative potential	The test methods for this endpoint are not applicable to UVCB substances.

### 12.4. Mobility in soil

#### Eni Rotra FE 75W-80

Ecology - soil	No data available.
----------------	--------------------

**Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)**

Log Koc	1,71 – 14,7
Ecology - soil	The test methods for this endpoint are not applicable to UVCB substances.

### 12.5. Results of PBT and vPvB assessment

#### Eni Rotra FE 75W-80

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

# Eni Rotra FE 75W-80

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Component	
Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	1-Decene, Trimer, Hydrogenated (157707-86-3), Distillates (petroleum), hydrotreated light naphthenic (64742-53-6), Mineral base oil, severely refined (N/A), Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5), Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched), C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9), Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)
Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	1-Decene, Trimer, Hydrogenated (157707-86-3), Distillates (petroleum), hydrotreated light naphthenic (64742-53-6), Mineral base oil, severely refined (N/A), Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5), Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched), C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9), Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)

### 12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

### 12.7. Other adverse effects

Other adverse effects

: None.

#### Eni Rotra FE 75W-80

Other information	No other effects known
-------------------	------------------------

#### Mineral base oil, severely refined (N/A)

Other information	This product has no specific properties for inhibition of bacterial activity. In any case, wastewater containing this product should be treated in plants that are suited for the specific purpose.
-------------------	---

#### Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5)

Other information	This product has no specific properties for inhibition of bacterial activity. In any case, wastewater containing this product should be treated in plants that are suited for the specific purpose.
-------------------	---

#### Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil— unspecified; [A complex combination of hydrocarbons obtained by removal of normal paraffins from a petroleum fraction by solvent crystallization. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C20 through C50 and produces a finished oil with a viscosity not less than 100 SUS at 100 °F (19cSt at 40 °C).] (64742-65-0)

Other information	This product has no specific properties for inhibition of bacterial activity. In any case, wastewater containing this product should be treated in plants that are suited for the specific purpose.
-------------------	---

# Eni Rotra FE 75W-80

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878




### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Do not dispose of the product, either new or used, by discharging into sewers, tunnels, lakes or water courses. Deliver to a qualified official collector. Dispose of empty containers and wastes safely.
Sewage disposal recommendations	: Dispose of in a safe manner in accordance with local/national regulations. Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.
Product/Packaging disposal recommendations	: European Waste Catalogue code(s) (Decision 2001/118/CE): 13 02 05* (mineral-based non-chlorinated engine, gear and lubricating oils). This EWC code is only a general indication, and takes into account the original composition of the product and its intended use. The user has the responsibility of choosing the right EWC code, considering the actual use of the product, alterations and contaminations.
Ecology - waste materials	: The product as it is does not contain halogenated substances.
EURAL code (EWC)	: 13 02 05* - Mineral-based non-chlorinated engine, gear and lubricating oils
HP Code	: HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

### SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
UN 3082	UN 3082	UN 3082	UN 3082	UN 3082
<b>14.2. UN proper shipping name</b>				
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	Environmentally hazardous substance, liquid, n.o.s.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
<b>Transport document description</b>				
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (C16-18-(even numbered, saturated and unsaturated)-alkylamines ; Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (C16-18-(even numbered, saturated and unsaturated)-alkylamines ; Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (C16-18-(even numbered, saturated and unsaturated)-alkylamines ; Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (C16-18-(even numbered, saturated and unsaturated)-alkylamines ; Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (C16-18-(even numbered, saturated and unsaturated)-alkylamines ; Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)), 9, III
<b>14.3. Transport hazard class(es)</b>				
9	9	9	9	9
				

# Eni Rotra FE 75W-80

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
<b>14.4. Packing group</b>				
III	III	III	III	III
<b>14.5. Environmental hazards</b>				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes EmS-No. (Fire): F-A EmS-No. (Spillage): S-F	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
None.				

### 14.6. Special precautions for user

#### Overland transport

Transport regulations (ADR)	: Not subject
Classification code (UN)	: M6
Special provisions (ADR)	: 274, 335, 375, 601, 650
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBV
Vehicle for tank carriage	: AT
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV13
Hazard identification number (Kemler No.)	: 90
Orange plates	: 
Tunnel restriction code	: -
EAC code	: •3Z

#### Transport by sea

Transport regulations (IMDG)	: Not subject
Special provisions (IMDG)	: 274, 335, 375, 969
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: LP01, P001
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP29
Stowage category (IMDG)	: A

#### Air transport

Transport regulations (IATA)	: Not subject
PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y964
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 964
PCA max net quantity (IATA)	: 450L
CAO packing instructions (IATA)	: 964

# Eni Rotra FE 75W-80

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

---

CAO max net quantity (IATA) : 450L  
Special provisions (IATA) : A97, A158, A197, A215  
ERG code (IATA) : 9L

### Inland waterway transport

Transport regulations (ADN) : Not subject  
Classification code (ADN) : M6  
Special provisions (ADN) : 274, 335, 375, 601, 650  
Limited quantities (ADN) : 5 L  
Excepted quantities (ADN) : E1  
Carriage permitted (ADN) : T  
Equipment required (ADN) : PP  
Number of blue cones/lights (ADN) : 0

### Rail transport

Transport regulations (RID) : Not subject  
Classification code (RID) : M6  
Special provisions (RID) : 274, 335, 375, 601, 650  
Limited quantities (RID) : 5L  
Excepted quantities (RID) : E1  
Packing instructions (RID) : P001, IBC03, LP01, R001  
Special packing provisions (RID) : PP1  
Mixed packing provisions (RID) : MP19  
Portable tank and bulk container instructions (RID) : T4  
Portable tank and bulk container special provisions (RID) : TP1, TP29  
Tank codes for RID tanks (RID) : LGBV  
Transport category (RID) : 3  
Special provisions for carriage – Packages (RID) : W12  
Special provisions for carriage - Loading and unloading (RID) : CW13, CW31  
Colis express (express parcels) (RID) : CE8  
Hazard identification number (RID) : 90

### 14.7. Maritime transport in bulk according to IMO instruments

IBC code : Not applicable.

# Eni Rotra FE 75W-80

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU-Regulations

##### REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(b)	1-Decene, Trimer, Hydrogenated ; Distillates (petroleum), hydrotreated light naphthenic ; Mineral base oil, severely refined ; Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) ; C16-18- (even numbered, saturated and unsaturated)-alkylamines	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	Eni Rotra FE 75W-80 ; Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) ; C16-18- (even numbered, saturated and unsaturated)-alkylamines	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1

##### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

##### REACH Candidate List (SVHC)

No ingredients are included in the REACH Candidate list (> 0,1 % m/m).

##### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

##### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

##### Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

##### Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

##### Seveso Directive (Disaster Risk Reduction)

Seveso Additional information : E2.

##### Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

# Eni Rotra FE 75W-80

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### Drug Precursors Regulation (EC 273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

### National regulations

#### France

Maladies professionnelles (F)	
Code	Description
RG 36	Diseases caused by oils and fats of mineral or synthetic origin

#### Germany

- Employment restrictions : Employment prohibitions or restrictions on the protection of young people at work according to § 22 JArbSchG in the case of formation of hazardous substances have to be observed.
- National Rules and Recommendations : TRGS 400: Hazard assessment for activities involving Hazardous Substances.  
TRGS 401: Risks resulting from skin contact - identification, assessment, measures.  
TRGS 402: Identification and Assessment of the Risks from Activities involving Hazardous Substances: Inhalation Exposure.  
TRGS 555: Working instruction and information for workers.  
TRGS 800: Fire protection measures.  
TRGS 900: Occupational Exposure Limits.  
TRGS 907: List of sensitizing substances and activities with sensitizing substances.
- VbF class (D) : Not applicable.
- Water hazard class (WGK) (D) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1).
- WGK remark : Classification is carried out on the basis of the Ordinance on facilities for handling substances that are hazardous to water (Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV)) of 18 April 2017 (BGBl 2017, Teil I, Nr. 22, Seite 905).
- Major Accidents Ordinance (12. BImSchV) : Is listed in the Major Accidents Ordinance (12. BImSchV)

Major Accidents Ordinance (12. BImSchV)				
Number	Code	Title	Lower-tier	Upper-tier
1.3.2	E2	Hazardous to the aquatic environment, Chronic 2	200.000 kg	500.000 kg

#### Netherlands

- Saneringsinspanningen : C - Minimize discharge
- SZW-lijst van kankerverwekkende stoffen : None of the components are listed
- SZW-lijst van mutagene stoffen : None of the components are listed
- SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
- SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed
- SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

#### Denmark

- Danish National Regulations : Young people under 18 years are not allowed to use the product  
Pregnant/breastfeeding women working with the product must not be in direct contact with it  
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

# Eni Rotra FE 75W-80

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### Poland

#### Polish National Regulations

- : Act of 25 February 2011 on chemical substances and their mixtures (J. o L. No. 63, item 322 as amended; consolidated text J. o L. 2019, item 1225).  
Act of 14 December 2012 on waste (J. o L. 2013, item 322 as amended; consolidated text J. o L. 2020, item 797).  
The announcement of Marshal of the Sejm of the Republic of Poland dated 19 October 2016 concerning the consolidated text announcement of the decree on the management of packaging and packaging waste (J. o L. 2016, item 1863 as amended).  
Decree of the Minister of Environment of 14 December 2014 on the catalogue of waste (J. o L. 2014, item 1923).  
Act of 19 August 2011 on the Carriage of Dangerous Goods (J. o L. 2011 No. 227, item 1367 as amended; consolidated text J. o L. 2020, item 154).  
Regulation of the Minister of Family, Labour and Social Policy of 12 June 2018 on the highest permissible concentration and intensity of noxious agents for health at work environment (J. o L. item 1286 as amended).  
The announcement of Minister of Health dated 9 September 2016 concerning the consolidated text announcement of the decree of the Minister of Health of 30 December 2004 on health and safety at work related to exposure to chemical agents at work (J. o L. of 16 September 2016, item 1488)  
Regulation of the Minister of Health of 2 February 2011 on tests and measurements of the noxious agents for health at work environment (J. o L. No. 33, item 166 as amended).  
Regulation of the Minister of Environment of 9 December 2003 on particularly hazardous substances to the environment (J. o L. No. 217, item 2141).  
ADR Agreement: Government Statement of 13 March 2023 on the entry into force of amendments to Annexes A and B to the Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), signed in Geneva on 30 September 1957 (J. o. L. 2023, item 891)  
Regulation of the Minister of Health of 25 August 2015 on the method of marking places, pipelines, and containers and tanks used for storing or containing hazardous substances or hazardous mixtures (J.o.L. 2015, item 1368 as amended)

### Spain

#### Royal Decree 665/1997

- : Is not subject to the Royal Decree 665/1997

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

**A chemical safety assessment has been carried out for the following components of this mixture::**

1-Decene, Trimer, Hydrogenated

Distillates (petroleum), hydrotreated heavy naphtenic

Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)

C16-18-(even numbered, saturated and unsaturated)-alkylamines

## SECTION 16: Other information

Indication of changes		
Section	Changed item	Comments
1.3	Supplier information	<b>Modified</b>
14	Carriage permitted (ADN)	<b>Added</b>
14	Special provisions (RID)	<b>Modified</b>
14	Special provisions (IMDG)	<b>Modified</b>
14.6	Special provisions (ADN)	<b>Modified</b>
14.6	Special provisions (ADR)	<b>Modified</b>

# Eni Rotra FE 75W-80

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Abbreviations and acronyms:	
	Complete text of the H phrases quoted in this Safety Data Sheet. These phrases are reported here for information only, and MAY NOT correspond to the classification of the product.
	N/D = not available
	N/A = not applicable
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Effective concentration for 50 percent of test population (median effective concentration)
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Lethal concentration for 50 percent of test population (median lethal concentration)
LD50	Lethal dose for 50 percent of test population (median lethal dose)
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals, Regulation (EC) No 1907/2006
RID	Regulation concerning the International Carriage of Dangerous Goods by Railways
SDS	Safety Data Sheet
STP	Sewage treatment plant
vPvB	Very Persistent and Very Bioaccumulative

Data sources	: This Safety Data Sheet is based on the real characteristics of the components and their combination, taking into account the information provided by the suppliers.
Training advice	: Provide adequate training to professional operators for the use of PPEs, according to the information contained in this Safety Data Sheet.
Other information	: Do not use the product for any purposes that have not been advised by the manufacturer.

Full text of H- and EUH-statements:	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1

# Eni Rotra FE 75W-80

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Full text of H- and EUH-statements:	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH208	Contains Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched). May produce an allergic reaction.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Aquatic Chronic 2	H411	Calculation method

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.